
Logtalk APIs

Release v3.77.0

Paulo Moura

Apr 02, 2024

CONTENTS

1	Libraries	1
1.1	arbitrary	1
1.1.1	arbitrary	1
1.2	assertions	7
1.2.1	assertions	8
1.2.2	assertions(Mode)	9
1.2.3	assertions_messages	11
1.3	assignvars	12
1.3.1	assignvars	12
1.3.2	assignvarsp	13
1.4	base64	17
1.4.1	base64	17
1.4.2	base64url	19
1.5	cbor	21
1.5.1	cbor	21
1.5.2	cbor(StringRepresentation)	22
1.6	code_metrics	24
1.6.1	cc_metric	24
1.6.2	code_metric	26
1.6.3	code_metrics	38
1.6.4	code_metrics_messages	40
1.6.5	code_metrics_utilities	41
1.6.6	coupling_metric	46
1.6.7	dit_metric	48
1.6.8	doc_metric	49
1.6.9	halstead_metric	53
1.6.10	halstead_metric(Stroud)	55
1.6.11	noc_metric	56
1.6.12	nor_metric	58
1.6.13	size_metric	59
1.6.14	upn_metric	61
1.7	core	62
1.7.1	core_messages	62
1.7.2	expanding	63
1.7.3	forwarding	65
1.7.4	logtalk	67
1.7.5	monitoring	79
1.7.6	user	81
1.8	coroutining	83
1.8.1	coroutining	83

1.9	csv	86
1.9.1	csv	86
1.9.2	csv(Header,Separator,IgnoreQuotes)	87
1.9.3	csv_guess_questions	89
1.9.4	csv_protocol	90
1.10	dates	101
1.10.1	date	101
1.10.2	datep	102
1.10.3	time	105
1.10.4	timep	107
1.11	dead_code_scanner	109
1.11.1	dead_code_scanner	109
1.11.2	dead_code_scanner_messages	116
1.12	debug_messages	118
1.12.1	debug_messages	118
1.13	debugger	122
1.13.1	debugger	122
1.13.2	debugger_messages	129
1.13.3	debuggerp	130
1.13.4	dump_trace	137
1.14	dependents	139
1.14.1	observer	139
1.14.2	subject	141
1.15	diagrams	144
1.15.1	diagram(Format)	144
1.15.2	diagrams	167
1.15.3	diagrams(Format)	168
1.15.4	directory_dependency_diagram	178
1.15.5	directory_dependency_diagram(Format)	180
1.15.6	directory_diagram(Format)	181
1.15.7	directory_load_diagram	185
1.15.8	directory_load_diagram(Format)	186
1.15.9	dot_graph_language	188
1.15.10	entity_diagram	190
1.15.11	entity_diagram(Format)	191
1.15.12	file_dependency_diagram	195
1.15.13	file_dependency_diagram(Format)	196
1.15.14	file_diagram(Format)	198
1.15.15	file_load_diagram	201
1.15.16	file_load_diagram(Format)	203
1.15.17	graph_language_protocol	205
1.15.18	graph_language_registry	209
1.15.19	inheritance_diagram	210
1.15.20	inheritance_diagram(Format)	212
1.15.21	library_dependency_diagram	213
1.15.22	library_dependency_diagram(Format)	214
1.15.23	library_diagram(Format)	216
1.15.24	library_load_diagram	221
1.15.25	library_load_diagram(Format)	222
1.15.26	modules_diagram_support	224
1.15.27	uses_diagram	226
1.15.28	uses_diagram(Format)	227
1.15.29	xref_diagram	229
1.15.30	xref_diagram(Format)	230

1.16	dictionaries	233
1.16.1	avltree	233
1.16.2	bintree	235
1.16.3	dictionaryp	237
1.16.4	rbtree	249
1.17	dif	251
1.17.1	dif	251
1.18	doclet	253
1.18.1	doclet	253
1.19	edcg	255
1.19.1	edcg	255
1.20	events	259
1.20.1	after_event_registry	259
1.20.2	before_event_registry	260
1.20.3	event_registry	261
1.20.4	event_registryp	262
1.20.5	monitor	266
1.20.6	monitorp	268
1.21	expand_library_alias_paths	271
1.21.1	expand_library_alias_paths	271
1.22	expecteds	273
1.22.1	either	273
1.22.2	expected	275
1.22.3	expected(Expected)	280
1.23	fcube	288
1.23.1	fcube	288
1.24	flags	292
1.24.1	flags	292
1.24.2	flags_validator	299
1.25	format	301
1.25.1	format	301
1.26	genint	303
1.26.1	genint	303
1.26.2	genint_core	305
1.27	gensym	307
1.27.1	gensym	307
1.27.2	gensym_core	308
1.28	git	311
1.28.1	git	311
1.28.2	git_protocol	312
1.29	grammars	316
1.29.1	blank_grammars(Format)	316
1.29.2	ip_grammars(Format)	323
1.29.3	number_grammars(Format)	324
1.29.4	sequence_grammars	330
1.30	heaps	334
1.30.1	heap(Order)	334
1.30.2	heapp	335
1.30.3	maxheap	340
1.30.4	minheap	342
1.31	help	343
1.31.1	help	343
1.31.2	help_info_support	349
1.32	hierarchies	352

1.32.1	class_hierarchy	352
1.32.2	class_hierarchyp	354
1.32.3	hierarchyp	361
1.32.4	proto_hierarchy	364
1.32.5	proto_hierarchyp	365
1.33	hook_flows	368
1.33.1	hook_pipeline(Pipeline)	368
1.33.2	hook_set(Set)	369
1.34	hook_objects	371
1.34.1	backend_adapter_hook	371
1.34.2	default_workflow_hook	372
1.34.3	grammar_rules_hook	373
1.34.4	identity_hook	375
1.34.5	object_wrapper_hook	376
1.34.6	object_wrapper_hook(Protocol)	377
1.34.7	object_wrapper_hook(Name,Relations)	379
1.34.8	print_goal_hook	380
1.34.9	prolog_module_hook(Module)	381
1.34.10	suppress_goal_hook	383
1.34.11	write_to_file_hook(File)	384
1.34.12	write_to_file_hook(File,Options)	385
1.34.13	write_to_stream_hook(Stream)	387
1.34.14	write_to_stream_hook(Stream,Options)	388
1.35	html	389
1.35.1	html	389
1.35.2	html5	392
1.35.3	xhtml11	393
1.36	ids	394
1.36.1	ids	394
1.36.2	ids(Representation,Bytes)	395
1.37	intervals	397
1.37.1	interval	397
1.37.2	intervalp	399
1.38	iso8601	405
1.38.1	iso8601	405
1.39	issue_creator	417
1.39.1	issue_creator	417
1.40	java	418
1.40.1	java	418
1.40.2	java(Reference)	419
1.40.3	java(Reference,ReturnValue)	421
1.40.4	java_access_protocol	422
1.40.5	java_hook	425
1.40.6	java_utils_protocol	427
1.41	json	436
1.41.1	json	436
1.41.2	json(StringRepresentation)	437
1.41.3	json(ObjectRepresentation,PairRepresentation,StringRepresentation)	438
1.41.4	json_protocol	440
1.42	lgtdoc	442
1.42.1	lgtdoc	442
1.42.2	lgtdoc_messages	445
1.42.3	lgtdocp	446
1.43	lgtunit	458

1.43.1	automation_report	458
1.43.2	coverage_report	459
1.43.3	lgtunit	461
1.43.4	lgtunit_messages	510
1.43.5	minimal_output	511
1.43.6	tap_output	512
1.43.7	tap_report	514
1.43.8	xunit_net_v2_output	517
1.43.9	xunit_net_v2_report	518
1.43.10	xunit_output	520
1.43.11	xunit_report	522
1.44	library	523
1.44.1	cloning	523
1.44.2	counters	525
1.44.3	streamvars	528
1.45	listing	531
1.45.1	listing	531
1.46	logging	534
1.46.1	logger	534
1.46.2	logging	536
1.46.3	loggingp	538
1.47	loops	542
1.47.1	loop	542
1.47.2	loopp	543
1.48	meta	549
1.48.1	meta	549
1.48.2	metap	550
1.49	meta_compiler	561
1.49.1	meta_compiler	561
1.50	metagol	563
1.50.1	metagol	563
1.50.2	metagol_example_protocol	570
1.51	mutations	572
1.51.1	default_atom_mutations	572
1.51.2	default_compound_mutations	574
1.51.3	default_float_mutations	575
1.51.4	default_integer_mutations	576
1.51.5	default_list_mutations	577
1.51.6	mutations	579
1.51.7	mutations_store	580
1.52	nested_dictionaries	583
1.52.1	navltree	583
1.52.2	nbintree	585
1.52.3	nested_dictionary_protocol	586
1.52.4	nrbtree	591
1.53	optionals	592
1.53.1	maybe	592
1.53.2	optional	594
1.53.3	optional(Optional)	598
1.54	options	605
1.54.1	options	606
1.54.2	options_protocol	607
1.55	os	613
1.55.1	os	613

1.55.2	os_types	615
1.55.3	osp	616
1.56	packs	634
1.56.1	pack_protocol	634
1.56.2	packs	638
1.56.3	packs_common	663
1.56.4	packs_messages	675
1.56.5	packs_specs_hook	676
1.56.6	registries	678
1.56.7	registry_loader_hook	689
1.56.8	registry_protocol	690
1.57	pddl_parser	694
1.57.1	pddl	694
1.57.2	read_file	697
1.58	ports_profiler	698
1.58.1	ports_profiler	698
1.59	queues	704
1.59.1	queue	704
1.59.2	queup	705
1.60	random	712
1.60.1	backend_random	712
1.60.2	fast_random	713
1.60.3	pseudo_random_protocol	716
1.60.4	random	718
1.60.5	random_protocol	720
1.61	reader	729
1.61.1	reader	730
1.62	recorded_database	739
1.62.1	recorded_database	739
1.62.2	recorded_database_core	740
1.63	redis	746
1.63.1	redis	746
1.64	sets	749
1.64.1	set	749
1.64.2	set(Type)	750
1.64.3	setp	753
1.65	statistics	763
1.65.1	population	763
1.65.2	sample	764
1.65.3	statistics	765
1.65.4	statisticsp	768
1.66	term_io	779
1.66.1	term_io	779
1.66.2	term_io_protocol	781
1.67	timeout	791
1.67.1	timeout	791
1.68	toychr	793
1.68.1	toychrdb	794
1.69	tsv	799
1.69.1	tsv	799
1.69.2	tsv(Header)	800
1.69.3	tsv_protocol	802
1.70	tutor	811
1.70.1	tutor	811

1.71	types	812
1.71.1	atom	812
1.71.2	atomic	814
1.71.3	callable	815
1.71.4	character	817
1.71.5	characterp	818
1.71.6	comparingp	827
1.71.7	compound	830
1.71.8	difflist	832
1.71.9	float	834
1.71.10	integer	835
1.71.11	list	838
1.71.12	list(Type)	840
1.71.13	listp	842
1.71.14	natural	864
1.71.15	number	865
1.71.16	numberlist	869
1.71.17	numberlistp	870
1.71.18	pairs	880
1.71.19	term	885
1.71.20	termp	887
1.71.21	type	894
1.71.22	varlist	899
1.71.23	varlistp	900
1.72	ulid	910
1.72.1	ulid	910
1.72.2	ulid(Representation)	911
1.72.3	ulid_protocol	913
1.72.4	ulid_types	916
1.73	union_find	917
1.73.1	union_find	917
1.73.2	union_find_protocol	919
1.74	uuid	923
1.74.1	uuid	923
1.74.2	uuid(Representation)	924
1.74.3	uuid_protocol	926
1.75	verdi_neruda	928
1.75.1	a_star_interpreter(W)	929
1.75.2	benchmark_generators	930
1.75.3	best_first	931
1.75.4	bfs_interpreter	933
1.75.5	bup_interpreter	934
1.75.6	counter	935
1.75.7	databasep	939
1.75.8	debug_expansion(Mode)	941
1.75.9	demodb	943
1.75.10	dfs_interpreter	944
1.75.11	flatting	945
1.75.12	heuristic_expansion(Mode)	947
1.75.13	iddfs_interpreter(Increment)	948
1.75.14	interpreterp	949
1.75.15	magic	951
1.75.16	magic_expansion(Mode)	953
1.75.17	rule_expansion(Mode)	954

1.75.18	shell	955
1.75.19	shell(Interpreters)	957
1.75.20	shell_expansion(Mode)	958
1.76	wrapper	959
1.76.1	wrapper	960
1.77	xml_parser	972
1.77.1	xml	972
1.78	zippers	980
1.78.1	zipperp	980
1.78.2	zlist	990
2	Directories	993
2.1	contributions/flags/	995
2.2	contributions/iso8601/	995
2.3	contributions/pddl_parser/	995
2.4	contributions/verdi_neruda/	995
2.5	contributions/xml_parser/	995
2.6	core/	995
2.7	library/	995
2.8	library/arbitrary/	995
2.9	library/assignvars/	995
2.10	library/base64/	995
2.11	library/cbor/	995
2.12	library/coroutining/	995
2.13	library/csv/	995
2.14	library/dates/	995
2.15	library/dependents/	995
2.16	library/dictionaries/	995
2.17	library/dif/	995
2.18	library/edcg/	995
2.19	library/events/	995
2.20	library/expand_library_alias_paths/	995
2.21	library/expecteds/	995
2.22	library/format/	995
2.23	library/genint/	995
2.24	library/gensym/	995
2.25	library/git/	995
2.26	library/grammars/	995
2.27	library/heaps/	995
2.28	library/hierarchies/	995
2.29	library/hook_flows/	995
2.30	library/hook_objects/	995
2.31	library/html/	995
2.32	library/ids/	995
2.33	library/intervals/	995
2.34	library/java/	995
2.35	library/json/	995
2.36	library/listing/	995
2.37	library/logging/	995
2.38	library/loops/	995
2.39	library/meta/	995
2.40	library/meta_compiler/	995
2.41	library/mutations/	995
2.42	library/nested_dictionaries/	995

2.43	library/optionals/	995
2.44	library/options/	995
2.45	library/os/	995
2.46	library/queues/	995
2.47	library/random/	995
2.48	library/reader/	995
2.49	library/recorded_database/	995
2.50	library/redis/	995
2.51	library/sets/	995
2.52	library/statistics/	995
2.53	library/term_io/	995
2.54	library/timeout/	995
2.55	library/tsv/	995
2.56	library/types/	995
2.57	library/ulid/	995
2.58	library/union_find/	995
2.59	library/uuid/	995
2.60	library/zippers/	995
2.61	ports/fcube/	995
2.62	ports/metagol/	995
2.63	ports/toychr/	995
2.64	tools/assertions/	995
2.65	tools/code_metrics/	995
2.66	tools/dead_code_scanner/	995
2.67	tools/debug_messages/	995
2.68	tools/debugger/	995
2.69	tools/diagrams/	995
2.70	tools/doclet/	995
2.71	tools/help/	995
2.72	tools/issue_creator/	995
2.73	tools/lgtdoc/	995
2.74	tools/lgtunit/	995
2.75	tools/packs/	995
2.76	tools/ports_profiler/	995
2.77	tools/tutor/	995
2.78	tools/wrapper/	995
3	Entities	997
3.1	Categories	997
3.2	Objects	997
3.3	Protocols	997
4	Predicates	999
4.1	(/)/2	999
4.2	(//)/2	999
4.3	(<)/2	999
4.4	(<=)/2	999
4.5	(=:=)/2	999
4.6	(=<)/2	1000
4.7	(=>)/2	1000
4.8	(=\=)/2	1000
4.9	=~/2	1000
4.10	(>)/2	1000
4.11	(>=)/2	1000

4.12	absolute_file_name/2	1000
4.13	activate_monitor/0	1000
4.14	add/1	1001
4.15	add/2	1001
4.16	add/3	1001
4.17	addDependent/1	1001
4.18	after/2	1001
4.19	after/3	1001
4.20	all/0	1001
4.21	all/1	1002
4.22	all_files/0	1002
4.23	all_files/1	1002
4.24	all_libraries/0	1002
4.25	all_libraries/1	1002
4.26	all_score/1	1002
4.27	ancestor/1	1002
4.28	ancestors/1	1003
4.29	apis/0	1003
4.30	apis/1	1003
4.31	append/2	1003
4.32	append/3	1003
4.33	apply/2	1003
4.34	apply/4	1003
4.35	approximately_equal/2	1003
4.36	approximately_equal/3	1004
4.37	arbitrary/1	1004
4.38	arbitrary/2	1004
4.39	archive/1	1004
4.40	arithmetic_mean/2	1004
4.41	array_list/2	1004
4.42	array_to_list/2	1004
4.43	array_to_terms/2	1004
4.44	array_to_terms/3	1005
4.45	as_curly_bracketed/2	1005
4.46	as_dictionary/2	1005
4.47	as_difflist/2	1005
4.48	as_heap/2	1005
4.49	as_list/2	1005
4.50	as_nested_dictionary/2	1005
4.51	as_set/2	1006
4.52	ask_question/5	1006
4.53	assertion/1	1006
4.54	assertion/2	1006
4.55	assignable/1	1006
4.56	assignable/2	1006
4.57	available/0	1006
4.58	available/1	1006
4.59	available/2	1007
4.60	average/2	1007
4.61	average_deviation/3	1007
4.62	before/2	1007
4.63	before/3	1007
4.64	bench_goal/1	1007
4.65	benchmark/2	1007

4.66	benchmark/3	1007
4.67	benchmark/4	1008
4.68	benchmark_reified/3	1008
4.69	between/3	1008
4.70	bit/1	1008
4.71	bits/1	1008
4.72	blank/0	1008
4.73	blanks/0	1008
4.74	body_pred/1	1008
4.75	branch/2	1009
4.76	built_in_directive/4	1009
4.77	built_in_flag/2	1009
4.78	built_in_method/4	1009
4.79	built_in_non_terminal/4	1009
4.80	built_in_predicate/4	1009
4.81	calendar_month/3	1009
4.82	call_with_timeout/2	1009
4.83	call_with_timeout/3	1010
4.84	cat/2	1010
4.85	change_directory/1	1010
4.86	changed/0	1010
4.87	changed/1	1010
4.88	chebyshev_distance/3	1010
4.89	chebyshev_norm/2	1010
4.90	check/1	1010
4.91	check/2	1011
4.92	check/3	1011
4.93	check_option/1	1011
4.94	check_options/1	1011
4.95	chr_is/2	1011
4.96	chr_no_spy/1	1011
4.97	chr_nospy/0	1011
4.98	chr_notrace/0	1011
4.99	chr_option/2	1012
4.100	chr_spy/1	1012
4.101	chr_trace/0	1012
4.102	class/1	1012
4.103	classes/1	1012
4.104	clause/5	1012
4.105	clause_location/6	1012
4.106	clean/0	1012
4.107	clean/1	1013
4.108	clean/2	1013
4.109	clone/1	1013
4.110	clone/3	1013
4.111	clone/4	1013
4.112	coefficient_of_variation/2	1013
4.113	command_line_arguments/1	1013
4.114	commit_author/2	1013
4.115	commit_date/2	1014
4.116	commit_hash/2	1014
4.117	commit_hash_abbreviated/2	1014
4.118	commit_log/3	1014
4.119	commit_message/2	1014

4.120	compile_aux_clauses/1	1014
4.121	compile_predicate_heads/4	1014
4.122	compile_predicate_indicators/3	1014
4.123	completion/2	1015
4.124	completions/2	1015
4.125	connect/1	1015
4.126	connect/3	1015
4.127	console/1	1015
4.128	contains/2	1015
4.129	control//0	1015
4.130	control_construct/4	1015
4.131	controls//0	1016
4.132	copy_file/2	1016
4.133	counter/2	1016
4.134	cover/1	1016
4.135	cpu_time/1	1016
4.136	current/2	1016
4.137	data/0	1016
4.138	data/1	1016
4.139	data/2	1017
4.140	date/4	1017
4.141	date/5	1017
4.142	date/6	1017
4.143	date/7	1017
4.144	date_string/3	1017
4.145	date_time/7	1017
4.146	days_in_month/3	1017
4.147	debug/0	1018
4.148	debug_handler/2	1018
4.149	debug_handler_provider/1	1018
4.150	debugging/0	1018
4.151	debugging/1	1018
4.152	decide/1	1018
4.153	decide/2	1018
4.154	decode_exception/2	1018
4.155	decode_exception/3	1019
4.156	decompile_predicate_heads/4	1019
4.157	decompile_predicate_indicators/4	1019
4.158	decompose_file_name/3	1019
4.159	decompose_file_name/4	1019
4.160	decrement_counter/1	1019
4.161	default_option/1	1019
4.162	default_options/1	1019
4.163	define_log_file/2	1020
4.164	defined/4	1020
4.165	defined_flag/6	1020
4.166	del_monitors/0	1020
4.167	del_monitors/4	1020
4.168	del_spy_points/4	1020
4.169	delete/0	1020
4.170	delete/1	1020
4.171	delete/2	1021
4.172	delete/3	1021
4.173	delete/4	1021

4.174 delete_all_after/2	1021
4.175 delete_all_after_and_unzip/2	1021
4.176 delete_all_before/2	1021
4.177 delete_all_before_and_unzip/2	1021
4.178 delete_and_next/2	1021
4.179 delete_and_previous/2	1022
4.180 delete_and_unzip/2	1022
4.181 delete_directory/1	1022
4.182 delete_file/1	1022
4.183 delete_in/4	1022
4.184 delete_matches/3	1022
4.185 delete_max/4	1022
4.186 delete_min/4	1022
4.187 dependents/1	1023
4.188 dependents/2	1023
4.189 dependents/3	1023
4.190 depth/2	1023
4.191 descendant/1	1023
4.192 descendant_class/1	1023
4.193 descendant_classes/1	1023
4.194 descendant_instance/1	1023
4.195 descendant_instances/1	1024
4.196 descendants/1	1024
4.197 describe/1	1024
4.198 describe/2	1024
4.199 description/1	1024
4.200 deterministic/1	1024
4.201 deterministic/2	1024
4.202 diagram_description/1	1024
4.203 diagram_name_suffix/1	1025
4.204 dif/1	1025
4.205 dif/2	1025
4.206 digit//1	1025
4.207 digits//1	1025
4.208 directories/1	1025
4.209 directories/2	1025
4.210 directories/3	1026
4.211 directory/1	1026
4.212 directory/2	1026
4.213 directory/3	1026
4.214 directory_exists/1	1026
4.215 directory_files/2	1027
4.216 directory_files/3	1027
4.217 directory_score/2	1027
4.218 disable/1	1027
4.219 disable/2	1027
4.220 disable_logging/1	1027
4.221 disconnect/1	1027
4.222 disjoint/2	1027
4.223 disjoint_sets/2	1028
4.224 doc_goal/1	1028
4.225 dot//1	1028
4.226 dowhile/2	1028
4.227 drop/3	1028

4.228	during/2	1028
4.229	easter_day/3	1028
4.230	edge/6	1028
4.231	edge_case/2	1029
4.232	either/3	1029
4.233	empty/1	1029
4.234	enable/1	1029
4.235	enable/2	1029
4.236	enable_logging/1	1029
4.237	enabled/1	1030
4.238	enabled/2	1030
4.239	ensure_directory/1	1030
4.240	ensure_file/1	1030
4.241	entity/1	1030
4.242	entity/2	1030
4.243	entity_info_pair_score_hook/3	1030
4.244	entity_info_score_hook/2	1031
4.245	entity_predicates_weights_hook/2	1031
4.246	entity_prefix/2	1031
4.247	entity_score/2	1031
4.248	enumerate/2	1031
4.249	environment_variable/2	1031
4.250	epsilon/1	1031
4.251	equal/2	1031
4.252	erase/1	1032
4.253	essentially_equal/3	1032
4.254	euclidean_distance/3	1032
4.255	euclidean_norm/2	1032
4.256	exclude/3	1032
4.257	execution_context/7	1032
4.258	expand_library_path/2	1032
4.259	expected/1	1032
4.260	expecteds/2	1033
4.261	extension/1	1033
4.262	extensions/1	1033
4.263	false/1	1033
4.264	fcube/0	1033
4.265	file/1	1033
4.266	file/2	1033
4.267	file_exists/1	1034
4.268	file_footer/3	1034
4.269	file_header/3	1034
4.270	file_modification_time/2	1034
4.271	file_permission/2	1034
4.272	file_score/2	1034
4.273	file_size/2	1034
4.274	file_to_bytes/2	1034
4.275	file_to_bytes/3	1035
4.276	file_to_chars/2	1035
4.277	file_to_chars/3	1035
4.278	file_to_codes/2	1035
4.279	file_to_codes/3	1035
4.280	file_to_terms/2	1035
4.281	file_to_terms/3	1035

4.282 file_type_extension/2	1035
4.283 files/1	1036
4.284 files/2	1036
4.285 files/3	1036
4.286 filter/2	1036
4.287 find/4	1036
4.288 find/5	1036
4.289 findall_member/4	1037
4.290 findall_member/5	1037
4.291 finished_by/2	1037
4.292 finishes/2	1037
4.293 flag_group_chk/1	1037
4.294 flag_groups/1	1037
4.295 flat_map/2	1037
4.296 flatten/2	1037
4.297 float//1	1038
4.298 fold_left/4	1038
4.299 fold_left_1/3	1038
4.300 fold_right/4	1038
4.301 fold_right_1/3	1038
4.302 fordownto/3	1038
4.303 fordownto/4	1038
4.304 fordownto/5	1038
4.305 foreach/3	1039
4.306 foreach/4	1039
4.307 format/2	1039
4.308 format/3	1039
4.309 format_entity_score//2	1039
4.310 format_object/1	1039
4.311 format_to_atom/3	1039
4.312 format_to_chars/3	1039
4.313 format_to_chars/4	1040
4.314 format_to_codes/3	1040
4.315 format_to_codes/4	1040
4.316 forto/3	1040
4.317 forto/4	1040
4.318 forto/5	1040
4.319 forward/1	1040
4.320 forward/2	1040
4.321 forward/3	1041
4.322 fractile/3	1041
4.323 freeze/2	1041
4.324 from_generator/2	1041
4.325 from_generator/3	1041
4.326 from_generator/4	1041
4.327 from_goal/2	1041
4.328 from_goal/3	1041
4.329 from_goal/4	1042
4.330 frozen/2	1042
4.331 full_device_path/1	1042
4.332 func_test/3	1042
4.333 functional/0	1042
4.334 generate/1	1042
4.335 generate/2	1042

4.336 generate/8	1043
4.337 genint/2	1043
4.338 gensym/2	1043
4.339 geometric_mean/2	1043
4.340 get/1	1043
4.341 get_field/2	1043
4.342 get_flag_value/2	1043
4.343 get_seed/1	1043
4.344 gnu/0	1044
4.345 goal_expansion/2	1044
4.346 graph_footer/5	1044
4.347 graph_header/5	1044
4.348 ground/1	1044
4.349 group_by_key/2	1044
4.350 group_consecutive_by_key/2	1044
4.351 group_sorted_by_key/2	1044
4.352 guess_arity/2	1045
4.353 guess_separator/2	1045
4.354 hamming_distance/3	1045
4.355 handbook/0	1045
4.356 handbook/1	1045
4.357 harmonic_mean/2	1045
4.358 head/2	1045
4.359 head_pred/1	1045
4.360 help/0	1046
4.361 hex_digit//1	1046
4.362 hex_digits//1	1046
4.363 home/1	1046
4.364 ibk/3	1046
4.365 if_empty/1	1046
4.366 if_expected/1	1046
4.367 if_expected_or_else/2	1046
4.368 if_present/1	1047
4.369 if_present_or_else/2	1047
4.370 if_unexpected/1	1047
4.371 include/3	1047
4.372 increase/1	1047
4.373 increment/0	1047
4.374 increment_counter/1	1047
4.375 init/0	1047
4.376 init_log_file/2	1048
4.377 inorder/2	1048
4.378 insert/3	1048
4.379 insert/4	1048
4.380 insert_after/3	1048
4.381 insert_all/3	1048
4.382 insert_before/3	1048
4.383 insert_in/4	1048
4.384 install/1	1049
4.385 install/2	1049
4.386 install/3	1049
4.387 install/4	1049
4.388 installed/0	1049
4.389 installed/1	1049

4.390	installed/3	1049
4.391	installed/4	1049
4.392	instance/1	1050
4.393	instance/2	1050
4.394	instances/1	1050
4.395	integer//1	1050
4.396	internal_os_path/2	1050
4.397	intersect/2	1050
4.398	intersection/2	1050
4.399	intersection/3	1050
4.400	intersection/4	1051
4.401	invoke/1	1051
4.402	invoke/2	1051
4.403	ipv4//1	1051
4.404	ipv6//1	1051
4.405	is_absolute_file_name/1	1051
4.406	is_alpha/1	1051
4.407	is_alphanumeric/1	1051
4.408	is_ascii/1	1052
4.409	is_bin_digit/1	1052
4.410	is_control/1	1052
4.411	is_dec_digit/1	1052
4.412	is_empty/0	1052
4.413	is_end_of_line/1	1052
4.414	is_expected/0	1052
4.415	is_false/1	1052
4.416	is_hex_digit/1	1053
4.417	is_layout/1	1053
4.418	is_letter/1	1053
4.419	is_lower_case/1	1053
4.420	is_newline/1	1053
4.421	is_null/1	1053
4.422	is_object/1	1053
4.423	is_octal_digit/1	1053
4.424	is_period/1	1054
4.425	is_present/0	1054
4.426	is_punctuation/1	1054
4.427	is_quote/1	1054
4.428	is_true/1	1054
4.429	is_unexpected/0	1054
4.430	is_upper_case/1	1054
4.431	is_void/1	1054
4.432	is_vowel/1	1055
4.433	is_white_space/1	1055
4.434	iterator_element/2	1055
4.435	join/3	1055
4.436	join_all/3	1055
4.437	jump/3	1055
4.438	jump_all/3	1055
4.439	jump_all_block/3	1055
4.440	key/2	1056
4.441	keys/2	1056
4.442	keys_values/3	1056
4.443	keysort/2	1056

4.444	kurtosis/2	1056
4.445	language_object/2	1056
4.446	last/2	1056
4.447	leaf/1	1056
4.448	leaf_class/1	1057
4.449	leaf_classes/1	1057
4.450	leaf_instance/1	1057
4.451	leaf_instances/1	1057
4.452	leap_year/1	1057
4.453	learn/0	1057
4.454	learn/1	1057
4.455	learn/2	1057
4.456	learn/3	1058
4.457	learn_seq/2	1058
4.458	learn_with_timeout/4	1058
4.459	leash/1	1058
4.460	leashing/1	1058
4.461	least_common_multiple/2	1058
4.462	leaves/1	1058
4.463	length/2	1058
4.464	libraries/1	1059
4.465	libraries/2	1059
4.466	libraries/3	1059
4.467	library/0	1059
4.468	library/1	1059
4.469	library/2	1059
4.470	library_score/2	1060
4.471	license/1	1060
4.472	line_to_chars/2	1060
4.473	line_to_chars/3	1060
4.474	line_to_codes/2	1060
4.475	line_to_codes/3	1060
4.476	lint/0	1060
4.477	lint/1	1060
4.478	lint/2	1061
4.479	list/0	1061
4.480	list_to_array/2	1061
4.481	listing/0	1061
4.482	listing/1	1061
4.483	loaded_file/1	1061
4.484	loaded_file_property/2	1061
4.485	log_event/2	1061
4.486	log_file/2	1062
4.487	logging/1	1062
4.488	logtalk_packs/0	1062
4.489	logtalk_packs/1	1062
4.490	lookup/2	1062
4.491	lookup/3	1062
4.492	lookup_in/3	1062
4.493	lower_upper/2	1062
4.494	magic/2	1063
4.495	magicise/4	1063
4.496	make_directory/1	1063
4.497	make_directory_path/1	1063

4.498	make_set/3	1063
4.499	man/1	1063
4.500	manhattan_distance/3	1063
4.501	manhattan_norm/2	1063
4.502	manuals/0	1064
4.503	map/2	1064
4.504	map/3	1064
4.505	map/4	1064
4.506	map/5	1064
4.507	map/6	1064
4.508	map/7	1065
4.509	map/8	1065
4.510	map_element/2	1065
4.511	map_reduce/5	1065
4.512	max/2	1065
4.513	max/3	1065
4.514	max_clauses/1	1065
4.515	max_inv_preds/1	1065
4.516	max_size/1	1066
4.517	maybe/0	1066
4.518	maybe/1	1066
4.519	maybe/2	1066
4.520	maybe_call/1	1066
4.521	maybe_call/2	1066
4.522	mean_deviation/2	1066
4.523	median/2	1066
4.524	median_deviation/2	1067
4.525	meets/2	1067
4.526	member/2	1067
4.527	memberchk/2	1067
4.528	merge/3	1067
4.529	message_hook/4	1067
4.530	message_prefix_stream/4	1067
4.531	message_tokens//2	1068
4.532	met_by/2	1068
4.533	meta_type/3	1068
4.534	metarule/6	1068
4.535	metarule_next_id/1	1068
4.536	min/2	1068
4.537	min/3	1068
4.538	min_clauses/1	1068
4.539	min_max/3	1069
4.540	modes/2	1069
4.541	module_property/2	1069
4.542	monitor/1	1069
4.543	monitor/4	1069
4.544	monitor_activated/0	1069
4.545	monitored/1	1069
4.546	monitors/1	1069
4.547	msort/2	1070
4.548	msort/3	1070
4.549	mutation/3	1070
4.550	name/1	1070
4.551	name_of_day/3	1070

4.552	name_of_month/3	1070
4.553	natural//1	1070
4.554	new/1	1070
4.555	new/2	1071
4.556	new/3	1071
4.557	new_line//0	1071
4.558	new_lines//0	1071
4.559	next/2	1071
4.560	next/3	1071
4.561	next/4	1071
4.562	nextto/3	1071
4.563	node/7	1072
4.564	nodebug/0	1072
4.565	non_blank//1	1072
4.566	non_blanks//1	1072
4.567	normal_element/2	1072
4.568	normalize_range/2	1072
4.569	normalize_range/4	1072
4.570	normalize_scalar/2	1072
4.571	normalize_unit/2	1073
4.572	nospy/1	1073
4.573	nospy/4	1073
4.574	nospyall/0	1073
4.575	note/2	1073
4.576	note/3	1073
4.577	notrace/0	1073
4.578	now/3	1073
4.579	nth0/3	1074
4.580	nth0/4	1074
4.581	nth1/3	1074
4.582	nth1/4	1074
4.583	null/1	1074
4.584	null_device_path/1	1074
4.585	number//1	1074
4.586	number_of_tests/1	1075
4.587	numbervars/1	1075
4.588	numbervars/3	1075
4.589	occurrences/2	1075
4.590	occurrences/3	1075
4.591	occurs/2	1075
4.592	of/2	1075
4.593	of_expected/2	1075
4.594	of_unexpected/2	1076
4.595	one_or_more//0	1076
4.596	one_or_more//1	1076
4.597	one_or_more//2	1076
4.598	operating_system_machine/1	1076
4.599	operating_system_name/1	1076
4.600	operating_system_release/1	1076
4.601	operating_system_type/1	1076
4.602	option/2	1077
4.603	option/3	1077
4.604	or/2	1077
4.605	or_else/2	1077

4.606	or_else_call/2	1077
4.607	or_else_fail/1	1077
4.608	or_else_get/2	1077
4.609	or_else_throw/1	1078
4.610	or_else_throw/2	1078
4.611	orphaned/0	1078
4.612	orphaned/2	1078
4.613	outdated/0	1078
4.614	outdated/1	1078
4.615	outdated/4	1078
4.616	output_file_name/2	1078
4.617	overlapped_by/2	1079
4.618	overlaps/2	1079
4.619	parent/1	1079
4.620	parenthesis/2	1079
4.621	parents/1	1079
4.622	parse/2	1079
4.623	parse/3	1079
4.624	parse_domain/2	1080
4.625	parse_domain/3	1080
4.626	parse_problem/2	1080
4.627	parse_problem/3	1080
4.628	partial_map/4	1080
4.629	partition/3	1080
4.630	partition/4	1080
4.631	partition/5	1080
4.632	partition/6	1081
4.633	path_concat/3	1081
4.634	permutation/2	1081
4.635	pid/1	1081
4.636	pin/0	1081
4.637	pin/1	1081
4.638	pinned/1	1081
4.639	plus/3	1081
4.640	port/5	1082
4.641	portray_clause/1	1082
4.642	postorder/2	1082
4.643	powerset/2	1082
4.644	pp/1	1082
4.645	pprint/1	1082
4.646	predicate/2	1082
4.647	predicate_info_pair_score_hook/4	1082
4.648	predicate_info_score_hook/3	1083
4.649	predicate_mode_score_hook/3	1083
4.650	predicate_mode_score_hook/5	1083
4.651	predicates/2	1083
4.652	prefix/0	1083
4.653	prefix/1	1083
4.654	prefix/2	1083
4.655	prefix/3	1083
4.656	preorder/2	1084
4.657	previous/2	1084
4.658	previous/3	1084
4.659	previous/4	1084

4.660	print_flags/0	1084
4.661	print_flags/1	1084
4.662	print_message/3	1084
4.663	print_message_token/4	1084
4.664	print_message_tokens/3	1085
4.665	product/2	1085
4.666	product/3	1085
4.667	program_to_clauses/2	1085
4.668	proper_prefix/2	1085
4.669	proper_prefix/3	1085
4.670	proper_suffix/2	1085
4.671	proper_suffix/3	1085
4.672	prove/2	1086
4.673	prove/3	1086
4.674	provides/2	1086
4.675	question_hook/6	1086
4.676	question_prompt_stream/4	1086
4.677	quick_check/1	1086
4.678	quick_check/2	1086
4.679	quick_check/3	1086
4.680	random/1	1087
4.681	random/3	1087
4.682	random_node/1	1087
4.683	random_tree/1	1087
4.684	randomize/1	1087
4.685	randseq/4	1087
4.686	randset/4	1087
4.687	range/2	1087
4.688	rdirectories/1	1088
4.689	rdirectories/2	1088
4.690	rdirectory/1	1088
4.691	rdirectory/2	1088
4.692	rdirectory/3	1088
4.693	rdirectory_score/2	1089
4.694	read_file/2	1089
4.695	read_file/3	1089
4.696	read_file_by_line/2	1089
4.697	read_file_by_line/3	1089
4.698	read_from_atom/2	1089
4.699	read_from_chars/2	1089
4.700	read_from_codes/2	1090
4.701	read_only_device_path/1	1090
4.702	read_stream/2	1090
4.703	read_stream/3	1090
4.704	read_stream_by_line/2	1090
4.705	read_stream_by_line/3	1090
4.706	read_term_from_atom/3	1090
4.707	read_term_from_chars/3	1091
4.708	read_term_from_chars/4	1091
4.709	read_term_from_codes/3	1091
4.710	read_term_from_codes/4	1091
4.711	readme/1	1091
4.712	readme/2	1091
4.713	recorda/2	1091

4.714 recorda/3	1091
4.715 recorded/2	1092
4.716 recorded/3	1092
4.717 recordz/2	1092
4.718 recordz/3	1092
4.719 relative_standard_deviation/2	1092
4.720 removeDependent/1	1092
4.721 remove_duplicates/2	1092
4.722 rename_file/2	1092
4.723 replace/3	1093
4.724 replace_sub_atom/4	1093
4.725 rescale/3	1093
4.726 reset/0	1093
4.727 reset/1	1093
4.728 reset_counter/1	1093
4.729 reset_counters/0	1093
4.730 reset_flags/0	1093
4.731 reset_flags/1	1094
4.732 reset_genint/0	1094
4.733 reset_genint/1	1094
4.734 reset_gensym/0	1094
4.735 reset_gensym/1	1094
4.736 reset_monitor/0	1094
4.737 reset_seed/0	1094
4.738 restore/1	1094
4.739 restore/2	1095
4.740 reverse/2	1095
4.741 rewind/2	1095
4.742 rewind/3	1095
4.743 rlibraries/1	1095
4.744 rlibraries/2	1095
4.745 rlibrary/1	1095
4.746 rlibrary/2	1096
4.747 rlibrary_score/2	1096
4.748 rule/2	1096
4.749 rule/3	1096
4.750 rule/4	1096
4.751 run/0	1096
4.752 run/1	1096
4.753 run/2	1097
4.754 run_test_sets/1	1097
4.755 same_length/2	1097
4.756 same_length/3	1097
4.757 save/0	1097
4.758 save/1	1097
4.759 save/2	1097
4.760 scalar_product/3	1097
4.761 scan_left/4	1098
4.762 scan_left_1/3	1098
4.763 scan_right/4	1098
4.764 scan_right_1/3	1098
4.765 search/1	1098
4.766 select/3	1098
4.767 select/4	1098

4.768	selectchk/3	1099
4.769	selectchk/4	1099
4.770	send/3	1099
4.771	sequence/3	1099
4.772	sequence/4	1099
4.773	serve/3	1099
4.774	set/1	1099
4.775	set/4	1099
4.776	set_element/2	1100
4.777	set_field/2	1100
4.778	set_flag_value/2	1100
4.779	set_flag_value/3	1100
4.780	set_monitor/4	1100
4.781	set_seed/1	1100
4.782	set_spy_point/4	1100
4.783	setup/0	1100
4.784	shell/1	1101
4.785	shell/2	1101
4.786	shell_command/1	1101
4.787	shrink/3	1101
4.788	shrink_sequence/3	1101
4.789	shrinker/1	1101
4.790	sign//1	1101
4.791	singletons/2	1101
4.792	size/2	1102
4.793	skewness/2	1102
4.794	sleep/1	1102
4.795	sort/2	1102
4.796	sort/3	1102
4.797	sort/4	1102
4.798	source_file_extension/1	1102
4.799	space//0	1102
4.800	spaces//0	1103
4.801	split/3	1103
4.802	split/4	1103
4.803	spy/1	1103
4.804	spy/4	1103
4.805	spy_point/4	1103
4.806	spying/1	1103
4.807	spying/4	1103
4.808	standard_deviation/2	1104
4.809	start/0	1104
4.810	start_redirect_to_file/2	1104
4.811	started_by/2	1104
4.812	starts/2	1104
4.813	stop_redirect_to_file/0	1104
4.814	stream_to_bytes/2	1104
4.815	stream_to_bytes/3	1104
4.816	stream_to_chars/2	1105
4.817	stream_to_chars/3	1105
4.818	stream_to_codes/2	1105
4.819	stream_to_codes/3	1105
4.820	stream_to_terms/2	1105
4.821	stream_to_terms/3	1105

4.822 subclass/1	1105
4.823 subclasses/1	1105
4.824 sublist/2	1106
4.825 subsequence/3	1106
4.826 subsequence/4	1106
4.827 subset/2	1106
4.828 substitute/4	1106
4.829 subsumes/2	1106
4.830 subterm/2	1106
4.831 subtract/3	1106
4.832 succ/2	1107
4.833 suffix/2	1107
4.834 suffix/3	1107
4.835 sum/2	1107
4.836 superclass/1	1107
4.837 superclasses/1	1107
4.838 suspend_monitor/0	1107
4.839 swap/2	1107
4.840 swap_consecutive/2	1108
4.841 symdiff/3	1108
4.842 tab/0	1108
4.843 tabs/0	1108
4.844 take/3	1108
4.845 temporary_directory/1	1108
4.846 term_expansion/2	1108
4.847 terms_to_array/2	1108
4.848 test/1	1109
4.849 time_stamp/1	1109
4.850 timeout/1	1109
4.851 timestamp/2	1109
4.852 timestamp/8	1109
4.853 today/3	1109
4.854 tolerance_equal/4	1109
4.855 top/3	1109
4.856 top_next/5	1110
4.857 trace/0	1110
4.858 trace_event/2	1110
4.859 transpose/2	1110
4.860 true/1	1110
4.861 type/1	1110
4.862 unexpected/1	1110
4.863 unexpecteds/2	1110
4.864 uninstall/0	1111
4.865 uninstall/1	1111
4.866 uninstall/2	1111
4.867 union/3	1111
4.868 union/4	1111
4.869 union_all/3	1111
4.870 unpin/0	1111
4.871 unpin/1	1111
4.872 unzip/2	1112
4.873 update/0	1112
4.874 update/1	1112
4.875 update/2	1112

4.876	update/3	1112
4.877	update/4	1112
4.878	update/5	1112
4.879	update_in/4	1113
4.880	update_in/5	1113
4.881	uuid_null/1	1113
4.882	uuid_v1/2	1113
4.883	uuid_v4/1	1113
4.884	valid/1	1113
4.885	valid/2	1113
4.886	valid/3	1114
4.887	valid_date/3	1114
4.888	valid_option/1	1114
4.889	valid_options/1	1114
4.890	validate/1	1114
4.891	value/1	1114
4.892	value/3	1114
4.893	value_reference/2	1114
4.894	values/2	1115
4.895	variables/2	1115
4.896	variance/2	1115
4.897	variant/2	1115
4.898	varnumbers/2	1115
4.899	varnumbers/3	1115
4.900	verify_commands_availability/0	1115
4.901	version/6	1115
4.902	versions/3	1116
4.903	void/1	1116
4.904	void_element/1	1116
4.905	wall_time/1	1116
4.906	weighted_mean/3	1116
4.907	welcome/0	1116
4.908	when/2	1116
4.909	whiledo/2	1116
4.910	white_space//0	1117
4.911	white_spaces//0	1117
4.912	with_output_to/2	1117
4.913	without//2	1117
4.914	working_directory/1	1117
4.915	write_file/3	1117
4.916	write_stream/3	1117
4.917	write_term_to_atom/3	1117
4.918	write_term_to_chars/3	1118
4.919	write_term_to_chars/4	1118
4.920	write_term_to_codes/3	1118
4.921	write_term_to_codes/4	1118
4.922	write_to_atom/2	1118
4.923	write_to_chars/2	1118
4.924	write_to_codes/2	1118
4.925	z_normalization/2	1118
4.926	zero_or_more//0	1119
4.927	zero_or_more//1	1119
4.928	zero_or_more//2	1119
4.929	zip/2	1119

4.930 zip/3	1119
4.931 zip_at_index/4	1119
5 Indices and tables	1121
Index	1123

LIBRARIES

To load any library (including developer tools, ports, and contributions), use the goal `logtalk_load(library_name(loader))`. To run the library tests, use the goal `logtalk_load(library_name(tester))`. To load an entity, always load the loader file of the library that includes it to ensure that all required dependencies are also loaded and that any required flags are used. The loading goal can be found in the entity documentation.

1.1 arbitrary

category

1.1.1 arbitrary

Adds predicates for generating and shrinking random values for selected types to the library type object. User extensible.

Availability:

```
logtalk_load(arbitrary(loader))
```

Author: Paulo Moura

Version: 2:35:0

Date: 2024-03-07

Compilation flags:

```
static
```

Complements:

```
type
```

Uses:

```
fast_random
```

```
integer
```

```
list
```

```
type
```

Remarks:

- Logtalk specific types: `entity`, `object`, `protocol`, `category`, `entity_identifier`, `object_identifier`, `protocol_identifier`, `category_identifier`, `event`, `predicate`.
- Prolog module related types (when the backend compiler supports modules): `module`, `module_identifier`, `qualified_callable`.
- Prolog base types: `term`, `var`, `nonvar`, `atomic`, `atom`, `number`, `integer`, `float`, `compound`, `callable`, `ground`.
- Atom derived types: `non_quoted_atom`, `non_empty_atom`, `non_empty_atom(CharSet)`, `boolean`, `character`, `in_character`, `char`, `operator_specifier`, `hex_char`.
- Atom derived parametric types: `atom(CharSet)`, `atom(CharSet,Length)`, `non_empty_atom(CharSet)`, `character(CharSet)`, `in_character(CharSet)`, `char(CharSet)`.
- Number derived types: `positive_number`, `negative_number`, `non_positive_number`, `non_negative_number`.
- Float derived types: `positive_float`, `negative_float`, `non_positive_float`, `non_negative_float`, `probability`.
- Integer derived types: `positive_integer`, `negative_integer`, `non_positive_integer`, `non_negative_integer`, `byte`, `in_byte`, `character_code`, `in_character_code`, `code`, `operator_priority`, `hex_code`.
- Integer derived parametric types: `character_code(CharSet)`, `in_character_code(CharSet)`, `code(CharSet)`.
- List types (compound derived types): `list`, `non_empty_list`, `partial_list`, `list_or_partial_list`, `list(Type)`, `list(Type,Length)`, `list(Type,Min,Max)`, `list(Type,Length,Min,Max)`, `non_empty_list(Type)`, `codes`, `chars`.
- Difference list types (compound derived types): `difference_list`, `difference_list(Type)`.
- List and difference list types length: The types that do not take a fixed length generate lists with a length in the `[0,MaxSize]` interval (`[1,MaxSize]` for non-empty list types).
- Predicate and non-terminal indicator types arity: These types generate indicators with an arity in the `[0,MaxSize]` interval.
- Other compound derived types: `compound(Name,Types)`, `predicate_indicator`, `non_terminal_indicator`, `predicate_or_non_terminal_indicator`, `clause`, `grammar_rule`, `pair`, `pair(KeyType,ValueType)`.
- Other types: `Object::Closure`, `between(Type,Lower,Upper)`, `property(Type,LambdaExpression)`, `one_of(Type,Set)`, `var_or(Type)`, `ground(Type)`, `types(Types)`, `types_frequency(Pairs)`, `transform(Type,Closure)`, `constrain(Type,Closure)`.
- Type `Object::Closure` notes: Allows calling public object predicates as generators and shrinkers. The `Closure` closure is extended with either a single argument, the generated arbitrary value, or with two arguments, when shrinking a value.
- Type `compound(Name,Types)` notes: Generate a random compound term with the given name with a random argument for each type.
- Type `types_frequency(Pairs)` notes: Generate a random term for one of the types in a list of Type-Frequency pairs. The type is randomly selected taking into account the types frequency.
- Type `transform(Type,Closure)` notes: Generate a random term by transforming the term generated for the given type using the given closure.

- Type constrain(Type,Closure) notes: Generate a random term for the given type that satisfy the given closure.
- Registering new types: Add clauses for the arbitrary/1-2 multifile predicates and optionally for the shrinker/1 and shrink/3 multifile predicates. The clauses must have a bound first argument to avoid introducing spurious choice-points.
- Shrinking values: The shrink/3 should either succeed or fail but never throw an exception.
- Character sets: `ascii_identifier`, `ascii_printable`, `ascii_full`, `byte`, `unicode_bmp`, `unicode_full`.
- Default character sets: The default character set when using a parameterizable type that takes a character set parameter depends on the type.
- Default character sets: Entity, predicate, and non-terminal identifier types plus compound and callable types default to an `ascii_identifier` functor. Character and character code types default to `ascii_full`. Other types default to `ascii_printable`.
- Caveats: The type argument (and any type parameterization) to the predicates is not type-checked (or checked for consistency) for performance reasons.
- Unicode limitations: Currently, correct character/code generation is only ensured for LVM and SWI-Prolog as other backends do not provide support for querying a Unicode code point category.

Inherited public predicates:

(none)

- Public predicates
 - `arbitrary/1`
 - `arbitrary/2`
 - `shrinker/1`
 - `shrink/3`
 - `shrink_sequence/3`
 - `edge_case/2`
 - `get_seed/1`
 - `set_seed/1`
 - `max_size/1`
- Protected predicates
- Private predicates
- Operators

Public predicates

arbitrary/1

Table of defined types for which an arbitrary value can be generated. A new type can be registered by defining a clause for this predicate and adding a clause for the arbitrary/2 multifile predicate.

Compilation flags:
static, multifile

Template:
arbitrary(Type)
Mode and number of proofs:
arbitrary(?callable) - zero_or_more

arbitrary/2

Generates an arbitrary term of the specified type. Fails if the type is not supported. A new generator can be defined by adding a clause for this predicate and registering it via the arbitrary/1 predicate.

Compilation flags:
static, multifile

Template:
arbitrary(Type,Term)
Meta-predicate template:
arbitrary(:,*)
Mode and number of proofs:
arbitrary(@callable,-term) - zero_or_one

shrinker/1

Table of defined types for which a shrinker is provided. A new shrinker can be registered by defining a clause for this predicate and adding a definition for the shrink/3 multifile predicate.

Compilation flags:
static, multifile

Template:

shrinker(Type)

Mode and number of proofs:

shrinker(?callable) - zero_or_more

shrink/3

Shrinks a value to a smaller value if possible. Must generate a finite number of solutions. Fails if the type is not supported. A new shrinker can be defined by adding a clause for this predicate and registering it via the shrinker/1 predicate.

Compilation flags:

static, multifile

Template:

shrink(Type, Large, Small)

Mode and number of proofs:

shrink(@callable, @term, -term) - zero_or_more

shrink_sequence/3

Shrinks a value repeatedly until shrinking is no longer possible returning the sequence of values (ordered from larger to smaller value). Fails if the type is not supported.

Compilation flags:

static

Template:

shrink_sequence(Type, Value, Sequence)

Mode and number of proofs:

shrink_sequence(@callable, @term, -list(term)) - zero_or_one

edge_case/2

Table of type edge cases. Fails if the given type have no defined edge cases. New edge cases for existing or new types can be added by defining a clause for this multifile predicate.

Compilation flags:

static, multifile

Template:

edge_case(Type,Term)

Mode and number of proofs:

edge_case(?callable,?term) - zero_or_more

get_seed/1

Gets the current random generator seed. Seed should be regarded as an opaque ground term.

Compilation flags:

static

Template:

get_seed(Seed)

Mode and number of proofs:

get_seed(-ground) - one

set_seed/1

Sets the random generator seed to a given value returned by calling the get_seed/1 predicate.

Compilation flags:

static

Template:

set_seed(Seed)

Mode and number of proofs:

set_seed(+ground) - one

`max_size/1`

User defined maximum size for types where its meaningful and implicit. When not defined, defaults to 42. When multiple definitions exist, the first valid one found is used.

Compilation flags:
 `static, multifile`

Template:
 `max_size(Size)`
Mode and number of proofs:
 `max_size(?positive_integer) - zero_or_one`

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

See also:

`type`

1.2 assertions

object

1.2.1 assertions

Proxy object for simplifying the use of the assertion meta-predicates.

Availability:

```
logtalk_load(assertions(loader))
```

Author: Paulo Moura

Version: 2:0:0

Date: 2014-04-03

Compilation flags:

```
static, context_switching_calls
```

Extends:

```
public assertions(_)
```

Remarks:

```
(none)
```

Inherited public predicates:

```
assertion/1 assertion/2 goal_expansion/2 term_expansion/2
```

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

object

1.2.2 assertions(Mode)

A simple assertions framework. Can be used as a hook object for either suppressing assertions (production mode) or expanding them with file context information (debug mode).

Availability:

```
logtalk_load(assertions(loader))
```

Author: Paulo Moura

Version: 2:2:2

Date: 2022-07-04

Compilation flags:

```
static, context_switching_calls
```

Implements:

```
public expanding
```

Uses:

```
logtalk
```

Remarks:

(none)

Inherited public predicates:

```
goal_expansion/2 term_expansion/2
```

- Public predicates
 - assertion/1

- assertion/2
- Protected predicates
- Private predicates
- Operators

Public predicates

assertion/1

Checks that an assertion is true. Uses the structured message printing mechanism for printing the results using a silent message for assertion success and a error message for assertion failure.

Compilation flags:
static

Template:
assertion(Goal)

Meta-predicate template:
assertion(0)

Mode and number of proofs:
assertion(@callable) - one

assertion/2

Checks that an assertion is true. Uses the structured message printing mechanism for printing the results using a silent message for assertion success and a error message for assertion failure. The context argument can be used to e.g. pass location data.

Compilation flags:
static

Template:
assertion(Context,Goal)

Meta-predicate template:
assertion(*,0)

Mode and number of proofs:
assertion(@term,@callable) - one

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

category

1.2.3 assertions_messages

Assertions framework default message translations.

Availability:

```
logtalk_load(assertions(loader))
```

Author: Paulo Moura

Version: 2:2:0

Date: 2018-02-20

Compilation flags:

```
static
```

Provides:

```
logtalk::message_prefix_stream/4
```

```
logtalk::message_tokens//2
```

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
- Protected predicates
- Private predicates

- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

1.3 assignvars

object

1.3.1 assignvars

Assignable variables (supporting backtracable assignment of non-variable terms).

Availability:

```
logtalk_load(assignvars(loader))
```

Author: Nobukuni Kino and Paulo Moura

Version: 1:7:0

Date: 2018-07-11

Compilation flags:

```
static, context_switching_calls
```

Implements:

```
public assignvarsp
```

Remarks:

(none)

Inherited public predicates:

(<=)/2 (=>)/2 assignable/1 assignable/2

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

protocol

1.3.2 assignvarsp

Assignable variables (supporting backtracable assignment of non-variable terms) protocol.

Availability:

logtalk_load(assignvars(loader))

Author: Nobukuni Kino and Paulo Moura

Version: 1:0:1

Date: 2019-06-10

Compilation flags:

static

Dependencies:

(none)

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
 - assignable/1
 - assignable/2
 - (\leq)/2
 - (\geq)/2
- Protected predicates
- Private predicates
- Operators
 - op(100,xfx, \leq)
 - op(100,xfx, \geq)

Public predicates

assignable/1

Makes Variable an assignable variable. Initial state will be empty.

Compilation flags:

static

Template:

assignable(Variable)

Mode and number of proofs:

assignable(--assignvar) - one

Exceptions:

Variable is not a variable:

type_error(variable,Variable)

assignable/2

Makes Variable an assignable variable and sets its initial state to Value.

Compilation flags:

static

Template:

assignable(Variable, Value)

Mode and number of proofs:

assignable(--assignvar, @nonvar) - one

Exceptions:

Variable is not a variable:

type_error(variable, Variable)

Value is not instantiated:

in instantiation_error

(<=)/2

Sets the state of the assignable variable Variable to Value (initializing the variable if needed).

Compilation flags:

static

Template:

Variable<=Value

Mode and number of proofs:

(?assignvar)<=(@nonvar) - one

Exceptions:

Value is not instantiated:

in instantiation_error

$(=>)/2$

Unifies Value with the current state of the assignable variable Variable.

Compilation flags:

static

Template:

Variable=>Value

Mode and number of proofs:

+assignvar=> ?nonvar - zero_or_one

Exceptions:

Variable is not instantiated:

instantiation_error

Protected predicates

(none)

Private predicates

(none)

Operators

op(100,xfx,<=)

Scope:

public

op(100,xfx,=>)

Scope:

public

See also:

assignvars

1.4 base64

object

1.4.1 base64

Base64 parser and generator.

Availability:

```
logtalk_load(base64(loader))
```

Author: Paulo Moura

Version: 0:10:0

Date: 2021-03-22

Compilation flags:

```
static, context_switching_calls
```

Uses:

```
reader
```

Remarks:

```
(none)
```

Inherited public predicates:

```
(none)
```

- Public predicates
 - parse/2
 - generate/2
- Protected predicates
- Private predicates
- Operators

Public predicates

parse/2

Parses the Base64 data from the given source (atom(Atom), chars(List), codes(List), stream(Stream), or file(Path)) into a list of bytes.

Compilation flags:

static

Template:

parse(Source,Bytes)

Mode and number of proofs:

parse(++compound,--list(byte)) - one_or_error

generate/2

Generates Base64 in the representation specified in the first argument (atom(Atom), chars(List), codes(List), stream(Stream), or file(Path)) for the list of bytes in the second argument.

Compilation flags:

static

Template:

generate(Sink,Bytes)

Mode and number of proofs:

generate(+compound,+list(byte)) - one_or_error

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

object

1.4.2 base64url

Base64URL parser and generator.

Availability:

`logtalk_load(base64(loader))`

Author: Paulo Moura

Version: 0:9:0

Date: 2021-03-10

Compilation flags:

`static, context_switching_calls`

Dependencies:

(none)

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
 - `parse/2`
 - `generate/2`
- Protected predicates
- Private predicates
- Operators

Public predicates

parse/2

Parses the Base64URL data from the given source (`atom(Atom)`, `chars(List)`, or `codes(List)`) into a URL (using the same format as the source).

Compilation flags:

static

Template:

parse(Source,URL)

Mode and number of proofs:

parse(++compound,--types([atom,chars,codes])) - one_or_error

generate/2

Generates Base64URL data in the representation specified in the first argument (`atom(Atom)`, `chars(List)`, or `codes(List)`) for the given URL (given in the same format as the sink).

Compilation flags:

static

Template:

generate(Sink,URL)

Mode and number of proofs:

generate(+compound,+types([atom,chars,codes])) - one_or_error

Protected predicates

(none)

Private predicates

(none)

Operators

(none)

1.5 cbor

object

1.5.1 cbor

Concise Binary Object Representation (CBOR) format exporter and importer. Uses atoms to represent decoded CBOR strings.

Availability:

```
logtalk_load(cbor(loader))
```

Author: Paulo Moura

Version: 1:0:0

Date: 2021-03-04

Compilation flags:

```
static, context_switching_calls
```

Extends:

```
public cbor(atom)
```

Remarks:

(none)

Inherited public predicates:

```
generate/2 parse/2
```

- Public predicates
- Protected predicates
- Private predicates

- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

object

1.5.2 cbor(StringRepresentation)

- StringRepresentation - Text representation to be used when decoding CBOR strings. Possible values are atom (default), chars, and codes.

Concise Binary Object Representation (CBOR) format exporter and importer.

Availability:

```
logtalk_load(cbor(loader))
```

Author: Paulo Moura

Version: 0:11:1

Date: 2021-12-06

Compilation flags:

```
static, context_switching_calls
```

Uses:

```
list
```

Remarks:

```
(none)
```

Inherited public predicates:

(none)

- Public predicates
 - parse/2
 - generate/2
- Protected predicates
- Private predicates
- Operators

Public predicates

parse/2

Parses a list of bytes in the CBOR format returning the corresponding term representation. Throws an error when parsing is not possible (usually due to an invalid byte sequence).

Compilation flags:

static

Template:

parse(Bytes,Term)

Mode and number of proofs:

parse(@list(byte),-ground) - one_or_error

generate/2

Generates a list of bytes in the CBOR format representing the given term. Throws an error when generating is not possible (usually due to a term that have no CBOR corresponding representation).

Compilation flags:

static

Template:

generate(Term,Bytes)

Mode and number of proofs:

generate(@ground,-list(byte)) - one_or_error

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

1.6 code_metrics

object

1.6.1 cc_metric

Cyclomatic complexity metric. All defined predicates that are not called or updated are counted as graph connected components (the reasoning being that these predicates can be considered entry points). The score is represented by a non-negative integer.

Availability:

```
logtalk_load(code_metrics(loader))
```

Author: Paulo Moura

Version: 0:5:0

Date: 2024-03-28

Compilation flags:

```
static, context_switching_calls
```

Imports:

```
public code_metrics_utilities  
public code_metric
```

Provides:

```
logtalk::message_tokens//2
```

Uses:

```
list  
logtalk
```

numberlist

Remarks:

(none)

Inherited public predicates:

all/0 all/1 all_score/1 check_option/1 check_options/1 default_option/1 default_options/1
 directory/1 directory/2 directory_score/2 entity/1 entity_score/2 file/1 file/2 file_score/2
 format_entity_score//2 library/1 library/2 library_score/2 option/2 option/3 rdirectory/1
 rdirectory/2 rdirectory_score/2 rlibrary/1 rlibrary/2 rlibrary_score/2 valid_option/1
 valid_options/1

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

category

1.6.2 code_metric

Core predicates for computing source code metrics.

Availability:

```
logtalk_load(code_metrics(loader))
```

Author: Ebrahim Azarisooreh and Paulo Moura

Version: 0:12:0

Date: 2024-03-28

Compilation flags:

```
static
```

Extends:

```
public code_metrics_utilities
```

```
public options
```

Uses:

```
list
```

```
logtalk
```

```
os
```

```
type
```

Remarks:

```
(none)
```

Inherited public predicates:

```
check_option/1 check_options/1 default_option/1 default_options/1 option/2 option/3  
valid_option/1 valid_options/1
```

- Public predicates

- entity/1

- file/2

- file/1

- directory/2

- directory/1

- rdirectory/2

- rdirectory/1

- library/2

- library/1
- rlibrary/2
- rlibrary/1
- all/1
- all/0
- entity_score/2
- library_score/2
- rlibrary_score/2
- file_score/2
- directory_score/2
- rdirectory_score/2
- all_score/1
- format_entity_score//2
- Protected predicates
 - process_entity/2
 - process_file/2
 - process_directory/2
 - process_rdirectory/2
 - process_library/2
 - process_rlibrary/2
 - process_all/1
 - sub_directory/2
 - sub_library/2
- Private predicates
- Operators

Public predicates

entity/1

Scans an entity and prints its metric score.

Compilation flags:

static

Template:

entity(Entity)

Mode and number of proofs:

entity(+term) - zero_or_one

file/2

Prints metric scores for all the entities defined in a loaded source file using the given options.

Compilation flags:

static

Template:

file(File,Options)

Mode and number of proofs:

file(+atom,+list(compound)) - zero_or_one

file/1

Prints metric scores for all the entities defined in a loaded source file using default options.

Compilation flags:

static

Template:

file(File)

Mode and number of proofs:

file(+atom) - zero_or_one

directory/2

Scans a directory and prints metric scores for all entities defined in its loaded source files using the given options.

Compilation flags:

static

Template:

directory(Directory,Options)

Mode and number of proofs:

directory(+atom,+list(compound)) - one

directory/1

Scans a directory and prints metric scores for all entities defined in its loaded source files using default options.

Compilation flags:

static

Template:

directory(Directory)

Mode and number of proofs:

directory(+atom) - one

rdirectory/2

Recursive version of the directory/1 predicate using the given options.

Compilation flags:

static

Template:

rdirectory(Directory,Options)

Mode and number of proofs:

rdirectory(+atom,+list(compound)) - one

rdirectory/1

Recursive version of the directory/1 predicate using default options.

Compilation flags:

static

Template:

rdirectory(Directory)

Mode and number of proofs:

rdirectory(+atom) - one

library/2

Prints metrics scores for all loaded entities from a given library using the given options.

Compilation flags:

static

Template:

library(Library,Options)

Mode and number of proofs:

library(+atom,+list(compound)) - one

library/1

Prints metrics scores for all loaded entities from a given library using default options.

Compilation flags:

static

Template:

library(Library)

Mode and number of proofs:

library(+atom) - one

rlibrary/2

Recursive version of the library/1 predicate using the given options.

Compilation flags:

static

Template:

rlibrary(Library,Options)

Mode and number of proofs:

rlibrary(+atom,+list(compound)) - one

rlibrary/1

Recursive version of the library/1 predicate using default options.

Compilation flags:

static

Template:

rlibrary(Library)

Mode and number of proofs:

rlibrary(+atom) - one

all/1

Scans all loaded entities and prints their metric scores using the given options.

Compilation flags:

static

Template:

all(Options)

Mode and number of proofs:

all(+list(compound)) - one

all/0

Scans all loaded entities and prints their metric scores using default options.

Compilation flags:

static

Mode and number of proofs:

all - one

entity_score/2

Score is a term that represents the metric score associated with a loaded entity. Fails if the metric does not apply.

Compilation flags:

static

Template:

entity_score(Entity,Score)

Mode and number of proofs:

entity_score(@entity_identifier,-ground) - zero_or_one

library_score/2

Score is a term that represents the metric score associated with a loaded library source files. Fails if the metric does not apply.

Compilation flags:

static

Template:

library_score(Library,Score)

Mode and number of proofs:

library_score(@atom,-ground) - zero_or_one

rlibrary_score/2

Score is a term that represents the metric score associated with loaded source files from a library and its sub-libraries. Fails if the metric does not apply.

Compilation flags:

static

Template:

rlibrary_score(Library,Score)

Mode and number of proofs:

rlibrary_score(@atom,-ground) - zero_or_one

file_score/2

Score is a term that represents the metric score associated with a loaded source file. Fails if the metric does not apply.

Compilation flags:

static

Template:

file_score(File,Score)

Mode and number of proofs:

file_score(@atom,-ground) - zero_or_one

directory_score/2

Score is a term that represents the metric score associated with loaded source files from a directory. Fails if the metric does not apply.

Compilation flags:

static

Template:

directory_score(Directory,Score)

Mode and number of proofs:

directory_score(@atom,-ground) - zero_or_one

rdirectory_score/2

Score is a term that represents the metric score associated with loaded source files from a directory and its sub-directories. Fails if the metric does not apply.

Compilation flags:

static

Template:

rdirectory_score(Directory,Score)

Mode and number of proofs:

rdirectory_score(@atom,-ground) - zero_or_one

all_score/1

Score is a term that represents the metric score associated with all loaded source files. Fails if the metric does not apply.

Compilation flags:

static

Template:

all_score(Score)

Mode and number of proofs:

all_score(-ground) - zero_or_one

`format_entity_score//2`

Formats the entity score for pretty printing.

Compilation flags:

`static`

Template:

`format_entity_score(Entity,Score)`

Mode and number of proofs:

`format_entity_score(@entity_identifier,+ground) - one`

Protected predicates

`process_entity/2`

Processes an entity of the given kind.

Compilation flags:

`static`

Template:

`process_entity(Kind,Entity)`

Mode and number of proofs:

`process_entity(+atom,@entity_identifier) - one`

`process_file/2`

Processes a source file using the given options.

Compilation flags:

`static`

Template:

`process_file(Path,Options)`

Mode and number of proofs:

`process_file(+atom,+list(compound)) - one`

`process_directory/2`

Processes a directory of source files using the given options.

Compilation flags:

`static`

Template:

`process_directory(Path,Options)`

Mode and number of proofs:

`process_directory(+atom,+list(compound)) - one`

`process_rdirectory/2`

Recursively process a directory of source files using the given options.

Compilation flags:

`static`

Template:

`process_rdirectory(Path,Options)`

Mode and number of proofs:

`process_rdirectory(+atom,+list(compound)) - one`

`process_library/2`

Processes a library of source files using the given options.

Compilation flags:

`static`

Template:

`process_library(Library,Options)`

Mode and number of proofs:

`process_library(+atom,+list(compound)) - one`

`process_rlibrary/2`

Recursively process a library of source files using the given options.

Compilation flags:

`static`

Template:

`process_rlibrary(Library,Options)`

Mode and number of proofs:

`process_rlibrary(+atom,+list(compound)) - one`

`process_all/1`

Processes all loaded source code using the given options.

Compilation flags:

`static`

Template:

`process_all(Options)`

Mode and number of proofs:

`process_all(+list(compound)) - one`

`sub_directory/2`

Enumerates, by backtracking, all directory sub-directories containing loaded files.

Compilation flags:

`static`

Template:

sub_directory(Directory,SubDirectory)

Mode and number of proofs:

sub_directory(+atom,-atom) - one

sub_library/2

Enumerates, by backtracking, all library sub-libraries.

Compilation flags:

static

Template:

sub_library(Library,SubLibrary)

Mode and number of proofs:

sub_library(+atom,-atom) - one

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

object

1.6.3 code_metrics

Helper object to apply all loaded code metrics.

Availability:

logtalk_load(code_metrics(loader))

Author: Ebrahim Azarisooreh and Paulo Moura

Version: 0:1:0

Date: 2017-12-31

Compilation flags:

static, context_switching_calls

Imports:

public code_metric

Uses:

logtalk

Remarks:

(none)

Inherited public predicates:

all/0 all/1 all_score/1 check_option/1 check_options/1 default_option/1 default_options/1
 directory/1 directory/2 directory_score/2 entity/1 entity_score/2 file/1 file/2 file_score/2
 format_entity_score//2 library/1 library/2 library_score/2 option/2 option/3 rdirectory/1
 rdirectory/2 rdirectory_score/2 rlibrary/1 rlibrary/2 rlibrary_score/2 valid_option/1
 valid_options/1

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

category

1.6.4 code_metrics_messages

Message translations for the code_metrics tool.

Availability:

```
logtalk_load(code_metrics(loader))
```

Author: Ebrahim Azarisooreh and Paulo Moura

Version: 0:8:0

Date: 2022-05-05

Compilation flags:

```
static
```

Provides:

```
logtalk::message_prefix_stream/4
```

```
logtalk::message_tokens//2
```

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

category

1.6.5 code_metrics_utilities

Internal predicates for analyzing source code.

Availability:

```
logtalk_load(code_metrics(loader))
```

Author: Ebrahim Azarisooreh

Version: 0:7:0

Date: 2024-03-28

Compilation flags:

```
static
```

Uses:

```
list
```

```
logtalk
```

Remarks:

- Usage: This is meant to be imported by any metric added to the system.
- Predicate Scope: This is meant for internal use by metrics only. As such, all provided predicates are protected.

Inherited public predicates:

(none)

- Public predicates
- Protected predicates
 - ancestor/4
 - current_entity/1
 - declares_predicate/2
 - defines_predicate/2
 - defines_predicate/3
 - entity_calls/3
 - entity_kind/2
 - entity_property/2
 - entity_updates/3
 - not_excluded_file/3
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

ancestor/4

True if Entity descends from Ancestor, and EntityKind and AncestorKind unify with their respective entity types.

Compilation flags:

static

Template:

ancestor(EntityKind,Entity,AncestorKind,Ancestor)

Mode and number of proofs:

ancestor(?entity,?entity_identifier,?entity,?entity_identifier) - zero_or_more

current_entity/1

True if Entity is a currently loaded entity.

Compilation flags:

static

Template:

current_entity(Entity)

Mode and number of proofs:

current_entity(?entity_identifier) - zero_or_more

declares_predicate/2

True if Entity declares Predicate internally.

Compilation flags:

static

Template:

declares_predicate(Entity,Predicate)

Mode and number of proofs:

declares_predicate(?entity_identifier,?predicate_indicator) - zero_or_more

defines_predicate/2

True if Entity defines an implementation of Predicate internally. Auxiliary predicates are excluded from results.

Compilation flags:

static

Template:

defines_predicate(Entity,Predicate)

Mode and number of proofs:

defines_predicate(?entity_identifier,?predicate_indicator) - zero_or_more

`defines_predicate/3`

Same as `defines_predicate/2`, except `Property` is unified with a property of the predicate.

Compilation flags:

`static`

Template:

`defines_predicate(Entity,Predicate,Property)`

Mode and number of proofs:

`defines_predicate(?entity_identifier,?predicate_indicator,?term) - zero_or_more`

`entity_calls/3`

True if a predicate `Caller` within `Entity` makes a `Call`.

Compilation flags:

`static`

Template:

`entity_calls(Entity,Caller,Call)`

Mode and number of proofs:

`entity_calls(?entity_identifier,?predicate_indicator,?predicate_indicator) - zero_or_one`

`entity_kind/2`

True if `Kind` defines `Entity` and is one of `category`, `protocol`, or `object`.

Compilation flags:

`static`

Template:

`entity_kind(Entity,Kind)`

Mode and number of proofs:

`entity_kind(+entity_identifier,-entity) - zero_or_one`

`entity_property/2`

True if Property is a valid property of Entity. Entity can be either a category, a protocol, or an object.

Compilation flags:

`static`

Template:

`entity_property(Entity,Property)`

Mode and number of proofs:

`entity_property(+entity_identifier,-term) - zero_or_more`

`entity_updates/3`

True if a predicate Updater within Entity makes a dynamic update to Updated (by using e.g. the `asserta/1` or `retract/1` predicates).

Compilation flags:

`static`

Template:

`entity_updates(Entity,Updater,Updated)`

Mode and number of proofs:

`entity_updates(+entity_identifier,?predicate_indicator,?predicate_indicator) - zero_or_one`

`not_excluded_file/3`

True if the file is not being excluded.

Compilation flags:

`static`

Template:

```
not_excluded_file(ExcludedFiles,Path,Basename)
```

Mode and number of proofs:

```
not_excluded_file(+list(atom),+atom,+atom) - zero_or_one
```

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

object

1.6.6 coupling_metric

Computes entity efferent coupling, afferent coupling, and instability.

Availability:

```
logtalk_load(code_metrics(loader))
```

Author: Ebrahim Azarisooreh and Paulo Moura

Version: 0:14:0

Date: 2024-03-27

Compilation flags:

```
static, context_switching_calls
```

Imports:

```
public code_metrics_utilities  
public code_metric
```

Uses:

```
list
```

Remarks:

- Efferent coupling (Ce): Number of entities that an entity depends on.
- Afferent coupling (Ca): Number of entities that depend on an entity.

- Instability (I): Computed as $Ce / (Ce + Ca)$. Measures the entity resilience to change. Ranging from 0 to 1, with 0 indicating a maximally stable entity and 1 indicating a maximally unstable entity. Ideally, an entity is either maximally stable or maximally unstable.
- Abstractness (A): Computed as the ratio between the number of static predicates with scope directives without a local definition and the number of static predicates with scope directives. Measures the rigidity of an entity. Ranging from 0 to 1, with 0 indicating a fully concrete entity and 1 indicating a fully abstract entity.
- Entity score: Represented as the compound term `ce_ca_i_a(Ce,Ca,I,A)`.
- Dependencies count: Includes direct entity relations plus calls or dynamic updates to predicates in external objects or categories.

Inherited public predicates:

```
all/0 all/1 all_score/1 check_option/1 check_options/1 default_option/1 default_options/1
directory/1 directory/2 directory_score/2 entity/1 entity_score/2 file/1 file/2 file_score/2
format_entity_score//2 library/1 library/2 library_score/2 option/2 option/3 rdirectory/1
rdirectory/2 rdirectory_score/2 rlibrary/1 rlibrary/2 rlibrary_score/2 valid_option/1
valid_options/1
```

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

object

1.6.7 dit_metric

Analyzes the depth of inheritance for objects, protocols, and categories.

Availability:

```
logtalk_load(code_metrics(loader))
```

Author: Ebrahim Azarisooreh

Version: 0:6:1

Date: 2024-03-28

Compilation flags:

```
static, context_switching_calls
```

Imports:

```
public code_metrics_utilities
```

```
public code_metric
```

Uses:

```
numberlist
```

Remarks:

- Depth: The depth is the maximum length of a node to the root entity. Lower scores are generally better.
- Inheritance: A level of inheritance defined by either one of specialization, instantiation, extension, importation, or implementation.
- Scoring: The maximum path length is determined for each entity in question.

Inherited public predicates:

```
all/0 all/1 all_score/1 check_option/1 check_options/1 default_option/1 default_options/1  
directory/1 directory/2 directory_score/2 entity/1 entity_score/2 file/1 file/2 file_score/2  
format_entity_score//2 library/1 library/2 library_score/2 option/2 option/3 rdirectory/1  
rdirectory/2 rdirectory_score/2 rlibrary/1 rlibrary/2 rlibrary_score/2 valid_option/1  
valid_options/1
```

- [Public predicates](#)
- [Protected predicates](#)
- [Private predicates](#)
- [Operators](#)

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

object

1.6.8 doc_metric

Entity and entity predicates documentation score.

Availability:

```
logtalk_load(code_metrics(loader))
```

Author: Paulo Moura

Version: 0:13:0

Date: 2022-05-05

Compilation flags:

```
static, context_switching_calls
```

Imports:

```
public code_metrics_utilities  
public code_metric
```

Uses:

```
list
```

numberlist

Remarks:

- Score range: Score is a integer percentage where a 100% score means that all expected documentation information is present.
- Score weights: The score is split by default between 20% for the entity documentation and 80% for the entity predicates documentation, Can be customized using the predicate `entity_predicates_weights_hook/2`.
- Score customization: The individual scores of entity info/1 pairs and predicate info/2 pairs can be customized using the `entity_info_pair_score_hook/3` and `predicate_info_pair_score_hook/4` predicates.

Inherited public predicates:

`all/0 all/1 all_score/1 check_option/1 check_options/1 default_option/1 default_options/1 directory/1 directory/2 directory_score/2 entity/1 entity_score/2 file/1 file/2 file_score/2 format_entity_score//2 library/1 library/2 library_score/2 option/2 option/3 rdirectory/1 rdirectory/2 rdirectory_score/2 rlibrary/1 rlibrary/2 rlibrary_score/2 valid_option/1 valid_options/1`

- Public predicates
 - `entity_predicates_weights_hook/2`
 - `entity_info_score_hook/2`
 - `entity_info_pair_score_hook/3`
 - `predicate_mode_score_hook/3`
 - `predicate_mode_score_hook/5`
 - `predicate_info_score_hook/3`
 - `predicate_info_pair_score_hook/4`
- Protected predicates
- Private predicates
- Operators

Public predicates

`entity_predicates_weights_hook/2`

Relative weight between entity documentation and predicates documentation in percentage. The sum of the two values must be equal to 100.

Compilation flags:

`dynamic, multifile`

Template:

entity_predicates_weights_hook(EntityWeight,PredicatesWeight)

Mode and number of proofs:

entity_predicates_weights_hook(?integer,?integer) - zero_or_one

entity_info_score_hook/2

Maximum score for entity info/1 directives.

Compilation flags:

dynamic, multifile

Template:

entity_info_score_hook(Entity,MaximumScore)

Mode and number of proofs:

entity_info_score_hook(?term,?integer) - zero_or_one

entity_info_pair_score_hook/3

Score for relevant entity info/1 directive pairs. If defined, the entity_info_score_hook/2 predicate should be defined accordingly.

Compilation flags:

dynamic, multifile

Template:

entity_info_pair_score_hook(Pair,Entity,Score)

Mode and number of proofs:

entity_info_pair_score_hook(?callable,?term,?integer) - zero_or_more

predicate_mode_score_hook/3

Maximum score for predicate mode/2 directives.

Compilation flags:

dynamic, multifile

Template:

predicate_mode_score_hook(Entity,Predicate,MaximumScore)

Mode and number of proofs:

predicate_mode_score_hook(?term,?term,?integer) - zero_or_more

predicate_mode_score_hook/5

Score for a predicate mode/2 directive. If defined, the predicate_mode_score_hook/3 predicate should be defined accordingly.

Compilation flags:

dynamic, multifile

Template:

predicate_mode_score_hook(Template,Solutions,Entity,Predicate,Score)

Mode and number of proofs:

predicate_mode_score_hook(?term,?term,?term,?term,?integer) - zero_or_one

predicate_info_score_hook/3

Maximum score for predicate info/2 directives.

Compilation flags:

dynamic, multifile

Template:

predicate_info_score_hook(Entity,Predicate,MaximumScore)

Mode and number of proofs:

predicate_info_score_hook(?term,?term,?integer) - zero_or_one

predicate_info_pair_score_hook/4

Score for a predicate info/2 directive pairs. If defined, the predicate_info_score_hook/3 predicate should be defined accordingly.

Compilation flags:
dynamic, multifile

Template:
predicate_info_pair_score_hook(Pair,Entity,Predicate,Score)
Mode and number of proofs:
predicate_info_pair_score_hook(?callable,?term,?term,?integer) - zero_or_more

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

object

1.6.9 halstead_metric

Computes Halstead complexity numbers for an entity using a Stroud of 18.

Availability:
logtalk_load(code_metrics(loader))

Author: Paulo Moura
Version: 1:0:0
Date: 2018-06-08

Compilation flags:

static, context_switching_calls

Extends:

public halstead_metric(18)

Remarks:

(none)

Inherited public predicates:

all/0 all/1 all_score/1 check_option/1 check_options/1 default_option/1 default_options/1
directory/1 directory/2 directory_score/2 entity/1 entity_score/2 file/1 file/2 file_score/2
format_entity_score//2 library/1 library/2 library_score/2 option/2 option/3 rdirectory/1
rdirectory/2 rdirectory_score/2 rlibrary/1 rlibrary/2 rlibrary_score/2 valid_option/1
valid_options/1

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

object

1.6.10 `halstead_metric`(Stroud)

- Stroud - Coefficient for computing the time required to program.

Computes Halstead complexity numbers for an entity.

Availability:

```
logtalk_load(code_metrics(loader))
```

Author: Paulo Moura

Version: 0:9:0

Date: 2024-03-27

Compilation flags:

```
static, context_switching_calls
```

Imports:

```
public code_metrics_utilities
public code_metric
```

Uses:

```
list
numberlist
pairs
```

Remarks:

- Definition of operators: Predicates declared, user-defined, and called are interpreted as operators. Built-in predicates and built-in control constructs are ignored.
- Definition of operands: Predicate arguments are abstracted and interpreted as operands. Note that this definition of operands is a significant deviation from the original definition, which used syntactic literals.
- P_n : Number of distinct predicates (declared, defined, called, or updated).
- PAn : Number of predicate arguments (assumed distinct).
- C_n : Number of predicate calls/updates + number of clauses.
- CAn : Number of predicate call/update arguments + number of clause head arguments.
- EV: Entity vocabulary: $EV = P_n + PAn$.
- EL: Entity length: $EL = C_n + CAn$.
- V: Volume: $V = EL * \log_2(EV)$.
- D: Difficulty: $D = (P_n/2) * (CAn/An)$.
- E: Effort: $E = D * V$.
- T: Time required to program: $T = E/k$ seconds (k is the Stroud number; defaults to 18).

- B: Number of delivered bugs: $B = V/3000$.
- Entity score: Represented as the compound term `pn_pan_cn_can_ev_el_v_d_e_t_b/11`.

Inherited public predicates:

`all/0 all/1 all_score/1 check_option/1 check_options/1 default_option/1 default_options/1
directory/1 directory/2 directory_score/2 entity/1 entity_score/2 file/1 file/2 file_score/2
format_entity_score//2 library/1 library/2 library_score/2 option/2 option/3 rdirectory/1
rdirectory/2 rdirectory_score/2 rlibrary/1 rlibrary/2 rlibrary_score/2 valid_option/1
valid_options/1`

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

object

1.6.11 `noc_metric`

Number of entity clauses metric. The score is represented using the compound term `number_of_clauses(Total, User)`.

Availability:

`logtalk_load(code_metrics(loader))`

Author: Ebrahim Azarisooreh and Paulo Moura

Version: 0:14:0
Date: 2024-03-28

Compilation flags:
static, context_switching_calls

Imports:
public code_metrics_utilities
public code_metric

Provides:
logtalk::message_tokens//2

Uses:
list
logtalk

Remarks:
(none)

Inherited public predicates:
all/0 all/1 all_score/1 check_option/1 check_options/1 default_option/1 default_options/1
directory/1 directory/2 directory_score/2 entity/1 entity_score/2 file/1 file/2 file_score/2
format_entity_score//2 library/1 library/2 library_score/2 option/2 option/3 rdirectory/1
rdirectory/2 rdirectory_score/2 rlibrary/1 rlibrary/2 rlibrary_score/2 valid_option/1
valid_options/1

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

object

1.6.12 `nor_metric`

Number of entity rules metric. The score is represented using the compound term `number_of_rules(Total, User)`.

Availability:

```
logtalk_load(code_metrics(loader))
```

Author: Paulo Moura

Version: 0:5:0

Date: 2024-03-28

Compilation flags:

```
static, context_switching_calls
```

Imports:

```
public code_metrics_utilities
```

```
public code_metric
```

Provides:

```
logtalk::message_tokens//2
```

Uses:

```
list
```

```
logtalk
```

Remarks:

```
(none)
```


Inherited public predicates:

all/0 all/1 all_score/1 check_option/1 check_options/1 default_option/1 default_options/1
 directory/1 directory/2 directory_score/2 entity/1 entity_score/2 file/1 file/2 file_score/2
 format_entity_score//2 library/1 library/2 library_score/2 option/2 option/3 rdirectory/1
 rdirectory/2 rdirectory_score/2 rlibrary/1 rlibrary/2 rlibrary_score/2 valid_option/1
 valid_options/1

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

object

1.6.13 size_metric

Source code size metric. Returned scores are upper bounds and based solely in source file sizes (expressed in bytes).

Availability:

```
logtalk_load(code_metrics(loader))
```

Author: Paulo Moura

Version: 0:7:0

Date: 2024-03-28

Compilation flags:

static, context_switching_calls

Imports:

public code_metrics_utilities
public code_metric

Provides:

logtalk::message_tokens//2

Uses:

list
logtalk
numberlist
os

Remarks:

(none)

Inherited public predicates:

all/0 all/1 all_score/1 check_option/1 check_options/1 default_option/1 default_options/1
directory/1 directory/2 directory_score/2 entity/1 entity_score/2 file/1 file/2 file_score/2
format_entity_score//2 library/1 library/2 library_score/2 option/2 option/3 rdirectory/1
rdirectory/2 rdirectory_score/2 rlibrary/1 rlibrary/2 rlibrary_score/2 valid_option/1
valid_options/1

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

object

1.6.14 upn_metric

Number of unique predicates nodes metric. The nodes include called and updated predicates independently of where they are defined. The score is represented by a non-negative integer.

Availability:

```
logtalk_load(code_metrics(loader))
```

Author: Paulo Moura

Version: 0:6:0

Date: 2024-03-28

Compilation flags:

```
static, context_switching_calls
```

Imports:

```
public code_metrics_utilities
```

```
public code_metric
```

Provides:

```
logtalk::message_tokens//2
```

Uses:

```
list
```

```
logtalk
```

```
numberlist
```

Remarks:

(none)

Inherited public predicates:

```
all/0 all/1 all_score/1 check_option/1 check_options/1 default_option/1 default_options/1
directory/1 directory/2 directory_score/2 entity/1 entity_score/2 file/1 file/2 file_score/2
format_entity_score//2 library/1 library/2 library_score/2 option/2 option/3 rdirectory/1
rdirectory/2 rdirectory_score/2 rlibrary/1 rlibrary/2 rlibrary_score/2 valid_option/1
valid_options/1
```

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

1.7 core

category

1.7.1 core_messages

Logtalk core (compiler and runtime) default message tokenization.

Availability:

`built_in`

Author: Paulo Moura

Version: 1:132:0

Date: 2024-03-02

Compilation flags:

`static`

Provides:

logtalk::message_prefix_stream/4
logtalk::message_tokens//2

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

protocol

1.7.2 expanding

Term and goal expansion protocol.

Availability:

built_in

Author: Paulo Moura

Version: 1:1:0

Date: 2016-07-12

Compilation flags:
static, built_in

Dependencies:
(none)

Remarks:
(none)

Inherited public predicates:
(none)

- Public predicates
 - goal_expansion/2
 - term_expansion/2
- Protected predicates
- Private predicates
- Operators

Public predicates

goal_expansion/2

Defines a goal expansion. Called recursively until a fixed point is reached on goals found while compiling a source file (except for goals wrapped using the `{}/1` compiler bypass control construct).

Compilation flags:
static

Template:
goal_expansion(Goal,ExpandedGoal)
Mode and number of proofs:
goal_expansion(+callable,-callable) - zero_or_one

term_expansion/2

Defines a term expansion. Called until it succeeds on all terms read while compiling a source file (except for terms skipped by using the conditional compilation directives or wrapped using the `{}/1` compiler bypass control construct).

Compilation flags:

static

Template:

term_expansion(Term,ExpandedTerms)

Mode and number of proofs:

term_expansion(+term,-term) - zero_or_one

term_expansion(+term,-list(term)) - zero_or_one

Protected predicates

(none)

Private predicates

(none)

Operators

(none)

protocol

1.7.3 forwarding

Message forwarding protocol.

Availability:

built_in

Author: Paulo Moura

Version: 1:0:0

Date: 2013-05-04

Compilation flags:

static, built_in

Dependencies:

(none)

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
 - forward/1
- Protected predicates
- Private predicates
- Operators

Public predicates

forward/1

User-defined message forwarding handler, automatically called (if defined) by the runtime for any message that the receiving object does not understand.

Compilation flags:

static

Template:

forward(Message)

Mode and number of proofs:

forward(@callable) - zero_or_more

Protected predicates

(none)

Private predicates

(none)

Operators

(none)

object

1.7.4 logtalk

Built-in object providing message printing, debugging, library, source file, and hacking methods.

Availability:

`built_in`

Author: Paulo Moura

Version: 1:23:0

Date: 2024-03-27

Compilation flags:

`static, built_in, context_switching_calls, threaded`

Dependencies:

(none)

Remarks:

- Default message kinds: `silent`, `silent(Key)`, `banner`, `help`, `comment`, `comment(Key)`, `information`, `information(Key)`, `warning`, `warning(Key)`, `error`, `error(Key)`, `debug`, `debug(Key)`, `question`, and `question(Key)`.
- Printing of silent messages: By default, silent messages are not printed. These messages are only useful when intercepted.
- Printing of banner and comment messages: By default, banner and comment messages are only printed when the report flag is turned on.
- Printing of help, information, and question messages: These messages are always printed by default as they provide requested output.
- Printing of warning messages: By default, warning messages are not printed when the report flag is turned off.

- Printing of error messages: These messages are always printed by default.
- Printing of debug messages: By default, debug messages are only printed when the debug flag is turned on. The compiler suppresses debug message printing goals when compiling in optimized mode.
- Meta messages: A meta message is a message that have another message as argument and is typically used for debugging messages. Meta messages avoid the need of defining tokenizer rules for every message but can be intercepted as any other message.
- Meta message @Message: By default, the message is printed as passed to the write/1 predicate followed by a newline.
- Meta message Key-Value: By default, the message is printed as “Key: Value” followed by a newline. The key is printed as passed to the write/1 predicate while the value is printed as passed to the writeq/1 predicate.
- Meta message Format+Arguments: By default, the message is printed as passed to the format/2 predicate.
- Meta message List: By default, the list items are printed indented one per line. The items are preceded by a dash and can be @Message, Key-Value, or Format+Arguments messages. If that is not the case, the item is printed as passed to the writeq/1 predicate.
- Meta message Title::List: By default, the title is printed followed by a newline and the indented list items, one per line. The items are printed as in the List meta message.
- Meta message [Stream,Prefix]>>Goal: By default, call user-defined Goal in the context of user. The use of a lambda expression allows passing the message stream and prefix. Printing the prefix is delegated to the goal.
- Meta message [Stream]>>Goal: By default, call user-defined Goal in the context of user. The use of a lambda expression allows passing the message stream.
- Message tokens: at_same_line, tab(Expression), nl, flush, Format-Arguments, term(Term,Options), ansi(Attributes,Format,Arguments), begin(Kind,Variable), and end(Variable).

Inherited public predicates:

(none)

- Public predicates
 - print_message/3
 - print_message_tokens/3
 - print_message_token/4
 - message_tokens//2
 - message_prefix_stream/4
 - message_hook/4
 - ask_question/5
 - question_hook/6
 - question_prompt_stream/4
 - trace_event/2

- debug_handler_provider/1
- debug_handler/2
- expand_library_path/2
- loaded_file/1
- loaded_file_property/2
- file_type_extension/2
- compile_aux_clauses/1
- entity_prefix/2
- compile_predicate_heads/4
- compile_predicate_indicators/3
- decompile_predicate_heads/4
- decompile_predicate_indicators/4
- execution_context/7
- Protected predicates
- Private predicates
- Operators

Public predicates

print_message/3

Prints a message of the given kind for the specified component.

Compilation flags:

static

Template:

print_message(Kind,Component,Message)

Mode and number of proofs:

print_message(+nonvar,+nonvar,+nonvar) - one

`print_message_tokens/3`

Print the messages tokens to the given stream, prefixing each line with the specified atom.

Compilation flags:

`static`

Template:

`print_message_tokens(Stream,Prefix,Tokens)`

Mode and number of proofs:

`print_message_tokens(@stream_or_alias,+atom,@list(nonvar)) - one`

`print_message_token/4`

User-defined hook predicate for printing a message token (see this object remarks).

Compilation flags:

`dynamic, multifile`

Template:

`print_message_token(Stream,Prefix,Token,Tokens)`

Mode and number of proofs:

`print_message_token(@stream_or_alias,@atom,@nonvar,@list(nonvar)) - zero_or_one`

`message_tokens//2`

User-defined hook grammar rule for converting a message into a list of tokens (see this object remarks).

Compilation flags:

`dynamic, multifile`

Template:

`message_tokens(Message,Component)`

Mode and number of proofs:

`message_tokens(+nonvar,+nonvar) - zero_or_one`

message_prefix_stream/4

Message line prefix and output stream to be used when printing a message given its kind and component.

Compilation flags:

dynamic, multifile

Template:

message_prefix_stream(Kind,Component,Prefix,Stream)

Mode and number of proofs:

message_prefix_stream(?nonvar,?nonvar,?atom,?stream_or_alias) - zero_or_more

message_hook/4

User-defined hook predicate for intercepting message printing calls.

Compilation flags:

dynamic, multifile

Template:

message_hook(Message,Kind,Component,Tokens)

Mode and number of proofs:

message_hook(+nonvar,+nonvar,+nonvar,+list(nonvar)) - zero_or_one

ask_question/5

Asks a question and reads the answer until the check predicate is true.

Compilation flags:

static

Template:

ask_question(Kind,Component,Question,Check,Answer)

Meta-predicate template:

ask_question(*,*,*,1,*)

Mode and number of proofs:

ask_question(+nonvar,+nonvar,+nonvar,+callable,-term) - one

question_hook/6

User-defined hook predicate for intercepting question asking calls.

Compilation flags:

dynamic, multifile

Template:

```
question_hook(Question,Kind,Component,Tokens,Check,Answer)
```

Meta-predicate template:

```
question_hook(*,*,*,*,1,*)
```

Mode and number of proofs:

```
question_hook(+nonvar,+nonvar,+nonvar,+list(nonvar),+callable,-term) - zero_or_one
```

question_prompt_stream/4

Prompt and input stream to be used when asking a question given its kind and component.

Compilation flags:

dynamic, multifile

Template:

```
question_prompt_stream(Kind,Component,Prompt,Stream)
```

Mode and number of proofs:

```
question_prompt_stream(?nonvar,?nonvar,?atom,?stream_or_alias) - zero_or_more
```

trace_event/2

Trace event handler. The runtime calls all trace event handlers using a failure-driven loop before calling the debug event handler.

Compilation flags:

dynamic, multifile

Template:

```
trace_event(Event,ExecutionContext)
```

Mode and number of proofs:

```
trace_event(@callable,@execution_context) - zero
```

Remarks:

- Unification events: Generated after a successful unification with a fact - fact(Entity,Fact,Clause,File,Line) - or a rule head - rule(Entity,Head,Clause,File,Line).
- Goal events: Generated when calling a goal: top_goal(Goal,CompiledGoal) or goal(Goal,CompiledGoal).

debug_handler_provider/1

Declares an object as the debug handler provider. There should be at most one debug handler provider loaded at any given moment.

Compilation flags:

```
static, multifile
```

Template:

```
debug_handler_provider(Provider)
```

Mode and number of proofs:

```
debug_handler_provider(?object_identifier) - zero_or_one
```

debug_handler/2

Debug event handler. Called by the runtime. When the call succeeds, the runtime assumes the event have been handled. In the case of a goal event, that the goal succeeded (possibly leaving choice-points that can be explored by backtracking).

Compilation flags:

```
static, multifile
```

Template:

```
debug_handler(Event,ExecutionContext)
```

Mode and number of proofs:

```
debug_handler(?entity_identifier,?atom) - zero_or_more
```

Remarks:

- Unification events: Generated after a successful unification with a fact - fact(Entity,Fact,Clause,File,Line) - or a rule head - rule(Entity,Head,Clause,File,Line).
 - Goal events: Generated when calling a goal: top_goal(Goal,CompiledGoal) or goal(Goal,CompiledGoal).
-

expand_library_path/2

Expands a library alias or a library path into its absolute path. Uses a depth bound to prevent loops.

Compilation flags:

static

Template:

expand_library_path(LibraryPath,AbsolutePath)

Mode and number of proofs:

expand_library_path(+atom,?atom) - zero_or_one

expand_library_path(+callable,?atom) - zero_or_one

loaded_file/1

Enumerates, by backtracking, all loaded files, returning their full paths.

Compilation flags:

static

Template:

loaded_file(Path)

Mode and number of proofs:

loaded_file(?atom) - zero_or_more

loaded_file_property/2

Enumerates, by backtracking, loaded file properties.

Compilation flags:

static

Template:

loaded_file_property(Path,Property)

Mode and number of proofs:

loaded_file_property(?atom,?compound) - zero_or_more

Remarks:

- Property basename/1: Basename of the file (includes the file extension, if any).
- Property directory/1: Directory of the file (ending with a slash).
- Property mode/1: Compilation mode of the file (possible values are optimal, normal, and debug).
- Property flags/1: Explicit flags used for compiling the file.
- Property text_properties/1: List of the file text properties (encoding/1 and bom/1). Empty if no encoding/1 directive is present and the stream used for reading the file does not have a bom/1 (or equivalent) property.
- Property target/1: Full path of the generated intermediate Prolog file.
- Property modified/1: File modification time stamp (should be regarded as an opaque but otherwise comparable term).
- Property parent/1: Full path of the parent file that loaded the file.
- Property includes/1: Full path of a file included by the file.
- Property library/1: Library alias for the library that includes the file.
- Property object/1: Identifier for an object defined in the file.
- Property protocol/1: Identifier for a protocol defined in the file.
- Property category/1: Identifier for a category defined in the file.

file_type_extension/2

Enumerates, by backtracking, all defined file type extensions. The defined types are: source, object, logtalk, prolog, and tmp. The source type returns both logtalk and prolog type extensions.

Compilation flags:

static

Template:

file_type_extension(Type,Extension)

Mode and number of proofs:

file_type_extension(?atom,?atom) - zero_or_more

compile_aux_clauses/1

Compiles a list of auxiliary clauses. Can only be called during source file compilation, usually from term_expansion/2 or goal_expansion/2 hook predicate definitions.

Compilation flags:

static

Template:

compile_aux_clauses(Clauses)

Mode and number of proofs:

compile_aux_clauses(@list(clause)) - one

entity_prefix/2

Converts between an entity identifier and the entity prefix that is used for its compiled code. When none of the arguments is instantiated, it returns the identifier and the prefix of the entity under compilation, if any.

Compilation flags:

static

Template:

entity_prefix(Entity,Prefix)

Mode and number of proofs:

entity_prefix(?entity_identifier,?atom) - zero_or_one

`compile_predicate_heads/4`

Compiles clause heads. The heads are compiled in the context of the entity under compilation when the entity argument is not instantiated.

Compilation flags:

static

Template:

`compile_predicate_heads(Heads,Entity,CompiledHeads,ExecutionContext)`

Mode and number of proofs:

`compile_predicate_heads(@list(callable),?entity_identifier,-list(callable),@execution_context) - zero_or_one`

`compile_predicate_heads(@conjunction(callable),?entity_identifier,-conjunction(callable),@execution_context) - zero_or_one`

`compile_predicate_heads(@callable,?entity_identifier,-callable,@execution_context) - zero_or_one`

`compile_predicate_indicators/3`

Compiles predicate indicators. The predicate are compiled in the context of the entity under compilation when the entity argument is not instantiated.

Compilation flags:

static

Template:

`compile_predicate_indicators(PredicateIndicators,Entity,CompiledPredicateIndicators)`

Mode and number of proofs:

`compile_predicate_indicators(@list(predicate_indicator),?entity_identifier,-list(predicate_indicator)) - zero_or_one`

`compile_predicate_indicators(@conjunction(predicate_indicator),?entity_identifier,-conjunction(predicate_indicator)) - zero_or_one`

`compile_predicate_indicators(@predicate_indicator,?entity_identifier,-predicate_indicator) - zero_or_one`

decompile_predicate_heads/4

Decompiles clause heads. All compiled clause heads must belong to the same entity, which must be loaded.

Compilation flags:

static

Template:

decompile_predicate_heads(CompiledHeads,Entity,Type,Heads)

Mode and number of proofs:

decompile_predicate_heads(@list(callable),-entity_identifier,-atom,-list(callable)) - zero_or_one

decompile_predicate_heads(@conjunction(callable),-entity_identifier,-atom,-conjunction(callable)) - zero_or_one

decompile_predicate_heads(@callable,-entity_identifier,-atom,-callable) - zero_or_one

decompile_predicate_indicators/4

Decompiles predicate indicators. All compiled predicate indicators must belong to the same entity, which must be loaded.

Compilation flags:

static

Template:

decompile_predicate_indicators(CompiledPredicateIndicators,Entity,Type,PredicateIndicators)

Mode and number of proofs:

decompile_predicate_indicators(@list(predicate_indicator),-entity_identifier,-atom,
-list(predicate_indicator)) - zero_or_one

decompile_predicate_indicators(@conjunction(predicate_indicator),-entity_identifier,-atom,
-conjunction(predicate_indicator)) - zero_or_one

decompile_predicate_indicators(@predicate_indicator,-entity_identifier,-atom,-predicate_indicator)
- zero_or_one

execution_context/7

Execution context term data. Execution context terms should be considered opaque terms subject to change without notice.

Compilation flags:

static

Template:

execution_context(ExecutionContext,Entity,Sender,This,Self,MetaCallContext,CoinductionStack)

Mode and number of proofs:

execution_context(?nonvar,?entity_identifier,?object_identifier,?object_identifier,?object_identifier,
@list(callable),@list(callable)) - zero_or_one

Protected predicates

(none)

Private predicates

(none)

Operators

(none)

protocol

1.7.5 monitoring

Event handlers protocol. The handlers are automatically called by the runtime for messages sent using the `::/2` control construct from objects or categories compiled with the events flag set to allow.

Availability:

built_in

Author: Paulo Moura

Version: 1:2:0

Date: 2018-11-29

Compilation flags:

static, built_in

Dependencies:

(none)

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
 - before/3
 - after/3
- Protected predicates
- Private predicates
- Operators

Public predicates

before/3

Event handler for before events. A before event handler may prevent a method from being looked up or called by failing.

Compilation flags:

static

Template:

before(Object,Message,Sender)

Mode and number of proofs:

before(?term,?term,?term) - zero_or_more

after/3

Event handler for after events. An after event handler may prevent a method from succeeding by failing.

Compilation flags:

static

Template:

after(Object,Message,Sender)

Mode and number of proofs:

after(?term,?term,?term) - zero_or_more

Protected predicates

(none)

Private predicates

(none)

Operators

(none)

object

1.7.6 user

Pseudo-object representing the plain Prolog database. Can be used as a monitor by defining before/3 and after/3 predicates. Can be used as a hook object by defining term_expansion/2 and goal_expansion/2 multifile and dynamic predicates.

Availability:

built_in

Author: Paulo Moura

Version: 1:5:0

Date: 2022-10-12

Compilation flags:

static, built_in, context_switching_calls, dynamic_declarations, threaded

Implements:

public expanding
public forwarding
public monitoring

Uses:

user

Remarks:

(none)

Inherited public predicates:

after/3 before/3 forward/1 goal_expansion/2 term_expansion/2

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

1.8 coroutining

object

1.8.1 coroutining

Coroutining predicates.

Availability:

```
logtalk_load(coroutining(loader))
```

Author: Paulo Moura

Version: 0:5:0

Date: 2021-12-17

Compilation flags:

```
static, context_switching_calls
```

Dependencies:

(none)

Remarks:

- Supported backend Prolog systems: ECLiPSe, LVM, SICStus Prolog, SWI-Prolog, Trealla Prolog, and YAP.

Inherited public predicates:

(none)

- Public predicates
 - dif/2
 - dif/1
 - freeze/2
 - frozen/2
 - when/2
- Protected predicates
- Private predicates
- Operators

Public predicates

dif/2

Sets a constraint that is true iff the two terms are different.

Compilation flags:

static

Template:

dif(Term1,Term2)

Mode and number of proofs:

dif(+term,+term) - zero_or_one

dif/1

Sets a set of constraints that are true iff all terms in a list are different.

Compilation flags:

static

Template:

dif(Terms)

Mode and number of proofs:

dif(+list(term)) - zero_or_one

freeze/2

Delays the execution of a goal until a variable is bound.

Compilation flags:

static

Template:

freeze(Variable,Goal)

Meta-predicate template:

freeze(*,0)

Mode and number of proofs:

`freeze(+term,+callable) - zero_or_more`

`frozen/2`

Unifies Goal with the goal delayed by Variable. When no goals are frozen on Variable, Goal is unified with true.

Compilation flags:

`static`

Template:

`frozen(Variable,Goal)`

Mode and number of proofs:

`frozen(@var,--callable) - one`

`when/2`

Calls Goal when Condition becomes true. The portable conditions are: `nonvar/1`, `ground/1`, `(,)/2`, and `(;)/2`.

Compilation flags:

`static`

Template:

`when(Condition,Goal)`

Meta-predicate template:

`when(*,0)`

Mode and number of proofs:

`when(+callable,+callable) - zero_or_more`

Protected predicates

(none)

Private predicates

(none)

Operators

(none)

1.9 csv

object

1.9.1 csv

CSV files reading and writing predicates using the options Header - keep, Separator - comma, and Ignore-Quotes - false.

Availability:

```
logtalk_load(csv(loader))
```

Author: Jacinto Dávila

Version: 1:0:0

Date: 2021-02-02

Compilation flags:

```
static, context_switching_calls
```

Extends:

```
public csv(keep,comma,false)
```

Remarks:

(none)

Inherited public predicates:

```
guess_arity/2 guess_separator/2 read_file/2 read_file/3 read_file_by_line/2  
read_file_by_line/3 read_stream/2 read_stream/3 read_stream_by_line/2  
read_stream_by_line/3 write_file/3 write_stream/3
```

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

object

1.9.2 csv(Header,Separator,IgnoreQuotes)

- Header - Header handling option with possible values missing, skip, and keep (default).
- Separator - Separator handling option with possible values comma (default for non .tsv and non .tab files or when no file name extension is available), tab (default for .tsv and .tab files), semicolon, and colon.
- IgnoreQuotes - Double-quotes handling option to ignore (true) or preserve (false; default) double quotes surrounding data.

CSV file and stream reading and writing predicates.

Availability:

```
logtalk_load(csv(loader))
```

Author: Jacinto Dávila and Paulo Moura

Version: 2:1:0

Date: 2023-11-15

Compilation flags:

```
static, context_switching_calls
```

Implements:

public csv_protocol

Uses:

list
logtalk
os
reader
type

Remarks:

(none)

Inherited public predicates:

guess_arity/2 guess_separator/2 read_file/2 read_file/3 read_file_by_line/2
read_file_by_line/3 read_stream/2 read_stream/3 read_stream_by_line/2
read_stream_by_line/3 write_file/3 write_stream/3

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

category

1.9.3 csv_guess_questions

Support for asking questions when guessing the separator and the record arity of CSV files.

Availability:

```
logtalk_load(csv(loader))
```

Author: Jacinto Dávila

Version: 1:0:0

Date: 2021-02-03

Compilation flags:

```
static
```

Provides:

```
logtalk::message_tokens//2
```

```
logtalk::question_prompt_stream/4
```

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

protocol

1.9.4 csv_protocol

CSV file and stream reading and writing protocol.

Availability:

`logtalk_load(csv(loader))`

Author: Jacinto Dávila and Paulo Moura

Version: 2:0:0

Date: 2023-03-13

Compilation flags:

`static`

Dependencies:

(none)

Remarks:

- Type-checking: Some of the predicate file and stream argument type-checking exceptions depend on the Prolog backend compliance with standards.

Inherited public predicates:

(none)

- Public predicates
 - read_file/3
 - read_stream/3
 - read_file/2
 - read_stream/2
 - read_file_by_line/3
 - read_stream_by_line/3
 - read_file_by_line/2
 - read_stream_by_line/2
 - write_file/3
 - write_stream/3
 - guess_separator/2
 - guess_arity/2
- Protected predicates
- Private predicates
- Operators

Public predicates

read_file/3

Reads a CSV file saving the data as clauses for the specified object predicate. Fails if the file cannot be parsed.

Compilation flags:

static

Template:

read_file(File, Object, Predicate)

Mode and number of proofs:

read_file(+atom, +object_identifier, +predicate_indicator) - zero_or_one

Exceptions:

File is a variable:

instantiation_error

File is neither a variable nor an atom:

type_error(atom, File)

File is an atom but not an existing file:

existence_error(file, File)

File is an existing file but cannot be opened for reading:

`permission_error(open,source_sink,File)`

Object is a variable:

`instantiation_error`

Object is neither a variable nor an object identifier:

`type_error(object_identifier,Object)`

Object is a valid object identifier but not an existing object:

`existence_error(object,Object)`

Predicate is a variable:

`instantiation_error`

Predicate is neither a variable nor a predicate indicator:

`type_error(predicate_indicator,Predicate)`

Predicate is a valid predicate indicator but not an existing public predicate:

`existence_error(predicate,Predicate)`

`read_stream/3`

Reads a CSV stream saving the data as clauses for the specified object predicate. Fails if the stream cannot be parsed.

Compilation flags:

`static`

Template:

`read_stream(Stream,Object,Predicate)`

Mode and number of proofs:

`read_stream(+stream_or_alias,+object_identifier,+predicate_indicator) - zero_or_one`

Exceptions:

Stream is a variable:

`instantiation_error`

Stream is neither a variable nor a stream-term or alias:

`domain_error(stream_or_alias,Stream)`

Stream is not an open stream:

`existence_error(stream,Stream)`

Stream is an output stream:

`permission_error(input,stream,Stream)`

Stream is a binary stream:

`permission_error(input,binary_stream,Stream)`

Object is a variable:

`instantiation_error`

Object is neither a variable nor an object identifier:

```

    type_error(object_identifier,Object)
Object is a valid object identifier but not an existing object:
    existence_error(object,Object)
Predicate is a variable:
    instantiation_error
Predicate is neither a variable nor a predicate indicator:
    type_error(predicate_indicator,Predicate)
Predicate is a valid predicate indicator but not an existing public predicate:
    existence_error(predicate,Predicate)

```

read_file/2

Reads a CSV file returning the data as a list of rows, each row a list of fields. Fails if the file cannot be parsed.

Compilation flags:

```
static
```

Template:

```
read_file(File,Rows)
```

Mode and number of proofs:

```
read_file(+atom,-list(list)) - zero_or_one
```

Exceptions:

File is a variable:

```
instantiation_error
```

File is neither a variable nor an atom:

```
type_error(atom,File)
```

File is an atom but not an existing file:

```
existence_error(file,File)
```

File is an existing file but cannot be opened for reading:

```
permission_error(open,source_sink,File)
```

read_stream/2

Reads a CSV stream returning the data as a list of rows, each row a list of fields. Fails if the stream cannot be parsed.

Compilation flags:

static

Template:

read_stream(Stream,Rows)

Mode and number of proofs:

read_stream(+stream_or_alias,-list(list)) - zero_or_one

Exceptions:

Stream is a variable:

instantiation_error

Stream is neither a variable nor a stream-term or alias:

domain_error(stream_or_alias,Stream)

Stream is not an open stream:

existence_error(stream,Stream)

Stream is an output stream:

permission_error(input,stream,Stream)

Stream is a binary stream:

permission_error(input,binary_stream,Stream)

read_file_by_line/3

Reads a CSV file saving the data as clauses for the specified object predicate. The file is read line by line. Fails if the file cannot be parsed.

Compilation flags:

static

Template:

read_file_by_line(File,Object,Predicate)

Mode and number of proofs:

read_file_by_line(+atom,+object_identifier,+predicate_indicator) - zero_or_one

Exceptions:

File is a variable:

```

instantiation_error
File is neither a variable nor an atom:
  type_error(atom,File)
File is an atom but not an existing file:
  existence_error(file,File)
File is an existing file but cannot be opened for reading:
  permission_error(open,source_sink,File)
Object is a variable:
  instantiation_error
Object is neither a variable nor an object identifier:
  type_error(object_identifier,Object)
Object is a valid object identifier but not an existing object:
  existence_error(object,Object)
Predicate is a variable:
  instantiation_error
Predicate is neither a variable nor a predicate indicator:
  type_error(predicate_indicator,Predicate)
Predicate is a valid predicate indicator but not an existing public predicate:
  existence_error(predicate,Predicate)

```

read_stream_by_line/3

Reads a CSV stream saving the data as clauses for the specified object predicate. The stream is read line by line. Fails if the stream cannot be parsed.

Compilation flags:

```
static
```

Template:

```
read_stream_by_line(Stream,Object,Predicate)
```

Mode and number of proofs:

```
read_stream_by_line(+stream_or_alias,+object_identifier,+predicate_indicator) - zero_or_one
```

Exceptions:

```

Stream is a variable:
  instantiation_error
Stream is neither a variable nor a stream-term or alias:
  domain_error(stream_or_alias,Stream)
Stream is not an open stream:
  existence_error(stream,Stream)
Stream is an output stream:
  permission_error(input,stream,Stream)

```

Stream is a binary stream:

permission_error(input,binary_stream,Stream)

Object is a variable:

instantiation_error

Object is neither a variable nor an object identifier:

type_error(object_identifier,Object)

Object is a valid object identifier but not an existing object:

existence_error(object,Object)

Predicate is a variable:

instantiation_error

Predicate is neither a variable nor a predicate indicator:

type_error(predicate_indicator,Predicate)

Predicate is a valid predicate indicator but not an existing public predicate:

existence_error(predicate,Predicate)

read_file_by_line/2

Reads a CSV file returning the data as a list of rows, each row a list of fields. The file is read line by line. Fails if the file cannot be parsed.

Compilation flags:

static

Template:

read_file_by_line(File,Rows)

Mode and number of proofs:

read_file_by_line(+atom,-list(list)) - zero_or_one

Exceptions:

File is a variable:

instantiation_error

File is neither a variable nor an atom:

type_error(atom,File)

File is an atom but not an existing file:

existence_error(file,File)

File is an existing file but cannot be opened for reading:

permission_error(open,source_sink,File)

`read_stream_by_line/2`

Reads a CSV stream returning the data as a list of rows, each row a list of fields. The stream is read line by line. Fails if the stream cannot be parsed.

Compilation flags:

`static`

Template:

`read_stream_by_line(Stream,Rows)`

Mode and number of proofs:

`read_stream_by_line(+stream_or_alias,-list(list)) - zero_or_one`

Exceptions:

Stream is a variable:

`instantiation_error`

Stream is neither a variable nor a stream-term or alias:

`domain_error(stream_or_alias,Stream)`

Stream is not an open stream:

`existence_error(stream,Stream)`

Stream is an output stream:

`permission_error(input,stream,Stream)`

Stream is a binary stream:

`permission_error(input,binary_stream,Stream)`

`write_file/3`

Writes a CSV file with the data represented by the clauses of the specified object predicate.

Compilation flags:

`static`

Template:

`write_file(File,Object,Predicate)`

Mode and number of proofs:

`write_file(+atom,+object_identifier,+predicate_indicator) - one`

Exceptions:

File is a variable:

`instantiation_error`

File is neither a variable nor an atom:

`type_error(atom,File)`

File is an atom but cannot be opened for writing:

`permission_error(open,source_sink,File)`

Object is a variable:

`in instantiation_error`

Object is neither a variable nor an object identifier:

`type_error(object_identifier,Object)`

Object is a valid object identifier but not an existing object:

`existence_error(object,Object)`

Predicate is a variable:

`in instantiation_error`

Predicate is neither a variable nor a predicate indicator:

`type_error(predicate_indicator,Predicate)`

Predicate is a valid predicate indicator but not an existing public predicate:

`existence_error(predicate,Predicate)`

`write_stream/3`

Writes a CSV stream with the data represented by the clauses of the specified object predicate.

Compilation flags:

`static`

Template:

`write_stream(Stream,Object,Predicate)`

Mode and number of proofs:

`write_stream(+stream_or_alias,+object_identifier,+predicate_indicator) - one`

Exceptions:

Stream is a variable:

`in instantiation_error`

Stream is neither a variable nor a stream-term or alias:

`domain_error(stream_or_alias,Stream)`

Stream is not an open stream:

`existence_error(stream,Stream)`

Stream is an input stream:

`permission_error(output,stream,Stream)`

Stream is a binary stream:

`permission_error(output,binary_stream,Stream)`

Object is a variable:

`in instantiation_error`

Object is neither a variable nor an object identifier:

`type_error(object_identifier,Object)`

Object is a valid object identifier but not an existing object:

`existence_error(object,Object)`

Predicate is a variable:

`instantiation_error`

Predicate is neither a variable nor a predicate indicator:

`type_error(predicate_indicator,Predicate)`

Predicate is a valid predicate indicator but not an existing public predicate:

`existence_error(predicate,Predicate)`

`guess_separator/2`

Guesses the separator used in a given file, asking the user to confirm.

Compilation flags:

`static`

Template:

`guess_separator(File,Separator)`

Mode and number of proofs:

`guess_separator(+atom,-atom) - one`

Exceptions:

File is a variable:

`instantiation_error`

File is neither a variable nor an atom:

`type_error(atom,File)`

File is an atom but not an existing file:

`existence_error(file,File)`

File is an atom but cannot be opened for writing:

`permission_error(open,source_sink,File)`

guess_arity/2

Guesses the arity of records in a given file, asking the user to confirm.

Compilation flags:

static

Template:

guess_arity(File,Arity)

Mode and number of proofs:

guess_arity(+atom,-number) - one

Exceptions:

File is a variable:

instantiation_error

File is neither a variable nor an atom:

type_error(atom,File)

File is an atom but not an existing file:

existence_error(file,File)

File is an atom but cannot be opened for writing:

permission_error(open,source_sink,File)

Protected predicates

(none)

Private predicates

(none)

Operators

(none)

1.10 dates

object

1.10.1 date

Date predicates.

Availability:

```
logtalk_load(dates(loader))
```

Author: Paulo Moura

Version: 1:2:0

Date: 2014-09-27

Compilation flags:

```
static, context_switching_calls
```

Implements:

```
public datep
```

Uses:

```
os
```

Remarks:

```
(none)
```

Inherited public predicates:

```
days_in_month/3 leap_year/1 name_of_day/3 name_of_month/3 today/3 valid/3
```

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

protocol

1.10.2 datep

Date protocol.

Availability:

logtalk_load(dates(loader))

Author: Paulo Moura

Version: 1:1:0

Date: 2005-03-17

Compilation flags:

static

Dependencies:

(none)

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
 - today/3
 - leap_year/1
 - name_of_day/3
 - name_of_month/3
 - days_in_month/3
 - valid/3
- Protected predicates
- Private predicates
- Operators

Public predicates

today/3

Returns current date.

Compilation flags:

static

Template:

today(Year,Month,Day)

Mode and number of proofs:

today(-integer,-integer,-integer) - one

leap_year/1

True if the argument is a leap year.

Compilation flags:

static

Template:

leap_year(Year)

Mode and number of proofs:

leap_year(+integer) - zero_or_one

`name_of_day/3`

Name and short name of day.

Compilation flags:

`static`

Template:

`name_of_day(Index,Name,Short)`

Mode and number of proofs:

`name_of_day(?integer,?atom,?atom) - zero_or_more`

`name_of_month/3`

Name and short name of month.

Compilation flags:

`static`

Template:

`name_of_month(Index,Name,Short)`

Mode and number of proofs:

`name_of_month(?integer,?atom,?atom) - zero_or_more`

`days_in_month/3`

Number of days in a month.

Compilation flags:

`static`

Template:

`days_in_month(Month,Year,Days)`

Mode and number of proofs:

days_in_month(?integer,+integer,?integer) - zero_or_more

valid/3

True if the arguments represent a valid date.

Compilation flags:

static

Template:

valid(Year,Month,Day)

Mode and number of proofs:

valid(@integer,@integer,@integer) - zero_or_one

Protected predicates

(none)

Private predicates

(none)

Operators

(none)

See also:

date, timep

object

1.10.3 time

Time predicates.

Availability:

logtalk_load(dates(loader))

Author: Paulo Moura

Version: 1:1:0

Date: 2014-09-27

Compilation flags:

static, context_switching_calls

Implements:

public timep

Uses:

os

Remarks:

(none)

Inherited public predicates:

cpu_time/1 now/3 valid/3

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

See also:

datep

protocol

1.10.4 timep

Time protocol.

Availability:

logtalk_load(dates(loader))

Author: Paulo Moura

Version: 1:0:0

Date: 2000-07-24

Compilation flags:

static

Dependencies:

(none)

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
 - now/3
 - cpu_time/1
 - valid/3
- Protected predicates
- Private predicates
- Operators

Public predicates

now/3

Returns current time.

Compilation flags:

static

Template:

now(Hours,Mins,Secs)

Mode and number of proofs:

now(-integer,-integer,-integer) - one

cpu_time/1

Returns the current cpu time.

Compilation flags:

static

Template:

cpu_time(Time)

Mode and number of proofs:

cpu_time(-number) - one

valid/3

True if the arguments represent a valid time value.

Compilation flags:

static

Template:

valid(Hours,Mins,Secs)

Mode and number of proofs:

valid(+integer,+integer,+integer) - zero_or_one

Protected predicates

(none)

Private predicates

(none)

Operators

(none)

See also:

`time`, `datep`

1.11 dead_code_scanner

object

1.11.1 dead_code_scanner

A tool for detecting likely dead code in compiled Logtalk entities and Prolog modules compiled as objects.

Availability:

```
logtalk_load(dead_code_scanner(loader))
```

Author: Barry Evans and Paulo Moura

Version: 0:14:0

Date: 2024-03-28

Compilation flags:

```
static, context_switching_calls
```

Imports:

```
public options
```

Uses:

```
list
```

```
logtalk
```

```
os
```

```
type
```

Remarks:

- Dead code: A predicate or non-terminal that is not called (directly or indirectly) by any scoped predicate or non-terminal. These predicates and non-terminals are not used, cannot be called without breaking encapsulation, and are thus considered dead code.
- Known issues: Use of local meta-calls with goal arguments only known at runtime can result in false positives. Calls from non-standard meta-predicates may be missed if the meta-calls are not optimized.
- Requirements: Source files must be compiled with the `source_data` flag turned on. To avoid false positives due to meta-calls, compilation of source files with the `optimized` flag turned on is also advised.

Inherited public predicates:

`check_option/1` `check_options/1` `default_option/1` `default_options/1` `option/2` `option/3`
`valid_option/1` `valid_options/1`

- Public predicates
 - `entity/1`
 - `file/2`
 - `file/1`
 - `directory/2`
 - `directory/1`
 - `rdirectory/2`
 - `rdirectory/1`
 - `library/2`
 - `library/1`
 - `rlibrary/2`
 - `rlibrary/1`
 - `all/1`
 - `all/0`
 - `predicates/2`
 - `predicate/2`
- Protected predicates
- Private predicates
- Operators

Public predicates

entity/1

Scans a loaded entity for dead code. Fails if the entity does not exist.

Compilation flags:

static

Template:

entity(Entity)

Mode and number of proofs:

entity(+entity_identifier) - zero_or_one

file/2

Scans all entities in a loaded source file for dead code using the given options. The file can be given by name, basename, full path, or using library notation. Fails if the file is not loaded.

Compilation flags:

static

Template:

file(File,Options)

Mode and number of proofs:

file(+atom,+list(compound)) - zero_or_one

file/1

Scans all entities in a loaded source file for dead code using default options. The file can be given by name, basename, full path, or using library notation. Fails if the file is not loaded.

Compilation flags:

static

Template:

file(File)

Mode and number of proofs:

file(+atom) - zero_or_one

directory/2

Scans all entities in all loaded files from a given directory for dead code using the given options.

Compilation flags:

static

Template:

directory(Directory,Options)

Mode and number of proofs:

directory(+atom,+list(compound)) - one

directory/1

Scans all entities in all loaded files from a given directory for dead code using default options.

Compilation flags:

static

Template:

directory(Directory)

Mode and number of proofs:

directory(+atom) - one

rdirectory/2

Scans all entities in all loaded files from a given directory and its sub-directories for dead code using the given options.

Compilation flags:

static

Template:

rdirectory(Directory,Options)

Mode and number of proofs:

rdirectory(+atom,+list(compound)) - one

rdirectory/1

Scans all entities in all loaded files from a given directory and its sub-directories for dead code using default options.

Compilation flags:

static

Template:

rdirectory(Directory)

Mode and number of proofs:

rdirectory(+atom) - one

library/2

Scans all entities in all loaded files from a given library for dead code using the given options.

Compilation flags:

static

Template:

library(Library,Options)

Mode and number of proofs:

library(+atom,+list(compound)) - one

library/1

Scans all entities in all loaded files from a given library for dead code using default options.

Compilation flags:

static

Template:

library(Library)

Mode and number of proofs:

library(+atom) - one

rlibrary/2

Scans all entities in all loaded files in a loaded library and its sub-libraries for dead code using the given options.

Compilation flags:

static

Template:

rlibrary(Library,Options)

Mode and number of proofs:

rlibrary(+atom,+list(compound)) - one

rlibrary/1

Scans all entities in all loaded files in a loaded library and its sub-libraries for dead code using default options.

Compilation flags:

static

Template:

rlibrary(Library)

Mode and number of proofs:

rlibrary(+atom) - one

all/1

Scans all entities for dead code using the given options.

Compilation flags:

static

Template:

all(Options)

Mode and number of proofs:

all(+list(compound)) - one

all/0

Scans all entities for dead code using default options.

Compilation flags:

static

Mode and number of proofs:

all - one

predicates/2

Returns an ordered set of local predicates (and non-terminals) that are not used, directly or indirectly, by scoped predicates for a loaded entity.

Compilation flags:

static

Template:

predicates(Entity,Predicates)

Mode and number of proofs:

predicates(+entity_identifier,-list(predicate_indicator)) - one

predicate/2

Enumerates, by backtracking, local predicates (and non-terminals) that are not used, directly or indirectly, by scoped predicates for a loaded entity.

Compilation flags:

static

Template:

predicate(Entity,Predicate)

Mode and number of proofs:

predicate(+entity_identifier,?predicate_indicator) - zero_or_more

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

category

1.11.2 dead_code_scanner_messages

Logtalk dead_code_scanner tool default message translations.

Availability:

logtalk_load(dead_code_scanner(loader))

Author: Barry Evans and Paulo Moura

Version: 0:7:0

Date: 2020-02-05

Compilation flags:

static

Provides:

logtalk::message_prefix_stream/4

logtalk::message_tokens//2

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

1.12 debug_messages

object

1.12.1 debug_messages

Supports selective enabling and disabling of debug and debug(Group) messages.

Availability:

```
logtalk_load(debug_messages(loader))
```

Author: Paulo Moura

Version: 1:0:1

Date: 2022-05-05

Compilation flags:

```
static, context_switching_calls
```

Provides:

```
logtalk::message_hook/4
```

Uses:

```
logtalk
```

Remarks:

- Limitations: Debug messages are suppressed by the compiler when the optimize flag is turned on and thus cannot be enabled in this case.

Inherited public predicates:

(none)

- Public predicates
 - enable/1
 - disable/1
 - enabled/1
 - enable/2
 - disable/2
 - enabled/2
- Protected predicates

- Private predicates
 - enabled_/1
 - enabled_/2
- Operators

Public predicates

enable/1

Enables all debug and debug(Group) messages for the given component.

Compilation flags:

static

Template:

enable(Component)

Mode and number of proofs:

enable(@term) - one

disable/1

Disables all debug and debug(Group) messages for the given component.

Compilation flags:

static

Template:

disable(Component)

Mode and number of proofs:

disable(@term) - one

enabled/1

Enumerates by backtracking the components with enabled debug and debug(Group) messages.

Compilation flags:

static

Template:

enabled(Component)

Mode and number of proofs:

enabled(?term) - zero_or_more

enable/2

Enables debug(Group) messages for the given component and group.

Compilation flags:

static

Template:

enable(Component,Group)

Mode and number of proofs:

enable(@term,@term) - one

disable/2

Disables debug(Group) messages for the given component and group.

Compilation flags:

static

Template:

disable(Component,Group)

Mode and number of proofs:

disable(@term,@term) - one

enabled/2

Enumerates by backtracking the enabled debug(Group) messages for each component.

Compilation flags:

static

Template:

enabled(Component,Group)

Mode and number of proofs:

enabled(?term,?term) - zero_or_more

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

enabled_/1

Table of components with currently enabled debug and debug(Group) messages.

Compilation flags:

dynamic

Template:

enabled_(Component)

Mode and number of proofs:

enabled_(?term) - zero_or_more

enabled_/2

Table of currently enabled debug(Group) per component.

Compilation flags:

dynamic

Template:

enabled_(Component,Group)

Mode and number of proofs:

enabled_(?term,?term) - zero_or_more

Operators

(none)

1.13 debugger

object

1.13.1 debugger

Command-line debugger based on an extended procedure box model supporting execution tracing and spy points.

Availability:

logtalk_load(debugger(loader))

Author: Paulo Moura

Version: 6:1:1

Date: 2023-11-23

Compilation flags:

static, context_switching_calls

Implements:

public debuggerp

Provides:

logtalk::debug_handler_provider/1

logtalk::debug_handler/2

Uses:

logtalk

Remarks:

(none)

Inherited public predicates:

debug/0 debugging/0 debugging/1 leash/1 leashing/1 nodebug/0 nospy/1 nospy/4 nospyall/0
 notrace/0 reset/0 spy/1 spy/4 spying/1 spying/4 trace/0

- Public predicates
- Protected predicates
- Private predicates
 - debugging_/0
 - tracing_/0
 - skipping_/0
 - skipping_unleashed_/1
 - quasi_skipping_/0
 - leaping_/1
 - spying_line_number_/2
 - spying_predicate_/3
 - spying_context_/4
 - leashing_/1
 - invocation_number_/1
 - jump_to_invocation_number_/1
 - zap_to_port_/1
 - write_max_depth_/1
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

debugging_/0

True iff debug is on.

Compilation flags:

dynamic

Mode and number of proofs:

debugging_ - zero_or_one

tracing_/0

True iff tracing is on.

Compilation flags:

dynamic

Mode and number of proofs:

tracing_ - zero_or_one

skipping_/0

True iff skipping.

Compilation flags:

dynamic

Mode and number of proofs:

skipping_ - zero_or_one

skipping_unleashed_/1

True iff skipping (a goal with invocation number N) but showing intermediate ports as unleashed.

Compilation flags:

dynamic

Template:

skipping_unleashed_(N)

Mode and number of proofs:

skipping_unleashed_(?integer) - zero_or_one

quasi_skipping_/0

True iff quasi-skipping.

Compilation flags:

dynamic

Mode and number of proofs:

quasi_skipping_ - zero_or_one

leaping_/1

True iff leaping in tracing or debugging mode.

Compilation flags:

dynamic

Template:

leaping_(Mode)

Mode and number of proofs:

leaping_(?atom) - zero_or_one

spying_line_number_/2

Table of line number breakpoints.

Compilation flags:

dynamic

Template:

spying_line_number_(Entity,Line)

Mode and number of proofs:

spying_line_number_(?object_identifier,?integer) - zero_or_more

spying_line_number_(?category_identifier,?integer) - zero_or_more

spying_predicate_/3

Table of predicate spy points.

Compilation flags:

dynamic

Template:

spying_predicate_(Functor,Arity,Original)

Mode and number of proofs:

spying_predicate_(?atom,?integer,?predicate_indicator) - zero_or_more

spying_predicate_(?atom,?integer,?non_terminal_indicator) - zero_or_more

spying_context_/4

Table of context spy points.

Compilation flags:

dynamic

Template:

spying_context_(Sender,This,Self,Goal)

Mode and number of proofs:

spying_context_(?object_identifier,?object_identifier,?object_identifier,?callable) - zero_or_more

leashing_/1

Table of currently leashed ports.

Compilation flags:

dynamic

Template:

leashing_(Port)

Mode and number of proofs:

leashing_(?atom) - zero_or_more

invocation_number_/1

Current call stack invocation number.

Compilation flags:

dynamic

Template:

invocation_number_(N)

Mode and number of proofs:

invocation_number_(?integer) - zero_or_one

jump_to_invocation_number_/1

Invocation number to jump to.

Compilation flags:

dynamic

Template:

jump_to_invocation_number_(N)

Mode and number of proofs:

jump_to_invocation_number_(?integer) - zero_or_one

zap_to_port_/1

Port to zap to.

Compilation flags:

dynamic

Template:

zap_to_port_(Port)

Mode and number of proofs:

zap_to_port_(?integer) - zero_or_one

write_max_depth_/1

Current term maximum depth.

Compilation flags:

dynamic

Template:

write_max_depth_(MaxDepth)

Mode and number of proofs:

write_max_depth_(?integer) - zero_or_one

Operators

(none)

category

1.13.2 debugger_messages

Logtalk debugger tool default message translations.

Availability:

```
logtalk_load(debugger(loader))
```

Author: Paulo Moura

Version: 3:1:0

Date: 2023-06-21

Compilation flags:

```
static
```

Provides:

```
logtalk::message_prefix_stream/4  
logtalk::question_prompt_stream/4  
logtalk::message_tokens//2
```

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

protocol

1.13.3 debuggerp

Debugger protocol.

Availability:

```
logtalk_load(debugger(loader))
```

Author: Paulo Moura

Version: 3:0:0

Date: 2023-04-26

Compilation flags:

```
static
```

Dependencies:

```
(none)
```

Remarks:

- Debugger help: Type the character h (condensed help) or the character ? (extended help) at a leashed port.
- Predicate spy point: Specified as a ground term Functor/Arity.
- Non-terminal spy point: Specified as a ground term Functor//Arity.
- Line number spy point (aka breakpoint): Specified as an Entity-Line term with both Entity and Line bound. Line must be the first source file line of an entity clause.
- Leash port shorthands: none - [], loose - [fact,rule,call], half - [fact,rule,call,redo], tight - [fact,rule,call,redo,fail,exception], and full - [fact,rule,call,exit,redo,fail,exception].

Inherited public predicates:

(none)

- Public predicates
 - reset/0
 - debug/0
 - nodebug/0
 - debugging/0
 - debugging/1
 - trace/0
 - notrace/0
 - spy/1
 - spying/1
 - spy/4
 - spying/4
 - nospy/1
 - nospy/4
 - nospyall/0
 - leash/1
 - leashing/1
- Protected predicates
- Private predicates
- Operators

Public predicates

reset/0

Resets all debugging settings, including spy points and leashed ports, and turns off debugging.

Compilation flags:

static

Mode and number of proofs:

reset - one

See also:

nospyall/0

debug/0

Starts debugging for all defined spy points.

Compilation flags:

static

Mode and number of proofs:

debug - one

nodebug/0

Stops debugging for all defined spy points. Also turns off tracing. Does not remove defined spy points.

Compilation flags:

static

Mode and number of proofs:

nodebug - one

See also:

[reset/0](#)

debugging/0

Reports current debugging settings, including spy points.

Compilation flags:

static

Mode and number of proofs:

debugging - one

debugging/1

Enumerates, by backtracking, all entities compiled in debug mode.

Compilation flags:

static

Template:

debugging(Entity)

Mode and number of proofs:

debugging(?entity_identifier) - zero_or_more

trace/0

Starts tracing all calls compiled in debug mode.

Compilation flags:

static

Mode and number of proofs:

trace - one

notrace/0

Stops tracing of calls compiled in debug mode. Debugger will still stop at defined spy points.

Compilation flags:

static

Mode and number of proofs:

notrace - one

spy/1

Sets a line number spy point, a predicate spy point, a non-terminal spy point, or a list of spy points. Fails if a spy point is invalid.

Compilation flags:

static

Template:

spy(SpyPoint)

Mode and number of proofs:

spy(@spy_point) - zero_or_one

spy(@list(spy_point)) - zero_or_one

spying/1

Enumerates, by backtracking, all defined line number, predicate, and non-terminal spy points.

Compilation flags:

static

Template:

spying(SpyPoint)

Mode and number of proofs:

spying(?spy_point) - zero_or_more

spy/4

Sets a context spy point.

Compilation flags:

static

Template:

spy(Sender,This,Self,Goal)

Mode and number of proofs:

spy(@term,@term,@term,@term) - one

spying/4

Enumerates, by backtracking, all defined context spy points.

Compilation flags:

static

Template:

spying(Sender,This,Self,Goal)

Mode and number of proofs:

spying(?term,?term,?term,?term) - zero_or_more

nospy/1

Removes all matching line number, predicate, and non-terminal spy points.

Compilation flags:

static

Template:

nospy(SpyPoint)

Mode and number of proofs:

nospy(@var) - one

nospy(@spy_point) - one

nospy(@list(spy_point)) - one

nospy/4

Removes all matching context spy points.

Compilation flags:

static

Template:

`nospy(Sender,This,Self,Goal)`

Mode and number of proofs:

`nospy(@term,@term,@term,@term) - one`

`nospyall/0`

Removes all line number, predicate, non-terminal, and context spy points.

Compilation flags:

`static`

Mode and number of proofs:

`nospyall - one`

See also:

`reset/0`

`leash/1`

Sets the debugger leash ports using an abbreviation (none, loose, half, tight, or full) or a list of ports (valid ports are fact, rule, call, exit, redo, fail, and exception).

Compilation flags:

`static`

Template:

`leash(Ports)`

Mode and number of proofs:

`leash(+atom) - one`

`leash(+list(atom)) - one`

leashing/1

Enumerates, by backtracking, all leashed ports (valid ports are fact, rule, call, exit, redo, fail, and exception).

Compilation flags:

static

Template:

leashing(Port)

Mode and number of proofs:

leashing(?atom) - zero_or_more

Protected predicates

(none)

Private predicates

(none)

Operators

(none)

See also:

[debugger](#)

[object](#)

1.13.4 dump_trace

Simple solution for redirecting a debugger trace to a file.

Availability:

logtalk_load(debugger(loader))

Author: Paulo Moura

Version: 1:0:1

Date: 2021-11-12

Compilation flags:

static, context_switching_calls

Uses:

debugger

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
 - start_redirect_to_file/2
 - stop_redirect_to_file/0
- Protected predicates
- Private predicates
- Operators

Public predicates

start_redirect_to_file/2

Starts redirecting debugger trace messages to a file.

Compilation flags:

static

Template:

start_redirect_to_file(File,Goal)

Meta-predicate template:

start_redirect_to_file(*,0)

Mode and number of proofs:

start_redirect_to_file(+atom,+callable) - zero_or_more

stop_redirect_to_file/0

Stops redirecting debugger trace messages to a file.

Compilation flags:

static

Mode and number of proofs:

stop_redirect_to_file - one

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

1.14 dependents

category

1.14.1 observer

Smalltalk dependent protocol.

Availability:

logtalk_load(dependents(loader))

Author: Paulo Moura

Version: 1:0:0

Date: 2003-02-09

Compilation flags:

static

Dependencies:

(none)

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
 - update/1
- Protected predicates
- Private predicates
- Operators

Public predicates

update/1

Called when an observed object is updated.

Compilation flags:

static

Template:

update(Change)

Mode and number of proofs:

update(?nonvar) - zero_or_one

Protected predicates

(none)

Private predicates

(none)

Operators

(none)

See also:

subject

category

1.14.2 subject

Smalltalk dependent handling predicates.

Availability:

logtalk_load(dependents(loader))

Author: Paulo Moura

Version: 1:0:0

Date: 2003-02-09

Compilation flags:

static

Dependencies:

(none)

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
 - changed/0
 - changed/1
 - dependents/1
 - addDependent/1

- removeDependent/1
- Protected predicates
- Private predicates
 - dependent_/1
- Operators

Public predicates

changed/0

Receiver changed in some way. Notify all dependents.

Compilation flags:

static

Mode and number of proofs:

changed - one

changed/1

Receiver changed as specified in the argument. Notify all dependents.

Compilation flags:

static

Template:

changed(Change)

Mode and number of proofs:

changed(?nonvar) - one

dependents/1

Returns a list of all dependent objects.

Compilation flags:

static

Template:

dependents(Dependents)

Mode and number of proofs:

dependents(-list) - one

addDependent/1

Adds a new dependent object.

Compilation flags:

static

Template:

addDependent(Dependent)

Mode and number of proofs:

addDependent(@object) - one

removeDependent/1

Removes a dependent object.

Compilation flags:

static

Template:

removeDependent(Dependent)

Mode and number of proofs:

removeDependent(?object) - zero_or_more

Protected predicates

(none)

Private predicates

dependent_/1

Table of dependent objects.

Compilation flags:

dynamic

Template:

dependent_(Dependent)

Mode and number of proofs:

dependent_(?object) - zero_or_more

Operators

(none)

See also:

observer

1.15 diagrams

category

1.15.1 diagram(Format)

- Format - Graph language file format.

Common predicates for generating diagrams.

Availability:

logtalk_load(diagrams(loader))

Author: Paulo Moura

Version: 3:5:0

Date: 2024-04-01

Compilation flags:

static

Extends:

public options

Provides:

logtalk::message_prefix_stream/4

logtalk::message_tokens//2

Uses:

graph_language_registry

list

logtalk

modules_diagram_support

os

pairs

type

user

Remarks:

(none)

Inherited public predicates:

check_option/1 check_options/1 default_option/1 default_options/1 option/2 option/3
valid_option/1 valid_options/1

- Public predicates
 - libraries/3
 - libraries/2
 - libraries/1
 - all_libraries/1
 - all_libraries/0
 - rlibrary/2
 - rlibrary/1
 - library/2
 - library/1
 - directories/3
 - directories/2
 - rdirectory/3
 - rdirectory/2

- rdirectory/1
- directory/3
- directory/2
- directory/1
- files/3
- files/2
- files/1
- all_files/1
- all_files/0
- format_object/1
- diagram_description/1
- diagram_name_suffix/1
- Protected predicates
 - diagram_caption/3
 - output_rlibrary/3
 - output_library/3
 - output_rdirectory/3
 - output externals/1
 - output_files/2
 - output_file/4
 - output_sub_diagrams/1
 - reset/0
 - output_node/6
 - node/6
 - edge/5
 - output_edges/1
 - save_edge/5
 - output_missing_externals/1
 - not_excluded_file/4
 - output_file_path/4
 - locate_library/2
 - locate_directory/2
 - locate_file/5
 - ground_entity_identifier/3
 - filter_file_extension/3

- filter_external_file_extension/3
- add_link_options/3
- omit_path_prefix/3
- add_node_zoom_option/4
- message_diagram_description/1
- Private predicates
 - node_/6
 - edge_/5
- Operators

Public predicates

libraries/3

Creates a diagram for a set of libraries using the specified options. The Project argument is used as a prefix for the diagram file name.

Compilation flags:

static

Template:

libraries(Project,Libraries,Options)

Mode and number of proofs:

libraries(+atom,+list(atom),+list(compound)) - one

libraries/2

Creates a diagram for a set of libraries using the default options. The Project argument is used as a prefix for the diagram file name.

Compilation flags:

static

Template:

libraries(Project,Libraries)

Mode and number of proofs:

libraries(+atom,+list(atom)) - one

libraries/1

Creates a diagram for a set of libraries using the default options. The prefix libraries is used for the diagram file name.

Compilation flags:

static

Template:

libraries(Libraries)

Mode and number of proofs:

libraries(+list(atom)) - one

all_libraries/1

Creates a diagram for all loaded libraries using the specified options.

Compilation flags:

static

Template:

all_libraries(Options)

Mode and number of proofs:

all_libraries(+list(compound)) - one

all_libraries/0

Creates a diagram for all loaded libraries using default options.

Compilation flags:

static

Mode and number of proofs:

all_libraries - one

rlibrary/2

Creates a diagram for a library and its sub-libraries using the specified options.

Compilation flags:

static

Template:

rlibrary(Library,Options)

Mode and number of proofs:

rlibrary(+atom,+list(compound)) - one

rlibrary/1

Creates a diagram for a library and its sub-libraries using default options.

Compilation flags:

static

Template:

rlibrary(Library)

Mode and number of proofs:

rlibrary(+atom) - one

library/2

Creates a diagram for a library using the specified options.

Compilation flags:

static

Template:

library(Library,Options)

Mode and number of proofs:

library(+atom,+list(compound)) - one

library/1

Creates a diagram for a library using default options.

Compilation flags:

static

Template:

library(Library)

Mode and number of proofs:

library(+atom) - one

directories/3

Creates a diagram for a set of directories using the specified options. The Project argument is used as a prefix for the diagram file name.

Compilation flags:

static

Template:

directories(Project,Directories,Options)

Mode and number of proofs:

directories(+atom,+list(atom),+list(compound)) - one

directories/2

Creates a diagram for a set of directories using the default options. The Project argument is used as a prefix for the diagram file name.

Compilation flags:

static

Template:

directories(Project,Directories)

Mode and number of proofs:

directories(+atom,+list(atom)) - one

rdirectory/3

Creates a diagram for a directory and its sub-directories using the specified options. The Project argument is used as a prefix for the diagram file name.

Compilation flags:

static

Template:

rdirectory(Project,Directory,Options)

Mode and number of proofs:

rdirectory(+atom,+atom,+list(compound)) - one

rdirectory/2

Creates a diagram for a directory and its sub-directories using default options. The Project argument is used as a prefix for the diagram file name.

Compilation flags:

static

Template:

rdirectory(Project,Directory)

Mode and number of proofs:

rdirectory(+atom,+atom) - one

rdirectory/1

Creates a diagram for a directory and its sub-directories using default options. The name of the directory is used as a prefix for the diagram file name.

Compilation flags:

static

Template:

rdirectory(Directory)

Mode and number of proofs:

rdirectory(+atom) - one

directory/3

Creates a diagram for a directory using the specified options. The Project argument is used as a prefix for the diagram file name.

Compilation flags:

static

Template:

directory(Project,Directory,Options)

Mode and number of proofs:

directory(+atom,+atom,+list(compound)) - one

directory/2

Creates a diagram for a directory using default options. The Project argument is used as a prefix for the diagram file name.

Compilation flags:

static

Template:

directory(Project,Directory)

Mode and number of proofs:

directory(+atom,+atom) - one

directory/1

Creates a diagram for a directory using default options. The name of the directory is used as a prefix for the diagram file name.

Compilation flags:

static

Template:

directory(Directory)

Mode and number of proofs:

directory(+atom) - one

files/3

Creates a diagram for a set of files using the specified options. The file can be specified by name, basename, full path, or using library notation. The Project argument is used as a prefix for the diagram file name.

Compilation flags:

static

Template:

files(Project,Files,Options)

Mode and number of proofs:

files(+atom,+list(atom),+list(compound)) - one

files/2

Creates a diagram for a set of files using the default options. The file can be specified by name, basename, full path, or using library notation. The Project argument is used as a prefix for the diagram file name.

Compilation flags:

static

Template:

files(Project,Files)

Mode and number of proofs:

files(+atom,+list(atom)) - one

files/1

Creates a diagram for a set of files using the default options. The file can be specified by name, basename, full path, or using library notation. The prefix files is used for the diagram file name.

Compilation flags:

static

Template:

files(Files)

Mode and number of proofs:

files(+list(atom)) - one

all_files/1

Creates a diagram for all loaded files using the specified options.

Compilation flags:

static

Template:

all_files(Options)

Mode and number of proofs:

all_files(+list(compound)) - one

all_files/0

Creates a diagram for all loaded files using default options.

Compilation flags:

static

Mode and number of proofs:

all_files - one

format_object/1

Returns the identifier of the object implementing the graph language currently being used. Fails if none is specified.

Compilation flags:

static

Template:

format_object(Object)

Mode and number of proofs:

format_object(-object_identifier) - zero_or_one

diagram_description/1

Returns the diagram description.

Compilation flags:

static

Template:

diagram_description(Description)

Mode and number of proofs:

diagram_description(-atom) - one

diagram_name_suffix/1

Returns the diagram name suffix.

Compilation flags:

static

Template:

diagram_name_suffix(Suffix)

Mode and number of proofs:

diagram_name_suffix(-atom) - one

Protected predicates

diagram_caption/3

Creates a diagram caption from the diagram description and the subject and its kind.

Compilation flags:

static

Template:

diagram_caption(Kind,Subject,Description)

Mode and number of proofs:

diagram_caption(+atom,+callable,-atom) - one

output_rlibrary/3

Generates diagram output for a library and its sub-libraries using the specified options.

Compilation flags:

static

Template:

`output_rlibrary(Library,Path,Options)`

Mode and number of proofs:

`output_rlibrary(+atom,+atom,+list(compound)) - one`

`output_library/3`

Generates diagram output for a library using the specified options.

Compilation flags:

`static`

Template:

`output_library(Library,Path,Options)`

Mode and number of proofs:

`output_library(+atom,+atom,+list(compound)) - one`

`output_rdirectory/3`

Generates diagram output for a directory and its sub-directories using the specified options.

Compilation flags:

`static`

Template:

`output_rdirectory(Project,Path,Options)`

Mode and number of proofs:

`output_rdirectory(+atom,+atom,+list(compound)) - one`

output_externals/1

Output external nodes using the specified options depending on the value of the boolean option externals/1.

Compilation flags:

static

Template:

output_externals(Options)

Mode and number of proofs:

output_externals(+list(compound)) - one

output_files/2

Generates diagram output for a list of files using the specified options.

Compilation flags:

static

Template:

output_files(Files,Options)

Mode and number of proofs:

output_files(+list,+list(compound)) - one

output_file/4

Generates diagram output for a file using the specified options.

Compilation flags:

static

Template:

output_file(Path,Basename,Directory,Options)

Mode and number of proofs:

output_file(+atom,+atom,+atom,+list(compound)) - one

output_sub_diagrams/1

Outputs sub-diagrams using the specified options.

Compilation flags:

static

Template:

output_sub_diagrams(Options)

Mode and number of proofs:

output_sub_diagrams(+list(compound)) - one

reset/0

Resets all temporary information used when generating a diagram.

Compilation flags:

static

Mode and number of proofs:

reset - one

output_node/6

Outputs a graph node.

Compilation flags:

static

Template:

output_node(Identifier,Label,Caption,Contents,Kind,Options)

Mode and number of proofs:

output_node(+nonvar,+nonvar,+nonvar,+list(nonvar),+atom,+list(compound)) - one

node/6

Enumerates, by backtracking, all saved nodes.

Compilation flags:

static

Template:

node(Identifier,Label,Caption,Contents,Kind,Options)

Mode and number of proofs:

node(?nonvar,?nonvar,?nonvar,?list(compound),?atom,?list(compound)) - zero_or_more

edge/5

Enumerates, by backtracking, all saved edges.

Compilation flags:

static

Template:

edge(From,To,Labels,Kind,Options)

Mode and number of proofs:

edge(?nonvar,?nonvar,?list(nonvar),?atom,?list(compound)) - zero_or_more

output_edges/1

Outputs all edges.

Compilation flags:

static

Template:

output_edges(Options)

Mode and number of proofs:

output_edges(+list(compound)) - one

save_edge/5

Saves a graph edge.

Compilation flags:

static

Template:

save_edge(From,To,Labels,Kind,Options)

Mode and number of proofs:

save_edge(+nonvar,+nonvar,+list(nonvar),+atom,+list(compound)) - one

output_missing externals/1

Outputs missing external nodes (usually due to unloaded resources) that are referenced from edges.

Compilation flags:

static

Template:

output_missing_externals(Options)

Mode and number of proofs:

output_missing_externals(+list(compound)) - one

not_excluded_file/4

True when the given file is not excluded from the generated output. Excluded files may be specified by full path or by basename and with or without extension. Excluded directories may be listed by full or relative path.

Compilation flags:

static

Template:

not_excluded_file(Path,Basename,ExcludedDirectories,ExcludedFiles)

Mode and number of proofs:

not_excluded_file(+atom,+atom,+list(atom),+list(atom)) - zero_or_one

`output_file_path/4`

Returns the output file path.

Compilation flags:

`static`

Template:

`output_file_path(Name,Options,Format,Path)`

Mode and number of proofs:

`output_file_path(+atom,+list(atom),+object_identifier,-atom) - one`

`locate_library/2`

Locates a library given its name.

Compilation flags:

`static`

Template:

`locate_library(Library,Path)`

Mode and number of proofs:

`locate_library(+atom,-atom) - one`

`locate_directory/2`

Locates a directory given its name or full path.

Compilation flags:

`static`

Template:

`locate_directory(Directory,Path)`

Mode and number of proofs:

locate_directory(+atom,-atom) - one

locate_file/5

Locates a file given its name, basename, full path, or library notation representation.

Compilation flags:

static

Template:

locate_file(File,Basename,Extension,Directory,Path)

Mode and number of proofs:

locate_file(+atom,+atom,+atom,+atom,-atom) - one

ground_entity_identifier/3

Converts an entity identifier to a ground term.

Compilation flags:

static

Template:

ground_entity_identifier(Kind,Identifier,GroundIdentifier)

Mode and number of proofs:

ground_entity_identifier(+atom,+callable,-callable) - one

filter_file_extension/3

Filters the file name extension depending on the file_extensions/1 option.

Compilation flags:

static

Template:

`filter_file_extension(BaseName,Options,Name)`

Mode and number of proofs:

`filter_file_extension(+atom,+list(compound),-atom) - one`

`filter_external_file_extension/3`

Filters the external file name extension depending on the `file_extensions/1` option.

Compilation flags:

`static`

Template:

`filter_external_file_extension(Path,Options,Name)`

Mode and number of proofs:

`filter_external_file_extension(+atom,+list(compound),-atom) - one`

`add_link_options/3`

Adds `url/1`, `urls/2`, and `tooltip/1` link options (for use by the graph language) based on the specified path to the list of options.

Compilation flags:

`static`

Template:

`add_link_options(Path,Options,LinkingOptions)`

Mode and number of proofs:

`add_link_options(+atom,+list(compound),-list(compound)) - one`

omit_path_prefix/3

Removes a prefix from a path, returning the relative path, when using the option omit_path_prefixes/1. Used mainly for constructing directory and file node identifiers and captions.

Compilation flags:

static

Template:

omit_path_prefix(Path,Options,Relative)

Mode and number of proofs:

omit_path_prefix(+atom,+list(compound),-atom) - one

add_node_zoom_option/4

Adds node zoom options when using the zoom option.

Compilation flags:

static

Template:

add_node_zoom_option(Identifier,Suffix,Options,NodeOptions)

Mode and number of proofs:

add_node_zoom_option(+atom,+atom,+list(compound),-list(compound)) - one

message_diagram_description/1

Diagram description for progress messages.

Compilation flags:

static

Template:

message_diagram_description(Description)

Mode and number of proofs:

message_diagram_description(?atom) - one

Private predicates

node_/6

Table of saved nodes.

Compilation flags:

dynamic

Template:

node_(Identifier,Label,Caption,Contents,Kind,Options)

Mode and number of proofs:

node_(?nonvar,?nonvar,?nonvar,?list(compound),?atom,?list(compound)) - zero_or_more

edge_/5

Table of saved edges.

Compilation flags:

dynamic

Template:

edge_(From,To,Labels,Kind,Options)

Mode and number of proofs:

edge_(?nonvar,?nonvar,?list(nonvar),?atom,?list(compound)) - zero_or_more

Operators

(none)

object

1.15.2 diagrams

Predicates for generating all supported diagrams for libraries, directories, and files in one step using the DOT format.

Availability:

```
logtalk_load(diagrams(loader))
```

Author: Paulo Moura

Version: 2:1:0

Date: 2019-04-07

Compilation flags:

```
static, context_switching_calls
```

Extends:

```
public diagrams(dot)
```

Remarks:

```
(none)
```

Inherited public predicates:

```
all_files/0 all_files/1 all_libraries/0 all_libraries/1 directories/2 directories/3 directory/1
directory/2 directory/3 files/1 files/2 files/3 libraries/1 libraries/2 libraries/3 library/1
library/2 rdirectory/1 rdirectory/2 rdirectory/3 rlibrary/1 rlibrary/2
```

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

object

1.15.3 diagrams(Format)

- Format - Graph language file format.

Predicates for generating all supported diagrams for libraries, directories, or files in one step using the specified format.

Availability:

```
logtalk_load(diagrams(loader))
```

Author: Paulo Moura

Version: 2:8:0

Date: 2019-06-13

Compilation flags:

```
static, context_switching_calls
```

Uses:

```
list
```

```
os
```

Remarks:

- Common options: title/1, date/1, output_directory/1, relation_labels/1, node_type_captions/1, exclude_files/1, exclude_libraries/1, url_prefixes/1, omit_path_prefix/1, entity_url_suffix_target/2, and layout/1.
- Limitations: Some of the provided predicates only make sense for some types of diagrams. Also, fine tuning may require generating individual diagrams directly instead of as a batch using this utility object.

Inherited public predicates:

(none)

- Public predicates
 - libraries/3
 - libraries/2
 - libraries/1
 - all_libraries/1
 - all_libraries/0
 - rlibrary/2
 - rlibrary/1
 - library/2
 - library/1
 - directories/3
 - directories/2
 - rdirectory/3
 - rdirectory/2
 - rdirectory/1
 - directory/3
 - directory/2
 - directory/1
 - files/3
 - files/2
 - files/1
 - all_files/1
 - all_files/0
- Protected predicates
- Private predicates
- Operators

Public predicates

libraries/3

Creates all supported diagrams for a set of libraries using the specified options. The Project argument is used as a prefix for the diagram file names.

Compilation flags:

static

Template:

libraries(Project,Libraries,Options)

Mode and number of proofs:

libraries(+atom,+list(atom),+list(compound)) - one

libraries/2

Creates all supported diagrams for a set of libraries using the default options. The Project argument is used as a prefix for the diagram file names.

Compilation flags:

static

Template:

libraries(Project,Libraries)

Mode and number of proofs:

libraries(+atom,+list(atom)) - one

libraries/1

Creates all supported diagrams for a set of libraries using the default options. The prefix libraries is used for the diagram file names.

Compilation flags:

static

Template:

libraries(Libraries)

Mode and number of proofs:

libraries(+list(atom)) - one

all_libraries/1

Creates all supported diagrams for all loaded libraries using the specified options.

Compilation flags:

static

Template:

all_libraries(Options)

Mode and number of proofs:

all_libraries(+list(compound)) - one

all_libraries/0

Creates all supported diagrams for all loaded libraries using default options.

Compilation flags:

static

Mode and number of proofs:

all_libraries - one

rlibrary/2

Creates all supported diagrams for a library and its sub-libraries using the specified options.

Compilation flags:

static

Template:

rlibrary(Library,Options)

Mode and number of proofs:

rlibrary(+atom,+list(compound)) - one

rlibrary/1

Creates all supported diagrams for a library and its sub-libraries using default options.

Compilation flags:

static

Template:

rlibrary(Library)

Mode and number of proofs:

rlibrary(+atom) - one

library/2

Creates all supported diagrams for a library using the specified options.

Compilation flags:

static

Template:

library(Library,Options)

Mode and number of proofs:

library(+atom,+list(compound)) - one

library/1

Creates all supported diagrams for a library using default options.

Compilation flags:

static

Template:

library(Library)

Mode and number of proofs:

library(+atom) - one

directories/3

Creates all supported diagrams for a set of directories using the specified options. The Project argument is used as a prefix for the diagram file names.

Compilation flags:

static

Template:

directories(Project,Directories,Options)

Mode and number of proofs:

directories(+atom,+list(atom),+list(compound)) - one

directories/2

Creates all supported diagrams for a directory using default options. The Project argument is used as a prefix for the diagram file names.

Compilation flags:

static

Template:

directories(Project,Directories)

Mode and number of proofs:

directories(+atom,+list(atom)) - one

rdirectory/3

Creates all supported diagrams for a directory and its sub-directories using the specified options. The Project argument is used as a prefix for the diagram file name.

Compilation flags:

static

Template:

rdirectory(Project,Directory,Options)

Mode and number of proofs:

rdirectory(+atom,+atom,+list(compound)) - one

rdirectory/2

Creates all supported diagrams for a directory and its sub-directories using default options. The Project argument is used as a prefix for the diagram file name.

Compilation flags:

static

Template:

rdirectory(Project,Directory)

Mode and number of proofs:

rdirectory(+atom,+atom) - one

rdirectory/1

Creates all supported diagrams for a directory and its sub-directories using default options. The name of the directory is used as a prefix for the diagram file name.

Compilation flags:

static

Template:

rdirectory(Directory)

Mode and number of proofs:

rdirectory(+atom) - one

directory/3

Creates all supported diagrams for a directory using the specified options. The Project argument is used as a prefix for the diagram file names.

Compilation flags:

static

Template:

directory(Project,Directory,Options)

Mode and number of proofs:

directory(+atom,+atom,+list(compound)) - one

directory/2

Creates all supported diagrams for a directory using default options. The Project argument is used as a prefix for the diagram file names.

Compilation flags:

static

Template:

directory(Project,Directory)

Mode and number of proofs:

directory(+atom,+atom) - one

directory/1

Creates all supported diagrams for a directory using default options. The name of the directory is used as a prefix for the diagram file names.

Compilation flags:

static

Template:

directory(Directory)

Mode and number of proofs:

directory(+atom) - one

files/3

Creates all supported diagrams for a set of files using the specified options. The file can be specified by name, basename, full path, or using library notation. The Project argument is used as a prefix for the diagram file names.

Compilation flags:

static

Template:

files(Project,Files,Options)

Mode and number of proofs:

files(+atom,+list(atom),+list(compound)) - one

files/2

Creates all supported diagrams for a set of files using the default options. The file can be specified by name, basename, full path, or using library notation. The Project argument is used as a prefix for the diagram file names.

Compilation flags:

static

Template:

files(Project,Files)

Mode and number of proofs:

files(+atom,+list(atom)) - one

files/1

Creates all supported diagrams for a set of files using the default options. The file can be specified by name, basename, full path, or using library notation. The prefix “files” is used for the diagram file names.

Compilation flags:

static

Template:

files(Files)

Mode and number of proofs:

files(+list(atom)) - one

all_files/1

Creates all supported diagrams for all loaded files using the specified options.

Compilation flags:

static

Template:

all_files(Options)

Mode and number of proofs:

all_files(+list(compound)) - one

all_files/0

Creates all supported diagrams for all loaded files using default options.

Compilation flags:

static

Mode and number of proofs:

all_files - one

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

object

1.15.4 directory_dependency_diagram

Predicates for generating directory dependency diagrams in DOT format.

Availability:

logtalk_load(diagrams(loader))

Author: Paulo Moura

Version: 1:0:0

Date: 2019-04-07

Compilation flags:

static, context_switching_calls

Extends:

public directory_dependency_diagram(dot)

Remarks:

(none)

Inherited public predicates:

all_files/0 all_files/1 all_libraries/0 all_libraries/1 check_option/1 check_options/1
default_option/1 default_options/1 diagram_description/1 diagram_name_suffix/1 directories/2
directories/3 directory/1 directory/2 directory/3 files/1 files/2 files/3 format_object/1
libraries/1 libraries/2 libraries/3 library/1 library/2 option/2 option/3 rdirectory/1
rdirectory/2 rdirectory/3 rlibrary/1 rlibrary/2 valid_option/1 valid_options/1

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

See also:

directory_load_diagram, file_load_diagram

object

1.15.5 directory_dependency_diagram(Format)

- Format - Graph language file format.

Predicates for generating directory dependency diagrams. A dependency exists when an entity in one directory makes a reference to an entity in another directory.

Availability:

```
logtalk_load(diagrams(loader))
```

Author: Paulo Moura

Version: 3:0:1

Date: 2024-04-01

Compilation flags:

```
static, context_switching_calls
```

Imports:

```
public directory_diagram(Format)
```

Uses:

```
file_dependency_diagram(Format)
```

```
list
```

```
logtalk
```

```
modules_diagram_support
```

Remarks:

```
(none)
```

Inherited public predicates:

```
all_files/0 all_files/1 all_libraries/0 all_libraries/1 check_option/1 check_options/1
default_option/1 default_options/1 diagram_description/1 diagram_name_suffix/1 directories/2
directories/3 directory/1 directory/2 directory/3 files/1 files/2 files/3 format_object/1
libraries/1 libraries/2 libraries/3 library/1 library/2 option/2 option/3 rdirectory/1
rdirectory/2 rdirectory/3 rlibrary/1 rlibrary/2 valid_option/1 valid_options/1
```

- Public predicates
- Protected predicates
- Private predicates
 - sub_diagram_/2
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

sub_diagram_/2

Table of directory sub-diagrams to support their generation.

Compilation flags:

dynamic

Template:

sub_diagram_(Project,Directory)

Mode and number of proofs:

sub_diagram_(?atom,?atom) - zero_or_more

Operators

(none)

See also:

directory_load_diagram(Format), file_load_diagram(Format), library_load_diagram(Format)

category

1.15.6 directory_diagram(Format)

- Format - Graph language file format.

Common predicates for generating directory diagrams.

Availability:

logtalk_load(diagrams(loader))

Author: Paulo Moura

Version: 1:12:1

Date: 2024-03-30

Compilation flags:

static

Extends:

public diagram(Format)

Uses:

list

Remarks:

(none)

Inherited public predicates:

all_files/0 all_files/1 all_libraries/0 all_libraries/1 check_option/1 check_options/1
default_option/1 default_options/1 diagram_description/1 diagram_name_suffix/1 directories/2
directories/3 directory/1 directory/2 directory/3 files/1 files/2 files/3 format_object/1
libraries/1 libraries/2 libraries/3 library/1 library/2 option/2 option/3 rdirectory/1
rdirectory/2 rdirectory/3 rlibrary/1 rlibrary/2 valid_option/1 valid_options/1

- Public predicates
- Protected predicates
 - remember_included_directory/1
 - remember_referenced_logtalk_directory/1
 - remember_referenced_prolog_directory/1
- Private predicates
 - included_directory_/1
 - referenced_logtalk_directory_/1
 - referenced_prolog_directory_/1
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

`remember_included_directory/1`

Remember included Logtalk directory in the diagram.

Compilation flags:

`static`

Template:

`remember_included_directory(Path)`

Mode and number of proofs:

`remember_included_directory(+atom) - one`

`remember_referenced_logtalk_directory/1`

Remember referenced Logtalk directory in the diagram.

Compilation flags:

`static`

Template:

`remember_referenced_logtalk_directory(Path)`

Mode and number of proofs:

`remember_referenced_logtalk_directory(+atom) - one`

`remember_referenced_prolog_directory/1`

Remember referenced Prolog directory in the diagram.

Compilation flags:

`static`

Template:

remember_referenced_prolog_directory(Path)

Mode and number of proofs:

remember_referenced_prolog_directory(+atom) - one

Private predicates

included_directory_/1

Table of Logtalk directories already included in the diagram.

Compilation flags:

dynamic

Template:

included_directory_(Path)

Mode and number of proofs:

included_directory_(?atom) - zero_or_more

referenced_logtalk_directory_/1

Table of referenced Logtalk directories in the diagram.

Compilation flags:

dynamic

Template:

referenced_logtalk_directory_(Path)

Mode and number of proofs:

referenced_logtalk_directory_(?atom) - zero_or_more

referenced_prolog_directory_/1

Table of referenced Prolog directories in the diagram.

Compilation flags:

dynamic

Template:

referenced_prolog_directory_(Path)

Mode and number of proofs:

referenced_prolog_directory_(?atom) - zero_or_more

Operators

(none)

object

1.15.7 directory_load_diagram

Predicates for generating directory loading dependency diagrams in DOT format.

Availability:

logtalk_load(diagrams(loader))

Author: Paulo Moura

Version: 1:0:0

Date: 2019-04-07

Compilation flags:

static, context_switching_calls

Extends:

public directory_load_diagram(dot)

Remarks:

(none)

Inherited public predicates:

all_files/0 all_files/1 all_libraries/0 all_libraries/1 check_option/1 check_options/1
default_option/1 default_options/1 diagram_description/1 diagram_name_suffix/1 directories/2
directories/3 directory/1 directory/2 directory/3 files/1 files/2 files/3 format_object/1
libraries/1 libraries/2 libraries/3 library/1 library/2 option/2 option/3 rdirectory/1
rdirectory/2 rdirectory/3 rlibrary/1 rlibrary/2 valid_option/1 valid_options/1

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

See also:

directory_dependency_diagram, file_dependency_diagram

object

1.15.8 directory_load_diagram(Format)

- Format - Graph language file format.

Predicates for generating directory loading dependency diagrams.

Availability:

logtalk_load(diagrams(loader))

Author: Paulo Moura

Version: 3:0:1

Date: 2024-04-01

Compilation flags:

static, context_switching_calls

Imports:

public directory_diagram(Format)

Uses:

file_dependency_diagram(Format)

file_load_diagram(Format)

list

logtalk

modules_diagram_support

Remarks:

(none)

Inherited public predicates:

all_files/0 all_files/1 all_libraries/0 all_libraries/1 check_option/1 check_options/1
 default_option/1 default_options/1 diagram_description/1 diagram_name_suffix/1 directories/2
 directories/3 directory/1 directory/2 directory/3 files/1 files/2 files/3 format_object/1
 libraries/1 libraries/2 libraries/3 library/1 library/2 option/2 option/3 rdirectory/1
 rdirectory/2 rdirectory/3 rlibrary/1 rlibrary/2 valid_option/1 valid_options/1

- Public predicates
- Protected predicates
- Private predicates
 - sub_diagram_/2
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

sub_diagram_/2

Table of directory sub-diagrams to support their generation.

Compilation flags:

dynamic

Template:

sub_diagram_(Project,Directory)

Mode and number of proofs:

sub_diagram_(?atom,?atom) - zero_or_more

Operators

(none)

See also:

directory_dependency_diagram(Format), file_dependency_diagram(Format), li-
brary_dependency_diagram(Format)

object

1.15.9 dot_graph_language

Predicates for generating graph files in the DOT language (version 2.36.0 or later).

Availability:

logtalk_load(diagrams(loader))

Author: Paulo Moura

Version: 3:8:1

Date: 2023-08-03

Compilation flags:

static, context_switching_calls

Implements:

public graph_language_protocol

Imports:

public options

Provides:

graph_language_registry::language_object/2

Uses:

list

os

term_io

user

Remarks:

(none)

Inherited public predicates:

check_option/1 check_options/1 default_option/1 default_options/1 edge/6 file_footer/3
file_header/3 graph_footer/5 graph_header/5 node/7 option/2 option/3 output_file_name/2
valid_option/1 valid_options/1

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

object

1.15.10 entity_diagram

Predicates for generating entity diagrams in DOT format with both inheritance and cross-referencing relation edges.

Availability:

```
logtalk_load(diagrams(loader))
```

Author: Paulo Moura

Version: 2:0:0

Date: 2014-01-01

Compilation flags:

```
static, context_switching_calls
```

Extends:

```
public entity_diagram(dot)
```

Remarks:

(none)

Inherited public predicates:

```
all_files/0 all_files/1 all_libraries/0 all_libraries/1 check_option/1 check_options/1
default_option/1 default_options/1 diagram_description/1 diagram_name_suffix/1 directories/2
directories/3 directory/1 directory/2 directory/3 file/1 file/2 files/1 files/2 files/3
format_object/1 libraries/1 libraries/2 libraries/3 library/1 library/2 option/2 option/3
rdirectory/1 rdirectory/2 rdirectory/3 rlibrary/1 rlibrary/2 valid_option/1 valid_options/1
```

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

See also:

`inheritance_diagram`, `uses_diagram`, `xref_diagram`
object

1.15.11 `entity_diagram`(Format)

- Format - Graph language file format.

Predicates for generating entity diagrams in the specified format with both inheritance and cross-referencing relation edges.

Availability:

```
logtalk_load(diagrams(loader))
```

Author: Paulo Moura

Version: 2:57:2

Date: 2024-04-01

Compilation flags:

```
static, context_switching_calls
```

Imports:

```
public diagram(Format)
```

Uses:

```
list  
logtalk  
modules_diagram_support  
user
```

Remarks:

(none)

Inherited public predicates:

all_files/0 all_files/1 all_libraries/0 all_libraries/1 check_option/1 check_options/1
default_option/1 default_options/1 diagram_description/1 diagram_name_suffix/1 directories/2
directories/3 directory/1 directory/2 directory/3 files/1 files/2 files/3 format_object/1
libraries/1 libraries/2 libraries/3 library/1 library/2 option/2 option/3 rdirectory/1
rdirectory/2 rdirectory/3 rlibrary/1 rlibrary/2 valid_option/1 valid_options/1

- Public predicates
 - file/2
 - file/1
- Protected predicates
- Private predicates
 - included_entity_/1
 - included_module_/1
 - referenced_entity_/2
 - referenced_module_/2
- Operators

Public predicates

file/2

Creates a diagram for all entities in a loaded source file using the specified options. The file can be specified by name, basename, full path, or using library notation.

Compilation flags:

static

Template:

file(File,Options)

Mode and number of proofs:

file(+atom,+list(compound)) - one

file/1

Creates a diagram for all entities in a loaded source file using default options. The file can be specified by name, basename, full path, or using library notation.

Compilation flags:

static

Template:

file(File)

Mode and number of proofs:

file(+atom) - one

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

included_entity_/1

Table of Logtalk entities already included in the diagram.

Compilation flags:

dynamic

Template:

included_entity_(Entity)

Mode and number of proofs:

included_entity_(?entity_identifier) - zero_or_more

included_module_/1

Table of Prolog modules already included in the diagram.

Compilation flags:

dynamic

Template:

included_module_(Module)

Mode and number of proofs:

included_module_(?module_identifier) - zero_or_more

referenced_entity_/2

Table of referenced Logtalk entities in the diagram.

Compilation flags:

dynamic

Template:

referenced_entity_(Referencer,Entity)

Mode and number of proofs:

referenced_entity_(?entity_identifier,?entity_identifier) - zero_or_more

referenced_module_/2

Table of referenced Logtalk entities in the diagram.

Compilation flags:

dynamic

Template:

referenced_module_(Referencer,Entity)

Mode and number of proofs:

referenced_module_(?entity_identifier,?module_identifier) - zero_or_more

Operators

(none)

See also:

`inheritance_diagram(Format)`, `uses_diagram(Format)`, `xref_diagram(Format)`, `library_diagram(Format)`
object

1.15.12 `file_dependency_diagram`

Predicates for generating file contents dependency diagrams in DOT format. A dependency exists when an entity in one file makes a reference to an entity in another file.

Availability:

```
logtalk_load(diagrams(loader))
```

Author: Paulo Moura

Version: 2:1:0

Date: 2019-06-13

Compilation flags:

```
static, context_switching_calls
```

Extends:

```
public file_dependency_diagram(dot)
```

Remarks:

(none)

Inherited public predicates:

```
all_files/0 all_files/1 all_libraries/0 all_libraries/1 check_option/1 check_options/1
default_option/1 default_options/1 diagram_description/1 diagram_name_suffix/1 directories/2
directories/3 directory/1 directory/2 directory/3 files/1 files/2 files/3 format_object/1
libraries/1 libraries/2 libraries/3 library/1 library/2 option/2 option/3 rdirectory/1
rdirectory/2 rdirectory/3 rlibrary/1 rlibrary/2 valid_option/1 valid_options/1
```

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

See also:

`file_load_diagram`, `directory_load_diagram`, `library_load_diagram`
object

1.15.13 `file_dependency_diagram`(Format)

- Format - Graph language file format.

Predicates for generating file contents dependency diagrams. A dependency exists when an entity in one file makes a reference to an entity in another file.

Availability:

```
logtalk_load(diagrams(loader))
```

Author: Paulo Moura

Version: 2:28:3

Date: 2024-04-01

Compilation flags:

```
static, context_switching_calls
```

Imports:

```
public file_diagram(Format)
```

Uses:

```
entity_diagram(Format)  
list  
logtalk  
modules_diagram_support  
os
```

Remarks:

(none)

Inherited public predicates:

all_files/0 all_files/1 all_libraries/0 all_libraries/1 check_option/1 check_options/1
 default_option/1 default_options/1 diagram_description/1 diagram_name_suffix/1 directories/2
 directories/3 directory/1 directory/2 directory/3 files/1 files/2 files/3 format_object/1
 libraries/1 libraries/2 libraries/3 library/1 library/2 option/2 option/3 rdirectory/1
 rdirectory/2 rdirectory/3 rlibrary/1 rlibrary/2 valid_option/1 valid_options/1

- Public predicates
- Protected predicates
- Private predicates
 - sub_diagram_/1
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

sub_diagram_/1

Table of file sub-diagrams to support their generation.

Compilation flags:

dynamic

Template:

sub_diagram_(File)

Mode and number of proofs:

sub_diagram_(?atom) - zero_or_more

Operators

(none)

See also:

`file_load_diagram(Format)`, `directory_load_diagram(Format)`, `library_load_diagram(Format)`
`category`

1.15.14 `file_diagram(Format)`

- Format - Graph language file format.

Common predicates for generating file diagrams.

Availability:

`logtalk_load(diagrams(loader))`

Author: Paulo Moura

Version: 2:13:2

Date: 2022-05-31

Compilation flags:

`static`

Extends:

`public diagram(Format)`

Uses:

`list`

`logtalk`

`modules_diagram_support`

Remarks:

(none)

Inherited public predicates:

`all_files/0` `all_files/1` `all_libraries/0` `all_libraries/1` `check_option/1` `check_options/1`
`default_option/1` `default_options/1` `diagram_description/1` `diagram_name_suffix/1` `directories/2`
`directories/3` `directory/1` `directory/2` `directory/3` `files/1` `files/2` `files/3` `format_object/1`
`libraries/1` `libraries/2` `libraries/3` `library/1` `library/2` `option/2` `option/3` `rdirectory/1`
`rdirectory/2` `rdirectory/3` `rlibrary/1` `rlibrary/2` `valid_option/1` `valid_options/1`

- Public predicates

- Protected predicates
 - remember_included_file/1
 - remember_referenced_logtalk_file/1
 - remember_referenced_prolog_file/1
- Private predicates
 - included_file_/1
 - referenced_logtalk_file_/1
 - referenced_prolog_file_/1
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

remember_included_file/1

Remember included Logtalk file in the diagram.

Compilation flags:

static

Template:

remember_included_file(Path)

Mode and number of proofs:

remember_included_file(+atom) - one

remember_referenced_logtalk_file/1

Remember referenced Logtalk file in the diagram.

Compilation flags:

static

Template:

remember_referenced_logtalk_file(Path)

Mode and number of proofs:

`remember_referenced_logtalk_file(+atom) - one`

`remember_referenced_prolog_file/1`

Remember referenced Prolog file in the diagram.

Compilation flags:

`static`

Template:

`remember_referenced_prolog_file(Path)`

Mode and number of proofs:

`remember_referenced_prolog_file(+atom) - one`

Private predicates

`included_file_/1`

Table of Logtalk files already included in the diagram.

Compilation flags:

`dynamic`

Template:

`included_file_(Path)`

Mode and number of proofs:

`included_file_(?atom) - zero_or_more`

referenced_logtalk_file_/1

Table of referenced Logtalk files in the diagram.

Compilation flags:

dynamic

Template:

referenced_logtalk_file_(Path)

Mode and number of proofs:

referenced_logtalk_file_(?atom) - zero_or_more

referenced_prolog_file_/1

Table of referenced Prolog files in the diagram.

Compilation flags:

dynamic

Template:

referenced_prolog_file_(Path)

Mode and number of proofs:

referenced_prolog_file_(?atom) - zero_or_more

Operators

(none)

object

1.15.15 file_load_diagram

Predicates for generating file loading dependency diagrams in DOT format. A dependency exists when a file loads or includes another file.

Availability:

logtalk_load(diagrams(loader))

Author: Paulo Moura

Version: 2:1:0

Date: 2019-06-13

Compilation flags:

static, context_switching_calls

Extends:

public file_load_diagram(dot)

Remarks:

(none)

Inherited public predicates:

all_files/0 all_files/1 all_libraries/0 all_libraries/1 check_option/1 check_options/1
default_option/1 default_options/1 diagram_description/1 diagram_name_suffix/1 directories/2
directories/3 directory/1 directory/2 directory/3 files/1 files/2 files/3 format_object/1
libraries/1 libraries/2 libraries/3 library/1 library/2 option/2 option/3 rdirectory/1
rdirectory/2 rdirectory/3 rlibrary/1 rlibrary/2 valid_option/1 valid_options/1

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

See also:

`file_dependency_diagram`, `directory_dependency_diagram`, `library_dependency_diagram`
object

1.15.16 `file_load_diagram`(Format)

- Format - Graph language file format.

Predicates for generating file loading dependency diagrams. A dependency exists when a file loads or includes another file.

Availability:

```
logtalk_load(diagrams(loader))
```

Author: Paulo Moura

Version: 2:30:1

Date: 2024-04-01

Compilation flags:

```
static, context_switching_calls
```

Imports:

```
public file_diagram(Format)
```

Uses:

```
entity_diagram(Format)  
list  
logtalk  
modules_diagram_support  
os
```

Remarks:

(none)

Inherited public predicates:

all_files/0 all_files/1 all_libraries/0 all_libraries/1 check_option/1 check_options/1
default_option/1 default_options/1 diagram_description/1 diagram_name_suffix/1 directories/2
directories/3 directory/1 directory/2 directory/3 files/1 files/2 files/3 format_object/1
libraries/1 libraries/2 libraries/3 library/1 library/2 option/2 option/3 rdirectory/1
rdirectory/2 rdirectory/3 rlibrary/1 rlibrary/2 valid_option/1 valid_options/1

- Public predicates
- Protected predicates
- Private predicates
 - sub_diagram_/1
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

sub_diagram_/1

Table of file sub-diagrams to support their generation.

Compilation flags:

dynamic

Template:

sub_diagram_(File)

Mode and number of proofs:

sub_diagram_(?atom) - zero_or_more

Operators

(none)

See also:

`file_dependency_diagram(Format)`, `directory_dependency_diagram(Format)`, `library_dependency_diagram(Format)`, `protocol`

1.15.17 graph_language_protocol

Predicates for generating graph files.

Availability:

`logtalk_load(diagrams(loader))`

Author: Paulo Moura

Version: 2:0:0

Date: 2014-12-30

Compilation flags:

`static`

Dependencies:

(none)

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
 - `output_file_name/2`
 - `file_header/3`
 - `file_footer/3`
 - `graph_header/5`
 - `graph_footer/5`
 - `node/7`
 - `edge/6`

- Protected predicates
- Private predicates
- Operators

Public predicates

`output_file_name/2`

Constructs the diagram file basename by adding a graph language dependent extension to the given name.

Compilation flags:

`static`

Template:

`output_file_name(Name,Basename)`

Mode and number of proofs:

`output_file_name(+atom,-atom) - one`

`file_header/3`

Writes the output file header using the specified options.

Compilation flags:

`static`

Template:

`file_header(Stream,Identifier,Options)`

Mode and number of proofs:

`file_header(+stream_or_alias,+atom,+list(compound)) - one`

file_footer/3

Writes the output file footer using the specified options.

Compilation flags:

static

Template:

file_footer(Stream,Identifier,Options)

Mode and number of proofs:

file_footer(+stream_or_alias,+atom,+list(compound)) - one

graph_header/5

Writes a graph header using the specified options.

Compilation flags:

static

Template:

graph_header(Stream,Identifier,Label,Kind,Options)

Mode and number of proofs:

graph_header(+stream_or_alias,+atom,+atom,+atom,+list(compound)) - one

graph_footer/5

Writes a graph footer using the specified options.

Compilation flags:

static

Template:

graph_footer(Stream,Identifier,Label,Kind,Options)

Mode and number of proofs:

graph_footer(+stream_or_alias,+atom,+atom,+atom,+list(compound)) - one

node/7

Writes a node using the specified options.

Compilation flags:

static

Template:

node(Stream,Identifier,Label,Caption,Lines,Kind,Options)

Mode and number of proofs:

node(+stream_or_alias,+nonvar,+nonvar,+nonvar,+list(nonvar),+atom,+list(compound)) - one

edge/6

Writes an edge between two nodes using the specified options.

Compilation flags:

static

Template:

edge(Stream,Start,End,Labels,Kind,Options)

Mode and number of proofs:

edge(+stream_or_alias,+nonvar,+nonvar,+list(nonvar),+atom,+list(compound)) - one

Protected predicates

(none)

Private predicates

(none)

Operators

(none)

object

1.15.18 graph_language_registry

Registry of implemented graph languages.

Availability:

```
logtalk_load(diagrams(loader))
```

Author: Paulo Moura

Version: 1:0:1

Date: 2020-03-25

Compilation flags:

```
static, context_switching_calls
```

Dependencies:

(none)

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
 - language_object/2
- Protected predicates
- Private predicates
- Operators

Public predicates

language_object/2

Table of defined graph languages and their implementation objects.

Compilation flags:
static, multifile

Template:
language_object(Language, Object)
Mode and number of proofs:
language_object(?atom, ?object_identifier) - zero_or_more

Protected predicates

(none)

Private predicates

(none)

Operators

(none)

object

1.15.19 inheritance_diagram

Predicates for generating entity diagrams in DOT format with inheritance relation edges but no cross-referencing relation edges.

Availability:
logtalk_load(diagrams(loader))

Author: Paulo Moura
Version: 2:0:0
Date: 2014-01-15

Compilation flags:

static, context_switching_calls

Extends:

public inheritance_diagram(dot)

Remarks:

(none)

Inherited public predicates:

all_files/0 all_files/1 all_libraries/0 all_libraries/1 check_option/1 check_options/1
 default_option/1 default_options/1 diagram_description/1 diagram_name_suffix/1 directories/2
 directories/3 directory/1 directory/2 directory/3 file/1 file/2 files/1 files/2 files/3
 format_object/1 libraries/1 libraries/2 libraries/3 library/1 library/2 option/2 option/3
 rdirectory/1 rdirectory/2 rdirectory/3 rlibrary/1 rlibrary/2 valid_option/1 valid_options/1

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

See also:

entity_diagram, uses_diagram, xref_diagram

object

1.15.20 inheritance_diagram(Format)

- Format - Graph language file format.

Predicates for generating entity diagrams in the specified format with inheritance relation edges but no cross-referencing relation edges.

Availability:

```
logtalk_load(diagrams(loader))
```

Author: Paulo Moura

Version: 2:20:0

Date: 2024-03-20

Compilation flags:

```
static, context_switching_calls
```

Extends:

```
public entity_diagram(Format)
```

Uses:

```
logtalk
```

Remarks:

```
(none)
```

Inherited public predicates:

```
all_files/0 all_files/1 all_libraries/0 all_libraries/1 check_option/1 check_options/1  
default_option/1 default_options/1 diagram_description/1 diagram_name_suffix/1 directories/2  
directories/3 directory/1 directory/2 directory/3 file/1 file/2 files/1 files/2 files/3  
format_object/1 libraries/1 libraries/2 libraries/3 library/1 library/2 option/2 option/3  
rdirectory/1 rdirectory/2 rdirectory/3 rlibrary/1 rlibrary/2 valid_option/1 valid_options/1
```

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

See also:

`entity_diagram(Format)`, `uses_diagram(Format)`, `xref_diagram(Format)`
object

1.15.21 `library_dependency_diagram`

Predicates for generating library dependency diagrams in DOT format.

Availability:

`logtalk_load(diagrams(loader))`

Author: Paulo Moura

Version: 2:1:0

Date: 2019-06-13

Compilation flags:

`static`, `context_switching_calls`

Extends:

`public library_dependency_diagram(dot)`

Remarks:

(none)

Inherited public predicates:

all_files/0 all_files/1 all_libraries/0 all_libraries/1 check_option/1 check_options/1
default_option/1 default_options/1 diagram_description/1 diagram_name_suffix/1 directories/2
directories/3 directory/1 directory/2 directory/3 files/1 files/2 files/3 format_object/1
libraries/1 libraries/2 libraries/3 library/1 library/2 option/2 option/3 rdirectory/1
rdirectory/2 rdirectory/3 rlibrary/1 rlibrary/2 valid_option/1 valid_options/1

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

See also:

library_load_diagram, file_load_diagram, entity_diagram

object

1.15.22 library_dependency_diagram(Format)

- Format - Graph language file format.

Predicates for generating library dependency diagrams. A dependency exists when an entity in one library makes a reference to an entity in another library.

Availability:

logtalk_load(diagrams(loader))

Author: Paulo Moura

Version: 2:33:1

Date: 2024-04-01

Compilation flags:

static, context_switching_calls

Imports:

public library_diagram(Format)

Uses:

entity_diagram(Format)

list

logtalk

modules_diagram_support

Remarks:

(none)

Inherited public predicates:

all_files/0 all_files/1 all_libraries/0 all_libraries/1 check_option/1 check_options/1
default_option/1 default_options/1 diagram_description/1 diagram_name_suffix/1 directories/2
directories/3 directory/1 directory/2 directory/3 files/1 files/2 files/3 format_object/1
libraries/1 libraries/2 libraries/3 library/1 library/2 option/2 option/3 rdirectory/1
rdirectory/2 rdirectory/3 rlibrary/1 rlibrary/2 valid_option/1 valid_options/1

- Public predicates
- Protected predicates
- Private predicates
 - sub_diagram_/1
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

sub_diagram_/1

Table of library sub-diagrams to support their generation.

Compilation flags:

dynamic

Template:

sub_diagram_(Library)

Mode and number of proofs:

sub_diagram_(?atom) - zero_or_more

Operators

(none)

See also:

library_load_diagram(Format), directory_load_diagram(Format), file_load_diagram(Format), entity_diagram(Format)

category

1.15.23 library_diagram(Format)

- Format - Graph language file format.

Common predicates for generating library diagrams.

Availability:

logtalk_load(diagrams(loader))

Author: Paulo Moura

Version: 2:16:1

Date: 2024-03-30

Compilation flags:

static

Extends:

public diagram(Format)

Uses:

list

user

Remarks:

(none)

Inherited public predicates:

all_files/0 all_files/1 all_libraries/0 all_libraries/1 check_option/1 check_options/1
 default_option/1 default_options/1 diagram_description/1 diagram_name_suffix/1 directories/2
 directories/3 directory/1 directory/2 directory/3 files/1 files/2 files/3 format_object/1
 libraries/1 libraries/2 libraries/3 library/1 library/2 option/2 option/3 rdirectory/1
 rdirectory/2 rdirectory/3 rlibrary/1 rlibrary/2 valid_option/1 valid_options/1

- Public predicates
- Protected predicates
 - add_library_documentation_url/4
 - remember_included_library/2
 - remember_referenced_logtalk_library/2
 - remember_referenced_prolog_library/2
- Private predicates
 - included_library_/2
 - referenced_logtalk_library_/2
 - referenced_prolog_library_/2
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

`add_library_documentation_url/4`

Adds a documentation URL when using the option `url_prefixes/2`.

Compilation flags:

`static`

Template:

`add_library_documentation_url(Kind,Options,Library,NodeOptions)`

Mode and number of proofs:

`add_library_documentation_url(+atom,+list(compound),+atom,-list(compound)) - one`

`remember_included_library/2`

Remember included Logtalk library in the diagram.

Compilation flags:

`static`

Template:

`remember_included_library(Library,Path)`

Mode and number of proofs:

`remember_included_library(+atom,+atom) - one`

`remember_referenced_logtalk_library/2`

Remember referenced Logtalk library in the diagram.

Compilation flags:

`static`

Template:

remember_referenced_logtalk_library(Library,Path)

Mode and number of proofs:

remember_referenced_logtalk_library(+atom,+atom) - one

remember_referenced_prolog_library/2

Remember referenced Prolog library in the diagram.

Compilation flags:

static

Template:

remember_referenced_prolog_library(Library,Path)

Mode and number of proofs:

remember_referenced_prolog_library(+atom,+atom) - one

Private predicates

included_library_/2

Table of Logtalk libraries already included in the diagram.

Compilation flags:

dynamic

Template:

included_library_(Library,Path)

Mode and number of proofs:

included_library_(?atom,?atom) - zero_or_more

referenced_logtalk_library_/2

Table of referenced Logtalk libraries in the diagram.

Compilation flags:

dynamic

Template:

referenced_logtalk_library_(Library,Path)

Mode and number of proofs:

referenced_logtalk_library_(?atom,?atom) - zero_or_more

referenced_prolog_library_/2

Table of referenced Prolog libraries in the diagram.

Compilation flags:

dynamic

Template:

referenced_prolog_library_(Library,Path)

Mode and number of proofs:

referenced_prolog_library_(?atom,?atom) - zero_or_more

Operators

(none)

See also:

inheritance_diagram(Format), uses_diagram(Format), xref_diagram(Format), entity_diagram(Format)
object

1.15.24 library_load_diagram

Predicates for generating library loading dependency diagrams in DOT format.

Availability:

```
logtalk_load(diagrams(loader))
```

Author: Paulo Moura

Version: 2:1:0

Date: 2019-06-13

Compilation flags:

```
static, context_switching_calls
```

Extends:

```
public library_load_diagram(dot)
```

Remarks:

```
(none)
```

Inherited public predicates:

```
all_files/0 all_files/1 all_libraries/0 all_libraries/1 check_option/1 check_options/1
default_option/1 default_options/1 diagram_description/1 diagram_name_suffix/1 directories/2
directories/3 directory/1 directory/2 directory/3 files/1 files/2 files/3 format_object/1
libraries/1 libraries/2 libraries/3 library/1 library/2 option/2 option/3 rdirectory/1
rdirectory/2 rdirectory/3 rlibrary/1 rlibrary/2 valid_option/1 valid_options/1
```

- [Public predicates](#)
- [Protected predicates](#)
- [Private predicates](#)
- [Operators](#)

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

See also:

`library_dependency_diagram`, `file_dependency_diagram`, `entity_diagram`
object

1.15.25 `library_load_diagram`(Format)

- Format - Graph language file format.

Predicates for generating library loading dependency diagrams.

Availability:

```
logtalk_load(diagrams(loader))
```

Author: Paulo Moura

Version: 2:33:1

Date: 2024-04-01

Compilation flags:

```
static, context_switching_calls
```

Imports:

```
public library_diagram(Format)
```

Uses:

```
entity_diagram(Format)  
list  
logtalk  
modules_diagram_support
```

Remarks:

(none)

Inherited public predicates:

all_files/0 all_files/1 all_libraries/0 all_libraries/1 check_option/1 check_options/1
 default_option/1 default_options/1 diagram_description/1 diagram_name_suffix/1 directories/2
 directories/3 directory/1 directory/2 directory/3 files/1 files/2 files/3 format_object/1
 libraries/1 libraries/2 libraries/3 library/1 library/2 option/2 option/3 rdirectory/1
 rdirectory/2 rdirectory/3 rlibrary/1 rlibrary/2 valid_option/1 valid_options/1

- Public predicates
- Protected predicates
- Private predicates
 - sub_diagram_/1
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

sub_diagram_/1

Table of library sub-diagrams to support their generation.

Compilation flags:

dynamic

Template:

sub_diagram_(Library)

Mode and number of proofs:

sub_diagram_(?atom) - zero_or_more

Operators

(none)

See also:

`library_dependency_diagram(Format)`, `directory_dependency_diagram(Format)`,
`file_dependency_diagram(Format)`, `entity_diagram(Format)`
`object`

1.15.26 `modules_diagram_support`

Utility predicates for supporting Prolog modules in diagrams.

Availability:

`logtalk_load(diagrams(loader))`

Author: Paulo Moura

Version: 0:19:5

Date: 2022-07-08

Compilation flags:

`static`, `context_switching_calls`

Dependencies:

(none)

Remarks:

- Supported backend Prolog systems: ECLiPSe, SICStus Prolog, SWI-Prolog, and YAP.

Inherited public predicates:

(none)

- Public predicates
 - `module_property/2`
 - `loaded_file_property/2`
 - `source_file_extension/1`
- Protected predicates
- Private predicates
- Operators

Public predicates

`module_property/2`

Access to module properties, at least `exports/1`, `file/1`, and `file/2` but also `declares/2`, `defines/2`, `calls/2`, and `provides/3` when possible.

Compilation flags:

`static`

Template:

`module_property(Module,Property)`

Mode and number of proofs:

`module_property(?atom,?callable) - zero_or_more`

`loaded_file_property/2`

Access to loaded source file properties, at least `basename/1`, `directory/1` but also `parent/1` when possible.

Compilation flags:

`static`

Template:

`loaded_file_property(File,Property)`

Mode and number of proofs:

`loaded_file_property(?atom,?callable) - zero_or_more`

`source_file_extension/1`

Valid source file extension for Prolog source files.

Compilation flags:

`static`

Template:

`source_file_extension(Extension)`

Mode and number of proofs:

source_file_extension(?atom) - one_or_more

Protected predicates

(none)

Private predicates

(none)

Operators

(none)

object

1.15.27 uses_diagram

Predicates for generating entity diagrams in DOT format with only uses/2 and use_module/2 relation edges.

Availability:

logtalk_load(diagrams(loader))

Author: Paulo Moura

Version: 2:0:1

Date: 2020-03-27

Compilation flags:

static, context_switching_calls

Extends:

public uses_diagram(dot)

Remarks:

(none)

Inherited public predicates:

all_files/0 all_files/1 all_libraries/0 all_libraries/1 check_option/1 check_options/1
 default_option/1 default_options/1 diagram_description/1 diagram_name_suffix/1 directories/2
 directories/3 directory/1 directory/2 directory/3 file/1 file/2 files/1 files/2 files/3
 format_object/1 libraries/1 libraries/2 libraries/3 library/1 library/2 option/2 option/3
 rdirectory/1 rdirectory/2 rdirectory/3 rlibrary/1 rlibrary/2 valid_option/1 valid_options/1

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

See also:

entity_diagram, inheritance_diagram, xref_diagram

object

1.15.28 uses_diagram(Format)

- Format - Graph language file format.

Predicates for generating entity diagrams with only uses/2 and use_module/2 relation edges.

Availability:

logtalk_load(diagrams(loader))

Author: Paulo Moura

Version: 2:21:0

Date: 2024-03-20

Compilation flags:

static, context_switching_calls

Extends:

public entity_diagram(Format)

Uses:

logtalk

Remarks:

(none)

Inherited public predicates:

all_files/0 all_files/1 all_libraries/0 all_libraries/1 check_option/1 check_options/1
default_option/1 default_options/1 diagram_description/1 diagram_name_suffix/1 directories/2
directories/3 directory/1 directory/2 directory/3 file/1 file/2 files/1 files/2 files/3
format_object/1 libraries/1 libraries/2 libraries/3 library/1 library/2 option/2 option/3
rdirectory/1 rdirectory/2 rdirectory/3 rlibrary/1 rlibrary/2 valid_option/1 valid_options/1

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

See also:

`entity_diagram(Format)`, `inheritance_diagram(Format)`, `xref_diagram(Format)`

object

1.15.29 xref_diagram

Predicates for generating predicate call cross-referencing diagrams in DOT format.

Availability:

```
logtalk_load(diagrams(loader))
```

Author: Paulo Moura

Version: 2:0:0

Date: 2014-01-01

Compilation flags:

```
static, context_switching_calls
```

Extends:

```
public xref_diagram(dot)
```

Remarks:

(none)

Inherited public predicates:

```
all_files/0 all_files/1 all_libraries/0 all_libraries/1 check_option/1 check_options/1
default_option/1 default_options/1 diagram_description/1 diagram_name_suffix/1 directories/2
directories/3 directory/1 directory/2 directory/3 entity/1 entity/2 file/1 file/2 files/1 files/2
files/3 format_object/1 libraries/1 libraries/2 libraries/3 library/1 library/2 option/2 option/3
rdirectory/1 rdirectory/2 rdirectory/3 rlibrary/1 rlibrary/2 valid_option/1 valid_options/1
```

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

See also:

`entity_diagram`, `inheritance_diagram`, `uses_diagram`
object

1.15.30 `xref_diagram`(Format)

- Format - Graph language file format.

Predicates for generating predicate call cross-referencing diagrams.

Availability:

```
logtalk_load(diagrams(loader))
```

Author: Paulo Moura

Version: 2:72:1

Date: 2024-04-02

Compilation flags:

```
static, context_switching_calls
```

Extends:

```
public entity_diagram(Format)
```

Uses:

```
atom  
list  
logtalk  
modules_diagram_support  
os  
user
```

Remarks:

(none)

Inherited public predicates:

all_files/0 all_files/1 all_libraries/0 all_libraries/1 check_option/1 check_options/1
 default_option/1 default_options/1 diagram_description/1 diagram_name_suffix/1 directories/2
 directories/3 directory/1 directory/2 directory/3 file/1 file/2 files/1 files/2 files/3
 format_object/1 libraries/1 libraries/2 libraries/3 library/1 library/2 option/2 option/3
 rdirectory/1 rdirectory/2 rdirectory/3 rlibrary/1 rlibrary/2 valid_option/1 valid_options/1

- Public predicates
 - entity/2
 - entity/1
- Protected predicates
- Private predicates
 - included_predicate_/1
 - referenced_predicate_/1
 - external_predicate_/1
- Operators

Public predicates

entity/2

Creates a diagram for a single entity using the specified options.

Compilation flags:

static

Template:

entity(Entity,Options)

Mode and number of proofs:

entity(+entity_identifier,+list(compound)) - one

entity/1

Creates a diagram for a single entity using default options.

Compilation flags:

static

Template:

entity(Entity)

Mode and number of proofs:

entity(+entity_identifier) - one

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

included_predicate_/1

Table of predicates already included in the diagram for the entity under processing.

Compilation flags:

dynamic

Template:

included_predicate_(Predicate)

Mode and number of proofs:

included_predicate_(?predicate_indicator) - zero_or_more

referenced_predicate_/1

Table of referenced predicates for the entity under processing.

Compilation flags:

dynamic

Template:

referenced_predicate_(Predicate)

Mode and number of proofs:

referenced_predicate_(?predicate_indicator) - zero_or_more

external_predicate_/1

Table of external predicate references for all the entities under processing.

Compilation flags:

dynamic

Template:

external_predicate_(Reference)

Mode and number of proofs:

external_predicate_(?compound) - zero_or_more

Operators

(none)

See also:

entity_diagram(Format), inheritance_diagram(Format), uses_diagram(Format)

1.16 dictionaries

object

1.16.1 avltree

AVL tree implementation of the dictionary protocol. Uses standard order to compare keys.

Availability:

logtalk_load(dictionaries(loader))

Author: R.A.O'Keefe, L.Damas, V.S.Costa, Glenn Burgess, Jiri Spitz, and Jan Wielemaker; Logtalk port and additional predicates by Paulo Moura

Version: 1:4:0

Date: 2021-04-12

Compilation flags:

static, context_switching_calls

Implements:

public dictionaryp

Extends:

public term

Uses:

list

Remarks:

(none)

Inherited public predicates:

(<)/2 (=:=)/2 (=<)/2 (=\\=)/2 (>)/2 (>=)/2 apply/4 as_curly_bracketed/2
as_dictionary/2 as_list/2 check/1 clone/3 clone/4 delete/4 delete_max/4 delete_min/4
depth/2 empty/1 ground/1 insert/4 intersection/2 intersection/3 keys/2 lookup/2 lookup/3
map/2 map/3 max/3 min/3 new/1 next/4 numbervars/1 numbervars/3 occurs/2 previous/4
singletons/2 size/2 subsumes/2 subterm/2 update/3 update/4 update/5 valid/1 values/2
variables/2 variant/2 varnumbers/2 varnumbers/3

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

See also:

bintree, rbtree

object

1.16.2 bintree

Simple binary tree implementation of the dictionary protocol. Uses standard order to compare keys.

Availability:

```
logtalk_load(dictionaries(loader))
```

Author: Paulo Moura and Paul Fodor

Version: 2:11:1

Date: 2022-05-05

Compilation flags:

```
static, context_switching_calls
```

Implements:

```
public dictionaryp
```

Extends:

```
public term
```

Uses:

```
list
```

Remarks:

(none)

Inherited public predicates:

```
(<)/2 (=:=)/2 (=<)/2 (=\\=)/2 (>)/2 (>=)/2 apply/4 as_curly_bracketed/2
as_dictionary/2 as_list/2 check/1 clone/3 clone/4 delete/4 delete_max/4 delete_min/4
depth/2 empty/1 ground/1 insert/4 intersection/2 intersection/3 keys/2 lookup/2 lookup/3
map/2 map/3 max/3 min/3 new/1 next/4 numbervars/1 numbervars/3 occurs/2 previous/4
singletons/2 size/2 subsumes/2 subterm/2 update/3 update/4 update/5 valid/1 values/2
variables/2 variant/2 varnumbers/2 varnumbers/3
```

- Public predicates
 - preorder/2
 - inorder/2
 - postorder/2
- Protected predicates
- Private predicates
- Operators

Public predicates

preorder/2

Preorder tree traversal.

Compilation flags:

static

Template:

preorder(Tree,List)

Mode and number of proofs:

preorder(@tree,-list) - one

inorder/2

Inorder tree traversal.

Compilation flags:

static

Template:

inorder(Tree,List)

Mode and number of proofs:

inorder(@tree,-list) - one

postorder/2

Postorder tree traversal.

Compilation flags:

static

Template:

postorder(Tree,List)

Mode and number of proofs:

postorder(@tree,-list) - one

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

See also:

avltree, rbtree

protocol

1.16.3 dictionaryp

Dictionary protocol.

Availability:

logtalk_load(dictionaries(loader))

Author: Paulo Moura

Version: 2:3:0

Date: 2021-04-12

Compilation flags:

static

Dependencies:

(none)

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
 - as_dictionary/2
 - as_list/2
 - as_curly_bracketed/2
 - clone/3
 - clone/4
 - insert/4
 - delete/4
 - update/4
 - update/5
 - update/3
 - empty/1
 - lookup/3
 - lookup/2
 - intersection/2
 - intersection/3
 - previous/4
 - next/4
 - min/3
 - max/3
 - delete_min/4
 - delete_max/4
 - keys/2
 - values/2
 - map/2

- map/3
- apply/4
- size/2
- Protected predicates
- Private predicates
- Operators

Public predicates

`as_dictionary/2`

Converts a list of key-value pairs to a dictionary.

Compilation flags:

`static`

Template:

`as_dictionary(Pairs,Dictionary)`

Mode and number of proofs:

`as_dictionary(@list(pairs),-dictionary) - one`

`as_list/2`

Converts a dictionary to an ordered list (as per standard order) of key-value pairs.

Compilation flags:

`static`

Template:

`as_list(Dictionary,Pairs)`

Mode and number of proofs:

`as_list(@dictionary,-list(pairs)) - one`

as_curly_bracketed/2

Creates a curly-bracketed term representation of a dictionary.

Compilation flags:

static

Template:

as_curly_bracketed(Dictionary,Term)

Mode and number of proofs:

as_curly_bracketed(+dictionary,--term) - one

clone/3

Clones a dictionary using the same keys but with all values unbound and returning a list of all the pairs in the new clone.

Compilation flags:

static

Template:

clone(Dictionary,Clone,ClonePairs)

Mode and number of proofs:

clone(+dictionary,-dictionary,-list(pairs)) - one

clone/4

Clones a dictionary using the same keys but with all values unbound and returning the list of all pairs in the dictionary and in the clone.

Compilation flags:

static

Template:

clone(Dictionary,Pairs,Clone,ClonePairs)

Mode and number of proofs:

clone(+dictionary,-list(pairs),-dictionary,-list(pairs)) - one

insert/4

Inserts a key-value pair into a dictionary, returning the updated dictionary. When the key already exists, the associated value is updated.

Compilation flags:

static

Template:

insert(OldDictionary,Key,Value,NewDictionary)

Mode and number of proofs:

insert(+dictionary,+ground,@term,-dictionary) - one

delete/4

Deletes a matching key-value pair from a dictionary, returning the updated dictionary.

Compilation flags:

static

Template:

delete(OldDictionary,Key,Value,NewDictionary)

Mode and number of proofs:

delete(+dictionary,@ground,?term,-dictionary) - zero_or_one

update/4

Updates the value associated with Key in a dictionary, returning the updated dictionary. Fails if it cannot find the key.

Compilation flags:

static

Template:

update(OldDictionary,Key,NewValue,NewDictionary)

Mode and number of proofs:

update(+dictionary,@ground,+term,-dictionary) - zero_or_one

update/5

Updates the value associated with a key in a dictionary, returning the updated dictionary. Fails if it cannot find the key or if the existing value does not match the old value.

Compilation flags:

static

Template:

update(OldDictionary,Key,OldValue,NewValue,NewDictionary)

Mode and number of proofs:

update(+dictionary,@ground,?term,+term,-dictionary) - zero_or_one

update/3

Updates the key-value pairs in a dictionary, returning the updated dictionary. Fails if it cannot find one of the keys.

Compilation flags:

static

Template:

update(OldDictionary,Pairs,NewDictionary)

Mode and number of proofs:

update(+dictionary,@list(pair),-dictionary) - zero_or_one

empty/1

True iff the dictionary is empty.

Compilation flags:

static

Template:

empty(Dictionary)

Mode and number of proofs:

empty(@dictionary) - zero_or_one

lookup/3

Lookups a matching key-value pair from a dictionary.

Compilation flags:

static

Template:

lookup(Key,Value,Dictionary)

Mode and number of proofs:

lookup(+ground,?term,@dictionary) - zero_or_one

lookup(-ground,?term,@dictionary) - zero_or_more

lookup/2

Lookups all matching key-value pairs from a dictionary. Fails if it cannot find one of the keys or if a value for a key does not unify.

Compilation flags:

static

Template:

lookup(Pairs,Dictionary)

Mode and number of proofs:

lookup(+list(pair),@dictionary) - zero_or_one

intersection/2

True iff the values of the dictionaries common keys unify. Trivially true when there are no common keys.

Compilation flags:
static

Template:
intersection(Dictionary1,Dictionary2)

Mode and number of proofs:
intersection(+dictionary,+dictionary) - zero_or_one

intersection/3

Returns the (possibly empty) intersection between two dictionaries when the values of their common keys unify.

Compilation flags:
static

Template:
intersection(Dictionary1,Dictionary2,Intersection)

Mode and number of proofs:
intersection(+dictionary,+dictionary,-dictionary) - zero_or_one

previous/4

Returns the previous pair in a dictionary given a key.

Compilation flags:
static

Template:
previous(Dictionary,Key,Previous,Value)

Mode and number of proofs:

previous(+dictionary,+key,-key,-value) - zero_or_one

next/4

Returns the next pair in a dictionary given a key.

Compilation flags:

static

Template:

next(Dictionary,Key,Next,Value)

Mode and number of proofs:

next(+dictionary,+key,-key,-value) - zero_or_one

min/3

Returns the pair with the minimum key (as per standard order) in a dictionary. Fails if the dictionary is empty.

Compilation flags:

static

Template:

min(Dictionary,Key,Value)

Mode and number of proofs:

min(+dictionary,-key,-value) - zero_or_one

max/3

Returns the pair with the maximum key (as per standard order) in a dictionary. Fails if the dictionary is empty.

Compilation flags:

static

Template:

max(Dictionary,Key,Value)

Mode and number of proofs:

max(+dictionary,-key,-value) - zero_or_one

delete_min/4

Deletes the pair with the minimum key (as per standard order) from a dictionary, returning the deleted pair and the updated dictionary.

Compilation flags:

static

Template:

delete_min(OldDictionary,Key,Value,NewDictionary)

Mode and number of proofs:

delete_min(+dictionary,-key,-value,-dictionary) - zero_or_one

delete_max/4

Deletes the pair with the maximum key (as per standard order) from a dictionary, returning the deleted pair and the updated dictionary.

Compilation flags:

static

Template:

delete_max(OldDictionary,Key,Value,NewDictionary)

Mode and number of proofs:

`delete_max(+dictionary,-key,-value,-dictionary) - zero_or_one`

`keys/2`

Returns a list with all the dictionary keys in ascending order (as per standard order).

Compilation flags:

`static`

Template:

`keys(Dictionary,Keys)`

Mode and number of proofs:

`keys(@dictionary,-list) - one`

`values/2`

Returns a list with all the dictionary values in ascending order of the keys (as per standard order).

Compilation flags:

`static`

Template:

`values(Dictionary,Values)`

Mode and number of proofs:

`values(@dictionary,-list) - one`

`map/2`

Maps a closure over each dictionary key-value pair. Fails if the mapped closure attempts to modify the keys.

Compilation flags:

`static`

Template:

map(Closure,Dictionary)

Meta-predicate template:

map(1,*)

Mode and number of proofs:

map(@callable,+dictionary) - zero_or_more

map/3

Maps a closure over each dictionary key-value pair, returning the new dictionary. Fails if the mapped closure attempts to modify the keys.

Compilation flags:

static

Template:

map(Closure,OldDictionary,NewDictionary)

Meta-predicate template:

map(2,*,*)

Mode and number of proofs:

map(@callable,+dictionary,-dictionary) - zero_or_more

apply/4

Applies a closure to a specific key-value pair, returning the new dictionary. Fails if the key cannot be found or if the mapped closure attempts to modify the key.

Compilation flags:

static

Template:

apply(Closure,OldDictionary,Key,NewDictionary)

Meta-predicate template:

apply(2,*,*,*)

Mode and number of proofs:

apply(+callable,+dictionary,+key,-dictionary) - zero_or_one

size/2

Number of dictionary entries.

Compilation flags:

static

Template:

size(Dictionary,Size)

Mode and number of proofs:

size(@dictionary,?integer) - zero_or_one

Protected predicates

(none)

Private predicates

(none)

Operators

(none)

See also:

avltree, bintree, rbtree

object

1.16.4 rbtree

Red-Black tree implementation of the dictionary protocol. Uses standard order to compare keys.

Availability:

logtalk_load(dictionaries(loader))

Author: Vitor Santos Costa; Logtalk port and additional predicates by Paulo Moura.

Version: 1:9:0

Date: 2021-04-12

Compilation flags:

static, context_switching_calls

Implements:

public dictionaryp

Extends:

public term

Remarks:

(none)

Inherited public predicates:

(<)/2 (:=)/2 (=<)/2 (=\\=)/2 (>)/2 (>=)/2 apply/4 as_curly_bracketed/2
as_dictionary/2 as_list/2 check/1 clone/3 clone/4 delete/4 delete_max/4 delete_min/4
depth/2 empty/1 ground/1 insert/4 intersection/2 intersection/3 keys/2 lookup/2 lookup/3
map/2 map/3 max/3 min/3 new/1 next/4 numbervars/1 numbervars/3 occurs/2 previous/4
singletons/2 size/2 subsumes/2 subterm/2 update/3 update/4 update/5 valid/1 values/2
variables/2 variant/2 varnumbers/2 varnumbers/3

- Public predicates
 - partial_map/4
- Protected predicates
- Private predicates
- Operators

Public predicates

partial_map/4

Applies a closure to the tree pairs identified by a set of keys.

Compilation flags:

static

Template:

partial_map(Tree,Keys,Closure,NewTree)

Meta-predicate template:

partial_map(*,*,2,*)

Mode and number of proofs:

partial_map(+tree,+list,@closure,-tree) - zero_or_one

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

See also:

avltree, bintree

1.17 dif

object

1.17.1 dif

Provides dif/2 and derived predicates.

Availability:

logtalk_load(dif(loader))

Author: Paulo Moura

Version: 1:3:0

Date: 2023-10-02

Compilation flags:

static, context_switching_calls

Dependencies:

(none)

Remarks:

- Supported backend Prolog systems: B-Prolog, ECLiPSe, SICStus Prolog, SWI-Prolog, Trealla Prolog, and YAP.

Inherited public predicates:

(none)

- Public predicates
 - dif/2
 - dif/1
- Protected predicates
- Private predicates
- Operators

Public predicates

dif/2

Sets a constraint that is true iff the two terms are different.

Compilation flags:

static

Template:

dif(Term1,Term2)

Mode and number of proofs:

dif(+term,+term) - zero_or_one

dif/1

Sets a set of constraints that are true iff all terms in a list are different.

Compilation flags:

static

Template:

dif(Terms)

Mode and number of proofs:

dif(+list(term)) - zero_or_one

Protected predicates

(none)

Private predicates

(none)

Operators

(none)

1.18 doclet

object

1.18.1 doclet

Utility object to help automate (re)generating documentation for a project.

Availability:

`logtalk_load(doclet(loader))`

Author: Paulo Moura

Version: 0:5:0

Date: 2017-01-05

Compilation flags:

`static, context_switching_calls`

Provides:

`logtalk::message_tokens//2`

Uses:

`logtalk`

`os`

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
 - update/0
 - doc_goal/1
 - shell_command/1
- Protected predicates
- Private predicates
- Operators

Public predicates

update/0

Updates the project documentation, first by calling a sequence of goals and second by executing a sequence of shell commands. Fails if any goal or shell command fails.

Compilation flags:

static

Mode and number of proofs:

update - zero_or_one

doc_goal/1

Table of goals, typically using the diagrams and the lgt doc tools, used to generate the documentation. Goals are called in the order they are defined and in the context of the user pseudo-object.

Compilation flags:

static

Template:

doc_goal(Goal)

Mode and number of proofs:

doc_goal(?callable) - one_or_more

shell_command/1

Table of shell commands to convert intermediate documentation files into user-friendly documentation. Commands are executed in the order they are defined.

Compilation flags:

static

Template:

shell_command(Command)

Mode and number of proofs:

shell_command(?atom) - one_or_more

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

See also:

lgtdocp, diagram(Format)

1.19 edcg

object

1.19.1 edcg

Multiple hidden parameters: an extension to Prolog's DCG notation. Ported to Logtalk as a hook object.

Availability:

logtalk_load(edcg(loader))

Author: Peter Van Roy; adapted to Logtalk by Paulo Moura.

Version: 1:4:2
Date: 2020-04-08

Copyright: Copyright (C) 1992 Peter Van Roy
License: MIT

Compilation flags:
static, context_switching_calls

Implements:
public expanding
Provides:
logtalk::message_tokens//2
Uses:
list
logtalk

Remarks:

- Usage: Compile source files with objects (or categories) defining EDCGs using the compiler option `hook(edcg)`.

Inherited public predicates:
goal_expansion/2 term_expansion/2

- Public predicates
- Protected predicates
- Private predicates
 - pred_info/3
 - acc_info/7
 - acc_info/5
 - pass_info/2
 - pass_info/1
- Operators
 - op(1200,xfx,-->>)

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

pred_info/3

Declares predicates that have the listed hidden parameters.

Compilation flags:

dynamic

Template:

pred_info(Name,Arity,HiddenParameters)

Mode and number of proofs:

pred_info(?atom,?integer,?list(atom)) - zero_or_more

acc_info/7

Long form for declaring accumulators.

Compilation flags:

dynamic

Template:

acc_info(Accumulator,Term,Left,Right,Joiner,LStart,RStart)

Mode and number of proofs:

acc_info(?atom,?term,?term,?term,?callable,?term,?term) - zero_or_more

acc_info/5

Short form for declaring accumulators.

Compilation flags:

dynamic

Template:

acc_info(Accumulator,Term,Left,Right,Joiner)

Mode and number of proofs:

acc_info(?atom,?term,?term,?term,?callable) - zero_or_more

pass_info/2

Long form for declaring passed arguments. Passed arguments are conceptually the same as accumulators with =/2 as the joiner function.

Compilation flags:

dynamic

Template:

pass_info(Argument,PStart)

Mode and number of proofs:

pass_info(?atom,?term) - zero_or_more

pass_info/1

Short form for declaring passed arguments. Passed arguments are conceptually the same as accumulators with =/2 as the joiner function.

Compilation flags:

dynamic

Template:

pass_info(Argument)

Mode and number of proofs:

pass_info(?atom) - zero_or_more

Operators

`op(1200,xfx,-->>)`

Scope:

public

1.20 events

object

1.20.1 after_event_registry

After events registry predicates.

Availability:

`logtalk_load(events(loader))`

Author: Paulo Moura

Version: 1:1:0

Date: 2009-10-08

Compilation flags:

`static, context_switching_calls, events`

Implements:

`public event_registryp`

Remarks:

(none)

Inherited public predicates:

`del_monitors/0 del_monitors/4 monitor/1 monitor/4 monitored/1 monitors/1 set_monitor/4`

- Public predicates
- Protected predicates
- Private predicates

- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

See also:

`before_event_registry`, `monitorp`
object

1.20.2 `before_event_registry`

Before events registry predicates.

Availability:

`logtalk_load(events(loader))`

Author: Paulo Moura

Version: 1:1:0

Date: 2009-10-08

Compilation flags:

`static`, `context_switching_calls`, `events`

Implements:

`public event_registryp`

Remarks:

(none)

Inherited public predicates:

del_monitors/0 del_monitors/4 monitor/1 monitor/4 monitored/1 monitors/1 set_monitor/4

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

See also:

after_event_registry, monitorp

object

1.20.3 event_registry

Before and after events registry predicates.

Availability:

logtalk_load(events(loader))

Author: Paulo Moura

Version: 1:1:0

Date: 2009-10-08

Compilation flags:

static, context_switching_calls, events

Implements:

public event_registryp

Remarks:

(none)

Inherited public predicates:

del_monitors/0 del_monitors/4 monitor/1 monitor/4 monitored/1 monitors/1 set_monitor/4

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

protocol

1.20.4 event_registryp

Event registry protocol.

Availability:

logtalk_load(events(loader))

Author: Paulo Moura

Version: 1:1:0

Date: 2009-10-08

Compilation flags:

static

Dependencies:

(none)

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
 - monitors/1
 - monitor/1
 - monitored/1
 - monitor/4
 - set_monitor/4
 - del_monitors/4
 - del_monitors/0
- Protected predicates
- Private predicates
- Operators

Public predicates

monitors/1

Returns a list of all current monitors.

Compilation flags:

static

Template:

monitors(Monitors)

Mode and number of proofs:

monitors(-list(object_identifier)) - one

monitor/1

Monitor is an object playing the role of a monitor.

Compilation flags:

static

Template:

monitor(Monitor)

Mode and number of proofs:

monitor(-object_identifier) - zero_or_more

monitor(+object_identifier) - zero_or_one

monitored/1

Returns a list of all currently monitored objects.

Compilation flags:

static

Template:

monitored(Objects)

Mode and number of proofs:

monitored(-list(object_identifier)) - one

monitor/4

True if the arguments describe a currently defined monitored event.

Compilation flags:

static

Template:

monitor(Object,Message,Sender,Monitor)

Mode and number of proofs:

monitor(?object_identifier,?nonvar,?object_identifier,?object_identifier) - zero_or_more

set_monitor/4

Sets a monitor for the set of matching events.

Compilation flags:

static

Template:

set_monitor(Object,Message,Sender,Monitor)

Mode and number of proofs:

set_monitor(?object_identifier,?nonvar,?object_identifier,+object_identifier) - zero_or_one

del_monitors/4

Deletes all matching monitored events.

Compilation flags:

static

Template:

del_monitors(Object,Message,Sender,Monitor)

Mode and number of proofs:

del_monitors(?object_identifier,?nonvar,?object_identifier,?object_identifier) - one

del_monitors/0

Deletes all monitored events.

Compilation flags:

static

Mode and number of proofs:

del_monitors - one

Protected predicates

(none)

Private predicates

(none)

Operators

(none)

See also:

`event_registry`, `monitorp`
`category`

1.20.5 monitor

Monitor predicates.

Availability:

`logtalk_load(events(loader))`

Author: Paulo Moura

Version: 1:3:0

Date: 2019-03-08

Compilation flags:

`static`, `events`

Implements:

`public monitorp`

Remarks:

(none)

Inherited public predicates:

`activate_monitor/0` `del_spy_points/4` `monitor_activated/0` `reset_monitor/0` `set_spy_point/4`
`spy_point/4` `suspend_monitor/0`

- Public predicates
- Protected predicates
- Private predicates
 - spy_point_/4
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

spy_point_/4

Stores current spy points.

Compilation flags:

dynamic

Template:

spy_point_(Event,Object,Message,Sender)

Mode and number of proofs:

spy_point_(?event,?object,?callable,?object) - zero_or_more

Operators

(none)

protocol

1.20.6 monitorp

Monitor protocol.

Availability:

logtalk_load(events(loader))

Author: Paulo Moura

Version: 1:0:0

Date: 2000-07-24

Compilation flags:

static

Dependencies:

(none)

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
 - monitor_activated/0
 - activate_monitor/0
 - suspend_monitor/0
 - reset_monitor/0
 - spy_point/4
 - set_spy_point/4
 - del_spy_points/4
- Protected predicates
- Private predicates
- Operators

Public predicates

monitor_activated/0

True if monitor is currently active.

Compilation flags:

static

Mode and number of proofs:

monitor_activated - zero_or_one

activate_monitor/0

Activates all spy points and start monitoring.

Compilation flags:

static

Mode and number of proofs:

activate_monitor - one

suspend_monitor/0

Suspends monitoring, deactivating all spy points.

Compilation flags:

static

Mode and number of proofs:

suspend_monitor - one

reset_monitor/0

Resets monitor, deactivating and deleting all spy points.

Compilation flags:

static

Mode and number of proofs:

reset_monitor - one

spy_point/4

Current spy point.

Compilation flags:

static

Template:

spy_point(Event, Object, Message, Sender)

Mode and number of proofs:

spy_point(?event, ?object, ?callable, ?object) - zero_or_more

set_spy_point/4

Sets a spy point.

Compilation flags:

static

Template:

set_spy_point(Event, Object, Message, Sender)

Mode and number of proofs:

set_spy_point(?event, ?object, ?callable, ?object) - one

`del_spy_points/4`

Deletes all matching spy points.

Compilation flags:

`static`

Template:

`del_spy_points(Event, Object, Message, Sender)`

Mode and number of proofs:

`del_spy_points(@event, @object, @callable, @object) - one`

Protected predicates

(none)

Private predicates

(none)

Operators

(none)

See also:

`monitor`, `event_registry`

1.21 expand_library_alias_paths

object

1.21.1 expand_library_alias_paths

Hook object for expanding library alias paths in `logtalk_library_path/2` facts when compiling a source file.

Availability:

`logtalk_load(expand_library_alias_paths(loader))`

Author: Paulo Moura

Version: 1:0:0

Date: 2018-04-12

Compilation flags:

static, context_switching_calls

Implements:

public expanding

Uses:

logtalk

os

Remarks:

(none)

Inherited public predicates:

goal_expansion/2 term_expansion/2

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

1.22 expecteds

object

1.22.1 either

Types and predicates for extended type-checking and handling of expected terms.

Availability:

```
logtalk_load(expecteds(loader))
```

Author: Paulo Moura

Version: 0:7:0

Date: 2021-01-03

Compilation flags:

```
static, context_switching_calls
```

Provides:

```
type::type/1
```

```
type::check/2
```

```
arbitrary::arbitrary/1
```

```
arbitrary::arbitrary/2
```

Uses:

```
expected
```

```
expected(Expected)
```

```
random
```

```
type
```

Remarks:

- Type-checking support: Defines a `either(ValueType, ErrorType)` type for checking expected terms where the value and error terms must be of the given types.
- QuickCheck support: Defines clauses for the `type::arbitrary/1-2` predicates to allow generating random values for the `either(ValueType, ErrorType)` type.

Inherited public predicates:

(none)

- Public predicates
 - expecteds/2
 - unexpecteds/2
 - partition/3
- Protected predicates
- Private predicates
- Operators

Public predicates

expecteds/2

Returns the values stored in the expected terms that hold a value.

Compilation flags:

static

Template:

expecteds(Expecteds,Values)

Mode and number of proofs:

expecteds(+list(expected),-list) - one

unexpecteds/2

Returns the errors stored in the expected terms that hold an error.

Compilation flags:

static

Template:

unexpecteds(Expecteds,Errors)

Mode and number of proofs:

unexpecteds(+list(expected),-list) - one

partition/3

Retrieves and partitions the values and errors hold by the expected terms.

Compilation flags:

static

Template:

partition(Expecteds,Values,Errors)

Mode and number of proofs:

partition(+list(expected),-list,-list) - one

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

See also:

expected, expected(Expected), type, arbitrary

object

1.22.2 expected

Constructors for expected terms. An expected term contains either a value or an error. Expected terms should be regarded as opaque terms and always used with the expected/1 object by passing the expected term as a parameter.

Availability:

logtalk_load(expecteds(loader))

Author: Paulo Moura

Version: 2:1:0

Date: 2021-01-03

Compilation flags:

static, context_switching_calls

Provides:

type::type/1
type::check/2

Remarks:

- Type-checking support: This object also defines a type expected for use with the type library object.

Inherited public predicates:

(none)

- Public predicates
 - of_unexpected/2
 - of_expected/2
 - from_goal/4
 - from_goal/3
 - from_goal/2
 - from_generator/4
 - from_generator/3
 - from_generator/2
- Protected predicates
- Private predicates
- Operators

Public predicates

of_unexpected/2

Constructs an expected term from an error that represent that the expected value is missing.

Compilation flags:

static

Template:

of_unexpected(Error,Expected)

Mode and number of proofs:

of_unexpected(@term,--nonvar) - one

of_expected/2

Constructs an expected term from an expected value.

Compilation flags:

static

Template:

of_expected(Value,Expected)

Mode and number of proofs:

of_expected(@term,--nonvar) - one

from_goal/4

Constructs an expected term holding a value bound by calling the given goal. Otherwise returns an expected term with the unexpected goal error or failure represented by the Error argument.

Compilation flags:

static

Template:

from_goal(Goal,Value,Error,Expected)

Meta-predicate template:

from_goal(0,*,*,*)

Mode and number of proofs:

from_goal(+callable,--term,@term,--nonvar) - one

from_goal/3

Constructs an expected term holding a value bound by calling the given goal. Otherwise returns an expected term with the unexpected goal error or the atom fail representing the unexpected failure.

Compilation flags:

static

Template:

from_goal(Goal,Value,Expected)

Meta-predicate template:

from_goal(0,*,*)

Mode and number of proofs:

from_goal(+callable,--term,--nonvar) - one

from_goal/2

Constructs an expected term holding a value bound by calling the given closure. Otherwise returns an expected term holding the unexpected closure error or the atom fail representing the unexpected failure.

Compilation flags:

static

Template:

from_goal(Closure,Expected)

Meta-predicate template:

from_goal(1,*)

Mode and number of proofs:

from_goal(+callable,--nonvar) - one

from_generator/4

Constructs expected terms with the values generated by calling the given goal. On goal error or failure, returns an expected term with the unexpected goal error or failure represented by the Error argument.

Compilation flags:

static

Template:

```
from_generator(Goal,Value,Error,Expected)
```

Meta-predicate template:

```
from_generator(0,*,*,*)
```

Mode and number of proofs:

```
from_generator(+callable,--term,@term,--nonvar) - one_or_more
```

`from_generator/3`

Constructs expected terms with the values generated by calling the given goal. On goal error or failure, returns an expected term with, respectively, the unexpected goal error or the atom fail representing the unexpected goal failure.

Compilation flags:

```
static
```

Template:

```
from_generator(Goal,Value,Expected)
```

Meta-predicate template:

```
from_generator(0,*,*)
```

Mode and number of proofs:

```
from_generator(+callable,--term,--nonvar) - one_or_more
```

`from_generator/2`

Constructs expected terms with the values generated by calling the given closure. On closure error or failure, returns an expected term with, respectively, the unexpected closure error or the atom fail representing the unexpected closure failure.

Compilation flags:

```
static
```

Template:

```
from_generator(Closure,Expected)
```

Meta-predicate template:

```
from_generator(1,*)
```

Mode and number of proofs:

```
from_generator(+callable,--nonvar) - one_or_more
```

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

See also:

`expected(Expected)`, type

object

1.22.3 `expected(Expected)`

Expected term predicates. Requires passing an expected term (constructed using the expected object predicates) as a parameter.

Availability:

`logtalk_load(expecteds(loader))`

Author: Paulo Moura

Version: 1:5:0

Date: 2020-01-06

Compilation flags:

`static, context_switching_calls`

Dependencies:

(none)

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
 - is_expected/0
 - is_unexpected/0
 - if_expected/1
 - if_unexpected/1
 - if_expected_or_else/2
 - unexpected/1
 - expected/1
 - map/2
 - flat_map/2
 - either/3
 - or_else/2
 - or_else_get/2
 - or_else_call/2
 - or_else_throw/1
 - or_else_fail/1
- Protected predicates
- Private predicates
- Operators

Public predicates

is_expected/0

True if the expected term holds a value. See also the if_expected/1 predicate.

Compilation flags:

static

Mode and number of proofs:

is_expected - zero_or_one

is_unexpected/0

True if the expected term holds an error. See also the if_unexpected/1 predicate.

Compilation flags:

static

Mode and number of proofs:

is_unexpected - zero_or_one

if_expected/1

Applies a closure when the expected term holds a value using the value as argument. Succeeds otherwise.

Compilation flags:

static

Template:

if_expected(Closure)

Meta-predicate template:

if_expected(1)

Mode and number of proofs:

if_expected(+callable) - zero_or_more

if_unexpected/1

Applies a closure when the expected term holds an error using the error as argument. Succeeds otherwise. Can be used to throw the exception hold by the expected term by calling it the atom throw.

Compilation flags:

static

Template:

if_unexpected(Closure)

Meta-predicate template:

if_unexpected(1)

Mode and number of proofs:

`if_unexpected(+callable) - zero_or_more`

`if_expected_or_else/2`

Applies either `ExpectedClosure` or `UnexpectedClosure` depending on the expected term holding a value or an error.

Compilation flags:

`static`

Template:

`if_expected_or_else(ExpectedClosure,UnexpectedClosure)`

Meta-predicate template:

`if_expected_or_else(1,1)`

Mode and number of proofs:

`if_expected_or_else(+callable,+callable) - zero_or_more`

`unexpected/1`

Returns the error hold by the expected term. Throws an error otherwise.

Compilation flags:

`static`

Template:

`unexpected(Error)`

Mode and number of proofs:

`unexpected(--term) - one_or_error`

Exceptions:

Expected term holds a value:

`existence_error(unexpected_error,Expected)`

expected/1

Returns the value hold by the expected term. Throws an error otherwise.

Compilation flags:

static

Template:

expected(Value)

Mode and number of proofs:

expected(--term) - one_or_error

Exceptions:

Expected term holds an error:

existence_error(expected_value,Expected)

map/2

When the expected term does not hold an error and mapping a closure with the expected value and the new value as additional arguments is successful, returns an expected term with the new value. Otherwise returns the same expected term.

Compilation flags:

static

Template:

map(Closure,NewExpected)

Meta-predicate template:

map(2,*)

Mode and number of proofs:

map(+callable,--nonvar) - one

`flat_map/2`

When the expected term does not hold an error and mapping a closure with the expected value and the new expected term as additional arguments is successful, returns the new expected term. Otherwise returns the same expected term.

Compilation flags:

`static`

Template:

`flat_map(Closure,NewExpected)`

Meta-predicate template:

`flat_map(2,*)`

Mode and number of proofs:

`flat_map(+callable,--nonvar) - one`

`either/3`

Applies either `ExpectedClosure` if the expected term holds a value or `UnexpectedClosure` if the expected term holds an error. Returns a new expected term if the applied closure is successful. Otherwise returns the same expected term.

Compilation flags:

`static`

Template:

`either(ExpectedClosure,UnexpectedClosure,NewExpected)`

Meta-predicate template:

`either(2,2,*)`

Mode and number of proofs:

`either(+callable,+callable,--nonvar) - one`

`or_else/2`

Returns the value hold by the expected term if it does not hold an error or the given default term if the expected term holds an error.

Compilation flags:

`static`

Template:

`or_else(Value,Default)`

Mode and number of proofs:

`or_else(--term,@term) - one`

`or_else_get/2`

Returns the value hold by the expected term if it does not hold an error. Otherwise applies a closure to compute the expected value. Throws an error when the expected term holds an error and a value cannot be computed.

Compilation flags:

`static`

Template:

`or_else_get(Value,Closure)`

Meta-predicate template:

`or_else_get(*,1)`

Mode and number of proofs:

`or_else_get(--term,+callable) - one_or_error`

Exceptions:

Expected term holds an unexpected error and an expected value cannot be computed:

`existence_error(expected_value,Expected)`

`or_else_call/2`

Returns the value hold by the expected term if it does not hold an error. Calls a goal deterministically otherwise.

Compilation flags:

`static`

Template:

`or_else_call(Value,Goal)`

Meta-predicate template:

`or_else_call(*,0)`

Mode and number of proofs:

`or_else_call(--term,+callable) - zero_or_one`

`or_else_throw/1`

Returns the value hold by the expected term if present. Throws the error hold by the expected term as an exception otherwise.

Compilation flags:

`static`

Template:

`or_else_throw(Value)`

Mode and number of proofs:

`or_else_throw(--term) - one_or_error`

`or_else_fail/1`

Returns the value hold by the expected term if it does not hold an error. Fails otherwise. Usually called to skip over expected terms holding errors.

Compilation flags:

`static`

Template:

`or_else_fail(Value)`

Mode and number of proofs:

`or_else_fail(--term) - zero_or_one`

Protected predicates

(none)

Private predicates

(none)

Operators

(none)

See also:

`expected`

1.23 fcube

object

1.23.1 fcube

FCube: An Efficient Prover for Intuitionistic Propositional Logic.

Availability:

`logtalk_load(fcube(loader))`

Author: Mauro Ferrari, Camillo Fiorentini, Guido Fiorino; ported to Logtalk by Paulo Moura.

Version: 5:0:1

Date: 2024-03-314

Copyright: Copyright 2012 Mauro Ferrari, Camillo Fiorentini, Guido Fiorino; Copyright 2020-2024 Paulo Moura

License: GPL-2.0-or-later

Compilation flags:

`static, context_switching_calls`

Uses:

integer
list
os
set
user

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
 - gnu/0
 - fcube/0
 - decide/1
 - decide/2
- Protected predicates
- Private predicates
- Operators
 - op(1200,xfy,<=>)
 - op(1110,xfy,=>)
 - op(1000,xfy,&&&)
 - op(500,fy,~)
 - op(1100,xfy,v)

Public predicates

gnu/0

Prints banner with copyright and license information.

Compilation flags:

static

Mode and number of proofs:

gnu - one

fcube/0

Reads a formula and applies the prover to it, printing its counter-model.

Compilation flags:

static

Mode and number of proofs:

fcube - one

decide/1

Applies the prover to the given formula and prints its counter-model.

Compilation flags:

static

Template:

decide(Formula)

Mode and number of proofs:

decide(++compound) - one

decide/2

Applies the prover to the given formula and returns its counter-model.

Compilation flags:

static

Template:

decide(Formula,CounterModel)

Mode and number of proofs:

decide(++compound,--compound) - one

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

op(1200,xfy,<=>)

Scope:

public

op(1110,xfy,=>)

Scope:

public

op(1000,xfy,&&)

Scope:

public

op(500,fy,~)

Scope:

public

op(1100,xfy,v)

Scope:

public

1.24 flags

category

1.24.1 flags

Implementation of persistent object flags.

Availability:

```
logtalk_load(flags(loader))
```

Author: Theofrastos Mantadelis

Version: 1:0:0

Date: 2010-11-27

Compilation flags:

```
static
```

Dependencies:

```
(none)
```

Remarks:

```
(none)
```

Inherited public predicates:

```
(none)
```

- Public predicates
 - `get_flag_value/2`
 - `set_flag_value/2`
 - `set_flag_value/3`
 - `reset_flags/0`
 - `reset_flags/1`
 - `flag_groups/1`
 - `flag_group_chk/1`
 - `print_flags/0`
 - `print_flags/1`
 - `defined_flag/6`

- built_in_flag/2
- Protected predicates
 - unsafe_set_flag_value/2
 - define_flag/1
 - define_flag/2
- Private predicates
 - defined_flag_/6
 - flag_value_/2
 - validate/3
 - validate_type/1
 - is_validator/1
- Operators

Public predicates

get_flag_value/2

Gets or tests the value of a flag.

Compilation flags:

static

Template:

get_flag_value(Flag,Value)

Mode and number of proofs:

get_flag_value(+atom,?nonvar) - zero_or_one

set_flag_value/2

Sets the value of a flag.

Compilation flags:

static

Template:

set_flag_value(Flag,NewValue)

Mode and number of proofs:

`set_flag_value(+atom,@nonvar) - one`

`set_flag_value/3`

Sets the value of a flag, returning the old value.

Compilation flags:

`static`

Template:

`set_flag_value(Flag,OldValue,NewValue)`

Mode and number of proofs:

`set_flag_value(+atom,?nonvar,@nonvar) - one`

`reset_flags/0`

Resets all flags to their default values.

Compilation flags:

`static`

Mode and number of proofs:

`reset_flags - one`

`reset_flags/1`

Resets all flags in a group to their default values.

Compilation flags:

`static`

Template:

`reset_flags(Group)`

Mode and number of proofs:

reset_flags(+atom) - one

flag_groups/1

Returns a list of all flag groups.

Compilation flags:

static

Template:

flag_groups(Groups)

Mode and number of proofs:

flag_groups(-list(atom)) - one

flag_group_chk/1

Checks if a given atom is a flag group.

Compilation flags:

static

Template:

flag_group_chk(Group)

Mode and number of proofs:

flag_group_chk(+atom) - zero_or_one

print_flags/0

Prints a listing of all flags.

Compilation flags:

static

Mode and number of proofs:

`print_flags` - one

`print_flags/1`

Prints a listing of all flags in a group.

Compilation flags:

`static`

Template:

`print_flags(Group)`

Mode and number of proofs:

`print_flags(+atom)` - one

`defined_flag/6`

Gets or test the existing (visible) flag definitions.

Compilation flags:

`static`

Template:

`defined_flag(Flag,Group,Type,DefaultValue,Description,Access)`

Mode and number of proofs:

`defined_flag(?atom,?atom,?nonvar,?nonvar,?atom,?atom)` - `zero_or_more`

`built_in_flag/2`

True if the argument is a built-in flag type with the specified default value.

Compilation flags:

`static`

Template:

```
built_in_flag(Type,DefaultValue)
```

Mode and number of proofs:

```
built_in_flag(?atom,?nonvar) - zero_or_more
```

Protected predicates

`unsafe_set_flag_value/2`

Sets the value of a flag without performing any validation checks.

Compilation flags:

```
static
```

Template:

```
unsafe_set_flag_value(Flag,NewValue)
```

Mode and number of proofs:

```
unsafe_set_flag_value(+atom,@nonvar) - one
```

`define_flag/1`

Defines a new flag using default options.

Compilation flags:

```
static
```

Template:

```
define_flag(Flag)
```

Mode and number of proofs:

```
define_flag(+atom) - one
```

`define_flag/2`

Defines a new flag using a given set of options (for example, `[group(general), type(nonvar), default(true), description(Flag), access(read_write)]`).

Compilation flags:

`static`

Template:

`define_flag(Flag,Options)`

Mode and number of proofs:

`define_flag(+atom,@list) - one`

Private predicates

`defined_flag_/6`

Gets or test the existing flag definitions.

Compilation flags:

`dynamic`

Template:

`defined_flag_(Flag,Group,Type,DefaultValue,Description,Access)`

Mode and number of proofs:

`defined_flag_(?atom,?atom,?nonvar,?nonvar,?atom,?atom) - zero_or_more`

`flag_value_/2`

Table of flag values.

Compilation flags:

`dynamic`

Template:

`flag_value_(Flag,Value)`

Mode and number of proofs:

flag_value_(?atom,?nonvar) - zero_or_more

validate/3

Compilation flags:

static

validate_type/1

Compilation flags:

static

is_validator/1

Compilation flags:

static

Operators

(none)

protocol

1.24.2 flags_validator

Flag validation protocol. Must be implemented by validator objects.

Availability:

logtalk_load(flags(loader))

Author: Theofrastos Mantadelis

Version: 1:0:0

Date: 2010-11-27

Compilation flags:

static

Dependencies:

(none)

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
 - print_flags/0
 - validate/1
- Protected predicates
- Private predicates
- Operators

Public predicates

print_flags/0

Validates the validator object itself.

Compilation flags:

static

Mode and number of proofs:

print_flags - zero_or_one

validate/1

Validates a flag value.

Compilation flags:

static

Template:

validate(Value)

Mode and number of proofs:

validate(@term) - zero_or_one

Protected predicates

(none)

Private predicates

(none)

Operators

(none)

1.25 format

object

1.25.1 format

Formatted output predicates.

Availability:

logtalk_load(format(loader))

Author: Paulo Moura

Version: 1:2:0

Date: 2023-10-02

Compilation flags:

static, context_switching_calls

Dependencies:

(none)

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
 - format/3
 - format/2
- Protected predicates
- Private predicates
- Operators

Public predicates

format/3

Writes a list of arguments after a format specification to the specified output stream.

Compilation flags:

static

Template:

format(Stream,Format,Arguments)

Mode and number of proofs:

format(@stream_or_alias,+atom,@list) - zero_or_one

format(@stream_or_alias,+list(character_code),@list) - zero_or_one

format(@stream_or_alias,+list(character),@list) - zero_or_one

format/2

Writes a list of arguments after a format specification to the current output stream.

Compilation flags:

static

Template:

format(Format,Arguments)

Mode and number of proofs:

format(+atom,@list) - zero_or_one

format(+list(character_code),@list) - zero_or_one

format(+list(character),@list) - zero_or_one

Protected predicates

(none)

Private predicates

(none)

Operators

(none)

1.26 genint

object

1.26.1 genint

Global object for generating increasing non-negative integers for named counters. The predicates are declared as synchronized when the library is compiled using a backend supporting threads.

Availability:

logtalk_load(genint(loader))

Author: Paulo Moura

Version: 1:0:0

Date: 2022-07-21

Compilation flags:

static, context_switching_calls

Imports:

public genint_core

Remarks:

(none)

Inherited public predicates:

genint/2 reset_genint/0 reset_genint/1

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

category

1.26.2 genint_core

Predicates for generating increasing non-negative integers. The predicates are declared as synchronized when the library is compiled using a backend supporting threads.

Availability:

```
logtalk_load(genint(loader))
```

Author: Paulo Moura

Version: 1:0:0

Date: 2022-07-26

Compilation flags:

```
static
```

Dependencies:

```
(none)
```

Remarks:

```
(none)
```

Inherited public predicates:

```
(none)
```

- Public predicates
 - reset_genint/0
 - reset_genint/1
 - genint/2
- Protected predicates
- Private predicates
 - counter_/2
- Operators

Public predicates

reset_genint/0

Resets all counters.

Compilation flags:

static, synchronized

Mode and number of proofs:

reset_genint - one

reset_genint/1

Resets the given counter.

Compilation flags:

static, synchronized

Template:

reset_genint(Counter)

Mode and number of proofs:

reset_genint(+atom) - one

genint/2

Returns the next integer for a given counter.

Compilation flags:

static, synchronized

Template:

genint(Counter,Integer)

Mode and number of proofs:

genint(+atom,-non_negative_integer) - one

Protected predicates

(none)

Private predicates

counter_/2

Table of current state of counters.

Compilation flags:

dynamic

Template:

counter_(Counter,Latest)

Mode and number of proofs:

counter_(?atom,?non_negative_integer) - zero_or_more

Operators

(none)

1.27 gensym

object

1.27.1 gensym

Global object for generating unique atoms. The predicates are declared as synchronized when the library is compiled using a backend supporting threads.

Availability:

logtalk_load(gensym(loader))

Author: Paulo Moura

Version: 2:0:0

Date: 2022-07-21

Compilation flags:

static, context_switching_calls

Imports:

public gensym_core

Remarks:

(none)

Inherited public predicates:

gensym/2 reset_gensym/0 reset_gensym/1

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

category

1.27.2 gensym_core

Predicates for generating unique atoms. Protocol based on the gensym module of SWI-Prolog. The predicates are declared as synchronized when the library is compiled using a backend supporting threads.

Availability:

logtalk_load(gensym(loader))

Author: Paulo Moura

Version: 2:1:0

Date: 2022-07-26

Compilation flags:

static

Dependencies:

(none)

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
 - reset_gensym/0
 - reset_gensym/1
 - gensym/2
- Protected predicates
- Private predicates
 - base_/2
- Operators

Public predicates

reset_gensym/0

Resets the generator counter for all bases.

Compilation flags:

static, synchronized

Mode and number of proofs:

reset_gensym - one

reset_gensym/1

Resets the generator counter for a given base.

Compilation flags:

static, synchronized

Template:

reset_gensym(Base)

Mode and number of proofs:

reset_gensym(+atom) - one

gensym/2

Returns a new unique atom with a given base (prefix).

Compilation flags:

static, synchronized

Template:

gensym(Base,Unique)

Mode and number of proofs:

gensym(+atom,-atom) - one

Protected predicates

(none)

Private predicates

base_/2

Table of generator bases and respective counters.

Compilation flags:

dynamic

Template:

base_(Base,Counter)

Mode and number of proofs:

base_(?atom,?integer) - zero_or_more

Operators

(none)

1.28 git

object

1.28.1 git

Predicates for accessing a git project current branch and latest commit data.

Availability:

logtalk_load(`git(loader)`)

Author: Paulo Moura

Version: 2:1:2

Date: 2024-03-11

Compilation flags:

static, context_switching_calls

Implements:

public `git_protocol`

Uses:

`os`

`user`

Remarks:

(none)

Inherited public predicates:

`branch/2` `commit_author/2` `commit_date/2` `commit_hash/2` `commit_hash_abbreviated/2`
`commit_log/3` `commit_message/2`

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

protocol

1.28.2 git_protocol

Predicates for accessing a git project current branch and latest commit data.

Availability:

logtalk_load(git(loader))

Author: Paulo Moura

Version: 1:1:0

Date: 2022-01-21

Compilation flags:

static

Dependencies:

(none)

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
 - branch/2
 - commit_author/2
 - commit_date/2
 - commit_hash/2
 - commit_hash_abbreviated/2
 - commit_message/2
 - commit_log/3
- Protected predicates
- Private predicates
- Operators

Public predicates

branch/2

Returns the name of the current git branch. Fails if the directory is not a git repo or a sub-directory of a git repo directory.

Compilation flags:

static

Template:

branch(Directory,Branch)

Mode and number of proofs:

branch(+atom,?atom) - zero_or_one

commit_author/2

Returns the latest commit author. Fails if the directory is not a git repo or a sub-directory of a git repo directory.

Compilation flags:

static

Template:

commit_author(Directory,Author)

Mode and number of proofs:

commit_author(+atom,-atom) - zero_or_one

commit_date/2

Returns the latest commit date (strict ISO 8601 format). Fails if the directory is not a git repo or a sub-directory of a git repo directory.

Compilation flags:

static

Template:

commit_date(Directory,Date)

Mode and number of proofs:

commit_date(+atom,-atom) - zero_or_one

commit_hash/2

Returns the latest commit hash. Fails if the directory is not a git repo or a sub-directory of a git repo directory.

Compilation flags:

static

Template:

commit_hash(Directory,Hash)

Mode and number of proofs:

`commit_hash(+atom,-atom) - zero_or_one`

`commit_hash_abbreviated/2`

Returns the latest commit abbreviated hash. Fails if the directory is not a git repo or a sub-directory of a git repo directory.

Compilation flags:

`static`

Template:

`commit_hash_abbreviated(Directory,Hash)`

Mode and number of proofs:

`commit_hash_abbreviated(+atom,-atom) - zero_or_one`

`commit_message/2`

Returns the latest commit message. Fails if the directory is not a git repo or a sub-directory of a git repo directory.

Compilation flags:

`static`

Template:

`commit_message(Directory,Message)`

Mode and number of proofs:

`commit_message(+atom,-atom) - zero_or_one`

`commit_log/3`

Returns the git latest commit log output for the given format (see e.g. <https://git-scm.com/docs/pretty-formats>). Fails if the directory is not a git repo or a sub-directory of a git repo directory.

Compilation flags:

`static`

Template:

`commit_log(Directory,Format,Output)`

Mode and number of proofs:

`commit_log(+atom,+atom,-atom) - zero_or_one`

Protected predicates

(none)

Private predicates

(none)

Operators

(none)

1.29 grammars

object

1.29.1 `blank_grammars(Format)`

Blank grammars.

Availability:

`logtalk_load(grammars(loader))`

Author: Paulo Moura

Version: 0:3:1

Date: 2022-10-08

Compilation flags:

static, context_switching_calls

Dependencies:

(none)

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
 - white_space//0
 - white_spaces//0
 - space//0
 - spaces//0
 - tab//0
 - tabs//0
 - new_line//0
 - new_lines//0
 - blank//0
 - blanks//0
 - non_blank//1
 - non_blanks//1
 - control//0
 - controls//0
- Protected predicates
- Private predicates
- Operators

Public predicates

`white_space//0`

Consumes a single space or tab.

Compilation flags:

`static`

Mode and number of proofs:

`white_space - zero_or_one`

`white_spaces//0`

Consumes zero or more spaces and tabs.

Compilation flags:

`static`

Mode and number of proofs:

`white_spaces - one`

`space//0`

Consumes a single space.

Compilation flags:

`static`

Mode and number of proofs:

`space - zero_or_one`

spaces//0

Consumes zero or more spaces.

Compilation flags:

static

Mode and number of proofs:

spaces - one

tab//0

Consumes a single tab.

Compilation flags:

static

Mode and number of proofs:

tab - zero_or_one

tabs//0

Consumes zero or more tabs.

Compilation flags:

static

Mode and number of proofs:

tabs - one

`new_line//0`

Consumes a single new line.

Compilation flags:

`static`

Mode and number of proofs:

`new_line - zero_or_one`

`new_lines//0`

Consumes zero or more new lines.

Compilation flags:

`static`

Mode and number of proofs:

`new_lines - one`

`blank//0`

Consumes a single space, tab, vertical tab, line feed, or new line.

Compilation flags:

`static`

Mode and number of proofs:

`blank - zero_or_one`

blanks//0

Consumes zero or more spaces, tabs, vertical tabs, line feeds, or new lines.

Compilation flags:

static

Mode and number of proofs:

blanks - one

non_blank//1

Returns a single non-blank character or character code.

Compilation flags:

static

Template:

non_blank(NonBlank)

Mode and number of proofs:

non_blank(-atomic) - zero_or_one

non_blanks//1

Returns a (possibly empty) list of non-blank characters or character codes.

Compilation flags:

static

Template:

non_blanks(NonBlanks)

Mode and number of proofs:

non_blanks(-list(atomic)) - one

control//0

Consumes a single control character or character code. Support for the null control character depends on the Prolog backend.

Compilation flags:

static

Mode and number of proofs:

control - zero_or_one

controls//0

Consumes zero or more control characters or character codes. Support for the null control character depends on the Prolog backend.

Compilation flags:

static

Mode and number of proofs:

controls - one

Protected predicates

(none)

Private predicates

(none)

Operators

(none)

object

1.29.2 ip_grammars(Format)

IP address grammars.

Availability:

logtalk_load(grammars(loader))

Author: Paulo Moura

Version: 0:1:1

Date: 2022-10-08

Compilation flags:

static, context_switching_calls

Uses:

number_grammars(Format)

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
 - ipv4//1
 - ipv6//1
- Protected predicates
- Private predicates
- Operators

Public predicates

ipv4//1

Parses an IPv4 network address in the format XXX.XXX.XXX.XXX where each XXX is an octet (i.e. an integer between 0 and 255).

Compilation flags:

static

Template:

ipv4(Octets)

Mode and number of proofs:

ipv4(?list(integer)) - zero_or_one

ipv6//1

Parses an IPv6 network address in the format XXXX.XXXX.XXXX.XXXX.XXXX.XXXX.XXXX.XXXX where each X is a hexadecimal digit.

Compilation flags:

static

Template:

ipv6(HexDigits)

Mode and number of proofs:

ipv6(?list(integer)) - one

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

object

1.29.3 number_grammars(Format)

Number grammars.

Availability:

logtalk_load(grammars(loader))

Author: Paulo Moura

Version: 0:2:2

Date: 2024-03-14

Compilation flags:

static, context_switching_calls

Uses:

list

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
 - bit//1
 - bits//1
 - digit//1
 - digits//1
 - hex_digit//1
 - hex_digits//1
 - natural//1
 - integer//1
 - float//1
 - number//1
 - sign//1
 - dot//1
- Protected predicates
- Private predicates
- Operators

Public predicates

bit//1

Parses a single bit.

Compilation flags:
static

Template:
bit(Bit)

Mode and number of proofs:
bit(?integer) - zero_or_one

bits//1

Parses a sequence of one or more bits.

Compilation flags:
static

Template:
bits(Bits)

Mode and number of proofs:
bits(?list(integer)) - zero_or_one

digit//1

Parses a single decimal digit.

Compilation flags:
static

Template:
digit(Digit)

Mode and number of proofs:
digit(?atomic) - zero_or_one

digits//1

Parses a sequence of zero or more digits.

Compilation flags:
static

Template:
digits(Digits)

Mode and number of proofs:
digits(?list(atomic)) - one

hex_digit//1

Parses a single hexa-decimal digit.

Compilation flags:
static

Template:
hex_digit(HexDigit)

Mode and number of proofs:
hex_digit(?atomic) - zero_or_one

hex_digits//1

Parses a sequence of zero or more hexa-decimal digits.

Compilation flags:
static

Template:
hex_digits(HexDigits)

Mode and number of proofs:

`hex_digits(?list(atomic)) - one`

`natural//1`

Parses a natural number (a non signed integer).

Compilation flags:

`static`

Template:

`natural(Natural)`

Mode and number of proofs:

`natural(?non_negative_integer) - zero_or_one`

`integer//1`

Parses an integer.

Compilation flags:

`static`

Template:

`integer(Integer)`

Mode and number of proofs:

`integer(?integer) - zero_or_one`

`float//1`

Parses a float.

Compilation flags:

`static`

Template:

float(Float)

Mode and number of proofs:

float(?float) - zero_or_one

number//1

Parses a number (an integer or a float).

Compilation flags:

static

Template:

number(Number)

Mode and number of proofs:

number(?number) - zero_or_one

sign//1

Parses a number sign (plus or minus).

Compilation flags:

static

Template:

sign(Sign)

Mode and number of proofs:

sign(?atomic) - zero_or_one

dot//1

Parses a decimal dot.

Compilation flags:

static

Template:

dot(Dot)

Mode and number of proofs:

dot(?atomic) - zero_or_one

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

object

1.29.4 sequence_grammars

Sequence grammars.

Availability:

logtalk_load(grammars(loader))

Author: Paulo Moura

Version: 0:3:0

Date: 2023-12-09

Compilation flags:

static, context_switching_calls

Dependencies:

(none)

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
 - zero_or_more//2
 - one_or_more//2
 - zero_or_more//1
 - one_or_more//1
 - zero_or_more//0
 - one_or_more//0
 - without//2
- Protected predicates
- Private predicates
- Operators

Public predicates

zero_or_more//2

Eagerly collect zero or more terminals that satisfy the given closure.

Compilation flags:

static

Template:

zero_or_more(Closure,Terminals)

Meta-predicate template:

zero_or_more(1,*)

Mode and number of proofs:

zero_or_more(+callable,-list(atomic)) - one

`one_or_more//2`

Eagerly collect one or more terminals that satisfy the given closure.

Compilation flags:

`static`

Template:

`one_or_more(Closure,Terminals)`

Meta-predicate template:

`one_or_more(1,*)`

Mode and number of proofs:

`one_or_more(+callable,-list(atomic)) - zero_or_one`

`zero_or_more//1`

Eagerly collect zero or more terminals.

Compilation flags:

`static`

Template:

`zero_or_more(Terminals)`

Mode and number of proofs:

`zero_or_more(-list(atomic)) - one`

`one_or_more//1`

Eagerly collect one or more terminals.

Compilation flags:

`static`

Template:

`one_or_more(Terminals)`

Mode and number of proofs:

`one_or_more(-list(atomic)) - zero_or_one`

zero_or_more//0

Eagerly parse zero or more terminals.

Compilation flags:

static

Mode and number of proofs:

zero_or_more - one

one_or_more//0

Eagerly parse one or more terminals.

Compilation flags:

static

Mode and number of proofs:

one_or_more - zero_or_one

without//2

Collects input terminals until one of the stop terminals is found. The stop terminals are excluded from the collected terminals.

Compilation flags:

static

Template:

without(StopTerminals,Terminals)

Mode and number of proofs:

without(+list(atomic),-list(atomic)) - one

Protected predicates

(none)

Private predicates

(none)

Operators

(none)

1.30 heaps

object

1.30.1 heap(Order)

Heap implementation, parameterized by the order to be used to compare keys (< or >).

Availability:

```
logtalk_load(heaps(loader))
```

Author: Richard O'Keefe; adapted to Logtalk by Paulo Moura and Victor Lagerkvist.

Version: 1:1:0

Date: 2019-05-18

Compilation flags:

```
static, context_switching_calls
```

Implements:

```
public heapp
```

Extends:

```
public compound
```

Remarks:

(none)

Inherited public predicates:

(<)/2 (=:=)/2 (=<)/2 (=\\=)/2 (>)/2 (>=)/2 as_heap/2 as_list/2 check/1 delete/4
 depth/2 empty/1 ground/1 insert/4 insert_all/3 merge/3 new/1 numbervars/1 numbervars/3
 occurs/2 singletons/2 size/2 subsumes/2 subterm/2 top/3 top_next/5 valid/1 variables/2
 variant/2 varnumbers/2 varnumbers/3

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

See also:

minheap, maxheap

protocol

1.30.2 heapp

Heap protocol. Key-value pairs are represented as Key-Value.

Availability:

```
logtalk_load(heaps(loader))
```

Author: Richard O'Keefe; adapted to Logtalk by Paulo Moura and Victor Lagerkvist.

Version: 1:0:1

Date: 2010-11-13

Compilation flags:

static

Dependencies:

(none)

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
 - insert/4
 - insert_all/3
 - delete/4
 - merge/3
 - empty/1
 - size/2
 - as_list/2
 - as_heap/2
 - top/3
 - top_next/5
- Protected predicates
- Private predicates
- Operators

Public predicates

insert/4

Inserts the new pair into a heap, returning the updated heap.

Compilation flags:

static

Template:

insert(Key,Value,Heap,NewHeap)

Mode and number of proofs:

`insert(+key,+value,+heap,-heap) - one`

`insert_all/3`

Inserts a list of pairs into a heap, returning the updated heap.

Compilation flags:

`static`

Template:

`insert_all(List,Heap,NewHeap)`

Mode and number of proofs:

`insert_all(@list(pairs),+heap,-heap) - one`

`delete/4`

Deletes and returns the top pair in a heap returning the updated heap.

Compilation flags:

`static`

Template:

`delete(Heap,TopKey,TopValue,NewHeap)`

Mode and number of proofs:

`delete(+heap,?key,?value,-heap) - zero_or_one`

`merge/3`

Merges two heaps.

Compilation flags:

`static`

Template:

`merge(Heap1,Heap2,NewHeap)`

Mode and number of proofs:

`merge(+heap,+heap,-heap) - one`

`empty/1`

True if the heap is empty.

Compilation flags:

`static`

Template:

`empty(Heap)`

Mode and number of proofs:

`empty(@heap) - zero_or_one`

`size/2`

Returns the number of heap elements.

Compilation flags:

`static`

Template:

`size(Heap,Size)`

Mode and number of proofs:

`size(+heap,?integer) - zero_or_one`

`as_list/2`

Returns the current set of pairs in the heap as a list, sorted into ascending order of the keys.

Compilation flags:

`static`

Template:

`as_list(Heap,List)`

Mode and number of proofs:

`as_list(+heap,-list) - one`

`as_heap/2`

Constructs a heap from a list of pairs.

Compilation flags:

`static`

Template:

`as_heap(List,Heap)`

Mode and number of proofs:

`as_heap(+list,-heap) - one`

`top/3`

Returns the top pair in the heap. Fails if the heap is empty.

Compilation flags:

`static`

Template:

`top(Heap,TopKey,TopValue)`

Mode and number of proofs:

`top(+heap,?key,?value) - zero_or_one`

`top_next/5`

Returns the top pair and the next pair in the heap. Fails if the heap does not have at least two elements.

Compilation flags:

`static`

Template:

`top_next(Heap,TopKey,TopValue,NextKey,NextValue)`

Mode and number of proofs:

`top_next(+heap,?key,?value,?key,?value) - zero_or_one`

Protected predicates

(none)

Private predicates

(none)

Operators

(none)

See also:

`heap(Order)`

object

1.30.3 maxheap

Max-heap implementation. Uses standard order to compare keys.

Availability:

`logtalk_load(heaps(loader))`

Author: Paulo Moura.

Version: 1:0:0

Date: 2010-02-19

Compilation flags:

static, context_switching_calls

Extends:

public heap(>)

Remarks:

(none)

Inherited public predicates:

(<)/2 (=:=)/2 (=<)/2 (=\\=)/2 (>)/2 (>=)/2 as_heap/2 as_list/2 check/1 delete/4
 depth/2 empty/1 ground/1 insert/4 insert_all/3 merge/3 new/1 numbervars/1 numbervars/3
 occurs/2 singletons/2 size/2 subsumes/2 subterm/2 top/3 top_next/5 valid/1 variables/2
 variant/2 varnumbers/2 varnumbers/3

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

object

1.30.4 minheap

Min-heap implementation. Uses standard order to compare keys.

Availability:

`logtalk_load(heaps(loader))`

Author: Paulo Moura.

Version: 1:0:0

Date: 2010-02-19

Compilation flags:

`static, context_switching_calls`

Extends:

`public heap(<)`

Remarks:

(none)

Inherited public predicates:

`(<)/2 (=:=)/2 (=<)/2 (=\\=)/2 (>)/2 (>=)/2 as_heap/2 as_list/2 check/1 delete/4
depth/2 empty/1 ground/1 insert/4 insert_all/3 merge/3 new/1 numbervars/1 numbervars/3
occurs/2 singletons/2 size/2 subsumes/2 subterm/2 top/3 top_next/5 valid/1 variables/2
variant/2 varnumbers/2 varnumbers/3`

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

1.31 help

object

1.31.1 help

Command-line help for Logtalk libraries, entities, plus built-in control constructs, predicates, non-terminals, and methods.

Availability:

`logtalk_load(help(loader))`

Author: Paulo Moura

Version: 0:33:0

Date: 2023-06-01

Compilation flags:

`static, context_switching_calls, complements(allow)`

Implements:

`public forwarding`

Uses:

`atom`

`os`

`user`

Remarks:

(none)

Inherited public predicates:

apis/0 apis/1 forward/1 handbook/0 handbook/1 man/1

- Public predicates
 - help/0
 - (/)/2
 - (//)/2
 - completion/2
 - completions/2
 - built_in_directive/4
 - built_in_predicate/4
 - built_in_method/4
 - control_construct/4
 - built_in_non_terminal/4
 - library/0
 - library/1
 - entity/1
 - manuals/0
- Protected predicates
- Private predicates
- Operators

Public predicates

help/0

Prints instructions on how to use the help tool.

Compilation flags:

static

Mode and number of proofs:

help - one

(/)/2

Provides help on the Functor/Arity built-in control construct, directive, predicate, or method.

Compilation flags:

static

Template:

Functor/Arity

Mode and number of proofs:

+atom/ +integer - zero_or_one

(//)/2

Provides help on the Functor//Arity built-in non-terminal.

Compilation flags:

static

Template:

Functor//Arity

Mode and number of proofs:

+atom// +integer - zero_or_one

completion/2

Provides a completion pair, Completion-Page, for a given prefix.

Compilation flags:

static

Template:

completion(Prefix,Completion)

Mode and number of proofs:

completion(+atom,-pair) - zero_or_more

completions/2

Provides a list of completions pairs, Completion-Page, for a given prefix.

Compilation flags:

static

Template:

completions(Prefix,Completions)

Mode and number of proofs:

completions(+atom,-lists(pair)) - zero_or_more

built_in_directive/4

Provides access to the HTML documenting files describing built-in directives.

Compilation flags:

static

Template:

built_in_directive(Functor,Arity,Directory,Basename)

Mode and number of proofs:

built_in_directive(?atom,?integer,-atom,-atom) - zero_or_more

built_in_predicate/4

Provides access to the HTML documenting files describing built-in predicates.

Compilation flags:

static

Template:

built_in_predicate(Functor,Arity,Directory,Basename)

Mode and number of proofs:

built_in_predicate(?atom,?integer,-atom,-atom) - zero_or_more

built_in_method/4

Provides access to the HTML documenting files describing built-in methods.

Compilation flags:

static

Template:

built_in_method(Functor,Arity,Directory,Basename)

Mode and number of proofs:

built_in_method(?atom,?integer,-atom,-atom) - zero_or_more

control_construct/4

Provides access to the HTML documenting files describing built-in control constructs.

Compilation flags:

static

Template:

control_construct(Functor,Arity,Directory,Basename)

Mode and number of proofs:

control_construct(?atom,?integer,-atom,-atom) - zero_or_more

built_in_non_terminal/4

Provides access to the HTML documenting files describing built-in DCG non-terminals.

Compilation flags:

static

Template:

built_in_non_terminal(Functor,Arity,Directory,Basename)

Mode and number of proofs:

built_in_non_terminal(?atom,?integer,-atom,-atom) - zero_or_more

library/0

Provides help on the standard Logtalk library.

Compilation flags:

static

Mode and number of proofs:

library - one

library/1

Provides help on the standard Logtalk libraries, library predicates, and library non-terminals.

Compilation flags:

static

Template:

library(Topic)

Mode and number of proofs:

library(+atom) - zero_or_one

library(+predicate_indicator) - zero_or_one

library(+non_terminal_indicator) - zero_or_one

entity/1

Provides help on Logtalk entities (objects, protocols, or categories).

Compilation flags:

static

Template:

entity(Entity)

Mode and number of proofs:

entity(+entity_identifier) - zero_or_one

manuals/0

Provides access to the Logtalk User and Reference manuals.

Compilation flags:

static

Mode and number of proofs:

manuals - one

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

category

1.31.2 help_info_support

Experimental help predicates for inline browsing of the Texinfo versions of the Handbook and APIs documentation. Currently requires Ciao Prolog, ECLiPSe, GNU Prolog, LVM, SICStus Prolog, SWI-Prolog, Trealla Prolog, XSB, or YAP as the backend running on a POSIX system.

Availability:

logtalk_load(help(loader))

Author: Paulo Moura

Version: 0:8:0

Date: 2024-01-30

Compilation flags:

static

Complements:

help

Uses:

os

user

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
 - handbook/0
 - handbook/1
 - apis/0
 - apis/1
 - man/1
- Protected predicates
- Private predicates
- Operators

Public predicates

handbook/0

Opens inline the Texinfo version of the Handbook.

Compilation flags:

static

Mode and number of proofs:

handbook - one

handbook/1

Opens inline the Texinfo version of the Handbook at the given topic.

Compilation flags:

static

Template:

handbook(Topic)

Mode and number of proofs:

handbook(+atom) - one

handbook(+predicate_indicator) - one

handbook(+non_terminal_indicator) - one

apis/0

Opens inline the Texinfo version of the APIs documentation.

Compilation flags:

static

Mode and number of proofs:

apis - one

apis/1

Opens inline the Texinfo version of the APIs documentation at the given topic.

Compilation flags:

static

Template:

apis(Topic)

Mode and number of proofs:

apis(+atom) - one

apis(+predicate_indicator) - one

apis(+non_terminal_indicator) - one

man/1

Opens inline the man page of the given script.

Compilation flags:

static

Template:

man(*Script*)

Mode and number of proofs:

man(+atom) - one

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

1.32 hierarchies

category

1.32.1 class_hierarchy

Class hierarchy predicates.

Availability:

logtalk_load(hierarchies(loader))

Author: Paulo Moura

Version: 1:1:0

Date: 2006-02-20

Compilation flags:

static

Implements:

public class_hierarchy

Remarks:

(none)

Inherited public predicates:

ancestor/1 ancestors/1 class/1 classes/1 descendant/1 descendant_class/1 descendant_classes/1
descendant_instance/1 descendant_instances/1 descendants/1 instance/1 instances/1 leaf/1
leaf_class/1 leaf_classes/1 leaf_instance/1 leaf_instances/1 leaves/1 subclass/1 subclasses/1
superclass/1 superclasses/1

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)
protocol

1.32.2 class_hierarchy

Class hierarchy protocol.

Availability:
logtalk_load(hierarchies(loader))

Author: Paulo Moura
Version: 1:0:0
Date: 2000-07-24

Compilation flags:
static

Extends:
public hierarchy

Remarks:
(none)

Inherited public predicates:
ancestor/1 ancestors/1 descendant/1 descendants/1 leaf/1 leaves/1

- Public predicates
 - class/1
 - classes/1
 - instance/1
 - instances/1
 - subclass/1
 - subclasses/1
 - superclass/1
 - superclasses/1
 - leaf_instance/1

- leaf_instances/1
- leaf_class/1
- leaf_classes/1
- descendant_instance/1
- descendant_instances/1
- descendant_class/1
- descendant_classes/1
- Protected predicates
- Private predicates
- Operators

Public predicates

class/1

Returns, by backtracking, all object classes.

Compilation flags:

static

Template:

class(Class)

Mode and number of proofs:

class(?object) - zero_or_more

classes/1

List of all object classes.

Compilation flags:

static

Template:

classes(Classes)

Mode and number of proofs:

classes(-list) - one

instance/1

Returns, by backtracking, all class instances.

Compilation flags:

static

Template:

instance(Instance)

Mode and number of proofs:

instance(?object) - zero_or_more

instances/1

List of all class instances.

Compilation flags:

static

Template:

instances(Instances)

Mode and number of proofs:

instances(-list) - one

subclass/1

Returns, by backtracking, all class subclasses.

Compilation flags:

static

Template:

subclass(Subclass)

Mode and number of proofs:

`subclass(?object) - zero_or_more`

`subclasses/1`

List of all class subclasses.

Compilation flags:

`static`

Template:

`subclasses(Subclasses)`

Mode and number of proofs:

`subclasses(-list) - one`

`superclass/1`

Returns, by backtracking, all class superclasses.

Compilation flags:

`static`

Template:

`superclass(Superclass)`

Mode and number of proofs:

`superclass(?object) - zero_or_more`

`superclasses/1`

List of all class superclasses.

Compilation flags:

`static`

Template:

superclasses(Superclasses)

Mode and number of proofs:

superclasses(-list) - one

leaf_instance/1

Returns, by backtracking, all class leaf instances.

Compilation flags:

static

Template:

leaf_instance(Leaf)

Mode and number of proofs:

leaf_instance(?object) - zero_or_more

leaf_instances/1

List of all class leaf instances.

Compilation flags:

static

Template:

leaf_instances(Leaves)

Mode and number of proofs:

leaf_instances(-list) - one

leaf_class/1

Returns, by backtracking, all class leaf subclasses.

Compilation flags:

static

Template:

leaf_class(Leaf)

Mode and number of proofs:

leaf_class(?object) - zero_or_more

leaf_classes/1

List of all class leaf leaf subclasses.

Compilation flags:

static

Template:

leaf_classes(Leaves)

Mode and number of proofs:

leaf_classes(-list) - one

descendant_instance/1

Returns, by backtracking, all class descendant instances.

Compilation flags:

static

Template:

descendant_instance(Descendant)

Mode and number of proofs:

descendant_instance(?object) - zero_or_more

descendant_instances/1

List of all class descendant instances.

Compilation flags:

static

Template:

descendant_instances(Descendants)

Mode and number of proofs:

descendant_instances(-list) - one

descendant_class/1

Returns, by backtracking, all class descendant subclasses.

Compilation flags:

static

Template:

descendant_class(Descendant)

Mode and number of proofs:

descendant_class(?object) - zero_or_more

descendant_classes/1

List of all class descendant subclasses.

Compilation flags:

static

Template:

descendant_classes(Descendants)

Mode and number of proofs:

descendant_classes(-list) - one

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

See also:

[class_hierarchy](#)

[protocol](#)

1.32.3 hierarchy

Common hierarchy protocol for prototype and class hierarchies.

Availability:

```
logtalk_load(hierarchies(loader))
```

Author: Paulo Moura

Version: 1:0:0

Date: 2000-07-24

Compilation flags:

```
static
```

Dependencies:

(none)

Remarks:

(none)

Inherited public predicates:

(none)

- [Public predicates](#)
 - [ancestor/1](#)

- ancestors/1
- leaf/1
- leaves/1
- descendant/1
- descendants/1
- Protected predicates
- Private predicates
- Operators

Public predicates

ancestor/1

Returns, by backtracking, all object ancestors.

Compilation flags:

static

Template:

ancestor(Ancestor)

Mode and number of proofs:

ancestor(?object) - zero_or_more

ancestors/1

List of all object ancestors.

Compilation flags:

static

Template:

ancestors(Ancestors)

Mode and number of proofs:

ancestors(-list) - one

leaf/1

Returns, by backtracking, all object leaves.

Compilation flags:

static

Template:

leaf(Leaf)

Mode and number of proofs:

leaf(?object) - zero_or_more

leaves/1

List of all object leaves.

Compilation flags:

static

Template:

leaves(Leaves)

Mode and number of proofs:

leaves(-list) - one

descendant/1

Returns, by backtracking, all object descendants.

Compilation flags:

static

Template:

descendant(Descendant)

Mode and number of proofs:

descendant(?object) - zero_or_more

descendants/1

List of all object descendants.

Compilation flags:

static

Template:

descendants(Descendants)

Mode and number of proofs:

descendants(-list) - one

Protected predicates

(none)

Private predicates

(none)

Operators

(none)

category

1.32.4 proto_hierarchy

Prototype hierarchy predicates.

Availability:

logtalk_load(hierarchies(loader))

Author: Paulo Moura

Version: 1:1:0

Date: 2006-02-20

Compilation flags:

static

Implements:

public proto_hierarchyp

Remarks:

(none)

Inherited public predicates:

ancestor/1 ancestors/1 descendant/1 descendants/1 extension/1 extensions/1 leaf/1 leaves/1
parent/1 parents/1

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

protocol

1.32.5 proto_hierarchyp

Prototype hierarchy protocol.

Availability:

logtalk_load(hierarchies(loader))

Author: Paulo Moura

Version: 1:1:0

Date: 2006-02-20

Compilation flags:

static

Extends:

public [hierarchyp](#)

Remarks:

(none)

Inherited public predicates:

[ancestor/1](#) [ancestors/1](#) [descendant/1](#) [descendants/1](#) [leaf/1](#) [leaves/1](#)

- Public predicates
 - [parent/1](#)
 - [parents/1](#)
 - [extension/1](#)
 - [extensions/1](#)
- Protected predicates
- Private predicates
- Operators

Public predicates

[parent/1](#)

Returns, by backtracking, all object parents.

Compilation flags:

static

Template:

[parent](#)(Parent)

Mode and number of proofs:

[parent](#)(?object) - zero_or_more

parents/1

List of all object parents.

Compilation flags:

static

Template:

parents(Parents)

Mode and number of proofs:

parents(-list) - one

extension/1

Returns, by backtracking, all object direct descendants.

Compilation flags:

static

Template:

extension(Extension)

Mode and number of proofs:

extension(?object) - zero_or_more

extensions/1

List of all object direct descendants.

Compilation flags:

static

Template:

extensions(Extensions)

Mode and number of proofs:

extensions(-list) - one

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

See also:

`proto_hierarchy`

1.33 hook_flows

object

1.33.1 hook_pipeline(Pipeline)

- Pipeline - List of hook objects.

Use a pipeline (represented using a list) of hook objects to expand terms and goals. The expansion results from a hook object are passed to the next hook object in the pipeline.

Availability:

`logtalk_load(hook_flows(loader))`

Author: Paulo Moura

Version: 1:0:3

Date: 2019-09-23

Compilation flags:

`static, context_switching_calls`

Implements:

public `expanding`

Remarks:

- Usage: Compile source files that should be expanded using the pipeline of hook objects using the compiler option `hook(hook_pipeline(Pipeline))`.

Inherited public predicates:

goal_expansion/2 term_expansion/2

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

See also:

hook_set(Set)

object

1.33.2 hook_set(Set)

- Set - Set (list) of hook objects.

Use a set (represented using a list) of hook objects to expand terms and goals. The hook objects are tried in sequence until one of them succeeds in expanding the current term (goal) into a different term (goal).

Availability:

logtalk_load(hook_flows(loader))

Author: Paulo Moura

Version: 1:0:1

Date: 2019-06-13

Compilation flags:

static, context_switching_calls

Implements:

public expanding

Remarks:

- Usage: Compile source files that should be expanded using the set of hook objects using the compiler option `hook(hook_set(Set))`.

Inherited public predicates:

goal_expansion/2 term_expansion/2

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

See also:

`hook_pipeline(Pipeline)`

1.34 hook_objects

object

1.34.1 backend_adapter_hook

This hook object applies the expansion rules defined in the Prolog backend adapter file.

Availability:

```
logtalk_load(hook_objects(loader))
```

Author: Paulo Moura

Version: 1:0:0

Date: 2020-02-17

Compilation flags:

```
static, context_switching_calls
```

Implements:

```
public expanding
```

Remarks:

```
(none)
```

Inherited public predicates:

```
goal_expansion/2 term_expansion/2
```

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

See also:

`default_workflow_hook`, `identity_hook`, `grammar_rules_hook`, `prolog_module_hook(Module)`, `object_wrapper_hook`, `write_to_stream_hook(Stream,Options)`, `write_to_stream_hook(Stream)`, `print_goal_hook`, `suppress_goal_hook`

object

1.34.2 `default_workflow_hook`

Use this object as the default hook object to restore the default expansion pipeline semantics used by the compiler.

Availability:

`logtalk_load(hook_objects(loader))`

Author: Paulo Moura

Version: 1:0:1

Date: 2020-03-24

Compilation flags:

`static`, `context_switching_calls`

Implements:

public `expanding`

Remarks:

(none)

Inherited public predicates:

`goal_expansion/2` `term_expansion/2`

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

See also:

`backend_adapter_hook`, `identity_hook`, `grammar_rules_hook`, `prolog_module_hook(Module)`, `object_wrapper_hook`, `write_to_stream_hook(Stream,Options)`, `write_to_stream_hook(Stream)`, `print_goal_hook`, `suppress_goal_hook`

object

1.34.3 `grammar_rules_hook`

This hook object expands grammar rules into clauses.

Availability:

`logtalk_load(hook_objects(loader))`

Author: Paulo Moura

Version: 1:0:0

Date: 2020-02-14

Compilation flags:

static, context_switching_calls

Implements:

public expanding

Remarks:

(none)

Inherited public predicates:

goal_expansion/2 term_expansion/2

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

See also:

backend_adapter_hook, default_workflow_hook, identity_hook, prolog_module_hook(Module),
object_wrapper_hook, write_to_stream_hook(Stream,Options), write_to_stream_hook(Stream),
print_goal_hook, suppress_goal_hook

object

1.34.4 identity_hook

Use this object as a file specific hook object to prevent any (other) user-defined expansion rules to be applied when compiling the file.

Availability:

```
logtalk_load(hook_objects(loader))
```

Author: Paulo Moura

Version: 1:0:0

Date: 2020-02-15

Compilation flags:

```
static, context_switching_calls
```

Implements:

```
public expanding
```

Remarks:

```
(none)
```

Inherited public predicates:

```
goal_expansion/2 term_expansion/2
```

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

See also:

`backend_adapter_hook`, `default_workflow_hook`, `grammar_rules_hook`, `prolog_module_hook(Module)`,
`object_wrapper_hook`, `write_to_stream_hook(Stream,Options)`, `write_to_stream_hook(Stream)`,
`print_goal_hook`, `suppress_goal_hook`

object

1.34.5 `object_wrapper_hook`

Use this object to wrap the contents of a plain Prolog file in an object named after the file. The wrapper sets the `context_switching_calls` flag to allow, enabling calling of the wrapped predicates using the `<</2` control construct.

Availability:

```
logtalk_load(hook_objects(loader))
```

Author: Paulo Moura

Version: 1:1:0

Date: 2020-10-30

Compilation flags:

```
static, context_switching_calls
```

Implements:

```
public expanding
```

Uses:

```
os
```

Remarks:

```
(none)
```

Inherited public predicates:

```
goal_expansion/2 term_expansion/2
```

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

See also:

`object_wrapper_hook(Protocol)`, `object_wrapper_hook(Name,Relations)`, `back-end_adapter_hook`, `default_workflow_hook`, `grammar_rules_hook`, `prolog_module_hook(Module)`, `write_to_stream_hook(Stream,Options)`, `write_to_stream_hook(Stream)`, `print_goal_hook`, `suppress_goal_hook`

`object`

1.34.6 `object_wrapper_hook(Protocol)`

Use this object to wrap the contents of a plain Prolog file in an object named after the file that implements the given protocol.

Availability:

```
logtalk_load(hook_objects(loader))
```

Author: Paulo Moura

Version: 1:0:0

Date: 2021-11-24

Compilation flags:

```
static, context_switching_calls
```

Implements:

public expanding

Uses:

os

Remarks:

(none)

Inherited public predicates:

goal_expansion/2 term_expansion/2

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

See also:

object_wrapper_hook, object_wrapper_hook(Name,Relations), backend_adapter_hook,
default_workflow_hook, grammar_rules_hook, prolog_module_hook(Module),
write_to_stream_hook(Stream,Options), write_to_stream_hook(Stream), print_goal_hook, sup-
press_goal_hook

object

1.34.7 object_wrapper_hook(Name,Relations)

Use this object to wrap the contents of a plain Prolog file in an object with the given name and object entity relations (a list).

Availability:

```
logtalk_load(hook_objects(loader))
```

Author: Paulo Moura

Version: 1:0:0

Date: 2022-02-03

Compilation flags:

```
static, context_switching_calls
```

Implements:

```
public expanding
```

Remarks:

```
(none)
```

Inherited public predicates:

```
goal_expansion/2 term_expansion/2
```

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

See also:

`object_wrapper_hook`, `object_wrapper_hook(Protocol)`, `backend_adapter_hook`,
`default_workflow_hook`, `grammar_rules_hook`, `prolog_module_hook(Module)`,
`write_to_stream_hook(Stream,Options)`, `write_to_stream_hook(Stream)`, `print_goal_hook`, `sup-`
`press_goal_hook`

object

1.34.8 `print_goal_hook`

Use this object to easily print entity predicate goals before, after, or before and after calling them.

Availability:

```
logtalk_load(hook_objects(loader))
```

Author: Paulo Moura

Version: 1:0:0

Date: 2020-03-14

Compilation flags:

```
static, context_switching_calls
```

Implements:

```
public expanding
```

Remarks:

- Usage: Mark a goal to be printed by prefixing it with an operator. Printing uses a comment message.
- To print goal before calling it: - Goal.
- To print goal after calling it: + Goal.
- To print goal before and after calling it: * Goal.

- Operators: This hook object uses the standard - and + prefix operators and also defines a global * prefix operator with the same type and priority.

Inherited public predicates:

goal_expansion/2 term_expansion/2

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

See also:

backend_adapter_hook, default_workflow_hook, grammar_rules_hook, identity_hook, prolog_module_hook(Module), object_wrapper_hook, write_to_stream_hook(Stream,Options), write_to_stream_hook(Stream), suppress_goal_hook

object

1.34.9 prolog_module_hook(Module)

This hook object applies the expansion rules defined in a Prolog module (e.g. user).

Availability:

logtalk_load(hook_objects(loader))

Author: Paulo Moura

Version: 1:0:0

Date: 2020-02-17

Compilation flags:

static, context_switching_calls

Implements:

public expanding

Remarks:

(none)

Inherited public predicates:

goal_expansion/2 term_expansion/2

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

See also:

backend_adapter_hook, default_workflow_hook, identity_hook, grammar_rules_hook, object_wrapper_hook, write_to_stream_hook(Stream,Options), write_to_stream_hook(Stream), print_goal_hook, suppress_goal_hook

object

1.34.10 suppress_goal_hook

Use this object to easily suppress a goal in a clause body.

Availability:

```
logtalk_load(hook_objects(loader))
```

Author: Paulo Moura

Version: 1:0:0

Date: 2020-05-04

Compilation flags:

```
static, context_switching_calls
```

Implements:

```
public expanding
```

Remarks:

- Usage: Mark a goal to be suppressed by prefixing it with the -- operator.
- Operators: This hook object uses the -- prefix operator declared by Logtalk for use in mode/2 directives.

Inherited public predicates:

```
goal_expansion/2 term_expansion/2
```

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

See also:

`backend_adapter_hook`, `default_workflow_hook`, `grammar_rules_hook`, `identity_hook`, `prolog_module_hook(Module)`, `object_wrapper_hook`, `write_to_stream_hook(Stream,Options)`, `write_to_stream_hook(Stream)`, `print_goal_hook`

object

1.34.11 `write_to_file_hook(File)`

This hook object writes term-expansion results to a file in canonical format. The terms are terminated by a period and a new line.

Availability:

```
logtalk_load(hook_objects(loader))
```

Author: Paulo Moura

Version: 1:0:0

Date: 2022-07-06

Compilation flags:

```
static, context_switching_calls
```

Extends:

```
public write_to_file_hook(File,[quoted(true),ignore_ops(true)])
```

Remarks:

(none)

Inherited public predicates:

```
goal_expansion/2 term_expansion/2
```

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

See also:

backend_adapter_hook, default_workflow_hook, identity_hook, grammar_rules_hook,
 prolog_module_hook(Module), object_wrapper_hook, write_to_file_hook(File,Options),
 write_to_stream_hook(Stream,Options), write_to_stream_hook(Stream), print_goal_hook, sup-
 press_goal_hook

object

1.34.12 write_to_file_hook(File,Options)

This hook object writes term-expansion results to a file using a list of write_term/3 options. The terms are terminated by a period and a new line.

Availability:

```
logtalk_load(hook_objects(loader))
```

Author: Paulo Moura

Version: 1:0:0

Date: 2022-07-06

Compilation flags:

```
static, context_switching_calls
```

Implements:

public expanding

Remarks:

(none)

Inherited public predicates:

goal_expansion/2 term_expansion/2

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

See also:

backend_adapter_hook, default_workflow_hook, identity_hook, grammar_rules_hook,
prolog_module_hook(Module), object_wrapper_hook, write_to_file_hook(File),
write_to_stream_hook(Stream,Options), write_to_stream_hook(Stream), print_goal_hook, sup-
press_goal_hook

object

1.34.13 write_to_stream_hook(Stream)

This hook object writes term-expansion results to a stream in canonical format. The terms are terminated by a period and a new line.

Availability:

```
logtalk_load(hook_objects(loader))
```

Author: Paulo Moura

Version: 1:0:0

Date: 2020-02-16

Compilation flags:

```
static, context_switching_calls
```

Extends:

```
public write_to_stream_hook(Stream,[quoted(true),ignore_ops(true)])
```

Remarks:

(none)

Inherited public predicates:

```
goal_expansion/2 term_expansion/2
```

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

See also:

`backend_adapter_hook`, `default_workflow_hook`, `identity_hook`, `grammar_rules_hook`, `prolog_module_hook(Module)`, `object_wrapper_hook`, `write_to_stream_hook(Stream,Options)`, `write_to_file_hook(File,Options)`, `write_to_file_hook(File)`, `print_goal_hook`, `suppress_goal_hook`
object

1.34.14 `write_to_stream_hook(Stream,Options)`

This hook object writes term-expansion results to a stream using a list of `write_term/3` options. The terms are terminated by a period and a new line.

Availability:

`logtalk_load(hook_objects(loader))`

Author: Paulo Moura

Version: 1:0:0

Date: 2020-02-16

Compilation flags:

`static`, `context_switching_calls`

Implements:

public `expanding`

Remarks:

(none)

Inherited public predicates:

`goal_expansion/2` `term_expansion/2`

- [Public predicates](#)
- [Protected predicates](#)
- [Private predicates](#)
- [Operators](#)

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

See also:

`backend_adapter_hook`, `default_workflow_hook`, `identity_hook`, `grammar_rules_hook`,
`prolog_module_hook(Module)`, `object_wrapper_hook`, `write_to_stream_hook(Stream)`,
`write_to_file_hook(File,Options)`, `write_to_file_hook(File)`, `print_goal_hook`, `suppress_goal_hook`

1.35 html

category

1.35.1 html

HTML generation.

Availability:

`logtalk_load(html(loader))`

Author: Paul Brown and Paulo Moura

Version: 0:3:0

Date: 2021-03-30

Compilation flags:

static

Dependencies:

(none)

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
 - generate/2
 - void_element/1
 - normal_element/2
- Protected predicates
- Private predicates
 - doctype/1
- Operators

Public predicates

generate/2

Generates HTML content using the representation specified in the first argument (stream(Stream) or file(Path)) for the term in the second argument.

Compilation flags:

static

Template:

generate(Sink,Term)

Mode and number of proofs:

generate(+compound,++term) - one_or_error

void_element/1

Enumerates, by backtracking, all void elements.

Compilation flags:

static

Template:

void_element(Element)

Mode and number of proofs:

void_element(?atom) - zero_or_more

normal_element/2

Enumerates, by backtracking, all normal elements. The value of the Display argument is either inline or block.

Compilation flags:

static

Template:

normal_element(Element,Display)

Mode and number of proofs:

normal_element(?atom,?atom) - zero_or_more

Protected predicates

(none)

Private predicates

doctype/1

Doctype text.

Compilation flags:

static

Template:

doctype(DocType)

Mode and number of proofs:

doctype(?atom) - one

Operators

(none)

object

1.35.2 html5

HTML content generation using the HTML 5 doctype.

Availability:

logtalk_load(html(loader))

Author: Paul Brown and Paulo Moura

Version: 1:0:0

Date: 2021-03-29

Compilation flags:

static, context_switching_calls

Imports:

public [html](#)

Remarks:

(none)

Inherited public predicates:

[generate/2](#) [normal_element/2](#) [void_element/1](#)

- [Public predicates](#)
- [Protected predicates](#)
- [Private predicates](#)
- [Operators](#)

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

object

1.35.3 xhtml11

XHTML content generation using the XHTML 1.1 doctype.

Availability:

`logtalk_load(html(loader))`

Author: Paul Brown and Paulo Moura

Version: 1:0:0

Date: 2021-03-29

Compilation flags:

`static, context_switching_calls`

Imports:

`public html`

Remarks:

(none)

Inherited public predicates:

`generate/2 normal_element/2 void_element/1`

- [Public predicates](#)
- [Protected predicates](#)
- [Private predicates](#)
- [Operators](#)

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

1.36 ids

object

1.36.1 ids

Generator of random identifiers with 160 bits (20 bytes) of randomness.

Availability:

```
logtalk_load(ids(loader))
```

Author: Paulo Moura

Version: 1:0:0

Date: 2022-11-23

Compilation flags:

```
static, context_switching_calls
```

Extends:

```
public ids(atom,20)
```


Remarks:

(none)

Inherited public predicates:

generate/1

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

See also:

ids(Representation,Bytes), uuid, ulid

object

1.36.2 ids(Representation,Bytes)

- Representation - Text representation for the identifier. Possible values are atom, chars, and codes.
- Bytes - Number of bytes of randomness.

Generator of random identifiers.

Availability:

logtalk_load(ids(loader))

Author: Paulo Moura

Version: 1:0:0
Date: 2022-11-23

Compilation flags:
static, context_switching_calls

Uses:
base64
fast_random
list
os

Remarks:
(none)

Inherited public predicates:
(none)

- Public predicates
 - generate/1
- Protected predicates
- Private predicates
- Operators

Public predicates

generate/1

Generate a random identifier.

Compilation flags:
static

Template:
generate(Identifier)
Mode and number of proofs:
generate(--textids) - one

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

See also:

ids, uuid, ulid

1.37 intervals

object

1.37.1 interval

Basic temporal interval relations. An interval is represented by a compound term, `i/2`, with two ground arguments, the start and end points.

Availability:

```
logtalk_load(intervals(loader))
```

Author: Paulo Moura

Version: 1:2:1

Date: 2022-01-15

Compilation flags:

```
static, context_switching_calls
```

Implements:

```
public intervalp
```

Aliases:

```
intervalp before/2 as b/2
```

```
intervalp after/2 as bi/2
```

```
intervalp meets/2 as m/2
```

```
intervalp met_by/2 as mi/2
```

```
intervalp overlaps/2 as o/2
```

```
intervalp overlapped_by/2 as oi/2
```

```
intervalp starts/2 as s/2
```

intervalp started_by/2 as si/2
intervalp during/2 as d/2
intervalp contains/2 as di/2
intervalp finishes/2 as f/2
intervalp finished_by/2 as fi/2
intervalp equal/2 as eq/2

Remarks:

(none)

Inherited public predicates:

after/2 before/2 contains/2 during/2 equal/2 finished_by/2 finishes/2 meets/2 met_by/2
new/3 overlapped_by/2 overlaps/2 started_by/2 starts/2 valid/1

- [Public predicates](#)
- [Protected predicates](#)
- [Private predicates](#)
- [Operators](#)

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

protocol

1.37.2 intervalp

Basic temporal interval relations protocol (based on James F. Allen Interval Algebra work).

Availability:

```
logtalk_load(intervals(loader))
```

Author: Paulo Moura

Version: 1:1:0

Date: 2014-04-26

Compilation flags:

```
static
```

Dependencies:

```
(none)
```

Remarks:

```
(none)
```

Inherited public predicates:

```
(none)
```

- Public predicates
 - new/3
 - valid/1
 - before/2
 - after/2
 - meets/2
 - met_by/2
 - overlaps/2
 - overlapped_by/2
 - starts/2
 - started_by/2
 - during/2
 - contains/2
 - finishes/2

- finished_by/2
- equal/2
- Protected predicates
- Private predicates
- Operators

Public predicates

new/3

Constructs a new interval given start and end points. The start point must strictly precede the end point.

Compilation flags:

static

Template:

new(Start,End,Interval)

Mode and number of proofs:

new(@ground,@ground,-interval) - zero_or_one

valid/1

True if Interval is a valid interval.

Compilation flags:

static

Template:

valid(Interval)

Mode and number of proofs:

valid(@interval) - zero_or_one

before/2

True if Interval1 takes place before Interval2.

Compilation flags:

static

Template:

before(Interval1,Interval2)

Mode and number of proofs:

before(@interval,@interval) - zero_or_one

after/2

True if Interval1 takes place after Interval2.

Compilation flags:

static

Template:

after(Interval1,Interval2)

Mode and number of proofs:

after(@interval,@interval) - zero_or_one

meets/2

True if Interval1 meets Interval2.

Compilation flags:

static

Template:

meets(Interval1,Interval2)

Mode and number of proofs:

meets(@interval,@interval) - zero_or_one

met_by/2

True if Interval1 is met by Interval2.

Compilation flags:

static

Template:

met_by(Interval1,Interval2)

Mode and number of proofs:

met_by(@interval,@interval) - zero_or_one

overlaps/2

True if Interval1 overlaps with Interval2.

Compilation flags:

static

Template:

overlaps(Interval1,Interval2)

Mode and number of proofs:

overlaps(@interval,@interval) - zero_or_one

overlapped_by/2

True if Interval1 is overlapped by Interval2.

Compilation flags:

static

Template:

overlapped_by(Interval1,Interval2)

Mode and number of proofs:

overlapped_by(@interval,@interval) - zero_or_one

starts/2

True if Interval1 starts Interval2.

Compilation flags:

static

Template:

starts(Interval1,Interval2)

Mode and number of proofs:

starts(@interval,@interval) - zero_or_one

started_by/2

True if Interval1 is started by Interval2.

Compilation flags:

static

Template:

started_by(Interval1,Interval2)

Mode and number of proofs:

started_by(@interval,@interval) - zero_or_one

during/2

True if Interval1 occurs during Interval2.

Compilation flags:

static

Template:

during(Interval1,Interval2)

Mode and number of proofs:

during(@interval,@interval) - zero_or_one

contains/2

True if Interval1 contains Interval2.

Compilation flags:

static

Template:

contains(Interval1,Interval2)

Mode and number of proofs:

contains(@interval,@interval) - zero_or_one

finishes/2

True if Interval1 finishes Interval2.

Compilation flags:

static

Template:

finishes(Interval1,Interval2)

Mode and number of proofs:

finishes(@interval,@interval) - zero_or_one

finished_by/2

True if Interval1 is finished by Interval2.

Compilation flags:

static

Template:

finished_by(Interval1,Interval2)

Mode and number of proofs:

finished_by(@interval,@interval) - zero_or_one

equal/2

True if Interval1 is equal to Interval2.

Compilation flags:

static

Template:

equal(Interval1,Interval2)

Mode and number of proofs:

equal(@interval,@interval) - zero_or_one

Protected predicates

(none)

Private predicates

(none)

Operators

(none)

See also:

interval

1.38 iso8601

object

1.38.1 iso8601

ISO 8601 (and European civil calendar) compliant library of date predicates.

Availability:

logtalk_load(iso8601(loader))

Author: Daniel L. Dudley

Version: 1:0:3

Date: 2019-10-09

Compilation flags:

static, context_switching_calls

Uses:

os

Remarks:

- Scope: This object currently provides a powerful, versatile and efficient set of date-handling predicates, which—thanks to Logtalk—may be used as is on a wide range of Prolog compilers. Besides taking time to familiarize oneself with each predicate, the user should take note of the following information.
- Validation of dates: Date parts are not validated—that is the caller’s responsibility! However, not being quite heartless yet, we do provide a predicate for this purpose.
- Date arithmetic: Many of the examples illustrate a simplified method of doing date arithmetic. Note, however, that we do not generally recommend this practice—it is all too easy to make mistakes. The safest way of finding the day difference between two dates is to first convert the dates to their Julian day numbers and then subtract one from the other. Similarly, the safe way to add or subtract a day offset to a particular date is to first convert the date to its Julian day number, add or subtract the day offset, and then convert the result to its corresponding date.
- BC years: ISO 8601 specifies that the Gregorian calendar be used, yet requires that years prior to 1 AD be handled arithmetically, i.e., the year we know as 1 BC is year 0, 2 BC is year -1, 3 BC is year -2 and so on. We do not follow ISO 8601 with regard to the handling of BC years. Our date predicates will accept and interpret an input year 0 as 1 BC; however, a negative year, Year, should always be interpreted as $\text{abs}(\text{Year}) ::= \text{Year BC}$. We believe that the average person will find our handling of BC years more user-friendly than the ISO 8601 one, but we encourage feedback from users with a view to a possible change in future versions.
- Week numbers: It is possible for a day (date) to have a week number that belongs to another year. Up to three of the first days of a calendar year may belong to the last week (number) of the prior calendar year, and up to three days of the last days of a calendar year may belong to the first week (number) of the next calendar year. It for this reason that the Week parameter in date/6-7 is a compound term, namely week(WeekNo,ActualYear).
- Computation of Gregorian Easter Sunday: The algorithm is based upon the “Gaussian rule”. Proleptic use is limited to years > 1582 AD, that is, after the introduction of the Gregorian calendar.
- Some Christian feast day offsets from Easter Sunday: Carnival Monday: -48 days, Mardi Gras (Shrove Tuesday): -47 days, Ash Wednesday: -46 days, Palm Sunday: -7 days, Easter Friday: -2 days, Easter Saturday: -1 day, Easter Monday: +1 day, Ascension of Christ: +39 days, Whitsunday: +49 days, Whitmonday: +50 days, Feast of Corpus Christi: +60 days.

Inherited public predicates:

(none)

- Public predicates
 - date/4
 - date/5
 - date/6
 - date/7
 - date_string/3
 - valid_date/3
 - leap_year/1
 - calendar_month/3
 - easter_day/3
- Protected predicates
- Private predicates
- Operators

Public predicates

date/4

Get the system date and/or its Julian Day # or convert a Julian Day # to/from given date parts.

Compilation flags:

static

Template:

date(JD,Year,Month,Day)

JD - Julian day serial number.

Year - 0 or negative if converted BC year, positive otherwise.

Month - Normally an integer between 1 and 12 inclusive.

Day - Normally an integer between 1 and 31 inclusive depending upon month.

Mode and number of proofs:

date(?integer,?integer,?integer,?integer) - zero_or_one

Examples:

Current date (i.e., today)

date(JD,Year,Month,Day)

JD=2453471,Year=2005,Month=4,Day=10

Convert a date to its Julian day number

date(JD,2000,2,29)

JD=2451604

Convert a Julian day number to its date

```
date(2451604,Year,Month,Day)
Year=2000,Month=2,Day=29
What is the date of day # 60 in year 2000?
date(JD,2000,1,60)
JD=2451604
What is the Julian of the 1st day prior to 2000-1-1?
date(JD,2000,1,0)
JD=2451544
What is the Julian of the 60th day prior to 2000-1-1?
date(JD,2000,1,-59)
JD=2451485
Illegal date is auto-adjusted (see also next query)
date(JD,1900,2,29)
JD=2415080
This is the correct date!
date(2415080,Year,Month,Day)
Year=1900,Month=3,Day=1
```

date/5

Ditto date/4 + get/check its day-of-week #.

Compilation flags:

static

Template:

```
date(JD,Year,Month,Day,DoW)
JD - Julian day serial number.
Year - 0 or negative if converted BC year, positive otherwise.
Month - Normally an integer between 1 and 12 inclusive.
Day - Normally an integer between 1 and 31 inclusive depending upon month.
DoW - Day of week, where Monday=1, Tuesday=2, ..., Sunday=7.
```

Mode and number of proofs:

```
date(?integer,?integer,?integer,?integer,?integer) - zero_or_one
```

Examples:

```
Get the Julian and the day-of-week # of a date
date(JD,2000,2,29,DoW)
JD=2451604,DoW=2
Check the validity of a given date (day-of-week is 2, not 4)
date(_,2002,3,5,4)
no
```

Get the Julian day of a given date if it is a Sunday

```
date(JD,2004,2,29,7)
```

```
JD=2453065
```

Get the date and day-of-week # of a Julian

```
date(2451545,Year,Month,Day,DoW)
```

```
Year=2000,Month=1,Day=1,DoW=6
```

date/6

Ditto date/5 + get/check its week #.

Compilation flags:

```
static
```

Template:

```
date(JD,Year,Month,Day,DoW,Week)
```

JD - Julian day serial number.

Year - 0 or negative if converted BC year, positive otherwise.

Month - Normally an integer between 1 and 12 inclusive.

Day - Normally an integer between 1 and 31 inclusive depending upon month.

DoW - Day of week, where Monday=1, Tuesday=2, ..., Sunday=7.

Week - Compound term, week(WeekNo,ActualYear), of a day.

Mode and number of proofs:

```
date(?integer,?integer,?integer,?integer,?integer,?compound) - zero_or_one
```

Examples:

Get the day-of-week and week number of a date

```
date(_,2000,1,1,DoW,Week)
```

```
DoW=6,Week=week(52,1999)
```

Get the week number and year of this week

```
date(_,_,_,_,Week)
```

```
Week=week(7,2004)
```

Get the Julian number and the week of a date if it is a Sunday

```
date(JD,2004,2,29,7,Week)
```

```
JD=2453065,Week=week(9,2004)
```

Get the day-of-week and week of a Julian day number

```
date(2453066,_,_,_,DoW,Week)
```

```
DoW=1,Week=week(10,2004)
```

Check that given date data matches

```
date(_,2004,3,1,1,week(10,2004))
```

```
yes
```

What is the date of a day of week (default is 1) in given week # and year?

```
date(__,Year,Month,Day,DoW,week(26,2004))
Year=2004,Month=6,Day=21,DoW=1
Ditto for Sunday
date(__,Year,Month,Day,7,week(1,2005))
Year=2005,Month=1,Day=9
Ditto for Tuesday in following week
date(__,Year,Month,Day,9,week(1,2005))
Year=2005,Month=1,Day=11
Ditto for Thursday in the prior week
date(__,Year,Month,Day,4,week(0,2005))
Year=2004,Month=12,Day=30
Ditto for Tuesday two weeks prior
date(__,Year,Month,Day,2,week(-1,2005))
Year=2004,Month=12,Day=21
Ditto for Saturday
date(__,Year,Month,Day,6,week(53,2004))
Year=2005,Month=1,Day=1
Ditto for Monday (note automatic compensation of nonexistent week number)
date(__,Year,Month,Day,1,week(60,2004))
Year=2005,Month=2,Day=14
```

date/7

Ditto date/6 + get/check its day-of-year #.

Compilation flags:

static

Template:

```
date(JD,Year,Month,Day,DoW,Week,DoY)
JD - Julian day serial number.
Year - 0 or negative if converted BC year, positive otherwise.
Month - Normally an integer between 1 and 12 inclusive.
Day - Normally an integer between 1 and 31 inclusive depending upon month.
DoW - Day of week, where Monday=1, Tuesday=2, ..., Sunday=7.
Week - Compound term, week(WeekNo,ActualYear), of a day.
DoY - Day of year (NB! calendar year, not week # year).
```

Mode and number of proofs:

```
date(?integer,?integer,?integer,?integer,?integer,?compound,?integer) - zero_or_one
```

Examples:

Get the date and day-of-year of a Julian number


```

date(2451649,Year,Month,Day,_,_,DoY)
Year=2000,Month=4,Day=14,DoY=105
Get the Julian number, week number and day-of-year of a date, confirming that it is a Sunday
date(JD,2004,2,29,7,Week,DoY)
JD=2453065,Week=week(9,2004),DoY=60
Confirm that a date is, in fact, a specific day-of-year
date(_,2004,3,1,_,_,61)
yes
Get the Julian number, week day and day-of-year of a date
date(JD,2004,10,18,DoW,_,DoY)
JD=2453297,DoW=1,DoY=292
Get today's day-of-year
date(_,_,_,_,_,DoY)
DoY=54
Get all missing date data (excl. Julian number) for the 60th calendar day of 2004
date(_,2004,Month,Day,DoW,Week,60)
Month=2,Day=29,DoW=7,Week=week(9,2004)
Match given date data and, if true, return the missing data (excl. Julian number)
date(_,2004,3,Day,DoW,Week,61)
Day=1,DoW=1,Week=week(10,2004)
Ditto (the 61st day-of-year cannot be both day 1 and 2 of the month)
date(_,2004,_,2,_,_,61)
no

```

date_string/3

Conversion between an ISO 8601 compliant date string and its components (truncated and expanded date representations are currently unsupported). Note that date components are not validated; that is the caller's responsibility!

Compilation flags:

```
static
```

Template:

```
date_string(Format,Components,String)
```

Format - ISO 8601 format.

Components - When bound and String is free, either a Julian number or a [Year,Month,Day] term; it binds to the system day/date if free When free and String is bound, it binds to an integer list representing the numeric elements of String.

String - ISO 8601 formatted string correspondent to Components.

Mode and number of proofs:

```
date_string(+atom,+integer,?atom) - zero_or_one
```

```
date_string(+atom,?list,?atom) - zero_or_one
```

Examples:

```
Date, complete, basic (section 5.2.1.1)
  date_string('YYYYMMDD',[2004,2,29],String)
  String='20040229'
Date, complete, basic (section 5.2.1.1)
  date_string('YYYYMMDD',Components,'20040229')
  Components=[2004,2,29]
Date, complete, extended (section 5.2.1.1)
  date_string('YYYY-MM-DD',[2003,12,16],String)
  String='2003-12-16'
Date, complete, extended (section 5.2.1.1)
  date_string('YYYY-MM-DD',Components,'2003-12-16')
  Components=[2003,12,16]
Date, complete, extended (section 5.2.1.1)
  date_string('YYYY-MM-DD',_,String)
  String='2004-02-17'
Date, complete, extended (section 5.2.1.1)
  date_string('YYYY-MM-DD',Components,'2004-02-17')
  Components=[2004,2,17]
Date, reduced, month (section 5.2.1.2 a)
  date_string('YYYY-MM',[2004,9,18],String)
  String='2004-09'
Date, reduced, month (section 5.2.1.2 a)
  date_string('YYYY-MM',Components,'2004-09')
  Components=[2004,9]
Date, reduced, year (section 5.2.1.2 b)
  date_string('YYYY',[1900,7,24],String)
  String='1900'
Date, reduced, year (section 5.2.1.2 b)
  date_string('YYYY',Components,'1900')
  Components=[1900]
Date, reduced, century (section 5.2.1.2 c)
  date_string('YY',2456557,String)
  String='20'
Date, reduced, century (section 5.2.1.2 c)
  date_string('YY',Components,'20')
  Components=[20]
Date, ordinal, complete (section 5.2.2.1)
  date_string('YYYYDDD',[2005,3,25],String)
  String='2005084'
Date, ordinal, complete (section 5.2.2.1)
  date_string('YYYYDDD',Components,'2005084')
  Components=[2005,84]
Date, ordinal, extended (section 5.2.2.1)
  date_string('YYYY-DDD',[1854,12,4],String)
  String='1854-338'
Date, ordinal, extended (section 5.2.2.1)
```

```

    date_string('YYYY-DDD',Components,'1854-338')
    Components=[1854,338]
Week, complete, basic (section 5.2.3.1)
    date_string('YYYYWwwD',[2000,1,2],String)
    String='1999W527'
Week, complete, basic (section 5.2.3.1)
    date_string('YYYYWwwD',Components,'1999W527')
    Components=[1999,52,7]
Week, complete, extended (section 5.2.3.1)
    date_string('YYYY-Www-D',[2003,12,29],String)
    String='2004-W01-1'
Week, complete, extended (section 5.2.3.1)
    date_string('YYYY-Www-D',Components,'2004-W01-1')
    Components=[2004,1,1]
Week, complete, extended (section 5.2.3.1)
    date_string('YYYY-Www-D',2453167,String)
    String='2004-W24-4'
Week, complete, extended (section 5.2.3.1)
    date_string('YYYY-Www-D',Components,'2004-W24-4')
    Components=[2004,24,4]
Week, reduced, basic (section 5.2.3.2)
    date_string('YYYYWww',[2004,2,29],String)
    String='2004W09'
Week, reduced, basic (section 5.2.3.2)
    date_string('YYYYWww',Components,'2004W09')
    Components=[2004,9]
Week, reduced, extended (section 5.2.3.2)
    date_string('YYYY-Www',[2004,2,29],String)
    String='2004-W09'
Week, reduced, extended (section 5.2.3.2)
    date_string('YYYY-Www',Components,'2004-W09')
    Components=[2004,9]

```

`valid_date/3`

Validate a given date in the Gregorian calendar.

Compilation flags:

```
static
```

Template:

```
valid_date(Year,Month,Day)
```

Mode and number of proofs:

valid_date(+integer,+integer,+integer) - zero_or_one

Examples:

Yes, the recent millennium was a leap year

```
valid_date(2000,2,29)
```

yes

2004 was also a leap year

```
valid_date(2004,2,29)
```

yes

Only 30 days in April

```
valid_date(2004,4,31)
```

no

1 BC was a leap year

```
valid_date(-1,2,29)
```

yes

leap_year/1

Succeed if given year is a leap year in the Gregorian calendar.

Compilation flags:

static

Template:

```
leap_year(Year)
```

Year - The Gregorian calendar year to investigate. If free, it binds to the system year.

Mode and number of proofs:

```
leap_year(?integer) - zero_or_one
```

Examples:

No, the prior centenary was not a leap year

```
leap_year(1900)
```

no

The recent millennium

```
leap_year(2000)
```

yes

This year

```
leap_year(Year)
```

```
Year=2004
```

This year (equivalent to prior query)

```
leap_year(_)
```

```

    yes
Next centennial
    leap_year(2100)
    no
Year 0, equivalent to 1 BC
    leap_year(0)
    yes
1 BC
    leap_year(-1)
    yes
4 BC
    leap_year(-4)
    no
5 BC
    leap_year(-5)
    yes

```

calendar_month/3

Compute a calendar month.

Compilation flags:

```
static
```

Template:

```
calendar_month(Year,Month,Calendar)
```

Year - The calendar year.

Month - The calendar month.

Calendar - A compound term, m/3, composed of three main arguments specifying year, month, and a list of week and week day numbers (calendar body).

Mode and number of proofs:

```
calendar_month(?integer,?integer,-compound) - zero_or_one
```

Examples:

Compute the calendar of March, 2005

```
calendar_month(2005,3,Calendar)
```

```
Calendar=m(2005,3,[w(9,[0,1,2,3,4,5,6]),w(10,[7,8,9,10,11,12,13]),w(11,[14,15,16,17,18,19,20]),
w(12,[21,22,23,24,25,26,27]),w(13,[28,29,30,31,0,0,0]),w(0,[0,0,0,0,0,0])])
```

easter_day/3

Compute a Gregorian Easter Sunday.

Compilation flags:

static

Template:

easter_day(Year,Month,Day)

Year - Integer specifying the year to be investigated.

Month - Month in which Easter Sunday falls for given year.

Day - Day of month in which Easter Sunday falls for given year.

Mode and number of proofs:

easter_day(?integer,-integer,-integer) - zero_or_one

Examples:

Compute Easter Sunday for a particular year

easter_day(2006,Month,Day)

Month=4,Day=16

Compute Easter Sunday for the current year

easter_day(Year,Month,Day)

Year=2005,Month=3,Day=27

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

1.39 issue_creator

object

1.39.1 issue_creator

Support for automatically creating bug report issues for failed tests in GitHub or GitLab servers.

Availability:

```
logtalk_load(issue_creator(loader))
```

Author: Paulo Moura

Version: 0:12:0

Date: 2022-01-20

Compilation flags:

```
static, context_switching_calls
```

Provides:

```
logtalk::message_hook/4
```

Uses:

```
git
```

```
os
```

```
term_io
```

```
user
```

Remarks:

- Usage: This tool is automatically loaded and used from the `logtalk_tester` automation script when using its `-b` option. See the script man page for details.

Inherited public predicates:

```
(none)
```

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

1.40 java

object

1.40.1 java

Abstract interface to JPL API utility predicates.

Availability:

`logtalk_load(java(loader))`

Author: Paulo Moura

Version: 1:8:0

Date: 2023-03-15

Compilation flags:

`static, context_switching_calls`

Implements:

`public java_utils_protocol`

Uses:

`user`

Remarks:

(none)

Inherited public predicates:

array_list/2 array_to_list/2 array_to_terms/2 array_to_terms/3 decode_exception/2
 decode_exception/3 false/1 is_false/1 is_null/1 is_object/1 is_true/1 is_void/1
 iterator_element/2 list_to_array/2 map_element/2 null/1 set_element/2 terms_to_array/2
 true/1 value_reference/2 void/1

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

See also:

java(Reference,ReturnValue), java(Reference), java_hook
 object

1.40.2 java(Reference)

- Reference - Either a class name or a Java reference to an object.

Minimal abstraction of the JPL API for calling Java from Logtalk using familiar message sending syntax and a forward/1 handler to resolve methods.

Availability:

logtalk_load(java(loader))

Author: Paulo Moura and Sergio Castro

Version: 1:0:1

Date: 2019-06-13

Compilation flags:

static, context_switching_calls

Extends:

public java(Reference,_)

Remarks:

- Usage: Send to this object any valid message as listed in the JavaDocs for the given reference.

Inherited public predicates:

forward/1 get_field/2 invoke/1 invoke/2 new/1 new/2 set_field/2

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

See also:

java(Reference,ReturnValue), java, java_hook

object

1.40.3 java(Reference,ReturnValue)

- Reference - Either a class name or a Java reference to an object.
- ReturnValue - Value returned by a method call (possibly the Java value void).

Minimal abstraction of the JPL API for calling Java from Logtalk using familiar message sending syntax and a forward/1 handler to resolve methods.

Availability:

```
logtalk_load(java(loader))
```

Author: Paulo Moura and Sergio Castro

Version: 1:4:0

Date: 2023-03-13

Compilation flags:

```
static, context_switching_calls
```

Implements:

```
public forwarding  
public java_access_protocol
```

Remarks:

- Usage: Send to this object any valid message as listed in the JavaDocs for the given reference.

Inherited public predicates:

```
forward/1 get_field/2 invoke/1 invoke/2 new/1 new/2 set_field/2
```

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

See also:

[java\(Reference\)](#), [java](#), [java_hook](#)
protocol

1.40.4 java_access_protocol

Protocol for a minimal abstraction for calling Java from Logtalk using familiar message sending syntax.

Availability:

```
logtalk_load(java(loader))
```

Author: Paulo Moura and Sergio Castro

Version: 1:2:1

Date: 2023-03-16

Compilation flags:

```
static
```

Dependencies:

(none)

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
 - get_field/2
 - set_field/2
 - new/2
 - new/1
 - invoke/1
 - invoke/2
- Protected predicates
- Private predicates
- Operators

Public predicates

get_field/2

Gets the value of a class or object field.

Compilation flags:

static

Template:

get_field(Field,Value)

Mode and number of proofs:

get_field(+atom,?nonvar) - zero_or_one

set_field/2

Sets the value of a class or object field.

Compilation flags:

static

Template:

set_field(Field,Value)

Mode and number of proofs:

set_field(+atom,+nonvar) - one

new/2

Creates a new instance using the specified parameter values.

Compilation flags:

static

Template:

new(Parameters,Instance)

Mode and number of proofs:

new(+list(nonvar),-reference) - one

new/1

Creates a new instance using default parameter values.

Compilation flags:

static

Template:

new(Instance)

Mode and number of proofs:

new(-reference) - one

invoke/1

Invokes a method. This is a more efficient compared with relying on the forward/1 handler to resolve methods.

Compilation flags:

static

Template:

invoke(Method)

Mode and number of proofs:

invoke(@nonvar) - one

invoke/2

Invokes a method. This is a more efficient compared with relying on the forward/1 handler to resolve methods.

Compilation flags:

static

Template:

invoke(Functor,Arguments)

Mode and number of proofs:

invoke(@nonvar,@list) - one

Protected predicates

(none)

Private predicates

(none)

Operators

(none)

object

1.40.5 java_hook

Hook object to optimize messages to the java/1-2 objects that otherwise would trigger the forward/1 handler.

Availability:

logtalk_load(java(loader))

Author: Paulo Moura

Version: 1:0:1

Date: 2019-06-13

Compilation flags:

static, context_switching_calls

Implements:

public `expanding`

Remarks:

- Usage: Compile source files with messages to the java/1-2 objects using the compiler option `hook(java_hook)`.

Inherited public predicates:

`goal_expansion/2` `term_expansion/2`

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

See also:

java(Reference,ReturnValue), java(Reference)

protocol

1.40.6 java_utils_protocol

Abstract interface to Java utility predicates.

Availability:

logtalk_load(java(loader))

Author: Paulo Moura

Version: 1:6:0

Date: 2023-03-13

Compilation flags:

static

Dependencies:

(none)

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
 - value_reference/2
 - true/1
 - false/1
 - void/1
 - null/1
 - is_true/1
 - is_false/1

- is_void/1
- is_null/1
- is_object/1
- terms_to_array/2
- array_to_terms/3
- array_to_terms/2
- array_to_list/2
- list_to_array/2
- array_list/2
- iterator_element/2
- map_element/2
- set_element/2
- decode_exception/2
- decode_exception/3
- Protected predicates
- Private predicates
- Operators

Public predicates

value_reference/2

Returns an opaque term that represents the Java value with the given name.

Compilation flags:

static

Template:

value_reference(Value,Reference)

Mode and number of proofs:

value_reference(?atom,--ground) - one_or_more

true/1

Returns an opaque term that represents the Java value true.

Compilation flags:

static

Template:

true(Reference)

Mode and number of proofs:

true(--ground) - one

false/1

Returns an opaque term that represents the Java value false.

Compilation flags:

static

Template:

false(Reference)

Mode and number of proofs:

false(--ground) - one

void/1

Returns an opaque term that represents the Java value void.

Compilation flags:

static

Template:

void(Reference)

Mode and number of proofs:

void(--ground) - one

null/1

Returns an opaque term that represents the Java value null.

Compilation flags:

static

Template:

null(Reference)

Mode and number of proofs:

null(--ground) - one

is_true/1

True when the argument is the Java value true. Fails if the argument is not instantiated.

Compilation flags:

static

Template:

is_true(Reference)

Mode and number of proofs:

is_true(@term) - zero_or_one

is_false/1

True when the argument is the Java value false. Fails if the argument is not instantiated.

Compilation flags:

static

Template:

is_false(Reference)

Mode and number of proofs:

is_false(@term) - zero_or_one

is_void/1

True when the argument is the Java value void. Fails if the argument is not instantiated.

Compilation flags:

static

Template:

is_void(Reference)

Mode and number of proofs:

is_void(@term) - zero_or_one

is_null/1

True when the argument is the Java value null. Fails if the argument is not instantiated.

Compilation flags:

static

Template:

is_null(Reference)

Mode and number of proofs:

is_null(@term) - zero_or_one

is_object/1

True when the argument is a reference to a Java object. Fails if the argument is not instantiated.

Compilation flags:

static

Template:

is_object(Reference)

Mode and number of proofs:

is_object(@term) - zero_or_one

terms_to_array/2

Converts a list of ground Prolog terms to an array (a Java reference).

Compilation flags:

static

Template:

terms_to_array(Terms,Array)

Mode and number of proofs:

terms_to_array(++list(ground),-array) - one

array_to_terms/3

Converts an array (a Java reference) to a list of ground Prolog terms returning also its length. The array elements must be atoms, integers, floats, or compound terms. Fails otherwise.

Compilation flags:

static

Template:

array_to_terms(Array,Terms,Length)

Mode and number of proofs:

array_to_terms(+array,-list(ground),-integer) - one

array_to_terms/2

Converts an array (a Java reference) to a list of ground Prolog terms. The array elements must be atoms, integers, floats, or ground compound terms. Fails otherwise.

Compilation flags:

static

Template:

array_to_terms(Array,Terms)

Mode and number of proofs:

array_to_terms(+array,-list(term)) - one

`array_to_list/2`

Converts an array (a Java reference) to a list of Java references or their values.

Compilation flags:

`static`

Template:

`array_to_list(Array,List)`

Mode and number of proofs:

`array_to_list(+array,-list) - one`

`list_to_array/2`

Converts a list of Java references or values to an array (a Java reference).

Compilation flags:

`static`

Template:

`list_to_array(List,Array)`

Mode and number of proofs:

`list_to_array(+list,-array) - one`

`array_list/2`

Converts between an array (a Java reference) and a list of Java references or their values. Deprecated. Use the `array_to_list/2` and `list_to_array/2` predicates instead.

Compilation flags:

`static`

Template:

`array_list(Array,List)`

Mode and number of proofs:

`array_list(+array,-list)` - one

`array_list(-array,+list)` - one

`iterator_element/2`

Enumerates, by backtracking, all iterator elements.

Compilation flags:

`static`

Template:

`iterator_element(Iterator,Element)`

Mode and number of proofs:

`iterator_element(+iterator,-element)` - zero_or_more

`map_element/2`

Enumerates, by backtracking, all map elements.

Compilation flags:

`static`

Template:

`map_element(Map,Element)`

Mode and number of proofs:

`map_element(+iterator,-element)` - zero_or_more

set_element/2

Enumerates, by backtracking, all set elements.

Compilation flags:

static

Template:

set_element(Set,Element)

Mode and number of proofs:

set_element(+iterator,-element) - zero_or_more

decode_exception/2

Decodes an exception into its corresponding cause. Fails if the exception is not a Java exception.

Compilation flags:

static

Template:

decode_exception(Exception,Cause)

Mode and number of proofs:

decode_exception(+callable,-atom) - zero_or_one

decode_exception/3

Decodes an exception into its corresponding cause and a stack trace. Fails if the exception is not a Java exception.

Compilation flags:

static

Template:

decode_exception(Exception,Cause,StackTrace)

Mode and number of proofs:

decode_exception(+callable,-atom,-list(atom)) - zero_or_one

Protected predicates

(none)

Private predicates

(none)

Operators

(none)

1.41 json

object

1.41.1 json

JSON parser and generator. Uses curly terms for parsed JSON objects, dashes for parsed JSON pairs, and atoms for parsed JSON strings.

Availability:

```
logtalk_load(json(loader))
```

Author: Paulo Moura and Jacinto Dávila

Version: 1:1:0

Date: 2022-11-14

Compilation flags:

```
static, context_switching_calls
```

Extends:

```
public json(curly,dash,atom)
```

Remarks:

(none)

Inherited public predicates:

```
generate/2 parse/2
```

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

object

1.41.2 json(StringRepresentation)

- StringRepresentation - Text representation to be used when decoding JSON strings. Possible values are atom (default), chars, and codes.

JSON parser and generator. Uses curly terms for parsed JSON objects and dashes for parsed JSON pairs.

Availability:

```
logtalk_load(json(loader))
```

Author: Paulo Moura

Version: 1:0:0

Date: 2022-11-14

Compilation flags:

```
static, context_switching_calls
```

Extends:

```
public json(curly,dash,StringRepresentation)
```

Remarks:

(none)

Inherited public predicates:

generate/2 parse/2

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

object

1.41.3 json(ObjectRepresentation,PairRepresentation,StringRepresentation)

- ObjectRepresentation - Object representation to be used when decoding JSON objects. Possible values are curly (default) and list.
- PairRepresentation - Pair representation to be used when decoding JSON objects. Possible values are dash (default), equal, and colon.
- StringRepresentation - Text representation to be used when decoding JSON strings. Possible values are atom (default), chars, and codes.

JSON parser and generator.

Availability:

logtalk_load(json(loader))

Author: Paulo Moura and Jacinto Dávila
Version: 0:12:2
Date: 2024-01-14

Compilation flags:
static, context_switching_calls

Implements:
public json_protocol

Uses:
reader

Remarks:
(none)

Inherited public predicates:
generate/2 parse/2

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

protocol

1.41.4 json_protocol

JSON parser and generator protocol.

Availability:

logtalk_load(json(loader))

Author: Paulo Moura and Jacinto Dávila

Version: 0:11:0

Date: 2022-11-09

Compilation flags:

static

Dependencies:

(none)

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
 - parse/2
 - generate/2
- Protected predicates
- Private predicates
- Operators

Public predicates

parse/2

Parses the JSON contents read from the given source (codes(List), stream(Stream), line(Stream), file(Path), chars(List), or atom(Atom)) into a term. Fails if the JSON contents cannot be parsed.

Compilation flags:

static

Template:

parse(Source,Term)

Mode and number of proofs:

parse(++compound,--term) - one_or_error

generate/2

Generates the content using the representation specified in the first argument (codes(List), stream(Stream), file(Path), chars(List), or atom(Atom)) for the term in the second argument. Fails if this term cannot be processed.

Compilation flags:

static

Template:

generate(Sink,Term)

Mode and number of proofs:

generate(+compound,++term) - one_or_error

Protected predicates

(none)

Private predicates

(none)

Operators

(none)

1.42 lgtdoc

object

1.42.1 lgtdoc

Documenting tool. Generates XML documenting files for loaded entities and for library, directory, entity, and predicate indexes.

Availability:

```
logtalk_load(lgtdoc(loader))
```

Author: Paulo Moura

Version: 10:0:0

Date: 2024-03-08

Compilation flags:

```
static, context_switching_calls
```

Implements:

```
public lgtdocp
```

Imports:

```
public options
```

Uses:

```
date  
list  
logtalk  
os  
type  
user  
varlist
```

Remarks:

(none)

Inherited public predicates:

all/0 all/1 check_option/1 check_options/1 default_option/1 default_options/1 directories/1
 directories/2 directory/1 directory/2 file/1 file/2 files/1 files/2 fix_option/2 fix_options/2
 libraries/1 libraries/2 library/1 library/2 merge_options/2 option/2 option/3 rdirectories/1
 rdirectories/2 rdirectory/1 rdirectory/2 rlibraries/1 rlibraries/2 rlibrary/1 rlibrary/2
 valid_option/1 valid_options/1

- Public predicates
- Protected predicates
- Private predicates
 - library_entity_/4
 - directory_entity_/4
 - type_entity_/4
 - predicate_entity_/4
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

library_entity_/4

Table of documented entities per library.

Compilation flags:

dynamic

Template:

library_entity_(Library,PrimarySortKey,SecondarySortKey,Entity)

Mode and number of proofs:

library_entity_(?atom,?nonvar,?nonvar,?atom) - zero_or_more

directory_entity_/4

Table of documented entities per directory.

Compilation flags:

dynamic

Template:

directory_entity__(Directory,PrimarySortKey,SecondarySortKey,Entity)

Mode and number of proofs:

directory_entity__(?atom,?nonvar,?nonvar,?atom) - zero_or_more

type_entity_/4

Table of documented entities per type.

Compilation flags:

dynamic

Template:

type_entity__(Type,PrimarySortKey,SecondarySortKey,Entity)

Mode and number of proofs:

type_entity__(?atom,?nonvar,?nonvar,?atom) - zero_or_more

predicate_entity_/4

Table of public predicates for all documented entities.

Compilation flags:

dynamic

Template:

predicate_entity__(Predicate,PrimarySortKey,SecondarySortKey,Entity)

Mode and number of proofs:

predicate_entity__(?predicate_indicator,?nonvar,?nonvar,?entity_identifier) - zero_or_more

Operators

(none)

category

1.42.2 lgtdoc_messages

Logtalk documentation tool default message translations.

Availability:

```
logtalk_load(lgtdoc(loader))
```

Author: Paulo Moura

Version: 3:0:0

Date: 2022-10-25

Compilation flags:

```
static
```

Provides:

```
logtalk::message_tokens//2
```

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

protocol

1.42.3 lgtdocp

Documenting tool protocol.

Availability:

`logtalk_load(lgtdoc(loader))`

Author: Paulo Moura

Version: 6:0:0

Date: 2024-03-08

Compilation flags:

`static`

Dependencies:

(none)

Remarks:

- Compiling files for generating XML documentation: All source files must be compiled with the `source_data` flag turned on.
- `xml_spec(Specification)` option: XML documenting files specification format. Possible option values are `dtd` (DTD specification; default) and `xsd` (XML Schema specification).
- `xml_spec_reference(Reference)` option: Reference to the XML specification file in XML documenting files. Possible values are `local` (default; DTD/XSD file in same folder as XML files), `web` (logtalk.org website DTD/XSD file), and `standalone` (no reference to specification files).

- `entity_xsl_file(File)` option: XSLT file to use with generated XML documenting files. Default is `logtalk_entity_to_xml.xsl`, allowing the XML files to be viewed by opening them with a browser supporting XSLT (after running the `lgt2xml.sh` script on the output directory).
- `index_xsl_file(File)` option: XSLT file to use with generated XML documenting files. Default is `logtalk_index_to_xml.xsl`, allowing the XML files to be viewed by opening them with a browser supporting XSLT (after running the `lgt2xml.sh` script on the output directory).
- `xml_docs_directory(Directory)` option: Directory where the XML documenting files will be generated. The default value is `./xml_docs`, a sub-directory of the source files directory.
- `bom(Boolean)` option: Defines if a BOM should be added to the generated XML documenting files.
- `encoding(Encoding)` option: Encoding to be used for the generated XML documenting files.
- `omit_path_prefixes(Prefixes)` option: List of path prefixes (atoms) to omit when writing directory paths. The default value is to omit the home directory.
- `exclude_files(List)` option: List of files to exclude when generating the XML documenting files.
- `exclude_paths(List)` option: List of relative library paths to exclude when generating the XML documenting files (default is []). All sub-directories of the excluded directories are also excluded.
- `exclude_prefixes(List)` option: List of path prefixes to exclude when generating the XML documenting files (default is []).
- `exclude_entities(List)` option: List of entities to exclude when generating the XML documenting files (default is []).
- `sort_predicates(Boolean)` option: Sort entity predicates (default is false).
- Known issues: Some options may depend on the used XSL processor. Most XSL processors support DTDs but only some of them support XML Schemas. Some processors (e.g. fop2) reject reference to a DTD.

Inherited public predicates:

(none)

- Public predicates
 - `rlibraries/2`
 - `rlibraries/1`
 - `rlibrary/2`
 - `rlibrary/1`
 - `libraries/2`
 - `libraries/1`
 - `library/2`
 - `library/1`
 - `rdirectories/2`
 - `rdirectories/1`
 - `rdirectory/2`

- rdirectory/1
- directories/2
- directories/1
- directory/2
- directory/1
- files/2
- files/1
- file/2
- file/1
- all/1
- all/0
- Protected predicates
- Private predicates
- Operators

Public predicates

rlibraries/2

Creates XML documenting files for all entities in all given libraries and their sub-libraries using the specified options.

Compilation flags:

static

Template:

rlibraries(Libraries,Options)

Mode and number of proofs:

rlibraries(+list(atom),+list) - one

rlibraries/1

Creates XML documenting files for all entities in all given libraries and their sub-libraries using default options.

Compilation flags:

static

Template:

rlibraries(Libraries)

Mode and number of proofs:

rlibraries(+list(atom)) - one

rlibrary/2

Creates XML documenting files for all entities in a library and its sub-libraries using the specified options.

Compilation flags:

static

Template:

rlibrary(Library,Options)

Mode and number of proofs:

rlibrary(+atom,+list) - one

Examples:

Generate XML documenting files for all tool entities for later conversion to Markdown files

```
rlibrary(tools,[xslfile('lgtmd.xml')])
```

```
yes
```

rlibrary/1

Creates XML documenting files for all entities in a library and its sub-libraries using default options.

Compilation flags:

static

Template:

rlibrary(Library)

Mode and number of proofs:

rlibrary(+atom) - one

Examples:

Generate XML documenting files for all tool entities for direct viewing in a browser (after indexing using the lgt2xml script)

rlibrary(tools)

yes

libraries/2

Creates XML documenting files for all entities in all given libraries using the specified options.

Compilation flags:

static

Template:

libraries(Libraries,Options)

Mode and number of proofs:

libraries(+list(atom),+list) - one

libraries/1

Creates XML documenting files for all entities in all given libraries using default options.

Compilation flags:

static

Template:

libraries(Libraries)

Mode and number of proofs:

libraries(+list(atom)) - one

library/2

Creates XML documenting files for all entities in a library using the specified options.

Compilation flags:

static

Template:

library(Library,Options)

Mode and number of proofs:

library(+atom,+list) - one

Examples:

Generate XML documenting files for all library entities for later conversion to PDF A4 files

```
library(library,[xslfile('logtalk_entity_to_pdf_a4.xml')])
yes
```

library/1

Creates XML documenting files for all entities in a library using default options.

Compilation flags:

static

Template:

library(Library)

Mode and number of proofs:

library(+atom) - one

rdirectories/2

Creates XML documenting files for all entities in all given directories and their sub-directories using the specified options.

Compilation flags:

static

Template:

rdirectories(Directories,Options)

Mode and number of proofs:

rdirectories(+list(atom),+list) - one

rdirectories/1

Creates XML documenting files for all entities in all given directories and their sub-directories using default options.

Compilation flags:

static

Template:

rdirectories(Directories)

Mode and number of proofs:

rdirectories(+list(atom)) - one

rdirectory/2

Creates XML documenting files for all entities in a directory and its sub-directories using the specified options.

Compilation flags:

static

Template:

rdirectory(Directory,Options)

Mode and number of proofs:

rdirectory(+atom,+list) - one

Examples:

Generate XML documenting files for all entities in the tools directory for later conversion to Markdown files

```
rdirectory('./tools',[xslfile('lgtmd.xml')])
```

```
yes
```

rdirectory/1

Creates XML documenting files for all entities in a directory and its sub-directories using default options.

Compilation flags:

static

Template:

rdirectory(Directory)

Mode and number of proofs:

rdirectory(+atom) - one

Examples:

Generate XML documenting files for all entities in the tools directory for direct viewing in a browser (after indexing using the lgt2xml script)

```
rdirectory('./tools')
```

```
yes
```

directories/2

Creates XML documenting files for all entities in all given directories using the specified options.

Compilation flags:

static

Template:

directories(Directories,Options)

Mode and number of proofs:

directories(+list(atom),+list) - one

directories/1

Creates XML documenting files for all entities in all given directories using default options.

Compilation flags:

static

Template:

directories(Directories)

Mode and number of proofs:

directories(+list(atom)) - one

directory/2

Creates XML documenting files for all entities in a directory using the specified options.

Compilation flags:

static

Template:

directory(Directory,Options)

Mode and number of proofs:

directory(+atom,+list) - one

Examples:

Generate XML documenting files for all the entities in the current directory for later conversion to PDF A4 files

```
directory('.',[xslfile('logtalk_entity_to_pdf_a4.xsl')])
yes
```

directory/1

Creates XML documenting files for all entities in a directory using default options.

Compilation flags:

static

Template:

directory(Directory)

Mode and number of proofs:

directory(+atom) - one

files/2

Creates XML documenting files for all entities in loaded source files using the specified options. The files can be given by name, basename, full path, or using library notation.

Compilation flags:

static

Template:

files(Files,Options)

Mode and number of proofs:

files(+list(atom),+list) - one

files/1

Creates XML documenting files for all entities in loaded source files using default options. The files can be given by name, basename, full path, or using library notation.

Compilation flags:

static

Template:

files(Files)

Mode and number of proofs:

files(+list(atom)) - one

file/2

Creates XML documenting files for all entities in a loaded source file using the specified options. The file can be given by name, basename, full path, or using library notation.

Compilation flags:

static

Template:

file(File,Options)

Mode and number of proofs:

file(+atom,+list) - one

file/1

Creates XML documenting files for all entities in a loaded source file using default options. The file can be given by name, basename, full path, or using library notation.

Compilation flags:

static

Template:

file(File)

Mode and number of proofs:

file(+atom) - one

all/1

Creates XML documenting files for all loaded entities using the specified options.

Compilation flags:

static

Template:

all(Options)

Mode and number of proofs:

all(+list) - one

all/0

Creates XML documenting files for all loaded entities using default options.

Compilation flags:

static

Mode and number of proofs:

all - one

Protected predicates

(none)

Private predicates

(none)

Operators

(none)

See also:

lgtdoc

1.43 lgtunit

object

1.43.1 automation_report

Intercepts unit test execution messages and generates a *.totals files for parsing by the logtalk_tester.sh automation shell script.

Availability:

logtalk_load(lgtunit(loader))

Author: Paulo Moura

Version: 5:0:0

Date: 2024-02-20

Compilation flags:

static, context_switching_calls

Provides:

logtalk::message_hook/4

Uses:

user

Remarks:

- Usage: Automatically loaded by the logtalk_tester.sh shell script.

Inherited public predicates:

(none)

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

object

1.43.2 coverage_report

Intercepts unit test execution messages and generates a `coverage_report.xml` file with a test suite code coverage results.

Availability:

```
logtalk_load(lgtunit(loader))
```

Author: Paulo Moura

Version: 3:2:0

Date: 2023-04-11

Compilation flags:

```
static, context_switching_calls
```

Provides:

```
logtalk::message_hook/4
```

Uses:

```
logtalk
```

user

Remarks:

- Usage: Simply load this object before running your tests using the goal `logtalk_load(lgtunit(coverage_report))`.

Inherited public predicates:

(none)

- Public predicates
- Protected predicates
- Private predicates
 - `timestamp_/6`
 - `object_file_/2`
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

`timestamp_/6`

Cache of the starting tests timestamp.

Compilation flags:

dynamic

Template:

`timestamp_(Year,Month,Day,Hours,Minutes,Seconds)`

Mode and number of proofs:

`timestamp_(-integer,-integer,-integer,-integer,-integer,-integer) - one`

object_file_/2

Cache of test object - file pairs.

Compilation flags:

dynamic

Template:

object_file__(Object,File)

Mode and number of proofs:

object_file__(?object_identifier,?atom) - zero_or_more

Operators

(none)

object

1.43.3 lgtunit

A unit test framework supporting predicate clause coverage, determinism testing, input/output testing, property-based testing, and multiple test dialects.

Availability:

logtalk_load(lgtunit(loader))

Author: Paulo Moura

Version: 17:0:0

Date: 2024-02-19

Compilation flags:

static, context_switching_calls

Implements:

public expanding

Provides:

logtalk::trace_event/2

Uses:

fast_random

list

logtalk

os
type
user

Remarks:

- Usage: Define test objects as extensions of the lgtunit object and compile their source files using the compiler option hook(lgtunit).
- Portability: Deterministic unit tests are currently not available when using Quintus Prolog as the backend compiler.
- Known issues: Parameter variables cannot currently be used in the definition of test options.

Inherited public predicates:

goal_expansion/2 term_expansion/2

- Public predicates
 - cover/1
 - run/0
 - run/1
 - run/2
 - run_test_sets/1
 - test/1
 - number_of_tests/1
 - deterministic/1
 - deterministic/2
 - assertion/1
 - assertion/2
 - quick_check/3
 - quick_check/2
 - quick_check/1
 - benchmark/2
 - benchmark_reified/3
 - benchmark/3
 - benchmark/4
 - variant/2
 - approximately_equal/2
 - approximately_equal/3

- essentially_equal/3
- tolerance_equal/4
- ==~ / 2
- epsilon/1
- Protected predicates
 - run_tests/0
 - run_tests/1
 - run_test_set/0
 - run_quick_check_tests/5
 - condition/0
 - setup/0
 - cleanup/0
 - make/1
 - note/1
 - file_path/2
 - suppress_text_output/0
 - suppress_binary_output/0
 - set_text_input/3
 - set_text_input/2
 - set_text_input/1
 - check_text_input/2
 - check_text_input/1
 - text_input_assertion/3
 - text_input_assertion/2
 - clean_text_input/0
 - set_binary_input/3
 - set_binary_input/2
 - set_binary_input/1
 - check_binary_input/2
 - check_binary_input/1
 - binary_input_assertion/3
 - binary_input_assertion/2
 - clean_binary_input/0
 - set_text_output/3
 - set_text_output/2

- set_text_output/1
- check_text_output/3
- check_text_output/2
- check_text_output/1
- text_output_assertion/4
- text_output_assertion/3
- text_output_assertion/2
- text_output_contents/3
- text_output_contents/2
- text_output_contents/1
- clean_text_output/0
- set_binary_output/3
- set_binary_output/2
- set_binary_output/1
- check_binary_output/2
- check_binary_output/1
- binary_output_assertion/3
- binary_output_assertion/2
- binary_output_contents/2
- binary_output_contents/1
- clean_binary_output/0
- create_text_file/3
- create_text_file/2
- create_binary_file/2
- check_text_file/3
- check_text_file/2
- text_file_assertion/4
- text_file_assertion/3
- check_binary_file/2
- binary_file_assertion/3
- clean_file/1
- clean_directory/1
- closed_input_stream/2
- closed_output_stream/2
- stream_position/1

- test/2
- Private predicates
 - running_test_sets_/0
 - test/3
 - auxiliary_predicate_counter_/1
 - test_/2
 - skipped_/1
 - passed_/3
 - failed_/3
 - flaky_/1
 - fired_/3
 - covered_/4
- Operators
 - op(700,xfx,==~)

Public predicates

cover/1

Declares entities being tested for which code coverage information should be collected.

Compilation flags:

static

Template:

cover(Entity)

Mode and number of proofs:

cover(?entity_identifier) - zero_or_more

run/0

Runs the unit tests, writing the results to the current output stream.

Compilation flags:

static

Mode and number of proofs:

run - one

run/1

Runs a unit test or a list of unit tests, writing the results to the current output stream. Runs the global setup and cleanup steps when defined. Fails when given a partial list of tests or when one of the test identifiers is not valid.

Compilation flags:

static

Template:

run(Tests)

Mode and number of proofs:

run(++callable) - zero_or_one

run(++list(callable)) - zero_or_one

run/2

Runs the unit tests, writing the results to the specified file. Mode can be either write (to create a new file) or append (to add results to an existing file).

Compilation flags:

static

Template:

run(File,Mode)

Mode and number of proofs:

run(+atom,+atom) - one

run_test_sets/1

Runs two or more test sets as a unified set generating a single code coverage report if one is requested. Fails if the list does not contains at least two test objects.

Compilation flags:

static

Template:

run_test_sets(TestObjects)

Mode and number of proofs:

run_test_sets(+list(object_identifier)) - zero_or_one

test/1

Enumerates, by backtracking, the identifiers of all defined unit tests.

Compilation flags:

static

Template:

test(Identifier)

Mode and number of proofs:

test(?callable) - zero_or_more

number_of_tests/1

Number of defined unit tests.

Compilation flags:

static

Template:

number_of_tests(NumerOfTests)

Mode and number of proofs:

number_of_tests(?integer) - zero_or_one

deterministic/1

True if the goal succeeds once without leaving choice-points.

Compilation flags:

static

Template:

deterministic(Goal)

Meta-predicate template:

deterministic(0)

Mode and number of proofs:

deterministic(+callable) - zero_or_one

deterministic/2

Reified version of the *deterministic/1* predicate. True if the goal succeeds. Returns a boolean value (true or false) indicating if the goal succeeded without leaving choice-points.

Compilation flags:

static

Template:

deterministic(Goal,Deterministic)

Meta-predicate template:

deterministic(0,*)

Mode and number of proofs:

deterministic(+callable,--atom) - zero_or_one

assertion/1

True if the assertion goal succeeds. Throws an error using the assertion goal as argument if the assertion goal throws an error or fails.

Compilation flags:

static

Template:

assertion(Assertion)

Meta-predicate template:

assertion(::)

Mode and number of proofs:

assertion(@callable) - one

Exceptions:

Assertion goal fails:

assertion_failure(Assertion)

Assertion goal throws Error:

assertion_error(Assertion,Error)

assertion/2

True if the assertion goal succeeds. Throws an error using the description as argument if the assertion goal throws an error or fails. The description argument helps to distinguish between different assertions in the same test body.

Compilation flags:

static

Template:

assertion(Description,Assertion)

Meta-predicate template:

assertion(*,0)

Mode and number of proofs:

assertion(+nonvar,@callable) - one

Exceptions:

Assertion goal fails:

assertion_failure(Description)

Assertion goal throws Error:
 `assertion_error(Description,Error)`

`quick_check/3`

Reified version of the `quick_check/2` predicate. Reports `passed(SequenceSeed,Discarded,Labels)`, `failed(Goal,SequenceSeed,TestSeed)`, `error(Error,Goal,SequenceSeed,TestSeed)`, or `broken(Why,Culprit)`. Goal is the failed test.

Compilation flags:
 `static`

Template:
 `quick_check(Template,Result,Options)`

Meta-predicate template:
 `quick_check(:,*,::)`

Mode and number of proofs:
 `quick_check(@callable,-callable,++list(compound)) - one`

Remarks:

- `SequenceSeed` argument: Can be used to re-run the same exact sequence of pseudo-random tests by using the `rs/1` option after changes to the code being tested.
 - `TestSeed` argument: Can be used to re-run the test that failed by using the `rs/1` option after changes to the code being tested.
 - `Discarded` argument: Number of generated tests that were discarded for failing to comply a pre-condition specified using the `pc/1` option.
 - `Labels` argument: List of pairs `Label-N` where `N` is the number of generated tests that are classified as `Label` by a closure specified using the `l/1` option.
 - `broken(Why,Culprit)` result: This result signals a broken setup. For example, an invalid template, a broken pre-condition or label goal, or broken test generation.
-

`quick_check/2`

Generates and runs random tests for a predicate given its mode template and a set of options. Fails when a generated test fails printing the test. Also fails on an invalid option, printing the option.

Compilation flags:

`static`

Template:

`quick_check(Template,Options)`

Meta-predicate template:

`quick_check(:,::,::)`

Mode and number of proofs:

`quick_check(@callable,++list(compound)) - zero_or_one`

Remarks:

- Number of tests: Use the `n(NumberOfTests)` option to specify the number of random tests. Default is 100.
 - Maximum number of shrink operations: Use the `s(MaxShrinks)` option to specify the number of shrink operations when a counter example is found. Default is 64.
 - Type edge cases: Use the `ec(Boolean)` option to specify if type edge cases are tested (before generating random tests). Default is `true`.
 - Starting seed: Use the `rs(Seed)` option to specify the random generator starting seed to be used when generating tests. No default. Seeds should be regarded as opaque terms.
 - Test generation filtering: Use the `pc/1` option to specify a pre-condition closure for filtering generated tests (extended with the test arguments; no default).
 - Generated tests classification: Use the `l/1` option to specify a label closure for classifying the generated tests (extended with the test arguments plus the labels argument; no default). The labelling predicate can return a single test label or a list of test labels.
 - Verbose test generation: Use the `v(Boolean)` option to specify verbose reporting of generated random tests. Default is `false`.
 - Progress bar: Use the `pb(Boolean, Tick)` option to print a progress bar for the executed tests, advancing at every `Tick` tests. Default is `false`. Only applies when the verbose option is `false`.
-

quick_check/1

Generates and runs random tests using default options for a predicate given its mode template. Fails when a generated test fails printing the test.

Compilation flags:

static

Template:

quick_check(Template)

Mode and number of proofs:

quick_check(@callable) - zero_or_one

benchmark/2

Benchmarks a goal and returns the total execution time in seconds. Uses CPU clock. Goals that may throw an exception should be wrapped by the catch/3 control construct.

Compilation flags:

static

Template:

benchmark(Goal,Time)

Meta-predicate template:

benchmark(0,*)

Mode and number of proofs:

benchmark(+callable,-float) - one

benchmark_reified/3

Benchmarks a goal and returns the total execution time in seconds plus its result (success, failure, or error(Error)). Uses CPU clock.

Compilation flags:

static

Template:

```
benchmark_reified(Goal,Time,Result)
```

Meta-predicate template:

```
benchmark_reified(0,*,*)
```

Mode and number of proofs:

```
benchmark_reified(+callable,-float,-callable) - one
```

benchmark/3

Benchmarks a goal by repeating it the specified number of times and returning the total execution time in seconds. Uses CPU clock. Goals that may throw an exception should be wrapped by the catch/3 control construct.

Compilation flags:

```
static
```

Template:

```
benchmark(Goal,Repetitions,Time)
```

Meta-predicate template:

```
benchmark(0,*,*)
```

Mode and number of proofs:

```
benchmark(@callable,+positive_integer,-float) - one
```

benchmark/4

Benchmarks a goal by repeating it the specified number of times and returning the total execution time in seconds using the given clock (cpu or wall). Goals that may throw an exception should be wrapped by the catch/3 control construct.

Compilation flags:

```
static
```

Template:

```
benchmark(Goal,Repetitions,Clock,Time)
```

Meta-predicate template:

```
benchmark(0,*,*,*)
```

Mode and number of proofs:

```
benchmark(@callable,+positive_integer,+atom,-float) - one
```

variant/2

True when the two arguments are a variant of each other. I.e. if is possible to rename the term variables to make them identical. Useful for checking expected test results that contain variables.

Compilation flags:

static

Template:

variant(Term1,Term2)

Mode and number of proofs:

variant(@term,@term) - zero_or_one

approximately_equal/2

Compares two numbers for approximate equality given the epsilon arithmetic constant value using the de facto standard formula $\text{abs}(\text{Number1} - \text{Number2}) = < \max(\text{abs}(\text{Number1}), \text{abs}(\text{Number2})) * \text{epsilon}$. Type-checked.

Compilation flags:

static

Template:

approximately_equal(Number1,Number2)

Mode and number of proofs:

approximately_equal(+number,+number) - zero_or_one

approximately_equal/3

Compares two numbers for approximate equality given a user-defined epsilon value using the de facto standard formula $\text{abs}(\text{Number1} - \text{Number2}) = < \max(\text{abs}(\text{Number1}), \text{abs}(\text{Number2})) * \text{Epsilon}$. Type-checked.

Compilation flags:

static

Template:

approximately_equal(Number1,Number2,Epsilon)

Mode and number of proofs:

approximately_equal(+number,+number,+number) - zero_or_one

Remarks:

- Epsilon range: Epsilon should be the epsilon arithmetic constant value or a small multiple of it. Only use a larger value if a greater error is expected.
- Comparison with essential equality: For the same epsilon value, approximate equality is weaker requirement than essential equality.

essentially_equal/3

Compares two numbers for essential equality given an epsilon value using the de facto standard formula $\text{abs}(\text{Number1} - \text{Number2}) \leq \min(\text{abs}(\text{Number1}), \text{abs}(\text{Number2})) * \text{Epsilon}$. Type-checked.

Compilation flags:

static

Template:

essentially_equal(Number1,Number2,Epsilon)

Mode and number of proofs:

essentially_equal(+number,+number,+number) - zero_or_one

Remarks:

- Comparison with approximate equality: For the same epsilon value, essential equality is a stronger requirement than approximate equality.

tolerance_equal/4

Compares two numbers for close equality given relative and absolute tolerances using the de facto standard formula $\text{abs}(\text{Number1} - \text{Number2}) \leq \max(\text{RelativeTolerance} * \max(\text{abs}(\text{Number1}), \text{abs}(\text{Number2})), \text{AbsoluteTolerance})$. Type-checked.

Compilation flags:

static

Template:

tolerance_equal(Number1,Number2,RelativeTolerance,AbsoluteTolerance)

Mode and number of proofs:

tolerance_equal(+number,+number,+number,+number) - zero_or_one

`=~= / 2`

Compares two numbers (or lists of numbers) for approximate equality using $100 \times \text{epsilon}$ for the absolute error and, if that fails, 99.999% accuracy for the relative error. But these precision values may not be adequate for all cases. Type-checked.

Compilation flags:

static

Template:

`=~=(Number1,Number2)`

Mode and number of proofs:

`=~=(+number,+number) - zero_or_one`

`=~=(+list(number),+list(number)) - zero_or_one`

`epsilon/1`

Returns the value of epsilon used in the definition of the `(=~=)/2` predicate.

Compilation flags:

static

Template:

`epsilon(Epsilon)`

Mode and number of proofs:

`epsilon(-float) - one`

Protected predicates

run_tests/0

Runs all defined unit tests.

Compilation flags:

static

Mode and number of proofs:

run_tests - one

run_tests/1

Runs all the tests defined in the given file.

Compilation flags:

static

Template:

run_tests(File)

Mode and number of proofs:

run_tests(+atom) - one

run_test_set/0

Runs a test set as part of running two or more test sets as a unified set.

Compilation flags:

static

Mode and number of proofs:

run_test_set - one

`run_quick_check_tests/5`

Runs a list of defined tests using the given options. Returns the starting seed used to generate the random tests, the number of discarded tests, and the test label statistics.

Compilation flags:

`static`

Template:

`run_quick_check_tests(Template,Options,Seed,Discarded,Labels)`

Meta-predicate template:

`run_quick_check_tests(:,::,*,*,*)`

Mode and number of proofs:

`run_quick_check_tests(@callable,+list,--nonvar,--number,--list(pair)) - one_or_error`

`condition/0`

Verifies conditions for running the tests. Defaults to the goal true.

Compilation flags:

`static`

Mode and number of proofs:

`condition - zero_or_one`

`setup/0`

Setup environment before running the test set. Defaults to the goal true.

Compilation flags:

`static`

Mode and number of proofs:

`setup - zero_or_one`

cleanup/0

Cleanup environment after running the test set. Defaults to the goal true.

Compilation flags:

static

Mode and number of proofs:

cleanup - zero_or_one

make/1

Make target for automatically running the test set when calling the logtalk_make/1 built-in predicate. No default. Possible values are all and check.

Compilation flags:

static

Template:

make(Target)

Mode and number of proofs:

make(?atom) - zero_or_one

note/1

Note to be printed after the test results. Defaults to the empty atom.

Compilation flags:

static

Template:

note(Note)

Mode and number of proofs:

note(?atom) - zero_or_one

`file_path/2`

Returns the absolute path for a file path that is relative to the tests object path. When the file path is already an absolute path, it is expanded to resolve any remaining relative file path parts.

Compilation flags:

`static`

Template:

`file_path(File,Path)`

Mode and number of proofs:

`file_path(+atom,-atom) - one`

See also:

`clean_file/1`

`clean_directory/1`

`suppress_text_output/0`

Suppresses text output. Useful to avoid irrelevant text output from predicates being tested to clutter the test logs.

Compilation flags:

`static`

Mode and number of proofs:

`suppress_text_output - one`

`suppress_binary_output/0`

Suppresses binary output. Useful to avoid irrelevant binary output from predicates being tested to clutter the test logs.

Compilation flags:

`static`

Mode and number of proofs:

`suppress_binary_output` - one

`set_text_input/3`

Creates a temporary file, in the same directory as the tests object, with the given text contents, and opens it for reading referenced by the given alias and using the additional options. If no `eof_action/1` option is specified, its value will be the default used by the backend compiler.

Compilation flags:

`static`

Template:

`set_text_input(Alias,Contents,Options)`

Mode and number of proofs:

`set_text_input(+atom,+atom,+list(stream_option))` - one

`set_text_input(+atom,+list(atom),+list(stream_option))` - one

See also:

`text_input_assertion/3`

`check_text_input/2`

`clean_text_input/0`

`set_text_input/2`

Creates a temporary file, in the same directory as the tests object, with the given text contents, and opens it for reading referenced by the given alias and using the default end-of-file action for the used backend compiler.

Compilation flags:

`static`

Template:

`set_text_input(Alias,Contents)`

Mode and number of proofs:

`set_text_input(+atom,+atom)` - one

`set_text_input(+atom,+list(atom))` - one

See also:

text_input_assertion/3
check_text_input/2
clean_text_input/0

set_text_input/1

Creates a temporary file, in the same directory as the tests object, with the given text contents, opens it for reading using the default end-of-file action for the used backend compiler, and sets the current input stream to the file.

Compilation flags:

static

Template:

set_text_input(Contents)

Mode and number of proofs:

set_text_input(+atom) - one

set_text_input(+list(atom)) - one

See also:

text_input_assertion/2
check_text_input/1
clean_text_input/0

check_text_input/2

Checks that the temporary file (referenced by the given alias) being read have the expected text contents.

Compilation flags:

static

Template:

check_text_input(Alias,Contents)

Mode and number of proofs:

check_text_input(+atom,+atom) - zero_or_one

See also:


```
set_text_input/2
set_text_input/2
text_input_assertion/3
clean_text_input/0
```

check_text_input/1

Checks that the temporary file being read have the expected text contents.

Compilation flags:

```
static
```

Template:

```
check_text_input(Contents)
```

Mode and number of proofs:

```
check_text_input(+atom) - zero_or_one
```

See also:

```
set_text_input/1
text_input_assertion/2
clean_text_input/0
```

text_input_assertion/3

Returns an assertion for checking that the temporary file (referenced by the given alias) being read have the expected text contents.

Compilation flags:

```
static
```

Template:

```
text_input_assertion(Alias,Contents,Assertion)
```

Mode and number of proofs:

```
text_input_assertion(+atom,+atom,--callable) - one
```

See also:

```
set_text_input/3
```

`check_text_input/2`
`clean_text_input/0`

`text_input_assertion/2`

Returns an assertion for checking that the temporary file being read have the expected text contents.

Compilation flags:

`static`

Template:

`text_input_assertion(Contents,Assertion)`

Mode and number of proofs:

`text_input_assertion(+atom,--callable) - one`

See also:

`set_text_input/1`
`check_text_input/1`
`clean_text_input/0`

`clean_text_input/0`

Cleans the temporary file used when testing text input.

Compilation flags:

`static`

Mode and number of proofs:

`clean_text_input - one`

See also:

`set_text_input/3`
`set_text_input/2`
`set_text_input/1`

`set_binary_input/3`

Creates a temporary file, in the same directory as the tests object, with the given binary contents, and opens it for reading referenced by the given alias and using the additional options. If no `eof_action/1` option is specified, its value will be the default used by the backend compiler.

Compilation flags:

`static`

Template:

`set_binary_input(Alias,Bytes,Options)`

Mode and number of proofs:

`set_binary_input(+atom,+list(byte),+list(stream_option)) - one`

See also:

`binary_input_assertion/3`

`check_binary_input/2`

`clean_binary_input/0`

`set_binary_input/2`

Creates a temporary file, in the same directory as the tests object, with the given binary contents, and opens it for reading referenced by the given alias and using the default end-of-file action for the used backend compiler.

Compilation flags:

`static`

Template:

`set_binary_input(Alias,Bytes)`

Mode and number of proofs:

`set_binary_input(+atom,+list(byte)) - one`

See also:

`binary_input_assertion/3`

`check_binary_input/2`

`clean_binary_input/0`

`set_binary_input/1`

Creates a temporary file, in the same directory as the tests object, with the given binary contents, and opens it for reading using the default end-of-file action for the used backend compiler, and sets the current input stream to the file.

Compilation flags:

`static`

Template:

`set_binary_input(Bytes)`

Mode and number of proofs:

`set_binary_input(+list(byte)) - one`

See also:

`binary_input_assertion/2`

`check_binary_input/1`

`clean_binary_input/0`

`check_binary_input/2`

Checks that the temporary file (referenced by the given alias) being read have the expected binary contents.

Compilation flags:

`static`

Template:

`check_binary_input(Alias,Bytes)`

Mode and number of proofs:

`check_binary_input(+atom,+list(byte)) - zero_or_one`

See also:

`set_binary_input/3`

`set_binary_input/2`

`binary_input_assertion/3`

`clean_binary_input/0`

[check_binary_input/1](#)

Checks that the temporary file being read have the expected binary contents.

Compilation flags:

static

Template:

`check_binary_input(Bytes)`

Mode and number of proofs:

`check_binary_input(+list(byte)) - zero_or_one`

See also:

[binary_input_assertion/2](#)

[set_binary_input/1](#)

[clean_binary_input/0](#)

[binary_input_assertion/3](#)

Returns an assertion for checking that the temporary file (referenced by the given alias) being read have the expected binary contents.

Compilation flags:

static

Template:

`binary_input_assertion(Alias,Bytes,Assertion)`

Mode and number of proofs:

`binary_input_assertion(+atom,+list(byte),--callable) - one`

See also:

[check_binary_input/2](#)

[set_binary_input/3](#)

[set_binary_input/2](#)

[clean_binary_input/0](#)

`binary_input_assertion/2`

Returns an assertion for checking that the temporary file being read have the expected binary contents.

Compilation flags:

`static`

Template:

`binary_input_assertion(Bytes,Assertion)`

Mode and number of proofs:

`binary_input_assertion(+list(byte),--callable) - one`

See also:

`check_binary_input/1`

`set_binary_input/1`

`clean_binary_input/0`

`clean_binary_input/0`

Cleans the temporary file used when testing binary input.

Compilation flags:

`static`

Mode and number of proofs:

`clean_binary_input - one`

See also:

`set_binary_input/3`

`set_binary_input/2`

`set_binary_input/1`

`set_text_output/3`

Creates a temporary file, in the same directory as the tests object, with the given text contents, and opens it for writing referenced by the given alias and using the additional options.

Compilation flags:

`static`

Template:

`set_text_output(Alias,Contents,Options)`

Mode and number of proofs:

`set_text_output(+atom,+atom,+list(stream_option)) - one`

`set_text_output(+atom,+list(atom),+list(stream_option)) - one`

See also:

`text_output_assertion/4`

`check_text_output/3`

`clean_text_output/0`

`set_text_output/2`

Creates a temporary file, in the same directory as the tests object, with the given text contents, and referenced by the given alias.

Compilation flags:

`static`

Template:

`set_text_output(Alias,Contents)`

Mode and number of proofs:

`set_text_output(+atom,+atom) - one`

`set_text_output(+atom,+list(atom)) - one`

See also:

`text_output_assertion/3`

`check_text_output/2`

`clean_text_output/0`

`set_text_output/1`

Creates a temporary file, in the same directory as the tests object, with the given text contents, and sets the current output stream to the file.

Compilation flags:

`static`

Template:

`set_text_output(Contents)`

Mode and number of proofs:

`set_text_output(+atom) - one`

`set_text_output(+list(atom)) - one`

See also:

`text_output_assertion/2`

`check_text_output/1`

`clean_text_output/0`

`check_text_output/3`

Checks that the temporary file (open with the given options and alias in the same directory as the tests object) being written have the expected text contents.

Compilation flags:

`static`

Template:

`check_text_output(Alias,Contents,Options)`

Mode and number of proofs:

`check_text_output(+atom,+atom,+list(stream_option)) - zero_or_one`

See also:

`set_text_output/3`

`text_output_assertion/4`

`clean_text_output/0`

`check_text_output/2`

Checks that the temporary file (open with default options and alias in the same directory as the tests object) being written have the expected text contents.

Compilation flags:

`static`

Template:

`check_text_output(Alias,Contents)`

Mode and number of proofs:

`check_text_output(+atom,+atom) - zero_or_one`

See also:

`set_text_output/2`

`text_output_assertion/3`

`clean_text_output/0`

`check_text_output/1`

Checks that the temporary file being written have the expected text contents.

Compilation flags:

`static`

Template:

`check_text_output(Contents)`

Mode and number of proofs:

`check_text_output(+atom) - zero_or_one`

See also:

`set_text_output/1`

`text_output_assertion/2`

`clean_text_output/0`

`text_output_assertion/4`

Returns an assertion for checking that the temporary file (open with the given options and alias in the same directory as the tests object) being written have the expected text contents.

Compilation flags:

`static`

Template:

`text_output_assertion(Alias,Contents,Options,Assertion)`

Mode and number of proofs:

`text_output_assertion(+atom,+atom,+list(stream_option),--callable) - one`

See also:

`set_text_output/3`

`check_text_output/3`

`clean_text_output/0`

`text_output_assertion/3`

Returns an assertion for checking that the temporary file (open with default options and alias in the same directory as the tests object) being written have the expected text contents.

Compilation flags:

`static`

Template:

`text_output_assertion(Alias,Contents,Assertion)`

Mode and number of proofs:

`text_output_assertion(+atom,+atom,--callable) - one`

See also:

`set_text_output/2`

`check_text_output/2`

`clean_text_output/0`

`text_output_assertion/2`

Returns an assertion for checking that the temporary file (open with default options in the same directory as the tests object) being written have the expected text contents.

Compilation flags:

`static`

Template:

`text_output_assertion(Contents,Assertion)`

Mode and number of proofs:

`text_output_assertion(+atom,--callable) - one`

See also:

`set_text_output/1`

`check_text_output/1`

`clean_text_output/0`

`text_output_contents/3`

Returns the contents of the temporary file (open with the given options and alias in the same directory as the tests object) being written.

Compilation flags:

`static`

Template:

`text_output_contents(Alias,Contents,Options)`

Mode and number of proofs:

`text_output_contents(+atom,-list(character),+list(stream_option)) - one`

`text_output_contents/2`

Returns the contents of the temporary file (open with default options and alias in the same directory as the tests object) being written.

Compilation flags:

`static`

Template:

`text_output_contents(Alias,Contents)`

Mode and number of proofs:

`text_output_contents(+atom,-list(character)) - one`

`text_output_contents/1`

Returns the contents of the temporary file (open with default options in the same directory as the tests object) being written.

Compilation flags:

`static`

Template:

`text_output_contents(Contents)`

Mode and number of proofs:

`text_output_contents(-list(character)) - one`

`clean_text_output/0`

Cleans the temporary file used when testing text output.

Compilation flags:

`static`

Mode and number of proofs:

`clean_text_output - one`

See also:

```
set_text_output/3  
set_text_output/2  
set_text_output/1
```

set_binary_output/3

Creates a temporary file, in the same directory as the tests object, with the given binary contents, and opens it for writing referenced by the given alias and using the additional options.

Compilation flags:

```
static
```

Template:

```
set_binary_output(Alias,Contents,Options)
```

Mode and number of proofs:

```
set_binary_output(+atom,+list(byte),+list(stream_option)) - one
```

See also:

```
binary_output_assertion/3  
check_binary_output/2  
clean_binary_output/0
```

set_binary_output/2

Creates a temporary file, in the same directory as the tests object, with the given binary contents, and opens it for writing referenced with the given alias.

Compilation flags:

```
static
```

Template:

```
set_binary_output(Alias,Bytes)
```

Mode and number of proofs:

```
set_binary_output(+atom,+list(byte)) - one
```

See also:

```
binary_output_assertion/3
```

`check_binary_output/2`
`clean_binary_output/0`

`set_binary_output/1`

Creates a temporary file, in the same directory as the tests object, with the given binary contents, and sets the current output stream to the file.

Compilation flags:

`static`

Template:

`set_binary_output(Bytes)`

Mode and number of proofs:

`set_binary_output(+list(byte)) - one`

See also:

`binary_output_assertion/2`

`check_binary_output/1`

`clean_binary_output/0`

`check_binary_output/2`

Checks that the temporary file (referenced by the given alias) have the expected binary contents.

Compilation flags:

`static`

Template:

`check_binary_output(Alias,Bytes)`

Mode and number of proofs:

`check_binary_output(+atom,+list(byte)) - zero_or_one`

See also:

`set_binary_output/3`

`set_binary_output/2`

`binary_output_assertion/3`

`clean_binary_output/0`

`check_binary_output/1`

Checks that the temporary file (open in the same directory as the tests object) have the expected binary contents.

Compilation flags:

`static`

Template:

`check_binary_output(Bytes)`

Mode and number of proofs:

`check_binary_output(+list(byte)) - zero_or_one`

See also:

`set_binary_output/1`

`binary_output_assertion/2`

`clean_binary_output/0`

`binary_output_assertion/3`

Returns an assertion for checking that the temporary file (referenced by the given alias) have the expected binary contents.

Compilation flags:

`static`

Template:

`binary_output_assertion(Alias,Bytes,Assertion)`

Mode and number of proofs:

`binary_output_assertion(+atom,+list(byte),--callable) - one`

See also:

`set_binary_output/2`

`check_binary_output/2`

`clean_binary_output/0`

`binary_output_assertion/2`

Returns an assertion for checking that the temporary file (open in the same directory as the tests object) have the expected binary contents.

Compilation flags:

`static`

Template:

`binary_output_assertion(Bytes,Assertion)`

Mode and number of proofs:

`binary_output_assertion(+list(byte),--callable) - one`

See also:

`set_binary_output/1`

`check_binary_output/1`

`clean_binary_output/0`

`binary_output_contents/2`

Returns the binary contents of the temporary file (referenced by the given alias) being written.

Compilation flags:

`static`

Template:

`binary_output_contents(Alias,Bytes)`

Mode and number of proofs:

`binary_output_contents(+atom,-list(byte)) - one`

binary_output_contents/1

Returns the binary contents of the temporary file being written.

Compilation flags:

static

Template:

binary_output_contents(Bytes)

Mode and number of proofs:

binary_output_contents(-list(byte)) - one

clean_binary_output/0

Cleans the temporary file used when testing binary output.

Compilation flags:

static

Mode and number of proofs:

clean_binary_output - one

See also:

set_binary_output/3

set_binary_output/2

set_binary_output/1

create_text_file/3

Creates a text file with the given contents. The file is open for writing using the given options. Relative file paths are interpreted as relative to the tests object path.

Compilation flags:

static

Template:

`create_text_file(File,Contents,Options)`

Mode and number of proofs:

`create_text_file(+atom,+atom,+list(stream_option))` - one

`create_text_file(+atom,+list(atom),+list(stream_option))` - one

`create_text_file/2`

Creates a text file with the given contents. The file is open for writing using default options. Relative file paths are interpreted as relative to the tests object path.

Compilation flags:

static

Template:

`create_text_file(File,Contents)`

Mode and number of proofs:

`create_text_file(+atom,+atom)` - one

`create_text_file(+atom,+list(atom))` - one

`create_binary_file/2`

Creates a binary file with the given contents. Relative file paths are interpreted as relative to the tests object path.

Compilation flags:

static

Template:

`create_binary_file(File,Bytes)`

Mode and number of proofs:

`create_binary_file(+atom,+list(byte))` - one

[check_text_file/3](#)

Checks that the contents of a text file match the expected contents. The file is open for reading using the given options. Relative file paths are interpreted as relative to the tests object path.

Compilation flags:

static

Template:

`check_text_file(File,Contents,Options)`

Mode and number of proofs:

`check_text_file(+atom,+atom,+list(stream_option)) - zero_or_one`

See also:

[text_file_assertion/4](#)

[check_text_file/2](#)

Checks that the contents of a text file (open for reading using default options) match the expected contents. Relative file paths are interpreted as relative to the tests object path.

Compilation flags:

static

Template:

`check_text_file(File,Contents)`

Mode and number of proofs:

`check_text_file(+atom,+atom) - zero_or_one`

See also:

[text_file_assertion/3](#)

[text_file_assertion/4](#)

Returns an assertion for checking that the given file have the expected text contents. The file is open for reading using the given options. Relative file paths are interpreted as relative to the tests object path.

Compilation flags:

static

Template:

`text_file_assertion(File,Contents,Options,Assertion)`

Mode and number of proofs:

`text_file_assertion(+atom,+atom,+list(stream_option),--callable) - one`

See also:

[check_text_file/3](#)

[text_file_assertion/3](#)

Returns an assertion for checking that the given file have the expected text contents. The file is open for reading using default options. Relative file paths are interpreted as relative to the tests object path.

Compilation flags:

static

Template:

`text_file_assertion(File,Contents,Assertion)`

Mode and number of proofs:

`text_file_assertion(+atom,+atom,--callable) - one`

See also:

[check_text_file/2](#)

[check_binary_file/2](#)

Checks the contents of a binary file match the expected contents. Relative file paths are interpreted as relative to the tests object path.

Compilation flags:

static

Template:

`check_binary_file(File,Bytes)`

Mode and number of proofs:

`check_binary_file(+atom,+list(byte)) - zero_or_one`

See also:

[binary_file_assertion/3](#)

[binary_file_assertion/3](#)

Returns an assertion for checking that the given file have the expected binary contents. Relative file paths are interpreted as relative to the tests object path.

Compilation flags:

static

Template:

`binary_file_assertion(File,Bytes,Assertion)`

Mode and number of proofs:

`binary_file_assertion(+atom,+list(byte),--callable) - one`

See also:

[check_binary_file/2](#)

[clean_file/1](#)

Closes any existing stream associated with the file and deletes the file if it exists. Relative file paths are interpreted as relative to the tests object path.

Compilation flags:

static

Template:

`clean_file(File)`

Mode and number of proofs:

`clean_file(+atom) - one`

See also:

[clean_directory/1](#)

[file_path/2](#)

[clean_directory/1](#)

Deletes an empty directory if it exists. Relative directory paths are interpreted as relative to the tests object path.

Compilation flags:

static

Template:

`clean_directory(Directory)`

Mode and number of proofs:

`clean_directory(+atom) - one`

See also:

[clean_file/1](#)

[file_path/2](#)

closed_input_stream/2

Opens a temporary file in the same directory as the tests object with the given options for reading, closes it, and returns its stream handle.

Compilation flags:

static

Template:

closed_input_stream(Stream,Options)

Mode and number of proofs:

closed_input_stream(-stream,+list(stream_option)) - one

closed_output_stream/2

Opens a temporary file in the same directory as the tests object with the given options for writing, closes it, and returns its stream handle.

Compilation flags:

static

Template:

closed_output_stream(Stream,Options)

Mode and number of proofs:

closed_output_stream(-stream,+list(stream_option)) - zero_or_one

stream_position/1

Returns a syntactically valid stream position by opening a temporary file in the same directory as the tests object.

Compilation flags:

static

Template:

stream_position(Position)

Mode and number of proofs:

`stream_position(-stream_position) - one`

test/2

Table of defined tests.

Compilation flags:

`static`

Template:

`test(Identifier,Test)`

Mode and number of proofs:

`test(?callable,?compound) - zero_or_more`

Private predicates

`running_test_sets_/0`

Internal flag used when running two or more test sets as a unified set.

Compilation flags:

`dynamic`

Mode and number of proofs:

`running_test_sets_ - zero_or_one`

test/3

Compiled unit tests. The list of variables is used to ensure variable sharing between a test with its test options.

Compilation flags:

`static`

Template:

test(Identifier,Variables,Outcome)

Meta-predicate template:

test(*,*,*)

Mode and number of proofs:

test(?callable,?list(variable),?nonvar) - zero_or_more

auxiliary_predicate_counter_/1

Counter for generating unique auxiliary predicate names.

Compilation flags:

dynamic

Template:

auxiliary_predicate_counter_(Counter)

Mode and number of proofs:

auxiliary_predicate_counter_(?integer) - one_or_more

test_/2

Table of compiled tests.

Compilation flags:

dynamic

Template:

test_(Identifier,Test)

Mode and number of proofs:

test_(?callable,?compound) - zero_or_more

skipped_/1

Counter for skipped tests.

Compilation flags:

dynamic

Template:

skipped_(Counter)

Mode and number of proofs:

skipped_(?integer) - zero_or_one

passed_/3

Counter and total time for passed tests.

Compilation flags:

dynamic

Template:

passed_(Counter,CPUTime,WallTime)

Mode and number of proofs:

passed_(?integer,-float,-float) - zero_or_one

failed_/3

Counter and total time for failed tests.

Compilation flags:

dynamic

Template:

failed_(Counter,CPUTime,WallTime)

Mode and number of proofs:

failed_(?integer,-float,-float) - zero_or_one

flaky_/1

Counter for failed tests that are marked as flaky.

Compilation flags:

dynamic

Template:

flaky_(Counter)

Mode and number of proofs:

flaky_(?integer) - zero_or_one

fired_/3

Fired clauses when running the unit tests.

Compilation flags:

dynamic

Template:

fired_(Entity,Predicate,Clause)

Mode and number of proofs:

fired_(?entity_identifier,?predicate_indicator,?integer) - zero_or_more

covered_/4

Auxiliary predicate for collecting statistics on clause coverage.

Compilation flags:

dynamic

Template:

covered_(Entity,Predicate,Covered,Total)

Mode and number of proofs:

covered_(?entity_identifier,?callable,?integer,?integer) - zero_or_more

Operators

op(700,xfx,=~=)

Scope:

public

category

1.43.4 lgtunit_messages

Logtalk unit test framework default message translations.

Availability:

logtalk_load(lgtunit(loader))

Author: Paulo Moura

Version: 9:0:0

Date: 2024-02-20

Compilation flags:

static

Provides:

logtalk::message_prefix_stream/4

logtalk::message_tokens//2

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

object

1.43.5 minimal_output

Intercepts unit test execution messages and outputs a minimal report.

Availability:

```
logtalk_load(lgtunit(loader))
```

Author: Paulo Moura

Version: 3:0:0

Date: 2021-05-27

Compilation flags:

```
static, context_switching_calls
```

Provides:

```
logtalk::message_hook/4
```

Remarks:

- Usage: Simply load this object before running your tests using the goal `logtalk_load(lgtunit(minimal_output))`.
- Limitations: Cannot be used when the test objects also intercept lgtunit messages.

Inherited public predicates:

(none)

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

object

1.43.6 tap_output

Intercepts unit test execution messages and outputs a report using the TAP format to the current output stream.

Availability:

`logtalk_load(lgtunit(loader))`

Author: Paulo Moura

Version: 4:0:1

Date: 2024-04-01

Compilation flags:

`static, context_switching_calls`

Provides:

`logtalk::message_hook/4`

Remarks:

- Usage: Simply load this object before running your tests using the goal `logtalk_load(lgtunit(tap_output))`.

Inherited public predicates:

(none)

- Public predicates
- Protected predicates
- Private predicates
 - `generating_/0`
 - `partial_/1`
 - `test_count_/1`
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

`generating_/0`

Flag to detect report in progress when processing two or more test sets as a unified set.

Compilation flags:

`dynamic`

Mode and number of proofs:

`generating_ - zero_or_one`

partial_/1

Cache of total of tests per test set.

Compilation flags:

dynamic

Template:

partial_(Count)

Mode and number of proofs:

partial_(?integer) - zero_or_more

test_count_/1

Test counter.

Compilation flags:

dynamic

Template:

test_count_(Count)

Mode and number of proofs:

test_count_(?integer) - zero_or_one

Operators

(none)

object

1.43.7 tap_report

Intercepts unit test execution messages and generates a tap_report.txt file using the TAP output format in the same directory as the tests object file.

Availability:

logtalk_load(lgtunit(loader))

Author: Paulo Moura

Version: 5:0:1

Date: 2024-04-01

Compilation flags:

static, context_switching_calls

Provides:

logtalk::message_hook/4

Uses:

logtalk

Remarks:

- Usage: Simply load this object before running your tests using the goal `logtalk_load(lgtunit(tap_report))`.

Inherited public predicates:

(none)

- Public predicates
- Protected predicates
- Private predicates
 - partial_/1
 - test_count_/1
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

partial_/1

Cache of total of tests per test set.

Compilation flags:

dynamic

Template:

partial_(Count)

Mode and number of proofs:

partial_(?integer) - zero_or_more

test_count_/1

Test counter.

Compilation flags:

dynamic

Template:

test_count_(Count)

Mode and number of proofs:

test_count_(?integer) - zero_or_one

Operators

(none)

object

1.43.8 xunit_net_v2_output

Intercepts unit test execution messages and outputs a report using the xUnit.net v2 XML format to the current output stream.

Availability:

```
logtalk_load(lgtunit(loader))
```

Author: Paulo Moura

Version: 4:0:1

Date: 2024-04-01

Compilation flags:

```
static, context_switching_calls
```

Provides:

```
logtalk::message_hook/4
```

Uses:

```
user
```

Remarks:

- Usage: Simply load this object before running your tests using the goal `logtalk_load(lgtunit(xunit_net_v2_output))`.

Inherited public predicates:

(none)

- Public predicates
- Protected predicates
- Private predicates
 - message_cache_/1
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

message_cache_/1

Table of messages emitted by the lgtunit tool when running tests.

Compilation flags:

dynamic

Template:

message_cache_(Message)

Mode and number of proofs:

message_cache_(?callable) - zero_or_more

Operators

(none)

object

1.43.9 xunit_net_v2_report

Intercepts unit test execution messages and generates a xunit_report.xml file using the xUnit.net v2 XML format in the same directory as the tests object file.

Availability:

logtalk_load(lgtunit(loader))

Author: Paulo Moura

Version: 5:0:1

Date: 2024-04-01

Compilation flags:

static, context_switching_calls

Provides:

logtalk::message_hook/4

Uses:

logtalk

user

Remarks:

- Usage: Simply load this object before running your tests using the goal `logtalk_load(lgtunit(xunit_net_v2_report))`.

Inherited public predicates:

(none)

- Public predicates
- Protected predicates
- Private predicates
 - message_cache_/1
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

message_cache_/1

Table of messages emitted by the lgtunit tool when running tests.

Compilation flags:

dynamic

Template:

message_cache_(Message)

Mode and number of proofs:

message_cache_(?callable) - zero_or_more

Operators

(none)

object

1.43.10 xunit_output

Intercepts unit test execution messages and outputs a report using the xUnit XML format to the current output stream.

Availability:

logtalk_load(lgtunit(loader))

Author: Paulo Moura

Version: 4:0:1

Date: 2024-04-01

Compilation flags:

static, context_switching_calls

Provides:

logtalk::message_hook/4

Uses:

logtalk

user

Remarks:

- Usage: Simply load this object before running your tests using the goal `logtalk_load(lgtunit(xunit_output))`.

Inherited public predicates:

(none)

- Public predicates
- Protected predicates
- Private predicates
 - message_cache_/1
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

message_cache_/1

Table of messages emitted by the lgtunit tool when running tests.

Compilation flags:

dynamic

Template:

message_cache_(Message)

Mode and number of proofs:

message_cache_(?callable) - zero_or_more

Operators

(none)

object

1.43.11 xunit_report

Intercepts unit test execution messages and generates a xunit_report.xml file using the xUnit XML format in the same directory as the tests object file.

Availability:

```
logtalk_load(lgtunit(loader))
```

Author: Paulo Moura

Version: 5:0:1

Date: 2024-04-01

Compilation flags:

```
static, context_switching_calls
```

Provides:

```
logtalk::message_hook/4
```

Uses:

```
logtalk
```

```
user
```

Remarks:

- Usage: Simply load this object before running your tests using the goal `logtalk_load(lgtunit(xunit_report))`.

Inherited public predicates:

(none)

- Public predicates
- Protected predicates
- Private predicates
 - message_cache_/1
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

message_cache_/1

Table of messages emitted by the lgtunit tool when running tests.

Compilation flags:

dynamic

Template:

message_cache_(Message)

Mode and number of proofs:

message_cache_(?callable) - zero_or_more

Operators

(none)

1.44 library

protocol

1.44.1 cloning

Object cloning protocol.

Availability:

logtalk_load(library(loader))

Author: Paulo Moura

Version: 1:0:0

Date: 2010-09-14

Compilation flags:

static

Dependencies:

(none)

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
 - clone/1
- Protected predicates
- Private predicates
- Operators

Public predicates

clone/1

Clones an object, returning the identifier of the new object if none is given.

Compilation flags:

static

Template:

clone(Clone)

Mode and number of proofs:

clone(?object) - zero_or_one

Protected predicates

(none)

Private predicates

(none)

Operators

(none)

category

1.44.2 counters

Named integer counters. Counter names can be any nonvar term.

Availability:

logtalk_load(library(loader))

Author: Paulo Moura

Version: 1:0:1

Date: 2022-02-11

Compilation flags:

static

Dependencies:

(none)

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
 - counter/2
 - increment_counter/1
 - decrement_counter/1

- reset_counter/1
- reset_counters/0
- Protected predicates
- Private predicates
 - counter_/2
- Operators

Public predicates

counter/2

True if Counter is a counter with value Value.

Compilation flags:

static

Template:

counter(Counter, Value)

Mode and number of proofs:

counter(?nonvar,?integer) - zero_or_more

increment_counter/1

Increments the named counter.

Compilation flags:

static

Template:

increment_counter(Counter)

Mode and number of proofs:

increment_counter(+nonvar) - one

decrement_counter/1

Decrements the named counter.

Compilation flags:

static

Template:

decrement_counter(Counter)

Mode and number of proofs:

decrement_counter(+nonvar) - one

reset_counter/1

Resets the named counter to zero. Creates the counter if it does not exist.

Compilation flags:

static

Template:

reset_counter(Counter)

Mode and number of proofs:

reset_counter(+nonvar) - one

reset_counters/0

Resets all existing named counters to zero.

Compilation flags:

static

Mode and number of proofs:

reset_counters - one

Protected predicates

(none)

Private predicates

counter_/2

Table of named counters.

Compilation flags:

dynamic

Template:

counter_(Counter, Value)

Mode and number of proofs:

counter_(?nonvar,?integer) - zero_or_more

Operators

(none)

object

1.44.3 streamvars

Stream variables (supporting logical, backtracable, adding and retrieving of terms).

Availability:

logtalk_load(library(loader))

Author: Nobukuni Kino and Paulo Moura

Version: 1:3:0

Date: 2019-06-15

Compilation flags:

static, context_switching_calls

Dependencies:

(none)

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
 - new/1
 - new/2
 - (<=)/2
 - (=>)/2
- Protected predicates
- Private predicates
- Operators
 - op(100,xfx,<=)
 - op(100,xfx,=>)

Public predicates

new/1

Makes Variable a stream variable. Initial state will be empty.

Compilation flags:

static

Template:

new(Variable)

Mode and number of proofs:

new(--streamvar) - one

Exceptions:

Variable is not a variable:

type_error(variable,Variable)

`new/2`

Makes Variable a stream variable and sets its initial state to Value.

Compilation flags:

`static`

Template:

`new(Variable,Value)`

Mode and number of proofs:

`new(--streamvar,@nonvar) - one`

Exceptions:

Variable is not a variable:

`type_error(variable,Variable)`

`(<=)/2`

Sets the state of the stream variable Variable to Value (initializing the variable if needed).

Compilation flags:

`static`

Template:

`Variable<=Value`

Mode and number of proofs:

`(?streamvar)<=(@nonvar) - one`

`(<=>)/2`

Unifies Value with the current state of the stream variable Variable.

Compilation flags:

`static`

Template:

Variable=>Value

Mode and number of proofs:

+streamvar=> ?nonvar - zero_or_one

Protected predicates

(none)

Private predicates

(none)

Operators

op(100,xfx,<=)

Scope:

public

op(100,xfx,=>)

Scope:

public

1.45 listing

category

1.45.1 listing

Listing predicates.

Availability:

logtalk_load(listing(loader))

Author: Paulo Moura

Version: 1:0:0

Date: 2024-01-26

Compilation flags:

static

Dependencies:

(none)

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
 - listing/0
 - listing/1
 - portray_clause/1
- Protected predicates
- Private predicates
- Operators

Public predicates

listing/0

Lists all clauses of all visible dynamic predicates to the current output stream.

Compilation flags:

static

Mode and number of proofs:

listing - one

listing/1

Lists all clauses of a visible dynamic predicate or non-terminal to the current output stream. When the argument is a clause head, lists all matching clauses.

Compilation flags:

static

Template:

listing(Spec)

Mode and number of proofs:

listing(+predicate_indicator) - one_or_error

listing(+non_terminal_indicator) - one_or_error

listing(+callable) - one_or_error

Exceptions:

Spec is not ground:

instantiation_error

Spec is ground but not a valid predicate indicator:

type_error(predicate_indicator,Spec)

Spec is ground but not a valid non-terminal indicator:

type_error(non_terminal_indicator,Spec)

Spec is a predicate indicator but not a visible predicate:

existence_error(predicate,Spec)

Spec is a non-terminal indicator but not a visible non-terminal:

existence_error(non_terminal,Spec)

Spec is a callable term with a Functor/Arity indicator but not a visible predicate:

existence_error(predicate,Functor/Arity)

Spec is a predicate indicator of a visible predicate but not a dynamic predicate:

permission_error(access,predicate,Spec)

Spec is a non-terminal indicator of a visible non-terminal but not a dynamic non-terminal:

permission_error(access,non_terminal,Spec)

Spec is a callable term for a visible predicate with a Functor/Arity indicator but not a dynamic predicate:

permission_error(access,predicate,Functor/Arity)

portray_clause/1

Pretty prints a clause to the current output stream.

Compilation flags:

static

Template:

portray_clause(Clause)

Mode and number of proofs:

portray_clause(+clause) - one

Protected predicates

(none)

Private predicates

(none)

Operators

(none)

1.46 logging

object

1.46.1 logger

Global logger object for logging events to files.

Availability:

logtalk_load(logging(loader))

Author: Paulo Moura

Version: 1:0:0

Date: 2011-01-06

Compilation flags:

static, context_switching_calls

Implements:

public loggingp

Remarks:

(none)

Inherited public predicates:

define_log_file/2 disable_logging/1 enable_logging/1 init_log_file/2 log_event/2 log_file/2
logging/1

- Public predicates
- Protected predicates
- Private predicates
 - log_file_/2
 - logging_to_file_/2
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

log_file_/2

Table of log files.

Compilation flags:

dynamic

Template:

log_file_(Alias,File)

Mode and number of proofs:

`log_file_(?atom,?nonvar) - zero_or_more`

`logging_to_file_/2`

Table of logging file status for log files.

Compilation flags:

`dynamic`

Template:

`logging_to_file_(Alias,Status)`

Mode and number of proofs:

`logging_to_file_(?atom,?atom) - zero_or_more`

Operators

(none)

category

1.46.2 logging

Logging events to files category.

Availability:

`logtalk_load(logging(loader))`

Author: Paulo Moura

Version: 1:0:0

Date: 2011-01-06

Compilation flags:

`static`

Implements:

`public loggingp`

Remarks:

(none)

Inherited public predicates:

define_log_file/2 disable_logging/1 enable_logging/1 init_log_file/2 log_event/2 log_file/2
logging/1

- Public predicates
- Protected predicates
- Private predicates
 - log_file_/2
 - logging_to_file_/2
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

log_file_/2

Table of log files.

Compilation flags:

dynamic

Template:

log_file_(Alias,File)

Mode and number of proofs:

log_file_(?atom,?nonvar) - zero_or_more

logging_to_file_/2

Table of logging file status for log files.

Compilation flags:

dynamic

Template:

logging_to_file_(Alias,Status)

Mode and number of proofs:

logging_to_file_(?atom,?atom) - zero_or_more

Operators

(none)

protocol

1.46.3 loggingp

Logging events to files protocol.

Availability:

logtalk_load(logging(loader))

Author: Paulo Moura

Version: 1:0:0

Date: 2011-01-06

Compilation flags:

static

Dependencies:

(none)

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
 - log_file/2
 - define_log_file/2
 - init_log_file/2
 - log_event/2
 - logging/1
 - enable_logging/1
 - disable_logging/1
- Protected predicates
- Private predicates
- Operators

Public predicates

log_file/2

Access to the table of log files.

Compilation flags:

static

Template:

log_file(Alias,File)

Mode and number of proofs:

log_file(?atom,?atom) - zero_or_more

define_log_file/2

Defines a log file with alias Alias and file name File. If the log file already exists, its contents are kept. Logging is enabled by default.

Compilation flags:

static

Template:

```
define_log_file(Alias,File)
```

Mode and number of proofs:

```
define_log_file(+atom,+atom) - one
```

`init_log_file/2`

Initializes a new log file with alias `Alias` and file name `File`. If the log file already exists, its contents are erased. Logging is enabled by default.

Compilation flags:

```
static
```

Template:

```
init_log_file(Alias,File)
```

Mode and number of proofs:

```
init_log_file(+atom,+atom) - one
```

`log_event/2`

Logs an event `Event` to a log file with alias `Alias`. Fails if a log file with alias `Alias` is not defined.

Compilation flags:

```
static
```

Template:

```
log_event(Alias,Event)
```

Mode and number of proofs:

```
log_event(+atom,+nonvar) - zero_or_one
```

logging/1

True if logging to file with alias Alias is enabled.

Compilation flags:

static

Template:

logging(Alias)

Mode and number of proofs:

logging(+atom) - zero_or_one

enable_logging/1

Enables logging to file with alias Alias. Fails if a log file with alias Alias is not defined.

Compilation flags:

static

Template:

enable_logging(Alias)

Mode and number of proofs:

enable_logging(+atom) - zero_or_one

disable_logging/1

Disables logging to file with alias Alias. Fails if a log file with alias Alias is not defined.

Compilation flags:

static

Template:

disable_logging(Alias)

Mode and number of proofs:

disable_logging(+atom) - zero_or_one

Protected predicates

(none)

Private predicates

(none)

Operators

(none)

See also:

logging

1.47 loops

object

1.47.1 loop

Loop control structures predicates.

Availability:

`logtalk_load(loops(loader))`

Author: Paulo Moura

Version: 1:4:1

Date: 2020-12-20

Compilation flags:

`static, context_switching_calls`

Implements:

`public loopp`

Remarks:

(none)

Inherited public predicates:

`dowhile/2 fordownto/3 fordownto/4 fordownto/5 foreach/3 foreach/4 forto/3 forto/4 forto/5 whiledo/2`

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

protocol

1.47.2 loopp

Loop control constructs protocol.

Availability:

```
logtalk_load(loops(loader))
```

Author: Paulo Moura

Version: 1:3:0

Date: 2017-03-20

Compilation flags:

```
static
```

Dependencies:

```
(none)
```

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
 - whiledo/2
 - dowhile/2
 - foreach/3
 - foreach/4
 - forto/3
 - forto/4
 - forto/5
 - fordownto/3
 - fordownto/4
 - fordownto/5
- Protected predicates
- Private predicates
- Operators

Public predicates

whiledo/2

While Condition is true do Action.

Compilation flags:

static

Template:

whiledo(Condition,Action)

Meta-predicate template:

whiledo(0,0)

Mode and number of proofs:

whiledo(+callable,@callable) - zero_or_one

dowhile/2

Do Action while Condition is true.

Compilation flags:

static

Template:

dowhile(Action,Condition)

Meta-predicate template:

dowhile(0,0)

Mode and number of proofs:

dowhile(@callable,+callable) - zero_or_one

foreach/3

For each Element in List call Goal.

Compilation flags:

static

Template:

foreach(Element,List,Goal)

Meta-predicate template:

foreach(*,*,0)

Mode and number of proofs:

foreach(@var,+list(term),@callable) - zero_or_one

foreach/4

For each Element in List at position Index call Goal. Index starts at 1.

Compilation flags:

static

Template:

foreach(Element,Index,List,Goal)

Meta-predicate template:

```
foreach(*,*,*,0)
```

Mode and number of proofs:

```
foreach(@var,@var,+list(term),@callable) - zero_or_one
```

forto/3

Calls Goal counting up from First to Last. Increment is 1. For convenience, First and Last can be arithmetic expressions. Fails iff Goal fails.

Compilation flags:

```
static
```

Template:

```
forto(First,Last,Goal)
```

Meta-predicate template:

```
forto(*,*,0)
```

Mode and number of proofs:

```
forto(+number,+number,@callable) - zero_or_one
```

forto/4

Calls Goal counting up from First to Last and binding Count to each successive value. Increment is 1. For convenience, First and Last can be arithmetic expressions. Fails iff Goal fails.

Compilation flags:

```
static
```

Template:

```
forto(Count,First,Last,Goal)
```

Meta-predicate template:

```
forto(*,*,*,0)
```

Mode and number of proofs:

```
forto(@var,+number,+number,@callable) - zero_or_one
```

forto/5

Calls Goal counting up from First to Last and binding Count to each successive value. For convenience, First, Last, and Increment can be arithmetic expressions (uses Increment absolute value). Fails iff Goal fails.

Compilation flags:

static

Template:

forto(Count,First,Last,Increment,Goal)

Meta-predicate template:

forto(*,*,*,*,0)

Mode and number of proofs:

forto(@var,+number,+number,+number,@callable) - zero_or_one

fordownto/3

Calls Goal counting down from First to Last. Decrement is 1. For convenience, First and Last can be arithmetic expressions. Fails iff Goal fails.

Compilation flags:

static

Template:

fordownto(First,Last,Goal)

Meta-predicate template:

fordownto(*,*,0)

Mode and number of proofs:

fordownto(+number,+number,@callable) - zero_or_one

fordownto/4

Calls Goal counting down from First to Last and binding Count to each successive value. Decrement is 1. For convenience, First and Last can be arithmetic expressions. Fails iff Goal fails.

Compilation flags:

static

Template:

```
fordownto(Count,First,Last,Goal)
```

Meta-predicate template:

```
fordownto(*,*,*,0)
```

Mode and number of proofs:

```
fordownto(@var,+number,+number,@callable) - zero_or_one
```

`fordownto/5`

Calls Goal counting down from First to Last and binding Count to each successive value. For convenience, First, Last, and Decrement can be arithmetic expressions (uses Decrement absolute value). Fails iff Goal fails.

Compilation flags:

```
static
```

Template:

```
fordownto(Count,First,Last,Decrement,Goal)
```

Meta-predicate template:

```
fordownto(*,*,*,*,0)
```

Mode and number of proofs:

```
fordownto(@var,+number,+number,+number,@callable) - zero_or_one
```

Protected predicates

(none)

Private predicates

(none)

Operators

(none)

See also:

[loop](#)

1.48 meta

object

1.48.1 meta

Some useful meta-predicates.

Availability:

```
logtalk_load(meta(loader))
```

Author: Paulo Moura

Version: 5:2:0

Date: 2016-10-06

Compilation flags:

```
static, context_switching_calls
```

Implements:

```
public metap
```

Aliases:

```
metap map/2 as succeeds/2
metap map/2 as maplist/2
metap map/3 as maplist/3
metap map/4 as maplist/4
metap map/5 as maplist/5
metap map/6 as maplist/6
metap map/7 as maplist/7
metap map/8 as maplist/8
metap include/3 as filter/3
metap fold_left/4 as foldl/4
metap fold_left_1/3 as foldl1/3
metap fold_right/4 as foldr/4
metap fold_right_1/3 as foldr1/3
metap scan_left/4 as scanl/4
metap scan_left_1/3 as scanl1/3
metap scan_right/4 as scanr/4
metap scan_right_1/3 as scanr1/3
```

Remarks:

```
(none)
```

Inherited public predicates:

exclude/3 findall_member/4 findall_member/5 fold_left/4 fold_left_1/3 fold_right/4
fold_right_1/3 include/3 map/2 map/3 map/4 map/5 map/6 map/7 map/8 map_reduce/5
partition/4 partition/6 scan_left/4 scan_left_1/3 scan_right/4 scan_right_1/3

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

See also:

`meta_compiler`

`protocol`

1.48.2 metap

Useful meta-predicates protocol.

Availability:

`logtalk_load(meta(loader))`

Author: Paulo Moura

Version: 6:1:0

Date: 2015-12-23

Compilation flags:

`static`

Dependencies:

(none)

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
 - include/3
 - exclude/3
 - findall_member/4
 - findall_member/5
 - partition/4
 - partition/6
 - fold_left/4
 - fold_left_1/3
 - scan_left/4
 - scan_left_1/3
 - fold_right/4
 - fold_right_1/3
 - scan_right/4
 - scan_right_1/3
 - map/2
 - map/3
 - map/4
 - map/5
 - map/6
 - map/7
 - map/8
 - map_reduce/5
- Protected predicates
- Private predicates
- Operators

Public predicates

`include/3`

Returns a list of all list elements that satisfy a predicate.

Compilation flags:

`static`

Template:

`include(Closure,List,Included)`

Meta-predicate template:

`include(1,*,*)`

Mode and number of proofs:

`include(+callable,+list,-list) - one`

`exclude/3`

Returns a list of all list elements that fail to satisfy a predicate.

Compilation flags:

`static`

Template:

`exclude(Closure,List,Excluded)`

Meta-predicate template:

`exclude(1,*,*)`

Mode and number of proofs:

`exclude(+callable,+list,-list) - one`

`findall_member/4`

Finds all members of a list that satisfy a given test.

Compilation flags:

`static`

Template:

```
findall_member(Member,List,Test,Result)
```

Meta-predicate template:

```
findall_member(*,*,0,*)
```

Mode and number of proofs:

```
findall_member(@term,+list,@callable,-list) - one
```

`findall_member/5`

Finds all members of a list that satisfy a given test appending the given tail to the result.

Compilation flags:

```
static
```

Template:

```
findall_member(Member,List,Test,Result,Tail)
```

Meta-predicate template:

```
findall_member(*,*,0,*,*)
```

Mode and number of proofs:

```
findall_member(@term,+list,@callable,-list,+list) - one
```

`partition/4`

Partition a list of elements in two lists using a predicate.

Compilation flags:

```
static
```

Template:

```
partition(Closure,List,Included,Excluded)
```

Meta-predicate template:

```
partition(1,*,*,*)
```

Mode and number of proofs:

```
partition(+callable,+list,-list,-list) - one
```

partition/6

Partitions a list in lists with values less, equal, and greater than a given value using a comparison predicate with the same argument order as compare/3.

Compilation flags:

static

Template:

partition(Closure,List,Value,Less,Equal,Greater)

Meta-predicate template:

partition(3,*,*,*,*)

Mode and number of proofs:

partition(+callable,+list,@term,-list,-list,-list) - one

fold_left/4

List folding (left associative). Closure is extended with three arguments: accumulator, list element, and updated accumulator.

Compilation flags:

static

Template:

fold_left(Closure,Accumulator,List,Result)

Meta-predicate template:

fold_left(3,*,*,*)

Mode and number of proofs:

fold_left(+callable,?term,+list,?term) - zero_or_more

fold_left_1/3

List folding (left associative). Closure is extended with three arguments: accumulator, list element, and updated accumulator. The initial value of the accumulator is the list first element. Fails for empty lists.

Compilation flags:

static

Template:

```
fold_left_1(Closure,List,Result)
```

Meta-predicate template:

```
fold_left_1(3,*,*)
```

Mode and number of proofs:

```
fold_left_1(+callable,+list,?term) - zero_or_more
```

scan_left/4

List scanning (left associative). Closure is extended with three arguments: accumulator, list element, and updated accumulator.

Compilation flags:

```
static
```

Template:

```
scan_left(Closure,Accumulator,List,Results)
```

Meta-predicate template:

```
scan_left(3,*,*,*)
```

Mode and number of proofs:

```
scan_left(+callable,?term,+list,?list) - zero_or_more
```

scan_left_1/3

List scanning (left associative). Closure is extended with three arguments: accumulator, list element, and updated accumulator. The accumulator is initialized with the list first element. Fails for empty lists.

Compilation flags:

```
static
```

Template:

```
scan_left_1(Closure,List,Results)
```

Meta-predicate template:

```
scan_left_1(3,*,*)
```

Mode and number of proofs:

```
scan_left_1(+callable,+list,?list) - zero_or_more
```

fold_right/4

List folding (right associative). Closure is extended with three arguments: list element, accumulator, and updated accumulator.

Compilation flags:

static

Template:

fold_right(Closure,Accumulator,List,Result)

Meta-predicate template:

fold_right(3,*,*,*)

Mode and number of proofs:

fold_right(+callable,?term,+list,?term) - zero_or_more

fold_right_1/3

List folding (right associative). Closure is extended with three arguments: list element, accumulator, and updated accumulator. The initial value of the accumulator is the list first element. Fails for empty lists.

Compilation flags:

static

Template:

fold_right_1(Closure,List,Result)

Meta-predicate template:

fold_right_1(3,*,*)

Mode and number of proofs:

fold_right_1(+callable,+list,?term) - zero_or_more

scan_right/4

List scanning (right associative). Closure is extended with three arguments: list element, accumulator, and updated accumulator.

Compilation flags:

static

Template:

```
scan_right(Closure,Accumulator,List,Results)
```

Meta-predicate template:

```
scan_right(3,*,*,*)
```

Mode and number of proofs:

```
scan_right(+callable,?term,+list,?list) - zero_or_more
```

scan_right_1/3

List scanning (right associative). Closure is extended with three arguments: list element, accumulator, and updated accumulator. The accumulator is initialized with the list first element. Fails for empty lists.

Compilation flags:

```
static
```

Template:

```
scan_right_1(Closure,List,Results)
```

Meta-predicate template:

```
scan_right_1(3,*,*)
```

Mode and number of proofs:

```
scan_right_1(+callable,+list,?list) - zero_or_more
```

map/2

True if the predicate succeeds for each list element.

Compilation flags:

```
static
```

Template:

```
map(Closure,List)
```

Meta-predicate template:

```
map(1,*)
```

Mode and number of proofs:

```
map(+callable,?list) - zero_or_more
```

map/3

List mapping predicate taken arguments from two lists of elements.

Compilation flags:

static

Template:

map(Closure,List1,List2)

Meta-predicate template:

map(2,*,*)

Mode and number of proofs:

map(+callable,?list,?list) - zero_or_more

map/4

List mapping predicate taken arguments from three lists of elements.

Compilation flags:

static

Template:

map(Closure,List1,List2,List3)

Meta-predicate template:

map(3,*,*,*)

Mode and number of proofs:

map(+callable,?list,?list,?list) - zero_or_more

map/5

List mapping predicate taken arguments from four lists of elements.

Compilation flags:

static

Template:

map(Closure,List1,List2,List3,List4)

Meta-predicate template:

```
map(4,*,*,*,*)
```

Mode and number of proofs:

```
map(+callable,?list,?list,?list,?list) - zero_or_more
```

map/6

List mapping predicate taken arguments from five lists of elements.

Compilation flags:

```
static
```

Template:

```
map(Closure,List1,List2,List3,List4,List5)
```

Meta-predicate template:

```
map(5,*,*,*,*,*)
```

Mode and number of proofs:

```
map(+callable,?list,?list,?list,?list,?list) - zero_or_more
```

map/7

List mapping predicate taken arguments from six lists of elements.

Compilation flags:

```
static
```

Template:

```
map(Closure,List1,List2,List3,List4,List5,List6)
```

Meta-predicate template:

```
map(6,*,*,*,*,*,*)
```

Mode and number of proofs:

```
map(+callable,?list,?list,?list,?list,?list,?list) - zero_or_more
```

map/8

List mapping predicate taken arguments from seven lists of elements.

Compilation flags:

static

Template:

map(Closure,List1,List2,List3,List4,List5,List6,List7)

Meta-predicate template:

map(7,*,*,*,*,*,*,*)

Mode and number of proofs:

map(+callable,?list,?list,?list,?list,?list,?list,?list) - zero_or_more

map_reduce/5

Map a list and apply a fold left (reduce) to the resulting list.

Compilation flags:

static

Template:

map_reduce(Map,Reduce,Accumulator,List,Result)

Meta-predicate template:

map_reduce(2,3,*,*,*)

Mode and number of proofs:

map_reduce(+callable,+callable,+term,?list,?term) - zero_or_more

Protected predicates

(none)

Private predicates

(none)

Operators

(none)

See also:

[meta](#)

1.49 meta_compiler

object

1.49.1 meta_compiler

Compiler for the meta object meta-predicates. Generates auxiliary predicates in order to avoid meta-call overheads.

Availability:

```
logtalk_load(meta_compiler(loader))
```

Author: Paulo Moura

Version: 0:13:1

Date: 2022-05-06

Compilation flags:

```
static, context_switching_calls
```

Implements:

```
public expanding
```

Uses:

```
gensym
```

```
list
```

```
logtalk
```

Remarks:

- Usage: Compile source files with calls to the meta object meta-predicates using the compiler option `hook(meta_compiler)`.

Inherited public predicates:

goal_expansion/2 term_expansion/2

- Public predicates
- Protected predicates
- Private predicates
 - generated_predicate_/1
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

generated_predicate_/1

Table of generated auxiliary predicates.

Compilation flags:

dynamic

Template:

generated_predicate_(Predicate)

Mode and number of proofs:

generated_predicate_(?predicate_indicator) - zero_or_more

Operators

(none)

See also:

meta

1.50 metagol

object

1.50.1 metagol

Inductive logic programming (ILP) system based on meta-interpretive learning.

Availability:

```
logtalk_load(metagol(loader))
```

Author: Metagol authors; adapted to Logtalk by Paulo Moura.

Version: 0:24:4

Date: 2024-03-15

Copyright: Copyright 2016 Metagol authors; Copyright 2018-2024 Paulo Moura

License: BSD-3-Clause

Compilation flags:

```
static, context_switching_calls
```

Implements:

```
public expanding
```

Provides:

```
logtalk::message_tokens//2
```

```
logtalk::message_prefix_stream/4
```

Uses:

```
coroutining
```

```
integer
```

```
list
```

```
logtalk
```

```
meta
```

```
timeout
```

Remarks:

```
(none)
```

Inherited public predicates:

```
goal_expansion/2 term_expansion/2
```

- Public predicates
 - learn/3
 - learn/2
 - learn_seq/2
 - learn_with_timeout/4
 - program_to_clauses/2
 - pprint/1
 - metarule/6
 - head_pred/1
 - body_pred/1
 - ibk/3
 - func_test/3
 - functional/0
 - min_clauses/1
 - max_clauses/1
 - max_inv_preds/1
 - metarule_next_id/1
 - timeout/1
- Protected predicates
 - pprint_clause/1
 - pprint_clauses/1
 - compiled_pred_call/2
 - body_pred_call/2
 - type/3
- Private predicates
- Operators

Public predicates

learn/3

Learns from a set of positive examples and a set of negative examples and returns the learned program.

Compilation flags:

static

Template:

```
learn(PositiveExamples,NegativeExamples,Program)
```

Mode and number of proofs:

```
learn(@list(example),@list(example),-list(term)) - zero_or_more
```

learn/2

Learns from a set of positive examples and a set of negative examples and pretty prints the learned program.

Compilation flags:

```
static
```

Template:

```
learn(PositiveExamples,NegativeExamples)
```

Mode and number of proofs:

```
learn(@list(example),@list(example)) - zero_or_more
```

learn_seq/2

Learns from a sequence of examples represented as a list of PositiveExamples/NegativeExamples elements and returns the learned program.

Compilation flags:

```
static
```

Template:

```
learn_seq(Examples,Program)
```

Mode and number of proofs:

```
learn_seq(@list(example),-list(clause)) - zero_or_one
```

learn_with_timeout/4

Learns from a set of positive examples and a set of negative examples and returns the learned program constrained by the given timeout or its default value.

Compilation flags:

static

Template:

learn_with_timeout(PositiveExamples,NegativeExamples,Program,Timeout)

Mode and number of proofs:

learn_with_timeout(@list(example),@list(example),-list(term),+number) - zero_or_one_or_error

learn_with_timeout(@list(example),@list(example),-list(term),-number) - zero_or_one_or_error

Exceptions:

Learning does not complete in the allowed time:

timeout(learn(PositiveExamples,NegativeExamples,Program))

program_to_clauses/2

Converts a learned program into a list of clauses.

Compilation flags:

static

Template:

program_to_clauses(Program,Clauses)

Mode and number of proofs:

program_to_clauses(@list(term),-list(clause)) - one

pprint/1

Pretty prints a learned program.

Compilation flags:

static

Template:

pprint(Program)

Mode and number of proofs:

pprint(@list(term)) - one

metarule/6

Compilation flags:

static

head_pred/1

Compilation flags:

static

body_pred/1

Compilation flags:

dynamic

ibk/3

Compilation flags:
static

func_test/3

Compilation flags:
static

functional/0

Compilation flags:
dynamic

min_clauses/1

Compilation flags:
dynamic

max_clauses/1

Compilation flags:
dynamic

max_inv_preds/1

Compilation flags:
dynamic

metarule_next_id/1

Compilation flags:
dynamic

timeout/1

Compilation flags:
dynamic

Protected predicates

pprint_clause/1

Compilation flags:
static

pprint_clauses/1

Compilation flags:
static

compiled_pred_call/2

Compilation flags:
dynamic

body_pred_call/2

Compilation flags:
dynamic

type/3

Compilation flags:
dynamic

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)
protocol

1.50.2 metagol_example_protocol

Convenient learning predicates for use in examples and unit tests.

Availability:
logtalk_load(metagol(loader))

Author: Paulo Moura.
Version: 0:1:1
Date: 2024-03-15

License: BSD-3-Clause

Compilation flags:

static

Dependencies:

(none)

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
 - learn/1
 - learn/0
- Protected predicates
- Private predicates
- Operators

Public predicates

learn/1

Learns and returns set of clauses.

Compilation flags:

static

Template:

learn(Clauses)

Mode and number of proofs:

learn(-list(clause)) - zero_or_more

learn/0

Learns and prints a set of clauses.

Compilation flags:

static

Mode and number of proofs:

learn - zero_or_more

Protected predicates

(none)

Private predicates

(none)

Operators

(none)

1.51 mutations

object

1.51.1 default_atom_mutations

Default atom mutations.

Availability:

logtalk_load(mutations(loader))

Author: Paulo Moura

Version: 0:1:0

Date: 2023-11-24

Compilation flags:

static, context_switching_calls

Provides:

mutations_store::mutation/4

Uses:

fast_random

list

type

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

See also:

type

object

1.51.2 default_compound_mutations

Default compound mutations.

Availability:

```
logtalk_load(mutations(loader))
```

Author: Paulo Moura

Version: 0:1:0

Date: 2023-11-23

Compilation flags:

```
static, context_switching_calls
```

Provides:

```
mutations_store::mutation/4
```

Uses:

```
mutations_store
```

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

See also:

type

object

1.51.3 default_float_mutations

Default float mutations.

Availability:

```
logtalk_load(mutations(loader))
```

Author: Paulo Moura

Version: 0:1:0

Date: 2023-11-23

Compilation flags:

```
static, context_switching_calls
```

Provides:

```
mutations_store::mutation/4
```

Remarks:

(none)

Inherited public predicates:

(none)

- [Public predicates](#)
- [Protected predicates](#)

- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

See also:

type

object

1.51.4 default_integer_mutations

Default integer mutations.

Availability:

```
logtalk_load(mutations(loader))
```

Author: Paulo Moura

Version: 0:1:0

Date: 2023-11-24

Compilation flags:

```
static, context_switching_calls
```

Provides:

```
mutations_store::mutation/4
```

Uses:

```
fast_random
```

```
list
```

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

See also:

type

object

1.51.5 default_list_mutations

Default list mutations.

Availability:

logtalk_load(mutations(loader))

Author: Paulo Moura

Version: 0:1:0

Date: 2023-11-24

Compilation flags:

static, context_switching_calls

Provides:

mutations_store::mutation/4

Uses:

fast_random

list

mutations_store

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

See also:

[type](#)

[category](#)

1.51.6 mutations

Adds mutations support to the library type object.

Availability:

```
logtalk_load(mutations(loader))
```

Author: Paulo Moura

Version: 1:0:0

Date: 2023-11-23

Compilation flags:

```
static
```

Complements:

```
type
```

Uses:

```
mutations_store
```

Remarks:

(none)

Inherited public predicates:

(none)

- [Public predicates](#)
 - [mutation/3](#)
- [Protected predicates](#)
- [Private predicates](#)
- [Operators](#)

Public predicates

mutation/3

Returns a random mutation of a term into another term of the same type. The input Term is assume to be valid for the given Type.

Compilation flags:

static

Template:

mutation(Type,Term,Mutation)

Mode and number of proofs:

mutation(@callable,@term,-term) - one

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

object

1.51.7 mutations_store

Stores mutation definitions for selected types. User extensible by defining objects or categories defining clauses for the mutation/3 predicate and using this object as a hook object for their compilation.

Availability:

logtalk_load(mutations(loader))

Author: Paulo Moura

Version: 0:1:0

Date: 2023-11-23

Compilation flags:

static, context_switching_calls

Implements:

public expanding

Uses:

fast_random

Remarks:

(none)

Inherited public predicates:

goal_expansion/2 term_expansion/2

- Public predicates
 - mutation/3
 - counter/2
- Protected predicates
- Private predicates
 - mutation/4
 - counter_/2
- Operators

Public predicates

mutation/3

Returns a random mutation of a term into another term of the same type. The input Term is assumed to be valid for the given Type.

Compilation flags:

static

Template:

mutation(Type,Term,Mutation)

Mode and number of proofs:

mutation(@callable,@term,-term) - one

counter/2

Table of the number of mutations available per type.

Compilation flags:

static

Template:

counter(Type,N)

Mode and number of proofs:

counter(?callable,?positive_integer) - zero_or_more

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

mutation/4

Returns a random mutation of a term into another term of the same type using mutator N. The input Term is assume to be valid for the given Type.

Compilation flags:

static, multifile

Template:

mutation(Type,N,Term,Mutation)

Mode and number of proofs:

mutation(?callable,?positive_integer,@term,-term) - zero_or_more

counter_/2

Internal counter for the number of mutations available for a given type.

Compilation flags:

dynamic

Template:

counter_(Type,N)

Mode and number of proofs:

counter_(?callable,?positive_integer) - zero_or_more

Operators

(none)

See also:

type

1.52 nested_dictionaries

object

1.52.1 navltree

Nested dictionary implementation based on the AVL tree implementation. Uses standard order to compare keys.

Availability:

logtalk_load(nested_dictionaries(loader))

Author: Paul Brown and Paulo Moura.

Version: 0:1:0

Date: 2021-04-09

Compilation flags:

static, context_switching_calls

Implements:

```
public nested_dictionary_protocol
```

Extends:

```
private avltree
```

Remarks:

(none)

Inherited public predicates:

```
as_curly_bracketed/2 as_nested_dictionary/2 delete_in/4 empty/1 insert_in/4 lookup_in/3  
new/1 update_in/4 update_in/5
```

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

See also:

nrmtree, nbintree

object

1.52.2 nbintree

Nested dictionary implementation based on the simple binary tree implementation. Uses standard order to compare keys.

Availability:

```
logtalk_load(nested_dictionaries(loader))
```

Author: Paul Brown and Paulo Moura.

Version: 0:1:0

Date: 2021-04-09

Compilation flags:

```
static, context_switching_calls
```

Implements:

```
public nested_dictionary_protocol
```

Extends:

```
private bintree
```

Remarks:

(none)

Inherited public predicates:

```
as_curly_bracketed/2 as_nested_dictionary/2 delete_in/4 empty/1 insert_in/4 lookup_in/3  
new/1 update_in/4 update_in/5
```

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

See also:

[nrbtree](#), [navltree](#)

[protocol](#)

1.52.3 nested_dictionary_protocol

Nested dictionary protocol.

Availability:

```
logtalk_load(nested_dictionaries(loader))
```

Author: Paul Brown and Paulo Moura

Version: 0:1:0

Date: 2021-04-07

Compilation flags:

```
static
```

Dependencies:

(none)

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
 - new/1
 - empty/1
 - as_nested_dictionary/2
 - as_curly_bracketed/2
 - lookup_in/3
 - update_in/4
 - update_in/5
 - insert_in/4
 - delete_in/4
- Protected predicates
- Private predicates
- Operators

Public predicates

new/1

Create an empty (nested) dictionary.

Compilation flags:

static

Template:

new(Dictionary)

Mode and number of proofs:

new(--dictionary) - one

empty/1

True iff the dictionary is empty.

Compilation flags:

static

Template:

empty(Dictionary)

Mode and number of proofs:

empty(@dictionary) - zero_or_one

as_nested_dictionary/2

Creates a (nested) dictionary term from a curly-bracketed term representation.

Compilation flags:

static

Template:

as_nested_dictionary(Term,Dictionary)

Mode and number of proofs:

as_nested_dictionary(++term,--dictionary) - one_or_error

as_curly_bracketed/2

Creates a a curly-bracketed term representation from a (nested) dictionary.

Compilation flags:

static

Template:

as_curly_bracketed(Dictionary,Term)

Mode and number of proofs:

as_curly_bracketed(+dictionary,--term) - one_or_error

lookup_in/3

Lookup a chain of keys in a nested dictionary. Unifies Value with Dictionary when Keys is the empty list.

Compilation flags:

static

Template:

lookup_in(Keys,Value,Dictionary)

Mode and number of proofs:

lookup_in(++list(ground),?term,+dictionary) - zero_or_more

update_in/4

Updates the value found by traversing through the nested keys.

Compilation flags:

static

Template:

update_in(OldDictionary,Keys,Value,NewDictionary)

Mode and number of proofs:

update_in(+dictionary,++list(ground),++term,--dictionary) - zero_or_one

update_in/5

Updates the value found by traversing through the nested keys, only succeeding if the value found after traversal matches the old value.

Compilation flags:

static

Template:

update_in(OldDictionary,Keys,OldValue,NewValue,NewDictionary)

Mode and number of proofs:

update_in(+dictionary,++list(ground),?term,++term,--dictionary) - zero_or_one

`insert_in/4`

Inserts a key-value pair into a dictionary by traversing through the nested keys. When the key already exists, the associated value is updated.

Compilation flags:

`static`

Template:

`insert_in(OldDictionary,Keys,Value,NewDictionary)`

Mode and number of proofs:

`insert_in(+dictionary,++list(ground),++term,--dictionary) - zero_or_one`

`delete_in/4`

Deletes a matching key-value pair from a dictionary by traversing through the nested keys, returning the updated dictionary.

Compilation flags:

`static`

Template:

`delete_in(OldDictionary,Keys,Value,NewDictionary)`

Mode and number of proofs:

`delete_in(+dictionary,++list(ground),?term,--dictionary) - zero_or_one`

Protected predicates

(none)

Private predicates

(none)

Operators

(none)

See also:

[navltree](#), [nbintree](#), [nrmtree](#)

object

1.52.4 nrmtree

Nested dictionary implementation based on the red-black tree implementation. Uses standard order to compare keys.

Availability:

```
logtalk_load(nested_dictionaries(loader))
```

Author: Paul Brown and Paulo Moura.

Version: 0:1:0

Date: 2021-04-09

Compilation flags:

```
static, context_switching_calls
```

Implements:

```
public nested_dictionary_protocol
```

Extends:

```
private rbtree
```

Remarks:

(none)

Inherited public predicates:

```
as_curly_bracketed/2 as_nested_dictionary/2 delete_in/4 empty/1 insert_in/4 lookup_in/3
new/1 update_in/4 update_in/5
```

- [Public predicates](#)
- [Protected predicates](#)

- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

See also:

navltree, nbintree

1.53 optionals

object

1.53.1 maybe

Types and predicates for type-checking and handling optional terms. Inspired by Haskell.

Availability:

```
logtalk_load(optionals(loader))
```

Author: Paulo Moura

Version: 0:7:0

Date: 2021-01-03

Compilation flags:

```
static, context_switching_calls
```

Provides:

```
type::type/1
```

```

type::check/2
arbitrary::arbitrary/1
arbitrary::arbitrary/2

```

Uses:

```

optional
optional(Optional)
random
type

```

Remarks:

- Type-checking support: Defines type `maybe(Type)` for checking optional terms where the value hold by the optional term must be of the given type.
- QuickCheck support: Defines clauses for the `arbitrary::arbitrary/1-2` predicates to allow generating random values for the `maybe(Type)` type.

Inherited public predicates:

(none)

- Public predicates
 - `cat/2`
- Protected predicates
- Private predicates
- Operators

Public predicates

`cat/2`

Returns the values stored in the non-empty optional terms.

Compilation flags:

`static`

Template:

`cat(Optionals,Values)`

Mode and number of proofs:

`cat(+list(optional),-list) - one`

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

See also:

`optional`, `optional(Optional)`, `type`, `arbitrary`
`object`

1.53.2 optional

Constructors for optional terms. An optional term is either empty or holds a value. Optional terms should be regarded as opaque terms and always used with the `optional/1` object by passing the optional term as a parameter.

Availability:

```
logtalk_load(optionals(loader))
```

Author: Paulo Moura

Version: 2:1:0

Date: 2021-01-03

Compilation flags:

```
static, context_switching_calls
```

Provides:

```
type::type/1  
type::check/2
```

Remarks:

- Type-checking support: This object also defines a type `optional` for use with the type library object.

Inherited public predicates:

(none)

- Public predicates
 - empty/1
 - of/2
 - from_goal/3
 - from_goal/2
 - from_generator/3
 - from_generator/2
- Protected predicates
- Private predicates
- Operators

Public predicates

empty/1

Constructs an empty optional term.

Compilation flags:

static

Template:

empty(Optional)

Mode and number of proofs:

empty(--nonvar) - one

of/2

Constructs an optional term holding the given value.

Compilation flags:

static

Template:

of(Value,Optional)

Mode and number of proofs:

of(@term,--nonvar) - one

from_goal/3

Constructs an optional term holding a value bound by calling the given goal. Returns an empty optional term if the goal fails or throws an error.

Compilation flags:

static

Template:

from_goal(Goal,Value,Optional)

Meta-predicate template:

from_goal(0,*,*)

Mode and number of proofs:

from_goal(+callable,--term,--nonvar) - one

from_goal/2

Constructs an optional term holding a value bound by calling the given closure. Returns an empty optional term if the closure fails or throws an error.

Compilation flags:

static

Template:

from_goal(Closure,Optional)

Meta-predicate template:

from_goal(1,*)

Mode and number of proofs:

from_goal(+callable,--nonvar) - one

`from_generator/3`

Constructs optional terms with the values generated by calling the given goal. On goal error or failure, returns an empty optional.

Compilation flags:

`static`

Template:

`from_generator(Goal,Value,Optional)`

Meta-predicate template:

`from_generator(0,*,*)`

Mode and number of proofs:

`from_generator(+callable,--term,--nonvar) - one_or_more`

`from_generator/2`

Constructs optional terms with the values generated by calling the given closure. On closure error or failure, returns an empty optional.

Compilation flags:

`static`

Template:

`from_generator(Closure,Optional)`

Meta-predicate template:

`from_generator(1,*)`

Mode and number of proofs:

`from_generator(+from_generator,--nonvar) - one_or_more`

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

See also:

`optional(Optional)`, type

object

1.53.3 `optional(Optional)`

Optional term handling predicates. Requires passing an optional term (constructed using the optional object predicates) as a parameter.

Availability:

`logtalk_load(optionals(loader))`

Author: Paulo Moura

Version: 1:7:0

Date: 2019-11-26

Compilation flags:

`static, context_switching_calls`

Dependencies:

(none)

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
 - `is_empty/0`
 - `is_present/0`
 - `if_empty/1`

- if_present/1
- if_present_or_else/2
- filter/2
- map/2
- flat_map/2
- or/2
- get/1
- or_else/2
- or_else_get/2
- or_else_call/2
- or_else_fail/1
- or_else_throw/2
- Protected predicates
- Private predicates
- Operators

Public predicates

is_empty/0

True if the optional term is empty. See also the if_empty/1 predicate.

Compilation flags:

static

Mode and number of proofs:

is_empty - zero_or_one

is_present/0

True if the optional term holds a value. See also the if_present/1 predicate.

Compilation flags:

static

Mode and number of proofs:

is_present - zero_or_one

if_empty/1

Calls a goal if the optional term is empty. Succeeds otherwise.

Compilation flags:

static

Template:

if_empty(Goal)

Meta-predicate template:

if_empty(0)

Mode and number of proofs:

if_empty(+callable) - zero_or_more

if_present/1

Applies a closure to the value hold by the optional term if not empty. Succeeds otherwise.

Compilation flags:

static

Template:

if_present(Closure)

Meta-predicate template:

if_present(1)

Mode and number of proofs:

if_present(+callable) - zero_or_more

`if_present_or_else/2`

Applies a closure to the value hold by the optional term if not empty. Otherwise calls the given goal.

Compilation flags:

`static`

Template:

`if_present_or_else(Closure,Goal)`

Meta-predicate template:

`if_present_or_else(1,0)`

Mode and number of proofs:

`if_present_or_else(+callable,+callable) - zero_or_more`

`filter/2`

Returns the optional term when it is not empty and the value it holds satisfies a closure. Otherwise returns an empty optional term.

Compilation flags:

`static`

Template:

`filter(Closure,NewOptional)`

Meta-predicate template:

`filter(1,*)`

Mode and number of proofs:

`filter(+callable,--nonvar) - one`

`map/2`

When the optional term is not empty and mapping a closure with the value it holds and the new value as additional arguments is successful, returns an optional term with the new value. Otherwise returns an empty optional term.

Compilation flags:

`static`

Template:

map(Closure,NewOptional)

Meta-predicate template:

map(2,*)

Mode and number of proofs:

map(+callable,--nonvar) - one

flat_map/2

When the optional term is not empty and mapping a closure with the value it holds and the new optional term as additional arguments is successful, returns the new optional term. Otherwise returns an empty optional term.

Compilation flags:

static

Template:

flat_map(Closure,NewOptional)

Meta-predicate template:

flat_map(2,*)

Mode and number of proofs:

flat_map(+callable,--nonvar) - one

or/2

Returns the same optional term if not empty. Otherwise calls closure to generate a new optional term. Fails if optional term is empty and calling the closure fails or throws an error.

Compilation flags:

static

Template:

or(NewOptional,Closure)

Meta-predicate template:

or(*,1)

Mode and number of proofs:

or(--term,@callable) - zero_or_one

get/1

Returns the value hold by the optional term if not empty. Throws an error otherwise.

Compilation flags:

static

Template:

get(Value)

Mode and number of proofs:

get(--term) - one_or_error

Exceptions:

Optional is empty:

existence_error(optional_term,Optional)

or_else/2

Returns the value hold by the optional term if not empty or the given default value if the optional term is empty.

Compilation flags:

static

Template:

or_else(Value,Default)

Mode and number of proofs:

or_else(--term,@term) - one

or_else_get/2

Returns the value hold by the optional term if not empty. Applies a closure to compute the value otherwise. Throws an error when the optional term is empty and the value cannot be computed.

Compilation flags:

static

Template:

`or_else_get(Value,Closure)`

Meta-predicate template:

`or_else_get(*,1)`

Mode and number of proofs:

`or_else_get(--term,+callable) - one_or_error`

Exceptions:

Optional is empty and the term cannot be computed:

`existence_error(optional_term,Optional)`

`or_else_call/2`

Returns the value hold by the optional term if not empty or calls a goal deterministically if the optional term is empty.

Compilation flags:

`static`

Template:

`or_else_call(Value,Goal)`

Meta-predicate template:

`or_else_call(*,0)`

Mode and number of proofs:

`or_else_call(--term,+callable) - zero_or_one`

`or_else_fail/1`

Returns the value hold by the optional term if not empty. Fails otherwise. Usually called to skip over empty optional terms.

Compilation flags:

`static`

Template:

`or_else_fail(Value)`

Mode and number of proofs:

`or_else_fail(--term) - zero_or_one`

`or_else_throw/2`

Returns the value hold by the optional term if not empty. Throws the given error otherwise.

Compilation flags:

`static`

Template:

`or_else_throw(Value,Error)`

Mode and number of proofs:

`or_else_throw(--term,@nonvar) - one_or_error`

Protected predicates

(none)

Private predicates

(none)

Operators

(none)

See also:

`optional`

1.54 options

category

1.54.1 options

Options processing predicates. Options are represented by compound terms where the functor is the option name.

Availability:

```
logtalk_load(options(loader))
```

Author: Paulo Moura

Version: 1:2:0

Date: 2022-01-03

Compilation flags:

```
static
```

Implements:

```
public options_protocol
```

Uses:

```
list
```

Remarks:

```
(none)
```

Inherited public predicates:

```
check_option/1 check_options/1 default_option/1 default_options/1 option/2 option/3  
valid_option/1 valid_options/1
```

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

protocol

1.54.2 options_protocol

Options protocol.

Availability:

logtalk_load(options(loader))

Author: Paulo Moura

Version: 1:2:0

Date: 2022-01-03

Compilation flags:

static

Dependencies:

(none)

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
 - check_option/1
 - check_options/1
 - valid_option/1
 - valid_options/1
 - default_option/1
 - default_options/1
 - option/2
 - option/3
- Protected predicates
 - merge_options/2
 - fix_options/2
 - fix_option/2
- Private predicates
- Operators

Public predicates

check_option/1

Succeeds if the option is valid. Throws an error otherwise.

Compilation flags:

static

Template:

check_option(Option)

Mode and number of proofs:

check_option(@term) - one_or_error

Exceptions:

Option is a variable:

instantiation_error

Option is neither a variable nor a compound term:

type_error(compound,Option)

Option is a compound term but not a valid option:

domain_error(option,Option)

check_options/1

Succeeds if all the options in a list are valid. Throws an error otherwise.

Compilation flags:

static

Template:

check_options(Options)

Mode and number of proofs:

check_options(@term) - one_or_error

Exceptions:

Options is a variable:

instantiation_error

Options is neither a variable nor a list:

type_error(list,Options)

An element Option of the list Options is a variable:

instantiation_error

An element Option of the list Options is neither a variable nor a compound term:

type_error(compound,Option)

An element Option of the list Options is a compound term but not a valid option:

domain_error(option,Option)

valid_option/1

Succeeds if the option is valid.

Compilation flags:

static

Template:

valid_option(Option)

Mode and number of proofs:

valid_option(@term) - zero_or_one

valid_options/1

Succeeds if all the options in a list are valid.

Compilation flags:

static

Template:

valid_options(Options)

Mode and number of proofs:

valid_options(@term) - one

default_option/1

Enumerates, by backtracking, the default options.

Compilation flags:

static

Template:

default_option(Option)

Mode and number of proofs:

default_option(?compound) - zero_or_more

default_options/1

Returns a list of the default options.

Compilation flags:

static

Template:

default_options(Options)

Mode and number of proofs:

default_options(-list(compound)) - one

option/2

True iff Option unifies with the first occurrence of the same option in the Options list.

Compilation flags:

static

Template:

option(Option,Options)

Mode and number of proofs:

option(+compound,+list(compound)) - zero_or_one

option/3

True iff Option unifies with the first occurrence of the same option in the Options list or, when that is not the case, if Option unifies with Default.

Compilation flags:

static

Template:

option(Option,Options,Default)

Mode and number of proofs:

option(+compound,+list(compound),+compound) - zero_or_one

Protected predicates

merge_options/2

Merges the user options with the default options, returning the final list of options. Calls the fix_options/2 predicate to preprocess the options after merging. Callers must ensure, if required, that the user options are valid.

Compilation flags:

static

Template:

`merge_options(UserOptions,Options)`

Mode and number of proofs:

`merge_options(+list(compound),-list(compound)) - one`

`fix_options/2`

Fixes a list of options, returning the list of options.

Compilation flags:

`static`

Template:

`fix_options(Options,FixedOptions)`

Mode and number of proofs:

`fix_options(+list(compound),-list(compound)) - one`

`fix_option/2`

Fixes an option.

Compilation flags:

`static`

Template:

`fix_option(Option,FixedOption)`

Mode and number of proofs:

`fix_option(+compound,-compound) - zero_or_one`

Private predicates

(none)

Operators

(none)

See also:

[options](#)

1.55 os

object

1.55.1 os

Portable operating-system access predicates.

Availability:

```
logtalk_load(os(loader))
```

Author: Paulo Moura

Version: 1:100:2

Date: 2024-03-25

Compilation flags:

```
static, context_switching_calls
```

Implements:

```
public osp
```

Uses:

```
list
```

Aliases:

```
osp absolute_file_name/2 as expand_path/2
```

Remarks:

- File path expansion: To ensure portability, all file paths are expanded before being handed to the backend Prolog system.
- Exception terms: Currently, there is no standardization of the exception terms thrown by the different backend Prolog systems.
- B-Prolog portability: The `wall_time/1` predicate is not supported.

- CxProlog portability: The `date_time/7` predicate returns zeros for all arguments.
- JIProlog portability: The `file_permission/2` and `command_line_arguments/1` predicates are not supported.
- Quintus Prolog: The `pid/1` and `shell/2` predicates are not supported.
- XSB portability: The `command_line_arguments/1` predicate is not supported.

Inherited public predicates:

`absolute_file_name/2` `change_directory/1` `command_line_arguments/1` `copy_file/2` `cpu_time/1`
`date_time/7` `decompose_file_name/3` `decompose_file_name/4` `delete_directory/1` `delete_file/1`
`directory_exists/1` `directory_files/2` `directory_files/3` `ensure_directory/1` `ensure_file/1`
`environment_variable/2` `file_exists/1` `file_modification_time/2` `file_permission/2` `file_size/2`
`full_device_path/1` `internal_os_path/2` `is_absolute_file_name/1` `make_directory/1`
`make_directory_path/1` `null_device_path/1` `operating_system_machine/1`
`operating_system_name/1` `operating_system_release/1` `operating_system_type/1`
`path_concat/3` `pid/1` `read_only_device_path/1` `rename_file/2` `shell/1` `shell/2` `sleep/1`
`temporary_directory/1` `time_stamp/1` `wall_time/1` `working_directory/1`

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

See also:

`os_types`

`category`

1.55.2 os_types

A set of operating-system related types.

Availability:

```
logtalk_load(os(loader))
```

Author: Paulo Moura

Version: 1:4:0

Date: 2021-02-12

Compilation flags:

```
static
```

Provides:

```
type::type/1
```

```
type::check/2
```

Uses:

```
list
```

```
os
```

Remarks:

- Provided types: This category adds `file`, `file(Extensions)`, `file(Extensions,Permissions)`, `directory`, `directory(Permissions)`, and `environment_variable` types for type-checking when using the type library object.
- Type `file`: For checking if a term is an atom and an existing file.
- Type `file(Extensions)`: For checking if a term is an atom and an existing file with one of the listed extensions (specified as `'.ext'`).
- Type `file(Extensions,Permissions)`: For checking if a term is an atom and an existing file with one of the listed extensions (specified as `'.ext'`) and listed permissions (`{read, write, execute}`).
- Type `directory`: For checking if a term is an atom and an existing directory.
- Type `directory(Permissions)`: For checking if a term is an atom and an existing directory with the listed permissions (`{read, write, execute}`).
- Type `environment_variable`: For checking if a term is an atom and an existing environment variable.

Inherited public predicates:

```
(none)
```

- [Public predicates](#)
- [Protected predicates](#)
- [Private predicates](#)
- [Operators](#)

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

See also:

[osp](#), [os](#), [type](#)

[protocol](#)

1.55.3 osp

Portable operating-system access protocol.

Availability:

`logtalk_load(os(loader))`

Author: Paulo Moura

Version: 1:38:1

Date: 2024-03-25

Compilation flags:

`static`

Dependencies:

(none)

Remarks:

- Error handling: Predicates that require a file or directory to exist throw an error when that is not the case. But the exact exception term is currently backend Prolog compiler dependent.

Inherited public predicates:

(none)

- Public predicates
 - pid/1
 - shell/2
 - shell/1
 - is_absolute_file_name/1
 - absolute_file_name/2
 - decompose_file_name/3
 - decompose_file_name/4
 - path_concat/3
 - internal_os_path/2
 - make_directory/1
 - make_directory_path/1
 - delete_directory/1
 - change_directory/1
 - working_directory/1
 - temporary_directory/1
 - null_device_path/1
 - full_device_path/1
 - read_only_device_path/1
 - directory_files/2
 - directory_files/3
 - directory_exists/1
 - ensure_directory/1
 - file_exists/1
 - file_modification_time/2
 - file_size/2
 - file_permission/2
 - copy_file/2

- rename_file/2
- delete_file/1
- ensure_file/1
- environment_variable/2
- time_stamp/1
- date_time/7
- cpu_time/1
- wall_time/1
- operating_system_type/1
- operating_system_name/1
- operating_system_machine/1
- operating_system_release/1
- command_line_arguments/1
- sleep/1
- Protected predicates
- Private predicates
- Operators

Public predicates

pid/1

Returns the process identifier of the running process.

Compilation flags:

static

Template:

pid(PID)

Mode and number of proofs:

pid(-integer) - one

shell/2

Runs an operating-system shell command and returns its exit status.

Compilation flags:

static

Template:

shell(Command,Status)

Mode and number of proofs:

shell(+atom,-integer) - one

shell/1

Runs an operating-system shell command.

Compilation flags:

static

Template:

shell(Command)

Mode and number of proofs:

shell(+atom) - zero_or_one

is_absolute_file_name/1

True iff the argument is an absolute file path. On POSIX systems, this predicate is true if File starts with a /. On Windows systems, this predicate is true if File starts with a drive letter. No attempt is made to expand File as a path.

Compilation flags:

static

Template:

is_absolute_file_name(File)

Mode and number of proofs:

is_absolute_file_name(+atom) - zero_or_one

`absolute_file_name/2`

Expands a file name to an absolute file path. An environment variable at the beginning of the file name is also expanded.

Compilation flags:

`static`

Template:

`absolute_file_name(File,Path)`

Mode and number of proofs:

`absolute_file_name(+atom,-atom) - one`

`decompose_file_name/3`

Decomposes a file name into its directory (which always ends with a slash; `./` is returned if absent) and its basename (which can be the empty atom).

Compilation flags:

`static`

Template:

`decompose_file_name(File,Directory,Basename)`

Mode and number of proofs:

`decompose_file_name(+atom,?atom,?atom) - one`

`decompose_file_name/4`

Decomposes a file name into its directory (which always ends with a slash; `./` is returned if absent), name (that can be the empty atom), and extension (which starts with a `.` when defined; the empty atom otherwise).

Compilation flags:

`static`

Template:

decompose_file_name(File,Directory,Name,Extension)

Mode and number of proofs:

decompose_file_name(+atom,?atom,?atom,?atom) - one

path_concat/3

Concatenates a path prefix and a path suffix, adding a / separator if required. Returns Suffix when it is an absolute path. Returns Prefix with a trailing / appended if missing when Suffix is the empty atom.

Compilation flags:

static

Template:

path_concat(Prefix,Suffix,Path)

Mode and number of proofs:

path_concat(+atom,+atom,--atom) - one

internal_os_path/2

Converts between the internal path representation (which is backend dependent) and the operating-system native path representation.

Compilation flags:

static

Template:

internal_os_path(InternalPath,OSPath)

Mode and number of proofs:

internal_os_path(+atom,-atom) - one

internal_os_path(-atom,+atom) - one

make_directory/1

Makes a new directory. Succeeds if the directory already exists.

Compilation flags:

static

Template:

make_directory(Directory)

Mode and number of proofs:

make_directory(+atom) - one

make_directory_path/1

Makes a new directory creating all the intermediate directories if necessary. Succeeds if the directory already exists.

Compilation flags:

static

Template:

make_directory_path(Directory)

Mode and number of proofs:

make_directory_path(+atom) - one

delete_directory/1

Deletes an empty directory. Throws an error if the directory does not exist.

Compilation flags:

static

Template:

delete_directory(Directory)

Mode and number of proofs:

delete_directory(+atom) - one_or_error

`change_directory/1`

Changes current working directory. Throws an error if the directory does not exist.

Compilation flags:

`static`

Template:

`change_directory(Directory)`

Mode and number of proofs:

`change_directory(+atom) - one_or_error`

`working_directory/1`

Current working directory.

Compilation flags:

`static`

Template:

`working_directory(Directory)`

Mode and number of proofs:

`working_directory(?atom) - zero_or_one`

`temporary_directory/1`

Temporary directory. Tries first environment variables: `TEMP` and `TMP` on Windows systems; `TMPDIR`, `TMP`, `TEMP`, and `TEMPDIR` on POSIX systems. When not defined, tries default locations. Returns the working directory as last resort.

Compilation flags:

`static`

Template:

temporary_directory(Directory)

Mode and number of proofs:

temporary_directory(?atom) - one

null_device_path/1

Null device path: nul on Windows systems and /dev/null on POSIX systems.

Compilation flags:

static

Template:

null_device_path(Path)

Mode and number of proofs:

null_device_path(?atom) - one

full_device_path/1

Full device path: /dev/full on Linux and BSD systems. Fails on other systems. Experimental.

Compilation flags:

static

Template:

full_device_path(Path)

Mode and number of proofs:

full_device_path(?atom) - zero_or_one

read_only_device_path/1

Read-only device path: /dev/urandom on macOS. Fails on other systems. Experimental.

Compilation flags:

static

Template:

read_only_device_path(Path)

Mode and number of proofs:

read_only_device_path(?atom) - zero_or_one

directory_files/2

Returns a list of all files (including directories, regular files, and hidden directories and files) in a directory. File paths are relative to the directory. Throws an error if the directory does not exist.

Compilation flags:

static

Template:

directory_files(Directory,Files)

Mode and number of proofs:

directory_files(+atom,-list(atom)) - one_or_error

directory_files/3

Returns a list of files filtered using the given list of options. Invalid options are ignored. Default option values are equivalent to directory_files/2. Throws an error if the directory does not exist.

Compilation flags:

static

Template:

directory_files(Directory,Files,Options)

Mode and number of proofs:

directory_files(+atom,-list(atom),+list(compound)) - one_or_error

Remarks:

- Option paths/1: Possible values are relative and absolute. Default is relative.
 - Option type/1: Possible values are all, regular, directory. Default is all.
 - Option extensions/1: Argument is a list of required extensions (using the format '.ext'). Default is the empty list.
 - Option prefixes/1: Argument is a list of required file prefixes (atoms). Default is the empty list.
 - Option suffixes/1: Argument is a list of required file suffixes (atoms). Default is the empty list.
 - Option dot_files/1: Possible values are true and false. Default is true.
-

directory_exists/1

True if the specified directory exists (irrespective of directory permissions).

Compilation flags:

static

Template:

directory_exists(Directory)

Mode and number of proofs:

directory_exists(+atom) - zero_or_one

ensure_directory/1

Ensures that a directory exists, creating it if necessary.

Compilation flags:

static

Template:

ensure_directory(Directory)

Mode and number of proofs:

ensure_directory(+atom) - one

file_exists/1

True if the specified file exists and is a regular file (irrespective of file permissions).

Compilation flags:

static

Template:

file_exists(File)

Mode and number of proofs:

file_exists(+atom) - zero_or_one

file_modification_time/2

File modification time (which can be used for comparison). Throws an error if the file does not exist.

Compilation flags:

static

Template:

file_modification_time(File,Time)

Mode and number of proofs:

file_modification_time(+atom,-integer) - one_or_error

file_size/2

File size (in bytes). Throws an error if the file does not exist.

Compilation flags:

static

Template:

file_size(File,Size)

Mode and number of proofs:

file_size(+atom,-integer) - one_or_error

file_permission/2

True iff the specified file has the specified permission (read, write, or execute). Throws an error if the file does not exist.

Compilation flags:

static

Template:

file_permission(File,Permission)

Mode and number of proofs:

file_permission(+atom,+atom) - zero_or_one_or_error

copy_file/2

Copies a file. Throws an error if the original file does not exist or if the copy cannot be created.

Compilation flags:

static

Template:

copy_file(File,Copy)

Mode and number of proofs:

copy_file(+atom,+atom) - one_or_error

rename_file/2

Renames a file or a directory. Throws an error if the file or directory does not exist.

Compilation flags:

static

Template:

rename_file(Old,New)

Mode and number of proofs:

rename_file(+atom,+atom) - one_or_error

delete_file/1

Deletes a file. Throws an error if the file does not exist.

Compilation flags:

static

Template:

delete_file(File)

Mode and number of proofs:

delete_file(+atom) - one_or_error

ensure_file/1

Ensures that a file exists, creating it if necessary.

Compilation flags:

static

Template:

ensure_file(File)

Mode and number of proofs:

ensure_file(+atom) - one

environment_variable/2

Returns an environment variable value. Fails if the variable does not exist.

Compilation flags:

static

Template:

environment_variable(Variable,Value)

Mode and number of proofs:

`environment_variable(+atom,?atom) - zero_or_one`

`time_stamp/1`

Returns a system-dependent time stamp, which can be used for sorting, but should be regarded otherwise as an opaque term.

Compilation flags:

`static`

Template:

`time_stamp(Time)`

Mode and number of proofs:

`time_stamp(-ground) - one`

`date_time/7`

Returns the current date and time. Note that most backends do not provide sub-second accuracy and in those cases the value of the Milliseconds argument is always zero.

Compilation flags:

`static`

Template:

`date_time(Year,Month,Day,Hours,Minutes,Seconds,Milliseconds)`

Mode and number of proofs:

`date_time(-integer,-integer,-integer,-integer,-integer,-integer,-integer) - one`

cpu_time/1

System cpu time in seconds.

Compilation flags:

static

Template:

cpu_time(Seconds)

Mode and number of proofs:

cpu_time(-number) - one

wall_time/1

Wall time in seconds.

Compilation flags:

static

Template:

wall_time(Seconds)

Mode and number of proofs:

wall_time(-number) - one

operating_system_type/1

Operating system type. Possible values are unix, windows, and unknown.

Compilation flags:

static

Template:

operating_system_type(Type)

Mode and number of proofs:

operating_system_type(?atom) - zero_or_one

`operating_system_name/1`

Operating system name. On POSIX systems, it returns the value of `uname -s`. On Windows systems, it returns 'Windows'.

Compilation flags:

`static`

Template:

`operating_system_name(Name)`

Mode and number of proofs:

`operating_system_name(?atom) - zero_or_one`

`operating_system_machine/1`

Operating system hardware platform. On POSIX systems, it returns the value of `uname -m`. On Windows systems, it returns the value of the `PROCESSOR_ARCHITECTURE` environment variable.

Compilation flags:

`static`

Template:

`operating_system_machine(Machine)`

Mode and number of proofs:

`operating_system_machine(?atom) - zero_or_one`

`operating_system_release/1`

Operating system release. On POSIX systems, it returns the value of `uname -r`. On Windows systems, it uses WMI code.

Compilation flags:

`static`

Template:

`operating_system_release(Release)`

Mode and number of proofs:

`operating_system_release(?atom) - zero_or_one`

`command_line_arguments/1`

Returns a list with the command line arguments that occur after --.

Compilation flags:

`static`

Template:

`command_line_arguments(Arguments)`

Mode and number of proofs:

`command_line_arguments(-list(atom)) - one`

`sleep/1`

Suspends execution the given number of seconds.

Compilation flags:

`static`

Template:

`sleep(Seconds)`

Mode and number of proofs:

`sleep(+number) - one`

Protected predicates

(none)

Private predicates

(none)

Operators

(none)

See also:

os, os_types

1.56 packs

protocol

1.56.1 pack_protocol

Pack specification protocol. Objects implementing this protocol should be named after the pack with a `_pack` suffix and saved in a file with the same name as the object.

Availability:

`logtalk_load(packs(loader))`

Author: Paulo Moura

Version: 0:17:0

Date: 2024-02-29

Compilation flags:

`static`

Dependencies:

(none)

Remarks:

(none)

Inherited public predicates:

(none)

- [Public predicates](#)

- name/1
- description/1
- license/1
- home/1
- version/6
- note/3
- Protected predicates
- Private predicates
- Operators

Public predicates

name/1

Pack name.

Compilation flags:

static

Template:

name(Name)

Mode and number of proofs:

name(?atom) - zero_or_one

description/1

Pack one line description.

Compilation flags:

static

Template:

description(Description)

Mode and number of proofs:

description(?atom) - zero_or_one

license/1

Pack license. Specified using the identifier from the SPDX License List (<https://spdx.org/licenses/>) when possible.

Compilation flags:

static

Template:

license(License)

Mode and number of proofs:

license(?atom) - zero_or_one

home/1

Pack home HTTPS or file URL.

Compilation flags:

static

Template:

home(Home)

Mode and number of proofs:

home(?atom) - zero_or_one

version/6

Table of available versions.

Compilation flags:

static

Template:

version(Version,Status,URL,Checksum,Dependencies,Portability)

Mode and number of proofs:

version(?compound,?atom,-atom,-pair(atom,atom),-list(pair(atom,callable)),?atom) - zero_or_more

```
version(?compound,?atom,-atom,-pair(atom,atom),-list(pair(atom,callable)),-list(atom)) -
zero_or_more
```

Remarks:

- **Version:** This argument uses the same format as entity versions: Major:Minor:Patch. Semantic versioning should be used.
- **Status:** Version development status. E.g stable, rc, beta, alpha, or deprecated.
- **URL:** File URL for a local directory, file URL for a local archive, download HTTPS URL for the pack archive, or download git archive URL for the pack archive.
- **Checksum:** A pair where the key is the hash algorithm and the value is the checksum. Currently, the hash algorithm must be sha256. For file:// URLs of local directories, use none instead of a pair.
- **Dependencies:** Pack dependencies list. Each dependency is a Dependency Operator Version term. Operator is a term comparison operator. Valid Dependency values are Registry::Pack, os(Name,Machine), logtalk, and a backend identifier atom.
- **Portability:** Either the atom all or a list of the supported backend Prolog compilers (using the identifier atoms used by the prolog_dialect flag).
- **Clause order:** Versions must be listed ordered from newest to oldest.

note/3

Table of notes per action and version.

Compilation flags:

```
static
```

Template:

```
note(Action,Version,Note)
```

Mode and number of proofs:

```
note(?atom,?term,-atom) - zero_or_more
```

Remarks:

- **Action:** Possible values are install, update, and uninstall. When unbound, the note apply to all actions.
- **Version:** Version acted on (i.e. version being installed, updated to, or uninstalled). When unbound, the note apply to all versions.
- **Note:** Note to print when performing an action on a pack version.

Protected predicates

(none)

Private predicates

(none)

Operators

(none)

object

1.56.2 packs

Pack handling predicates.

Availability:

logtalk_load(packs(loader))

Author: Paulo Moura

Version: 0:73:0

Date: 2024-03-26

Compilation flags:

static, context_switching_calls

Imports:

public packs_common

public options

Uses:

list

logtalk

os

registries

type

user

Remarks:

(none)

Inherited public predicates:

check_option/1 check_options/1 default_option/1 default_options/1 directory/1 directory/2
help/0 logtalk_packs/0 logtalk_packs/1 option/2 option/3 pin/0 pin/1 pinned/1 prefix/0
prefix/1 readme/1 readme/2 reset/0 setup/0 unpin/0 unpin/1 valid_option/1 valid_options/1
verify_commands_availability/0

- Public predicates

- available/2
- available/1
- available/0
- installed/4
- installed/3
- installed/1
- installed/0
- outdated/4
- outdated/1
- outdated/0
- orphaned/2
- orphaned/0
- versions/3
- describe/2
- describe/1
- search/1
- install/4
- install/3
- install/2
- install/1
- update/3
- update/2
- update/1
- update/0
- uninstall/2
- uninstall/1
- uninstall/0
- clean/2
- clean/1
- clean/0

- save/2
- save/1
- restore/2
- restore/1
- dependents/3
- dependents/2
- dependents/1
- lint/2
- lint/1
- lint/0
- Protected predicates
- Private predicates
- Operators

Public predicates

available/2

Enumerates, by backtracking, all available packs.

Compilation flags:

static

Template:

available(Registry,Pack)

Mode and number of proofs:

available(?atom,?atom) - zero_or_more

Exceptions:

Registry is neither a variable nor an atom:

type_error(atom,Registry)

Pack is neither a variable nor an atom:

type_error(atom,Pack)

available/1

Lists all the packs that are available for installation from the given registry.

Compilation flags:

static

Template:

available(Registry)

Mode and number of proofs:

available(+atom) - one

Exceptions:

Registry is a variable:

instantiation_error

Registry is neither a variable nor an atom:

type_error(atom,Registry)

available/0

Lists all the packs that are available for installation from all defined registries.

Compilation flags:

static

Mode and number of proofs:

available - one

installed/4

Enumerates by backtracking all installed packs.

Compilation flags:

static

Template:

installed(Registry,Pack,Version,Pinned)

Mode and number of proofs:

installed(?atom,?atom,?compound,?boolean) - zero_or_more

Exceptions:

Registry is neither a variable nor an atom:

type_error(atom,Registry)

Pack is neither a variable nor an atom:

type_error(atom,Pack)

Version is neither a variable nor a compound term:

type_error(compound,Version)

Pinned is neither a variable nor a boolean:

type_error(boolean,Pinned)

installed/3

Enumerates by backtracking all installed packs.

Compilation flags:

static

Template:

installed(Registry,Pack,Version)

Mode and number of proofs:

installed(?atom,?atom,?compound) - zero_or_more

Exceptions:

Registry is neither a variable nor an atom:

type_error(atom,Registry)

Pack is neither a variable nor an atom:

type_error(atom,Pack)

Version is neither a variable nor a compound term:

type_error(compound,Version)

installed/1

Lists all the packs that are installed from the given registry. Fails if the registry is unknown.

Compilation flags:

static

Template:

installed(Registry)

Mode and number of proofs:

installed(+atom) - zero_or_one

Exceptions:

Registry is a variable:

instantiation_error

Registry is neither a variable nor an atom:

type_error(atom,Registry)

installed/0

Lists all the packs that are installed.

Compilation flags:

static

Mode and number of proofs:

installed - one

outdated/4

Enumerates by backtracking all installed but outdated packs (together with the current version installed and the latest version available).

Compilation flags:

static

Template:

outdated(Registry,Pack,Version,LatestVersion)

Mode and number of proofs:

outdated(?atom,?atom,?compound,?compound) - zero_or_more

Exceptions:

Registry is neither a variable nor an atom:

type_error(atom,Registry)

Pack is neither a variable nor an atom:

type_error(atom,Pack)

Version is neither a variable nor a compound term:

type_error(compound,Version)

LatestVersion is neither a variable nor a compound term:

type_error(compound,LatestVersion)

outdated/1

Lists all the packs from the given registry that are installed but outdated.

Compilation flags:

static

Template:

outdated(Registry)

Mode and number of proofs:

outdated(+atom) - one

Exceptions:

Registry is neither a variable nor an atom:

type_error(atom,Registry)

outdated/0

Lists all the packs that are installed but outdated.

Compilation flags:

static

Mode and number of proofs:
outdated - one

orphaned/2

Lists all the packs that are installed but whose registry is no longer defined.

Compilation flags:
static

Template:
orphaned(Registry,Pack)
Mode and number of proofs:
orphaned(?atom,?atom) - zero_or_more

Exceptions:
Registry is neither a variable nor an atom:
type_error(atom,Registry)
Pack is neither a variable nor an atom:
type_error(atom,Pack)

orphaned/0

Lists all the packs that are installed but whose registry is no longer defined.

Compilation flags:
static

Mode and number of proofs:
orphaned - one

versions/3

Returns a list of all available pack versions. Fails if the pack is unknown.

Compilation flags:

static

Template:

versions(Registry,Pack,Versions)

Mode and number of proofs:

versions(+atom,+atom,-list) - zero_or_one

Exceptions:

Registry is a variable:

instantiation_error

Registry is neither a variable nor an atom:

type_error(atom,Registry)

Pack is a variable:

instantiation_error

Pack is neither a variable nor an atom:

type_error(atom,Pack)

describe/2

Describes a registered pack, including installed version if applicable. Fails if the pack is unknown.

Compilation flags:

static

Template:

describe(Registry,Pack)

Mode and number of proofs:

describe(+atom,+atom) - zero_or_one

Exceptions:

Registry is a variable:

instantiation_error

Registry is neither a variable nor an atom:

type_error(atom,Registry)

Pack is a variable:

instantiation_error

Pack is neither a variable nor an atom:

type_error(atom,Pack)

describe/1

Describes a registered pack, including installed version if applicable. Fails if the pack is unknown.

Compilation flags:

static

Template:

describe(Pack)

Mode and number of proofs:

describe(+atom) - zero_or_one

Exceptions:

Pack is a variable:

instantiation_error

Pack is neither a variable nor an atom:

type_error(atom,Pack)

search/1

Searches packs whose name or description includes the search term (case sensitive).

Compilation flags:

static

Template:

search(Term)

Mode and number of proofs:

search(+atom) - one

Exceptions:

Term is a variable:

instantiation_error

Term is neither a variable nor an atom:

`type_error(atom,Term)`

install/4

Installs a new pack using the specified options. Fails if the pack is unknown or already installed but not using `update(true)` or `force(true)` options. Fails also if the pack version is unknown.

Compilation flags:

`static`

Template:

`install(Registry,Pack,Version,Options)`

Mode and number of proofs:

`install(+atom,+atom,++compound,++list(compound)) - zero_or_one`

Exceptions:

Registry is a variable:

`instantiation_error`

Registry is neither a variable nor an atom:

`type_error(atom,Registry)`

Pack is a variable:

`instantiation_error`

Pack is neither a variable nor an atom:

`type_error(atom,Pack)`

Version is a variable:

`instantiation_error`

Version is neither a variable nor a valid version:

`type_error(pack_version,Version)`

Options is a variable:

`instantiation_error`

Options is neither a variable nor a list:

`type_error(list,Options)`

An element Option of the list Options is a variable:

`instantiation_error`

An element Option of the list Options is neither a variable nor a compound term:

`type_error(compound,Option)`

An element Option of the list Options is a compound term but not a valid option:

`domain_error(option,Option)`

Remarks:

- `update(Boolean)` option: Update pack if already installed. Default is false. Overrides the `force/1` option.
 - `force(Boolean)` option: Force pack re-installation if already installed. Default is false.
 - `compatible(Boolean)` option: Restrict installation to compatible packs. Default is true.
 - `clean(Boolean)` option: Clean pack archive after installation. Default is false.
 - `verbose(Boolean)` option: Verbose installing steps. Default is false.
 - `checksum(Boolean)` option: Verify pack archive checksum. Default is true.
 - `checksig(Boolean)` option: Verify pack archive signature. Default is false.
 - `curl(Atom)` option: Extra command-line options. Default is ''.
 - `gpg(Atom)` option: Extra command-line options. Default is ''.
 - `tar(Atom)` option: Extra command-line options. Default is ''.
-

install/3

Installs the specified version of a pack from the given registry using default options. Fails if the pack is already installed or unknown. Fails also if the pack version is unknown.

Compilation flags:

`static`

Template:

`install(Registry,Pack,Version)`

Mode and number of proofs:

`install(+atom,+atom,?compound) - zero_or_one`

Exceptions:

Registry is a variable:

`instantiation_error`

Registry is neither a variable nor an atom:

`type_error(atom,Registry)`

Pack is a variable:

`instantiation_error`

Pack is neither a variable nor an atom:

`type_error(atom,Pack)`

Version is a variable:

`instantiation_error`

Version is neither a variable nor a valid version:

`type_error(pack_version,Version)`

install/2

Installs the latest version of a pack from the given registry using default options. Fails if the pack is already installed or unknown.

Compilation flags:

static

Template:

install(Registry,Pack)

Mode and number of proofs:

install(+atom,+atom) - zero_or_one

Exceptions:

Registry is a variable:

instantiation_error

Registry is neither a variable nor an atom:

type_error(atom,Registry)

Pack is a variable:

instantiation_error

Pack is neither a variable nor an atom:

type_error(atom,Pack)

install/1

Installs a pack (if its name is unique among all registries) using default options. Fails if the pack is already installed or unknown. Fails also if the pack is available from multiple registries.

Compilation flags:

static

Template:

install(Pack)

Mode and number of proofs:

install(+atom) - zero_or_one

Exceptions:

Pack is a variable:

instantiation_error

Pack is not an atom:

```
type_error(atom,Pack)
```

update/3

Updates an outdated pack to the specified version using the specified options. Fails if the pack or the pack version is unknown or if the pack is not installed. Fails also if the pack is orphaned or pinned and not using a force(true) option.

Compilation flags:

```
static
```

Template:

```
update(Pack,Version,Options)
```

Mode and number of proofs:

```
update(+atom,++callable,++list(callable)) - zero_or_one
```

Exceptions:

Pack is a variable:

```
instantiation_error
```

Pack is neither a variable nor an atom:

```
type_error(atom,Pack)
```

Version is a variable:

```
instantiation_error
```

Version is neither a variable nor a valid version:

```
type_error(pack_version,Version)
```

Options is a variable:

```
instantiation_error
```

Options is neither a variable nor a list:

```
type_error(list,Options)
```

An element Option of the list Options is a variable:

```
instantiation_error
```

An element Option of the list Options is neither a variable nor a compound term:

```
type_error(compound,Option)
```

An element Option of the list Options is a compound term but not a valid option:

```
domain_error(option,Option)
```

Remarks:

- install(Boolean) option: Install pack latest version if not already installed. Default is false.
- force(Boolean) option: Force update if the pack is pinned or breaks installed packs. Default is false.
- compatible(Boolean) option: Restrict updating to compatible packs. Default is true.

- `clean(Boolean)` option: Clean pack archive after updating. Default is false.
 - `verbose(Boolean)` option: Verbose updating steps. Default is false.
 - `checksum(Boolean)` option: Verify pack archive checksum. Default is true.
 - `checksig(Boolean)` option: Verify pack archive signature. Default is false.
 - `curl(Atom)` option: Extra command-line options. Default is ''.
 - `gpg(Atom)` option: Extra command-line options. Default is ''.
 - `tar(Atom)` option: Extra command-line options. Default is ''.
-

`update/2`

Updates an outdated pack to its latest version using the specified options. Fails if the pack is orphaned, unknown, or not installed. Fails also if the pack is pinned and not using a `force(true)` option.

Compilation flags:

`static`

Template:

`update(Pack,Options)`

Mode and number of proofs:

`update(+atom,++list(callable)) - zero_or_one`

Exceptions:

Pack is a variable:

`instantiation_error`

Pack is neither a variable nor an atom:

`type_error(atom,Pack)`

Options is a variable:

`instantiation_error`

Options is neither a variable nor a list:

`type_error(list,Options)`

An element Option of the list Options is a variable:

`instantiation_error`

An element Option of the list Options is neither a variable nor a compound term:

`type_error(compound,Option)`

An element Option of the list Options is a compound term but not a valid option:

`domain_error(option,Option)`

Remarks:

- `install(Boolean)` option: Install pack latest version if not already installed. Default is false.

- `force(Boolean)` option: Force update if the pack is pinned or breaks installed packs. Default is false.
- `compatible(Boolean)` option: Restrict updating to compatible packs. Default is true.
- `clean(Boolean)` option: Clean pack archive after updating. Default is false.
- `verbose(Boolean)` option: Verbose updating steps. Default is false.
- `checksum(Boolean)` option: Verify pack archive checksum. Default is true.
- `checksig(Boolean)` option: Verify pack archive signature. Default is false.
- `curl(Atom)` option: Extra command-line options. Default is ''.
- `gpg(Atom)` option: Extra command-line options. Default is ''.
- `tar(Atom)` option: Extra command-line options. Default is ''.

update/1

Updates an outdated pack to its latest version using default options. Fails if the pack is pinned, orphaned, not installed, unknown, or breaks installed packs.

Compilation flags:

`static`

Template:

`update(Pack)`

Mode and number of proofs:

`update(+atom) - zero_or_one`

Exceptions:

Pack is a variable:

`instantiation_error`

Pack is neither a variable nor an atom:

`type_error(atom,Pack)`

update/0

Updates all outdated packs (that are not pinned) using default options.

Compilation flags:

`static`

Mode and number of proofs:

update - zero_or_one

uninstall/2

Uninstalls a pack using the specified options. Fails if the pack is unknown or not installed. Fails also if the pack is pinned or have dependents and not using a force(true) option.

Compilation flags:

static

Template:

uninstall(Pack,Options)

Mode and number of proofs:

uninstall(+atom,++list(compound)) - zero_or_one

Exceptions:

Pack is a variable:

instantiation_error

Pack is neither a variable nor an atom:

type_error(atom,Pack)

Options is a variable:

instantiation_error

Options is neither a variable nor a list:

type_error(list,Options)

An element Option of the list Options is a variable:

instantiation_error

An element Option of the list Options is neither a variable nor a compound term:

type_error(compound,Option)

An element Option of the list Options is a compound term but not a valid option:

domain_error(option,Option)

Remarks:

- force(Boolean) option: Force deletion if the pack is pinned. Default is false.
 - clean(Boolean) option: Clean pack archive after deleting. Default is false.
 - verbose(Boolean) option: Verbose uninstalling steps. Default is false.
-

uninstall/1

Uninstalls a pack using default options. Fails if the pack is pinned, have dependents, not installed, or unknown.

Compilation flags:

static

Template:

uninstall(Pack)

Mode and number of proofs:

uninstall(+atom) - zero_or_one

Exceptions:

Pack is a variable:

instantiation_error

Pack is neither a variable nor an atom:

type_error(atom,Pack)

uninstall/0

Uninstalls all packs using the force(true) option.

Compilation flags:

static

Mode and number of proofs:

uninstall - zero_or_one

clean/2

Cleans all pack archives. Fails if the the pack is unknown.

Compilation flags:

static

Template:

`clean(Registry,Pack)`

Mode and number of proofs:

`clean(+atom,+atom) - zero_or_one`

Exceptions:

Registry is a variable:

`instantiation_error`

Registry is neither a variable nor an atom:

`type_error(atom,Registry)`

Pack is a variable:

`instantiation_error`

Pack is neither a variable nor an atom:

`type_error(atom,Pack)`

`clean/1`

Cleans all pack archives. Fails if the pack is unknown.

Compilation flags:

`static`

Template:

`clean(Pack)`

Mode and number of proofs:

`clean(+atom) - zero_or_one`

Exceptions:

Pack is a variable:

`instantiation_error`

Pack is neither a variable nor an atom:

`type_error(atom,Pack)`

clean/0

Cleans all archives for all packs.

Compilation flags:

static

Mode and number of proofs:

clean - one

save/2

Saves a list of all installed packs and registries plus pinning status to a file using the given options. Registries without installed packs are saved when using the option `save(all)` and skipped when using the option `save(installed)` (default).

Compilation flags:

static

Template:

`save(File,Options)`

Mode and number of proofs:

`save(+atom,++list(compound)) - one_or_error`

Exceptions:

File is a variable:

`instantiation_error`

File is neither a variable nor an atom:

`type_error(atom,File)`

File is an existing file but cannot be written:

`permission_error(open,source_sink,File)`

Options is a variable:

`instantiation_error`

Options is neither a variable nor a list:

`type_error(list,Options)`

An element Option of the list Options is a variable:

`instantiation_error`

An element Option of the list Options is neither a variable nor a compound term:

`type_error(compound,Option)`

An element Option of the list Options is a compound term but not a valid option:

`domain_error(option,Option)`

save/1

Saves a list of all installed packs and their registries plus pinning status to a file using default options.

Compilation flags:

static

Template:

save(File)

Mode and number of proofs:

save(+atom) - one_or_error

Exceptions:

File is a variable:

instantiation_error

File is neither a variable nor an atom:

type_error(atom,File)

File is an existing file but cannot be written:

permission_error(open,source_sink,File)

restore/2

Restores a list of registries and packs plus their pinning status from a file using the given options. Fails if restoring is not possible.

Compilation flags:

static

Template:

restore(File,Options)

Mode and number of proofs:

restore(+atom,++list(compound)) - zero_or_one_or_error

Exceptions:

File is a variable:

instantiation_error

File is neither a variable nor an atom:


```

    type_error(atom,File)
File is an atom but not an existing file:
    existence_error(file,File)
File is an existing file but cannot be read:
    permission_error(open,source_sink,File)
Options is a variable:
    instantiation_error
Options is neither a variable nor a list:
    type_error(list,Options)
An element Option of the list Options is a variable:
    instantiation_error
An element Option of the list Options is neither a variable nor a compound term:
    type_error(compound,Option)
An element Option of the list Options is a compound term but not a valid option:
    domain_error(option,Option)

```

Remarks:

- `force(Boolean)` option: Force restoring if a registry is already defined or a pack is already installed. Default is true.
- `compatible(Boolean)` option: Restrict installation to compatible packs. Default is true.
- `clean(Boolean)` option: Clean registry and pack archives after restoring. Default is false.
- `verbose(Boolean)` option: Verbose restoring steps. Default is false.
- `checksum(Boolean)` option: Verify pack archive checksums. Default is true.
- `checksig(Boolean)` option: Verify pack archive signatures. Default is false.
- `curl(Atom)` option: Extra command-line options. Default is ''.
- `gpg(Atom)` option: Extra command-line options. Default is ''.
- `tar(Atom)` option: Extra command-line options. Default is ''.

restore/1

Restores a list of registries and packs plus their pinning status from a file using default options. Fails if restoring is not possible.

Compilation flags:

```
static
```

Template:

```
restore(File)
```

Mode and number of proofs:

```
restore(+atom) - zero_or_one_or_error
```

Exceptions:

File is a variable:

`instantiation_error`

File is neither a variable nor an atom:

`type_error(atom,File)`

File is an atom but not an existing file:

`existence_error(file,File)`

File is an existing file but cannot be read:

`permission_error(open,source_sink,File)`

`dependents/3`

Returns a list of all installed packs that depend on the given pack from the given registry. Fails if the pack is unknown.

Compilation flags:

`static`

Template:

`dependents(Registry,Pack,Dependents)`

Mode and number of proofs:

`dependents(+atom,+atom,-list(atom)) - zero_or_one`

Exceptions:

Registry is a variable:

`instantiation_error`

Registry is neither a variable nor an atom:

`type_error(atom,Registry)`

Pack is a variable:

`instantiation_error`

Pack is neither a variable nor an atom:

`type_error(atom,Pack)`

dependents/2

Prints a list of all installed packs that depend on the given pack from the given registry. Fails if the pack is unknown.

Compilation flags:

static

Template:

dependents(Registry,Pack)

Mode and number of proofs:

dependents(+atom,+atom) - zero_or_one

Exceptions:

Registry is a variable:

instantiation_error

Registry is neither a variable nor an atom:

type_error(atom,Registry)

Pack is a variable:

instantiation_error

Pack is neither a variable nor an atom:

type_error(atom,Pack)

dependents/1

Prints a list of all installed packs that depend on the given pack if unique from all defined registries. Fails if the pack is unknown or available from multiple registries.

Compilation flags:

static

Template:

dependents(Pack)

Mode and number of proofs:

dependents(+atom) - zero_or_one

Exceptions:

Pack is a variable:

instantiation_error

Pack is neither a variable nor an atom:

`type_error(atom,Pack)`

`lint/2`

Checks the pack specification. Fails if the pack is unknown or if linting detects errors.

Compilation flags:

`static`

Template:

`lint(Registry,Pack)`

Mode and number of proofs:

`lint(+atom,+atom) - zero_or_one`

Exceptions:

Registry is a variable:

`instantiation_error`

Registry is neither a variable nor an atom:

`type_error(atom,Registry)`

Pack is a variable:

`instantiation_error`

Pack is neither a variable nor an atom:

`type_error(atom,Pack)`

`lint/1`

Checks the pack specification. Fails if the pack is unknown, or available from multiple registries, or if linting detects errors.

Compilation flags:

`static`

Template:

`lint(Pack)`

Mode and number of proofs:

`lint(+atom) - zero_or_one`

Exceptions:

Pack is a variable:

instantiation_error

Pack is neither a variable nor an atom:

type_error(atom,Pack)

lint/0

Checks all pack specifications.

Compilation flags:

static

Mode and number of proofs:

lint - one

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

category

1.56.3 packs_common

Common predicates for the packs tool objects.

Availability:

logtalk_load(packs(loader))

Author: Paulo Moura

Version: 0:31:0

Date: 2023-11-23

Compilation flags:

static

Provides:

type::type/1
type::check/2

Uses:

list
logtalk
os
type
user

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
 - setup/0
 - reset/0
 - verify_commands_availability/0
 - help/0
 - pin/1
 - pin/0
 - unpin/1
 - unpin/0
 - pinned/1
 - directory/2
 - directory/1
 - readme/2
 - readme/1
 - logtalk_packs/1
 - logtalk_packs/0

- prefix/1
- prefix/0
- Protected predicates
 - readme_file_path/2
 - print_readme_file_path/1
 - command/2
 - load_registry/1
 - tar_command/1
 - supported_archive/1
 - supported_url_archive/1
 - decode_url_spaces/2
- Private predicates
- Operators

Public predicates

setup/0

Ensures that registries and packs directory structure exists. Preserves any defined registries and installed packs.

Compilation flags:

static

Mode and number of proofs:

setup - one

reset/0

Resets registries and packs directory structure. Deletes any defined registries and installed packs.

Compilation flags:

static

Mode and number of proofs:

reset - one

verify_commands_availability/0

Verifies required shell commands availability. Fails printing an error message if a command is missing.

Compilation flags:

static

Mode and number of proofs:

verify_commands_availability - zero_or_one

help/0

Provides help about the main predicates.

Compilation flags:

static

Mode and number of proofs:

help - one

pin/1

Pins a resource (pack or registry) preventing it from being updated, uninstalled, or deleted. Fails if the resource is not found.

Compilation flags:

static

Template:

pin(Resource)

Mode and number of proofs:

pin(+atom) - zero_or_one

Exceptions:

Resource is a variable:

instantiation_error

Resource is neither a variable nor an atom:

type_error(atom,Resource)

pin/0

Pins all resource (packs or registries) preventing them from being updated, uninstalled, or deleted. Note that resources added after calling this predicate will not be pinned.

Compilation flags:

static

Mode and number of proofs:

pin - one

unpin/1

Unpins a resource (pack or registry), allowing it to be updated, uninstalled, or deleted. Fails if the resource is not found.

Compilation flags:

static

Template:

unpin(Resource)

Mode and number of proofs:

unpin(+atom) - zero_or_one

Exceptions:

Resource is a variable:

instantiation_error

Resource is neither a variable nor an atom:

type_error(atom,Resource)

unpin/0

Unpins all resources (packs or registries), allowing them to be updated, uninstalled, or deleted.

Compilation flags:

static

Mode and number of proofs:

unpin - one

pinned/1

True iff the resource (pack or registry) is defined or installed and if it is pinned.

Compilation flags:

static

Template:

pinned(Resource)

Mode and number of proofs:

pinned(+atom) - zero_or_one

Exceptions:

Resource is a variable:

instantiation_error

Resource is neither a variable nor an atom:

type_error(atom,Resource)

directory/2

Enumerates by backtracking all packs or registries and respective installation or definition directories (using the internal backend format).

Compilation flags:

static

Template:

directory(Resource,Directory)

Mode and number of proofs:

directory(?atom,?atom) - zero_or_more

Exceptions:

Resource is neither a variable nor an atom:

type_error(atom,Resource)

Directory is neither a variable nor an atom:

type_error(atom,Directory)

directory/1

Prints the directory where the registry or the pack is installed (using the native operating-system format).

Compilation flags:

static

Template:

directory(Resource)

Mode and number of proofs:

directory(+atom) - zero_or_one

Exceptions:

Resource is a variable:

instantiate_error

Resource is neither a variable nor an atom:

type_error(atom,Resource)

readme/2

Returns the path to the resource (pack or registry) readme file (using the internal backend format). Fails if the resource is not defined or installed or if no readme file is found for it.

Compilation flags:

static

Template:

readme(Resource,ReadMeFile)

Mode and number of proofs:

readme(+atom,-atom) - zero_or_one

Exceptions:

Resource is a variable:

instantiation_error

Resource is neither a variable nor an atom:

type_error(atom,Resource)

ReadMeFile is neither a variable nor an atom:

type_error(atom,ReadMeFile)

readme/1

Prints the path to the resource (pack or registry) readme file (using the native operating-system format). Fails if the resource is not defined or installed or if no readme file is found for it.

Compilation flags:

static

Template:

readme(Resource)

Mode and number of proofs:

readme(+atom) - zero_or_one

Exceptions:

Resource is a variable:

instantiation_error

Resource is neither a variable nor an atom:

type_error(atom,Resource)

logtalk_packs/1

Returns the directory prefix (using the internal backend format) where the registries, packs, and archives are installed.

Compilation flags:

static

Template:

logtalk_packs(LogtalkPacks)

Mode and number of proofs:

logtalk_packs(-atom) - one

Exceptions:

LogtalkPacks is neither a variable nor an atom:

type_error(atom,LogtalkPacks)

logtalk_packs/0

Prints the directory prefix (using the native operating-system format) where the registries, packs, and archives are installed.

Compilation flags:

static

Mode and number of proofs:

logtalk_packs - one

prefix/1

Returns the directory prefix (using the internal backend format) where the registries or packs are installed.

Compilation flags:

static

Template:

prefix(Prefix)

Mode and number of proofs:

prefix(-atom) - one

Exceptions:

Prefix is neither a variable nor an atom:

type_error(atom,Prefix)

prefix/0

Prints the directory prefix (using the native operating-system format) where the registries or packs are installed.

Compilation flags:

static

Mode and number of proofs:

prefix - one

Protected predicates

readme_file_path/2

Returns the absolute path for the given directory readme file if it exists.

Compilation flags:

static

Template:

readme_file_path(Directory,ReadMeFile)

Mode and number of proofs:

readme_file_path(+atom,-atom) - zero_or_one

Remarks:

- Valid file names: Case variations of README and NOTES with or without a .md or .txt extension. The recommended file name is README.md.
-

`print_readme_file_path/1`

Prints the absolute path for the given directory readme file if it exists. Succeeds otherwise.

Compilation flags:

`static`

Template:

`print_readme_file_path(Directory)`

Mode and number of proofs:

`print_readme_file_path(+atom) - one`

`command/2`

Executes a shell command. Prints an error message and fails if the command fails.

Compilation flags:

`static`

Template:

`command(Command,FailureMessage)`

Mode and number of proofs:

`command(+atom,@nonvar) - zero_or_one`

`load_registry/1`

Loads all registry files from the given directory.

Compilation flags:

`static`

Template:

`load_registry(Directory)`

Mode and number of proofs:

`load_registry(+atom) - zero_or_one`

tar_command/1

Returns the name of the tar command to be used depending on the operating-system.

Compilation flags:

static

Template:

tar_command(Command)

Mode and number of proofs:

tar_command(-atom) - one

supported_archive/1

True iff the archive format is supported.

Compilation flags:

static

Template:

supported_archive(Extension)

Mode and number of proofs:

supported_archive(+atom) - zero_or_one

supported_url_archive/1

True iff the URL archive is supported.

Compilation flags:

static

Template:

supported_url_archive(URL)

Mode and number of proofs:

supported_url_archive(+atom) - zero_or_one

`decode_url_spaces/2`

Decodes encoded spaces (%20) in URLs to spaces.

Compilation flags:

`static`

Template:

`decode_url_spaces(URL,Decoded)`

Mode and number of proofs:

`decode_url_spaces(+atom,-atom) - one`

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

category

1.56.4 packs_messages

Packs default message translations.

Availability:

`logtalk_load(packs(loader))`

Author: Paulo Moura

Version: 0:33:1

Date: 2024-03-29

Compilation flags:

`static`

Provides:

`logtalk::message_prefix_stream/4`

`logtalk::message_tokens//2`

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

object

1.56.5 packs_specs_hook

Hook object for filtering registry and pack specification file contents.

Availability:

logtalk_load(packs(loader))

Author: Paulo Moura

Version: 0:13:0

Date: 2022-06-28

Compilation flags:

static, context_switching_calls

Implements:

public expanding

Uses:

character

logtalk

Remarks:

(none)

Inherited public predicates:

goal_expansion/2 term_expansion/2

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

object

1.56.6 registries

Registry handling predicates.

Availability:

```
logtalk_load(packs(loader))
```

Author: Paulo Moura

Version: 0:58:0

Date: 2024-03-25

Compilation flags:

```
static, context_switching_calls
```

Imports:

```
public packs_common
```

```
public options
```

Uses:

```
list
```

```
logtalk
```

```
os
```

```
type
```

```
user
```

Remarks:

```
(none)
```

Inherited public predicates:

```
check_option/1 check_options/1 default_option/1 default_options/1 directory/1 directory/2  
help/0 logtalk_packs/0 logtalk_packs/1 option/2 option/3 pin/0 pin/1 pinned/1 prefix/0  
prefix/1 readme/1 readme/2 reset/0 setup/0 unpin/0 unpin/1 valid_option/1 valid_options/1  
verify_commands_availability/0
```

- Public predicates

- list/0

- describe/1

- defined/4

- add/3

- add/2

- add/1

- update/2
- update/1
- update/0
- delete/2
- delete/1
- delete/0
- clean/1
- clean/0
- provides/2
- lint/1
- lint/0
- Protected predicates
- Private predicates
- Operators

Public predicates

list/0

Prints a list of all defined registries, including how defined (git, archive, or directory) and if they are pinned.

Compilation flags:

static

Mode and number of proofs:

list - one

describe/1

Prints all registry entries.

Compilation flags:

static

Template:

describe(Registry)

Mode and number of proofs:

describe(+atom) - one

Exceptions:

Registry is a variable:

instantiation_error

Registry is neither a variable nor an atom:

type_error(atom,Registry)

defined/4

Enumerates by backtracking all defined registries, their definition URL, how they are defined (git, archive, or directory), and if they are pinned.

Compilation flags:

static

Template:

defined(Registry,URL,HowDefined,Pinned)

Mode and number of proofs:

defined(?atom,?atom,?atom,?boolean) - zero_or_more

Exceptions:

Registry is neither a variable nor an atom:

type_error(atom,Registry)

URL is neither a variable nor an atom:

type_error(atom,URL)

HowDefined is neither a variable nor an atom:

type_error(atom,HowDefined)

Pinned is neither a variable nor a boolean:

type_error(boolean,Pinned)

add/3

Adds a new registry using the given options. Fails if the registry cannot be added or if it is already defined but not using `update(true)` or `force(true)` options. A `file://` URL can be used for a local directory.

Compilation flags:

`static`

Template:

`add(Registry,URL,Options)`

Mode and number of proofs:

`add(+atom,+atom,++list(compound)) - zero_or_one`

Exceptions:

Registry is a variable:

`instantiation_error`

Registry is neither a variable nor an atom:

`type_error(atom,Registry)`

URL is a variable:

`instantiation_error`

URL is neither a variable nor an atom:

`type_error(atom,URL)`

Options is a variable:

`instantiation_error`

Options is neither a variable nor a list:

`type_error(list,Options)`

An element Option of the list Options is a variable:

`instantiation_error`

An element Option of the list Options is neither a variable nor a compound term:

`type_error(compound,Option)`

An element Option of the list Options is a compound term but not a valid option:

`domain_error(option,Option)`

Remarks:

- Registry name: Must be the URL basename when using a git URL or a local directory URL. Must also be the declared registry name in the registry specification object.
- HTTPS URLs: Must end with either a `.git` extension or an archive extension.
- `update(Boolean)` option: Update registry if already defined. Default is `false`. Overrides the `force/1` option.
- `force(Boolean)` option: Force registry re-installation if already defined by first deleting the previous installation. Default is `false`.
- `clean(Boolean)` option: Clean registry archive after updating. Default is `false`.

- verbose(Boolean) option: Verbose adding steps. Default is false.
 - curl(Atom) option: Extra command-line options. Default is ''.
 - gpg(Atom) option: Extra command-line options. Default is ''.
 - tar(Atom) option: Extra command-line options. Default is ''.
-

add/2

Adds a new registry using default options. Fails if the registry cannot be added or if it is already defined. HTTPS URLs must end with either a .git extension or a an archive extension. A file:// URL can be used for a local directory.

Compilation flags:

static

Template:

add(Registry,URL)

Mode and number of proofs:

add(+atom,+atom) - zero_or_one

Exceptions:

Registry is a variable:

instantiation_error

Registry is neither a variable nor an atom:

type_error(atom,Registry)

URL is a variable:

instantiation_error

URL is neither a variable nor an atom:

type_error(atom,URL)

Remarks:

- Registry name: Must be the URL basename when using a git URL or a local directory URL. Must also be the declared registry name in the registry specification object.
-

add/1

Adds a new registry from a git cloning or local directory URL using default options. Fails if the registry cannot be added or if it is already defined. HTTPS URLs must end with a .git extension. A file:// URL can be used for a local directory.

Compilation flags:

static

Template:

add(URL)

Mode and number of proofs:

add(+atom) - zero_or_one

Exceptions:

URL is a variable:

instantiation_error

URL is neither a variable nor an atom:

type_error(atom,URL)

Remarks:

- Limitations: Cannot be used for archive download URLs.
 - Registry name: Taken from the URL basename.
-

update/2

Updates a defined registry using the specified options. Fails if the registry is not defined.

Compilation flags:

static

Template:

update(Registry,Options)

Mode and number of proofs:

update(+atom,++list(compound)) - zero_or_one

Exceptions:

Registry is a variable:

instantiation_error

Registry is neither a variable nor an atom:

```
type_error(atom,Registry)
Options is a variable:
  instantiation_error
Options is neither a variable nor a list:
  type_error(list,Options)
An element Option of the list Options is a variable:
  instantiation_error
An element Option of the list Options is neither a variable nor a compound term:
  type_error(compound,Option)
An element Option of the list Options is a compound term but not a valid option:
  domain_error(option,Option)
```

Remarks:

- force(Boolean) option: Force update if the registry is pinned. Default is false.
 - clean(Boolean) option: Clean registry archive after updating. Default is false.
 - verbose(Boolean) option: Verbose updating steps. Default is false.
 - curl(Atom) option: Extra command-line options. Default is ''.
 - gpg(Atom) option: Extra command-line options. Default is ''.
 - tar(Atom) option: Extra command-line options. Default is ''.
-

update/1

Updates a defined registry using default options. Fails if the registry is not defined.

Compilation flags:

```
static
```

Template:

```
update(Registry)
```

Mode and number of proofs:

```
update(+atom) - zero_or_one
```

Exceptions:

Registry is a variable:

```
instantiation_error
```

Registry is neither a variable nor an atom:

```
type_error(atom,Registry)
```

update/0

Updates all defined registries using default options.

Compilation flags:

static

Mode and number of proofs:

update - zero_or_one

delete/2

Deletes a registry using the specified options (if not pinned).

Compilation flags:

static

Template:

delete(Registry,Options)

Mode and number of proofs:

delete(+atom,++list(compound)) - zero_or_one

Exceptions:

Registry is a variable:

instantiation_error

Registry is neither a variable nor an atom:

type_error(atom,Registry)

Options is a variable:

instantiation_error

Options is neither a variable nor a list:

type_error(list,Options)

An element Option of the list Options is a variable:

instantiation_error

An element Option of the list Options is neither a variable nor a compound term:

type_error(compound,Option)

An element Option of the list Options is a compound term but not a valid option:

domain_error(option,Option)

Remarks:

- `force(Boolean)` option: Force deletion if the registry is pinned or there are installed registry packs. Default is false.
 - `clean(Boolean)` option: Clean registry archive after deleting. Default is false.
 - `verbose(Boolean)` option: Verbose deleting steps. Default is false.
 - `curl(Atom)` option: Extra command-line options. Default is ''.
 - `gpg(Atom)` option: Extra command-line options. Default is ''.
 - `tar(Atom)` option: Extra command-line options. Default is ''.
-

`delete/1`

Deletes a registry using default options.

Compilation flags:

`static`

Template:

`delete(Registry)`

Mode and number of proofs:

`delete(+atom) - zero_or_one`

Exceptions:

Registry is a variable:

`instantiation_error`

Registry is neither a variable nor an atom:

`type_error(atom,Registry)`

`delete/0`

Deletes all registries using the `force(true)` option.

Compilation flags:

`static`

Mode and number of proofs:

`delete - zero_or_one`

clean/1

Cleans all registry archives. Fails if the registry is not defined.

Compilation flags:

static

Template:

clean(Registry)

Mode and number of proofs:

clean(+atom) - zero_or_one

Exceptions:

Registry is a variable:

instantiation_error

Registry is neither a variable nor an atom:

type_error(atom,Registry)

clean/0

Cleans all archives for all registries.

Compilation flags:

static

Mode and number of proofs:

clean - one

provides/2

Enumerates by backtracking all packs provided by a registry.

Compilation flags:

static

Template:

provides(Registry,Pack)

Mode and number of proofs:

provides(?atom,?atom) - zero_or_more

Exceptions:

Registry is neither a variable nor an atom:

type_error(atom,Registry)

Pack is neither a variable nor an atom:

type_error(atom,Pack)

lint/1

Checks the registry specification. Fails if the registry is not defined or if linting detects errors.

Compilation flags:

static

Template:

lint(Registry)

Mode and number of proofs:

lint(+atom) - zero_or_one

Exceptions:

Registry is a variable:

instantiation_error

Registry is neither a variable nor an atom:

type_error(atom,Registry)

lint/0

Checks all registry specifications.

Compilation flags:

static

Mode and number of proofs:

lint - one

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

object

1.56.7 registry_loader_hook

Hook object for filtering registry loader file contents.

Availability:

`logtalk_load(packs(loader))`

Author: Paulo Moura

Version: 0:13:0

Date: 2022-11-20

Compilation flags:

`static, context_switching_calls`

Implements:

`public expanding`

Uses:

`character`

`logtalk`

Remarks:

(none)

Inherited public predicates:

`goal_expansion/2 term_expansion/2`

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

protocol

1.56.8 registry__protocol

Registry specification protocol. Objects implementing this protocol should be named after the pack with a `_registry` suffix and saved in a file with the same name as the object.

Availability:

`logtalk_load(packs(loader))`

Author: Paulo Moura

Version: 0:12:0

Date: 2022-06-28

Compilation flags:

`static`

Dependencies:

(none)

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
 - name/1
 - description/1
 - home/1
 - clone/1
 - archive/1
 - note/2
- Protected predicates
- Private predicates
- Operators

Public predicates

name/1

Registry name. Preferably a valid unquoted atom.

Compilation flags:

static

Template:

name(Name)

Mode and number of proofs:

name(?atom) - zero_or_one

description/1

Registry one line description.

Compilation flags:

static

Template:

description(Description)

Mode and number of proofs:

description(?atom) - zero_or_one

home/1

Registry home HTTPS or file URL.

Compilation flags:

static

Template:

home(Home)

Mode and number of proofs:

home(?atom) - zero_or_one

clone/1

Registry git clone HTTPS URL (must end with the .git extension). Git repos should have the same name as the registry.

Compilation flags:

static

Template:

clone(URL)

Mode and number of proofs:

clone(?atom) - zero_or_one

archive/1

Registry archive download HTTPS URL.

Compilation flags:
static

Template:
archive(URL)

Mode and number of proofs:
archive(?atom) - zero_or_one

note/2

Table of notes per action.

Compilation flags:
static

Template:
note(Action,Note)

Mode and number of proofs:
note(?atom,-atom) - zero_or_more

Remarks:

- Action: Possible values are add, update, and delete. When unbound, the note apply to all actions.
 - Note: Note to print when performing an action on a registry.
-

Protected predicates

(none)

Private predicates

(none)

Operators

(none)

1.57 pddl_parser

object

1.57.1 pddl

Simple parser of PDDL 3.0 files.

Availability:

```
logtalk_load(pddl_parser(loader))
```

Author: Robert Sasak, Charles University in Prague. Adapted to Logtalk by Paulo Moura.

Version: 1:2:2

Date: 2024-03-14

Compilation flags:

```
static, context_switching_calls
```

Imports:

```
public read_file
```

Uses:

```
user
```

Remarks:

(none)

Inherited public predicates:

```
read_file/2
```

- Public predicates
 - parse_domain/3
 - parse_domain/2
 - parse_problem/2
 - parse_problem/3
- Protected predicates
- Private predicates
- Operators

Public predicates

parse_domain/3

Parses a PDDL 3.0 domain file, returning a compound term representing its contents and rest of the file. Useful when domain and problem are in one file.

Compilation flags:

static

Template:

parse_domain(File,Output,RestOfFile)

Mode and number of proofs:

parse_domain(+atom,-compound,-list(atom)) - one

parse_domain/2

Parses a PDDL 3.0 domain file, returning a compound term representing its contents.

Compilation flags:

static

Template:

parse_domain(File,Output)

Mode and number of proofs:

parse_domain(+atom,-compound) - one

parse_problem/2

Parses a PDDL 3.0 problem file, returning a compound term representing its contents.

Compilation flags:

static

Template:

parse_problem(File,Output)

Mode and number of proofs:

parse_problem(+atom,-compound) - one

parse_problem/3

Parses a PDDL 3.0 problem file, returning a compound term representing its contents and rest of the file. Useful when domain and problem are in one file.

Compilation flags:

static

Template:

parse_problem(File,Output,RestOfFile)

Mode and number of proofs:

parse_problem(+atom,-compound,-list(atom)) - one

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

category

1.57.2 read_file

Utility predicates for parsing a file as a list of atoms.

Availability:

logtalk_load(pddl_parser(loader))

Author: Robert Sasak, Charles University in Prague. Adapted to Logtalk by Paulo Moura.

Version: 1:0:0

Date: 2011-08-04

Compilation flags:

static

Dependencies:

(none)

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
 - read_file/2
- Protected predicates
- Private predicates
- Operators

Public predicates

`read_file/2`

Reads a file character by character, parsing it into a list of atoms.

Compilation flags:

`static`

Template:

`read_file(File,List)`

Mode and number of proofs:

`read_file(+atom,-list(atom)) - one`

Protected predicates

(none)

Private predicates

(none)

Operators

(none)

1.58 ports_profiler

object

1.58.1 ports_profiler

Predicate execution box model port profiler.

Availability:

`logtalk_load(ports_profiler(loader))`

Author: Paulo Moura

Version: 1:13:0

Date: 2023-10-02

Compilation flags:

static, context_switching_calls

Provides:

logtalk::debug_handler_provider/1

logtalk::debug_handler/2

Uses:

logtalk

user

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
 - data/0
 - data/1
 - data/2
 - reset/0
 - reset/1
 - port/5
 - clause_location/6
 - clause/5
- Protected predicates
- Private predicates
 - clause_location_/6
 - port_/5
 - clause_/5
 - entity_defines_/2
- Operators

Public predicates

data/0

Prints a table with all port profiling data.

Compilation flags:
static

Mode and number of proofs:
data - one

data/1

Prints a table with all port profiling data for the specified entity.

Compilation flags:
static

Template:
data(Entity)
Mode and number of proofs:
data(+entity__identifier) - one

data/2

Prints a table with all port profiling data for the specified entity predicate (or non-terminal).

Compilation flags:
static

Template:
data(Entity,Predicate)
Mode and number of proofs:
data(+entity__identifier,+predicate__indicator) - one
data(+entity__identifier,+non__terminal__indicator) - one

reset/0

Resets all port profiling data.

Compilation flags:

static

Mode and number of proofs:

reset - one

reset/1

Resets all port profiling data for the specified entity.

Compilation flags:

static

Template:

reset(Entity)

Mode and number of proofs:

reset(+entity__identifier) - one

port/5

Enumerates, by backtracking, all collected port profiling data.

Compilation flags:

static

Template:

port(Port,Entity,Functor,Arity,Count)

Mode and number of proofs:

port(?atom,?entity__identifier,?atom,?integer,?integer) - zero_or_more

clause_location/6

Enumerates, by backtracking, all collected profiled clause location data.

Compilation flags:

static

Template:

clause_location(Entity, Functor, Arity, ClauseNumber, File, BeginLine)

Mode and number of proofs:

clause_location(?entity__identifier, ?atom, ?integer, ?integer, ?atom, ?integer) - zero_or_more

clause/5

Enumerates, by backtracking, all collected clause profiling data.

Compilation flags:

dynamic

Template:

clause(Entity, Functor, Arity, ClauseNumber, Count)

Mode and number of proofs:

clause(?entity__identifier, ?atom, ?integer, ?integer, ?integer) - zero_or_more

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

clause_location_/6

Internal table of collected profiled clause location data.

Compilation flags:

dynamic

Template:

clause_location_(Entity, Functor, Arity, ClauseNumber, File, BeginLine)

Mode and number of proofs:

clause_location_(?entity__identifier, ?atom, ?integer, ?integer, ?atom, ?integer) - zero_or_more

port_/5

Internal table of collected port profiling data.

Compilation flags:

dynamic

Template:

port_(Port, Entity, Functor, Arity, Count)

Mode and number of proofs:

port_(?atom, ?entity__identifier, ?atom, ?integer, ?integer) - zero_or_more

clause_/5

Internal table of collected clause profiling data.

Compilation flags:

dynamic

Template:

clause_(Entity, Functor, Arity, ClauseNumber, Count)

Mode and number of proofs:

clause_(?entity__identifier, ?atom, ?integer, ?integer, ?integer) - zero_or_more

entity_defines_/2

Internal cache for profiled predicates.

Compilation flags:

dynamic

Template:

entity_defines_(Entity,Predicate)

Mode and number of proofs:

entity_defines_(?entity_identifier,?predicate_indicator) - zero_or_more

Operators

(none)

1.59 queues

object

1.59.1 queue

Queue predicates implemented using difference lists.

Availability:

logtalk_load(queues(loader))

Author: Paulo Moura

Version: 1:3:0

Date: 2020-12-09

Compilation flags:

static, context_switching_calls

Implements:

public queuep

Extends:

public compound

Remarks:

(none)

Inherited public predicates:

(<)/2 (=:=)/2 (=<)/2 (=\\=)/2 (>)/2 (>=)/2 append/3 as_list/2 check/1 depth/2
empty/1 ground/1 head/2 join/3 join_all/3 jump/3 jump_all/3 jump_all_block/3 length/2
map/2 map/3 new/1 numbervars/1 numbervars/3 occurs/2 serve/3 singletons/2 subsumes/2
subterm/2 valid/1 variables/2 variant/2 varnumbers/2 varnumbers/3

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

protocol

1.59.2 queuep

Queue protocol.

Availability:

logtalk_load(queues(loader))

Author: Paulo Moura

Version: 1:3:0

Date: 2020-12-09

Compilation flags:

static

Dependencies:

(none)

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
 - empty/1
 - head/2
 - join/3
 - join_all/3
 - jump/3
 - jump_all/3
 - jump_all_block/3
 - append/3
 - length/2
 - serve/3
 - as_list/2
 - map/2
 - map/3
- Protected predicates
- Private predicates
- Operators

Public predicates

empty/1

True if the queue is empty.

Compilation flags:

static

Template:

empty(Queue)

Mode and number of proofs:

empty(@queue) - zero_or_one

head/2

Unifies Head with the first element of the queue.

Compilation flags:

static

Template:

head(Queue,Head)

Mode and number of proofs:

head(+queue,?term) - zero_or_one

join/3

Adds the new element at the end of the queue.

Compilation flags:

static

Template:

join(Element,Queue,NewQueue)

Mode and number of proofs:

join(@term,+queue,-queue) - zero_or_one

join_all/3

Adds the new elements at the end of the queue. The elements are added in the same order that they appear in the list.

Compilation flags:

static

Template:

join_all(List,Queue,NewQueue)

Mode and number of proofs:

join_all(+list,+queue,-queue) - zero_or_one

jump/3

Adds the new element at the front of the queue.

Compilation flags:

static

Template:

jump(Element,Queue,NewQueue)

Mode and number of proofs:

jump(@term,+queue,-queue) - zero_or_one

jump_all/3

Adds the new elements at the front of the queue. The last element in the list will be at the front of the queue.

Compilation flags:

static

Template:

```
jump_all(Elements,Queue,NewQueue)
```

Mode and number of proofs:

```
jump_all(+list,+queue,-queue) - zero_or_one
```

```
jump_all_block/3
```

Adds the new elements as a block at the front of the queue. The first element in the list will be at the front of the queue.

Compilation flags:

```
static
```

Template:

```
jump_all_block(Elements,Queue,NewQueue)
```

Mode and number of proofs:

```
jump_all_block(+list,+queue,-queue) - zero_or_one
```

```
append/3
```

Appends two queues. The new queue will have the elements of the first queue followed by the elements of the second queue.

Compilation flags:

```
static
```

Template:

```
append(Queue1,Queue2,NewQueue)
```

Mode and number of proofs:

```
append(+queue,+queue,-queue) - one
```

length/2

Queue length.

Compilation flags:

static

Template:

length(Queue,Length)

Mode and number of proofs:

length(+heap,?integer) - zero_or_one

serve/3

Removes the first element of the queue for service.

Compilation flags:

static

Template:

serve(Queue,Head,NewQueue)

Mode and number of proofs:

serve(+queue,?term,-queue) - zero_or_one

as_list/2

Converts a queue to a list.

Compilation flags:

static

Template:

as_list(Queue,List)

Mode and number of proofs:

as_list(+queue,-list) - one

map/2

Applies a closure to all elements of a queue.

Compilation flags:

static

Template:

map(Closure,Queue)

Meta-predicate template:

map(1,*)

Mode and number of proofs:

map(+callable,+queue) - zero_or_one

map/3

Applies a closure to all elements of a queue constructing a new queue.

Compilation flags:

static

Template:

map(Closure,Queue,NewQueue)

Meta-predicate template:

map(2,*,*)

Mode and number of proofs:

map(+callable,+queue,?queue) - zero_or_one

Protected predicates

(none)

Private predicates

(none)

Operators

(none)

See also:

[queue](#)

1.60 random

object

1.60.1 backend_random

Random number generator predicates using the backend Prolog compiler built-in random generator.

Availability:

```
logtalk_load(random(loader))
```

Author: Paulo Moura

Version: 1:20:0

Date: 2023-11-24

Compilation flags:

```
static, context_switching_calls
```

Implements:

```
public pseudo_random_protocol
```

Uses:

```
list
```

Remarks:

- **Implementation:** The backend Prolog compiler built-in random generator is only used for the basic `random/1`, `get_seed/1`, and `set_seed/1` predicates.
- **Portability:** B-Prolog, CxProlog, ECLiPSe, JIProlog, Qu-Prolog, and Quintus Prolog do not provide implementations for the `get_seed/1` and `set_seed/1` predicates and calling these predicates simply succeed without performing any action.

Inherited public predicates:

between/3 enumerate/2 get_seed/1 maybe/0 maybe/1 maybe/2 maybe_call/1 maybe_call/2
 member/2 permutation/2 random/1 random/3 randseq/4 randset/4 select/3 select/4
 sequence/4 set/4 set_seed/1 swap/2 swap_consecutive/2

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

See also:

random, fast_random

object

1.60.2 fast_random

Fast portable random number generator predicates. Core predicates originally written by Richard O'Keefe. Based on algorithm AS 183 from Applied Statistics.

Availability:

logtalk_load(random(loader))

Author: Paulo Moura

Version: 2:11:0

Date: 2023-11-24

Compilation flags:

static, context_switching_calls

Implements:

public pseudo_random_protocol

Uses:

list

Remarks:

- Single random number generator: This object provides a faster version of the random library object but does not support being extended to define multiple random number generators.
- Randomness: Loading this object always initializes the random generator seed to the same value, thus providing a pseudo random number generator. The `randomize/1` predicate can be used to initialize the seed with a random value.

Inherited public predicates:

between/3 enumerate/2 get_seed/1 maybe/0 maybe/1 maybe/2 maybe_call/1 maybe_call/2
member/2 permutation/2 random/1 random/3 randseq/4 randset/4 select/3 select/4
sequence/4 set/4 set_seed/1 swap/2 swap_consecutive/2

- Public predicates
 - reset_seed/0
 - randomize/1
- Protected predicates
- Private predicates
 - seed_/3
- Operators

Public predicates

reset_seed/0

Resets the random generator seed to its default value. Use `get_seed/1` and `set_seed/1` instead if you need reproducibility.

Compilation flags:

static, synchronized

Mode and number of proofs:

reset_seed - one

randomize/1

Randomizes the random generator using a positive integer to compute a new seed. Use of a large integer is recommended. In alternative, when using a small integer argument, discard the first dozen random values.

Compilation flags:

static, synchronized

Template:

randomize(Seed)

Mode and number of proofs:

randomize(+positive_integer) - one

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

seed_/3

Stores the current random generator seed values.

Compilation flags:

dynamic

Template:

seed_(S0,S1,S2)

Mode and number of proofs:

seed_(-integer,-integer,-integer) - one

Operators

(none)

See also:

random, backend_random

protocol

1.60.3 pseudo_random_protocol

Pseudo-random number generator protocol for seed handling predicates. These predicates are declared as synchronized when the library is compiled using a backend supporting threads.

Availability:

logtalk_load(random(loader))

Author: Paulo Moura

Version: 1:0:0

Date: 2021-02-21

Compilation flags:

static

Extends:

public random_protocol

Remarks:

(none)

Inherited public predicates:

between/3 enumerate/2 maybe/0 maybe/1 maybe/2 maybe_call/1 maybe_call/2 member/2
permutation/2 random/1 random/3 randseq/4 randset/4 select/3 select/4 sequence/4 set/4
swap/2 swap_consecutive/2

- Public predicates
 - get_seed/1
 - set_seed/1
- Protected predicates
- Private predicates
- Operators

Public predicates`get_seed/1`

Gets the current random generator seed. Seed should be regarded as an opaque ground term.

Compilation flags:

static, synchronized

Template:

`get_seed(Seed)`

Mode and number of proofs:

`get_seed(-ground) - one`

`set_seed/1`

Sets the random generator seed to a given value returned by calling the `get_seed/1` predicate.

Compilation flags:

static, synchronized

Template:

`set_seed(Seed)`

Mode and number of proofs:

`set_seed(+ground) - one`

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

See also:

random, backend_random, fast_random

object

1.60.4 random

Portable random number generator predicates. Core predicates originally written by Richard O’Keefe. Based on algorithm AS 183 from Applied Statistics.

Availability:

```
logtalk_load(random(loader))
```

Author: Paulo Moura

Version: 2:11:0

Date: 2023-11-24

Compilation flags:

```
static, context_switching_calls
```

Implements:

```
public pseudo_random_protocol
```

Uses:

```
list
```

Remarks:

- Multiple random number generators: To define multiple random number generators, simply extend this object. The derived objects must send to self the reset_seed/0 message.
- Randomness: Loading this object always initializes the random generator seed to the same value, thus providing a pseudo random number generator. The randomize/1 predicate can be used to initialize the seed with a random value.

Inherited public predicates:

```
between/3 enumerate/2 get_seed/1 maybe/0 maybe/1 maybe/2 maybe_call/1 maybe_call/2  
member/2 permutation/2 random/1 random/3 randseq/4 randset/4 select/3 select/4  
sequence/4 set/4 set_seed/1 swap/2 swap_consecutive/2
```

- Public predicates
 - reset_seed/0
 - randomize/1
- Protected predicates
- Private predicates
 - seed_/3
- Operators

Public predicates

reset_seed/0

Resets the random generator seed to its default value. Use get_seed/1 and set_seed/1 instead if you need reproducibility.

Compilation flags:

static, synchronized

Mode and number of proofs:

reset_seed - one

randomize/1

Randomizes the random generator using a positive integer to compute a new seed. Use of a large integer is recommended. In alternative, when using a small integer argument, discard the first dozen random values.

Compilation flags:

static, synchronized

Template:

randomize(Seed)

Mode and number of proofs:

randomize(+positive_integer) - one

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

seed_/3

Stores the current random generator seed values.

Compilation flags:

dynamic

Template:

seed_(S0,S1,S2)

Mode and number of proofs:

seed_(-integer,-integer,-integer) - one

Operators

(none)

See also:

[fast_random](#), [backend_random](#)

[protocol](#)

1.60.5 random_protocol

Random number generator protocol. The predicates are declared as synchronized when the library is compiled using a backend supporting threads.

Availability:

logtalk_load(random(loader))

Author: Paulo Moura

Version: 3:3:0

Date: 2023-11-24

Compilation flags:

static

Dependencies:

(none)

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
 - random/1
 - between/3
 - member/2
 - select/3
 - select/4
 - swap/2
 - swap_consecutive/2
 - enumerate/2
 - permutation/2
 - sequence/4
 - set/4
 - random/3
 - randseq/4
 - randset/4
 - maybe/0
 - maybe/1
 - maybe/2
 - maybe_call/1
 - maybe_call/2
- Protected predicates
- Private predicates
- Operators

Public predicates

random/1

Returns a new random float value in the interval [0.0, 1.0[.

Compilation flags:

static, synchronized

Template:

random(Random)

Mode and number of proofs:

random(-float) - one

between/3

Returns a new random integer in the interval [Lower, Upper]. Fails if Lower or Upper are not integers or if Lower > Upper.

Compilation flags:

static

Template:

between(Lower,Upper,Random)

Mode and number of proofs:

between(+integer,+integer,-integer) - zero_or_one

member/2

Returns a random member of a list. Fails if the list is empty.

Compilation flags:

static

Template:

member(Random,List)

Mode and number of proofs:

member(-term,+list(term)) - zero_or_one

select/3

Returns a random member of a list and the rest of the list. Fails if the list is empty.

Compilation flags:

static

Template:

select(Random,List,Rest)

Mode and number of proofs:

select(-term,+list(term),-list(term)) - zero_or_one

select/4

Returns a random member of a list, replacing it with a new element and returning the resulting list.

Compilation flags:

static

Template:

select(Random,OldList,New,NewList)

Mode and number of proofs:

select(-term,+list(term),@term,-list(term)) - zero_or_one

swap/2

Swaps two randomly selected elements of a list. Fails if the list is empty or contains a single element.

Compilation flags:

static

Template:

swap(OldList,NewList)

Mode and number of proofs:

swap(-term,+list(term)) - zero_or_one

swap_consecutive/2

Swaps two randomly selected consecutive elements of a list. Fails if the list is empty or contains a single element.

Compilation flags:

static

Template:

swap_consecutive(OldList,NewList)

Mode and number of proofs:

swap_consecutive(-term,+list(term)) - zero_or_one

enumerate/2

Enumerates the elements of a list in random order. Fails if the list is empty.

Compilation flags:

static

Template:

enumerate(List,Random)

Mode and number of proofs:

enumerate(+list(term),--term) - zero_or_more

permutation/2

Returns a random permutation of a list.

Compilation flags:

static, synchronized

Template:

permutation(List,Permutation)

Mode and number of proofs:

permutation(+list,-list) - one

sequence/4

Returns list of random integers of given length in random order in interval [Lower, Upper]. Fails if Length, Lower, or Upper are not integers or if Lower > Upper.

Compilation flags:

static, synchronized

Template:

sequence(Length,Lower,Upper,List)

Mode and number of proofs:

sequence(+integer,+integer,+integer,-list(integer)) - zero_or_one

set/4

Returns ordered set of random integers of given size in interval [Lower, Upper]. Fails if Length, Lower, or Upper are not integers, if Lower > Upper, or if Length > Upper - Lower + 1.

Compilation flags:

static, synchronized

Template:

set(Length,Lower,Upper,Set)

Mode and number of proofs:

set(+integer,+integer,+integer,-list(integer)) - zero_or_one

random/3

Returns a new random value in the interval [Lower, Upper[. Fails if Lower > Upper. Deprecated. Use between/3 for integers.

Compilation flags:

static, synchronized

Template:

random(Lower,Upper,Random)

Mode and number of proofs:

random(+integer,+integer,-integer) - zero_or_one

random(+float,+float,-float) - zero_or_one

randseq/4

Returns list of random values of given length in random order in interval [Lower, Upper[. Fails if Lower > Upper or if the arguments are neither integers or floats. Deprecated. Use sequence/4 for integers.

Compilation flags:

static, synchronized

Template:

randseq(Length,Lower,Upper,List)

Mode and number of proofs:

randseq(+integer,+integer,+integer,-list(integer)) - zero_or_one

randseq(+integer,+float,+float,-list(float)) - zero_or_one

randset/4

Returns ordered set of random values of given size in interval [Lower, Upper[. Fails if the arguments are neither integers or floats, Lower > Upper, or Length > Upper - Lower when arguments are integers. Deprecated. Use set/4 for integers.

Compilation flags:

static, synchronized

Template:

randset(Length,Lower,Upper,Set)

Mode and number of proofs:

randset(+integer,+integer,+integer,-list(integer)) - zero_or_one

randset(+integer,+float,+float,-list(float)) - zero_or_one

maybe/0

Succeeds or fails with equal probability.

Compilation flags:

static

Mode and number of proofs:

maybe - zero_or_one

maybe/1

Succeeds with probability Probability or fails with probability 1 - Probability. Fails if Probability is not a float or is outside the interval [0.0, 1.0].

Compilation flags:

static

Template:

maybe(Probability)

Mode and number of proofs:

maybe(+probability) - zero_or_one

maybe/2

Succeeds with probability K/N where K and N are integers satisfying the equation $0 \leq K \leq N$. Fails otherwise.

Compilation flags:

static

Template:

maybe(K,N)

Mode and number of proofs:

maybe(+non_negative_integer,+non_negative_integer) - zero_or_one

maybe_call/1

Calls a goal or fails without calling it with equal probability. When the goal is called, it determines if this predicate succeeds once or fails.

Compilation flags:

static

Template:

maybe_call(Goal)

Meta-predicate template:

maybe_call(0)

Mode and number of proofs:

maybe_call(+callable) - zero_or_one

`maybe_call/2`

Calls a goal or fails without calling it with probability `Probability`. When the goal is called, it determines if this predicate succeeds once or fails.

Compilation flags:

`static`

Template:

`maybe_call(Probability,Goal)`

Meta-predicate template:

`maybe_call(*,0)`

Mode and number of proofs:

`maybe_call(+probability,+callable) - zero_or_one`

Protected predicates

(none)

Private predicates

(none)

Operators

(none)

See also:

`random`, `backend_random`, `fast_random`

1.61 reader

object

1.61.1 reader

Predicates for reading text file and text stream contents to lists of terms, characters, or character codes and for reading binary file and binary stream contents to lists of bytes.

Availability:

```
logtalk_load(reader(loader))
```

Author: Paulo Moura

Version: 2:2:0

Date: 2023-11-14

Compilation flags:

```
static, context_switching_calls
```

Dependencies:

```
(none)
```

Remarks:

```
(none)
```

Inherited public predicates:

```
(none)
```

- Public predicates
 - file_to_codes/2
 - file_to_codes/3
 - file_to_chars/2
 - file_to_chars/3
 - file_to_terms/2
 - file_to_terms/3
 - file_to_bytes/2
 - file_to_bytes/3
 - stream_to_codes/2
 - stream_to_codes/3
 - stream_to_chars/2
 - stream_to_chars/3
 - stream_to_terms/2

- stream_to_terms/3
- stream_to_bytes/2
- stream_to_bytes/3
- line_to_chars/2
- line_to_chars/3
- line_to_codes/2
- line_to_codes/3
- Protected predicates
- Private predicates
- Operators

Public predicates

file_to_codes/2

Reads a text file into a list of character codes.

Compilation flags:

static

Template:

file_to_codes(File,Codes)

Mode and number of proofs:

file_to_codes(+atom,-list(character_code)) - one

file_to_codes/3

Reads a text file into a list of character codes. The list is terminated by the given tail.

Compilation flags:

static

Template:

file_to_codes(File,Codes,Tail)

Mode and number of proofs:

file_to_codes(+atom,-list(character_code),@term) - one

`file_to_chars/2`

Reads a text file into a list of characters.

Compilation flags:

`static`

Template:

`file_to_chars(File,Chars)`

Mode and number of proofs:

`file_to_chars(+atom,-list(character)) - one`

`file_to_chars/3`

Reads a text file into a list of characters. The list is terminated by the given tail.

Compilation flags:

`static`

Template:

`file_to_chars(File,Chars,Tail)`

Mode and number of proofs:

`file_to_chars(+atom,-list(character),@term) - one`

`file_to_terms/2`

Reads a text file into a list of terms.

Compilation flags:

`static`

Template:

`file_to_terms(File,Terms)`

Mode and number of proofs:

`file_to_terms(+atom,-list(term))` - one

`file_to_terms/3`

Reads a text file into a list of terms. The list is terminated by the given tail.

Compilation flags:

`static`

Template:

`file_to_terms(File,Terms,Tail)`

Mode and number of proofs:

`file_to_terms(+atom,-list(term),@term)` - one

`file_to_bytes/2`

Reads a binary file into a list of bytes.

Compilation flags:

`static`

Template:

`file_to_bytes(File,Bytes)`

Mode and number of proofs:

`file_to_bytes(+atom,-list(byte))` - one

`file_to_bytes/3`

Reads a binary file into a list of bytes. The list is terminated by the given tail.

Compilation flags:

`static`

Template:

`file_to_bytes(File,Bytes,Tail)`

Mode and number of proofs:

`file_to_bytes(+atom,-list(byte),@term) - one`

`stream_to_codes/2`

Reads a text stream into a list of character codes. Does not close the stream.

Compilation flags:

`static`

Template:

`stream_to_codes(Stream,Codes)`

Mode and number of proofs:

`stream_to_codes(+stream_or_alias,-list(character_code)) - one`

`stream_to_codes/3`

Reads a text stream into a list of character codes. Does not close the stream. The list is terminated by the given tail.

Compilation flags:

`static`

Template:

`stream_to_codes(Stream,Codes,Tail)`

Mode and number of proofs:

`stream_to_codes(+stream_or_alias,-list(character_code),@term) - one`

`stream_to_chars/2`

Reads a text stream into a list of characters. Does not close the stream.

Compilation flags:

`static`

Template:

`stream_to_chars(Stream,Chars)`

Mode and number of proofs:

`stream_to_chars(+stream_or_alias,-list(char)) - one`

`stream_to_chars/3`

Reads a text stream into a list of characters. Does not close the stream. The list is terminated by the given tail.

Compilation flags:

`static`

Template:

`stream_to_chars(Stream,Chars,Tail)`

Mode and number of proofs:

`stream_to_chars(+stream_or_alias,-list(char),@term) - one`

`stream_to_terms/2`

Reads a text stream into a list of terms. Does not close the stream.

Compilation flags:

`static`

Template:

`stream_to_terms(Stream,Terms)`

Mode and number of proofs:

`stream_to_terms(+stream_or_alias,-list(term)) - one`

`stream_to_terms/3`

Reads a text stream into a list of terms. Does not close the stream. The list is terminated by the given tail.

Compilation flags:

`static`

Template:

`stream_to_terms(Stream, Terms, Tail)`

Mode and number of proofs:

`stream_to_terms(+stream_or_alias, -list(term), @term) - one`

`stream_to_bytes/2`

Reads a binary stream into a list of bytes. Does not close the stream.

Compilation flags:

`static`

Template:

`stream_to_bytes(Stream, Bytes)`

Mode and number of proofs:

`stream_to_bytes(+stream_or_alias, -list(byte)) - one`

`stream_to_bytes/3`

Reads a binary stream into a list of bytes. Does not close the stream. The list is terminated by the given tail.

Compilation flags:

`static`

Template:

`stream_to_bytes(Stream, Bytes, Tail)`

Mode and number of proofs:

`stream_to_bytes(+stream_or_alias,-list(byte),@term) - one`

`line_to_chars/2`

Reads a line from a text stream into a list of characters. Discards the end-of-line characters. Unifies Chars with `end_of_file` at the end of the file.

Compilation flags:

`static`

Template:

`line_to_chars(Stream,Chars)`

Mode and number of proofs:

`line_to_chars(+stream_or_alias,-types([atom,list(character)])) - one`

`line_to_chars/3`

Reads a line from a text stream into a list of characters. Keeps the end-of-line marker normalized to the line feed control character. The list is terminated by the given tail, which is unified with the empty list at the end of the file.

Compilation flags:

`static`

Template:

`line_to_chars(Stream,Chars,Tail)`

Mode and number of proofs:

`line_to_chars(+stream_or_alias,-list(character),?term) - one`

line_to_codes/2

Reads a line from a text stream into a list of character codes. Discards the end-of-line character codes. Unifies Codes with end_of_file at the end of the file.

Compilation flags:

static

Template:

line_to_codes(Stream,Codes)

Mode and number of proofs:

line_to_codes(+stream_or_alias,-types([atom,list(character_code)])) - one

line_to_codes/3

Reads a line from a text stream into a list of character codes. Keeps the end-of-line marker normalized to the line feed control character code. The list is terminated by the given tail, which is unified with the empty list at the end of the file.

Compilation flags:

static

Template:

line_to_codes(Stream,Codes,Tail)

Mode and number of proofs:

line_to_codes(+stream_or_alias,-list(character_code),?term) - one

Protected predicates

(none)

Private predicates

(none)

Operators

(none)

1.62 recorded_database

object

1.62.1 recorded_database

Legacy recorded database predicates. Provides an application global database.

Availability:

```
logtalk_load(recorded_database(loader))
```

Author: Paulo Moura

Version: 1:0:0

Date: 2023-12-17

Compilation flags:

```
static, context_switching_calls
```

Imports:

```
public recorded_database_core
```

Remarks:

(none)

Inherited public predicates:

```
erase/1 instance/2 recorda/2 recorda/3 recorded/2 recorded/3 recordz/2 recordz/3
```

- [Public predicates](#)
- [Protected predicates](#)
- [Private predicates](#)
- [Operators](#)

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

category

1.62.2 recorded_database_core

Legacy recorded database predicates. Can be imported into an object to provide a local database.

Availability:

logtalk_load(recorded_database(loader))

Author: Paulo Moura

Version: 1:0:0

Date: 2023-12-17

Compilation flags:

static

Dependencies:

(none)

Remarks:

- References: Opaque ground terms.

Inherited public predicates:

(none)

- Public predicates
 - recorda/3
 - recorda/2
 - recordz/3
 - recordz/2
 - recorded/3
 - recorded/2
 - erase/1
 - instance/2
- Protected predicates
- Private predicates
 - record_/3
 - reference_/1
- Operators

Public predicates

recorda/3

Adds a term as the first term for the given key, returning its reference.

Compilation flags:

static

Template:

recorda(Key,Term,Reference)

Mode and number of proofs:

recorda(+recorded_database_key,+term,--recorded_database_reference) - one_or_error

Exceptions:

Key is a variable:

instantiation_error

Key is neither a variable nor an atomic term or compound term:

type_error(recorded_database_key,Key)

Reference is a not a variable:

uninstantiation_error(Reference)

recorda/2

Adds a term as the first term for the given key.

Compilation flags:

static

Template:

recorda(Key,Term)

Mode and number of proofs:

recorda(+recorded_database_key,+term) - one_or_error

Exceptions:

Key is a variable:

instantiation_error

Key is neither a variable nor an atomic term or compound term:

type_error(recorded_database_key,Key)

recordz/3

Adds a term as the last term for the given key, returning its reference.

Compilation flags:

static

Template:

recordz(Key,Term,Reference)

Mode and number of proofs:

recordz(+recorded_database_key,+term,--recorded_database_reference) - one_or_error

Exceptions:

Key is a variable:

instantiation_error

Key is neither a variable nor an atomic term or compound term:

type_error(recorded_database_key,Key)

Reference is not a variable:

uninstantiation_error(Reference)

recordz/2

Adds a term as the last term for the given key.

Compilation flags:

static

Template:

recordz(Key,Term)

Mode and number of proofs:

recordz(+recorded_database_key,+term) - one_or_error

Exceptions:

Key is a variable:

instantiation_error

Key is neither a variable nor an atomic term or compound term:

type_error(recorded_database_key,Key)

recorded/3

Enumerates, by backtracking, all record key-term pairs and their references.

Compilation flags:

static

Template:

recorded(Key,Term,Reference)

Mode and number of proofs:

recorded(?recorded_database_key,?term,-recorded_database_reference) - zero_or_more

recorded(?recorded_database_key,?term,+recorded_database_reference) - zero_or_one

recorded/2

Enumerates, by backtracking, all record key-term pairs.

Compilation flags:

static

Template:

recorded(Key,Term)

Mode and number of proofs:

recorded(?recorded_database_key,?term) - zero_or_more

erase/1

Erases the record indexed by the given reference. Fails if there is no record with the given reference.

Compilation flags:

static

Template:

erase(Reference)

Mode and number of proofs:

erase(@recorded_database_reference) - zero_or_one_or_error

Exceptions:

Reference is a variable:

instantiation_error

instance/2

.

Compilation flags:

static

Template:

instance(Reference,Term)

Mode and number of proofs:

instance(@recorded_database_reference,?term) - zero_or_one_or_error

Exceptions:

Reference is a variable:

instantiation_error

Protected predicates

(none)

Private predicates

record_/3

Records table.

Compilation flags:

dynamic

Template:

record_(Key,Term,Reference)

Mode and number of proofs:

record_(?recorded_database_key,?term,?recorded_database_reference) - zero_or_more

reference_/1

Reference count.

Compilation flags:

dynamic

Template:

reference_(Reference)

Mode and number of proofs:

reference_(?non_negative_integer) - zero_or_one

Operators

(none)

1.63 redis

object

1.63.1 redis

Redis client. Inspired by Sean Charles GNU Prolog Redis client.

Availability:

```
logtalk_load(redis(loader))
```

Author: Paulo Moura

Version: 0:5:1

Date: 2021-12-06

Compilation flags:

```
static, context_switching_calls
```

Provides:

```
logtalk::message_tokens//2
```

Uses:

```
list
```

```
logtalk
```

Remarks:

- **Command representation:** Use the Redis command name as the functor of a compound term where the arguments are the command arguments.
- **Valid arguments:** Atoms, integers, and floats. Always use atoms instead of double-quoted “strings”. This helps portability by not depending on the value of the `double_quotes` flag.

Inherited public predicates:

(none)

- Public predicates
 - connect/1
 - connect/3
 - disconnect/1
 - send/3
 - console/1
- Protected predicates
- Private predicates
- Operators

Public predicates

connect/1

Connect to a Redis server running on localhost using the default 6379 port.

Compilation flags:
static

Template:

connect(Connection)

Mode and number of proofs:

connect(--ground) - one

connect/3

Connect to a Redis server running on the given host and port.

Compilation flags:
static

Template:

connect(Host,Port,Connection)

Mode and number of proofs:

connect(+atom,+integer,--ground) - one

disconnect/1

Disconnect from a Redis server.

Compilation flags:

static

Template:

disconnect(Connection)

Mode and number of proofs:

disconnect(++ground) - one

send/3

Sends a request to the a Redis server and returns its reply.

Compilation flags:

static

Template:

send(Connection,Request,Reply)

Mode and number of proofs:

send(++ground,++callable,--callable) - one

console/1

Sends a request to a Redis server running on localhost at the default 6379 port and prints the reply.

Compilation flags:

static

Template:

console(Request)

Mode and number of proofs:

console(++callable) - one

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

1.64 sets

object

1.64.1 set

Set predicates implemented using ordered lists. Uses `==/2` for element comparison and standard term ordering.

Availability:

```
logtalk_load(sets(loader))
```

Author: Richard O'Keefe (main predicates); adapted to Logtalk by Paulo Moura.

Version: 1:12:0

Date: 2019-05-23

Compilation flags:

```
static, context_switching_calls
```

Implements:

```
public setp
```

Extends:

```
public compound
```

Aliases:

```
setp size/2 as length/2
```

Remarks:

(none)

Inherited public predicates:

(<)/2 (=:=)/2 (=<)/2 (=\\=)/2 (>)/2 (>=)/2 as_list/2 as_set/2 check/1 delete/3 depth/2 disjoint/2 empty/1 equal/2 ground/1 insert/3 insert_all/3 intersect/2 intersection/3 intersection/4 member/2 memberchk/2 new/1 numbervars/1 numbervars/3 occurs/2 powerset/2 product/3 select/3 selectchk/3 singletons/2 size/2 subset/2 subsumes/2 subterm/2 subtract/3 symdiff/3 union/3 union/4 valid/1 variables/2 variant/2 varnumbers/2 varnumbers/3

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

See also:

set(Type)

object

1.64.2 set(Type)

Set predicates with elements constrained to a single type and custom comparing rules.

Availability:

logtalk_load(sets(loader))

Author: Paulo Moura and Adrian Arroyo

Version: 1:24:0

Date: 2022-02-03

Compilation flags:

static, context_switching_calls

Extends:

public set

Uses:

list

Remarks:

(none)

Inherited public predicates:

(<)/2 (=:=)/2 (=<)/2 (=\\=)/2 (>)/2 (>=)/2 as_list/2 as_set/2 check/1 delete/3 depth/2 disjoint/2 empty/1 equal/2 ground/1 insert/3 insert_all/3 intersect/2 intersection/3 intersection/4 member/2 memberchk/2 new/1 numbervars/1 numbervars/3 occurs/2 powerset/2 product/3 select/3 selectchk/3 singletons/2 size/2 subset/2 subsumes/2 subterm/2 subtract/3 symdiff/3 union/3 union/4 valid/1 variables/2 variant/2 varnumbers/2 varnumbers/3

- Public predicates
- Protected predicates
- Private predicates
 - sort/2
 - partition/4
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

sort/2

Sorts a list in ascending order.

Compilation flags:

static

Template:

sort(List,Sorted)

Mode and number of proofs:

sort(+list,-list) - one

partition/4

List partition in two sub-lists using a pivot.

Compilation flags:

static

Template:

partition(List,Pivot,Lowes,Biggers)

Mode and number of proofs:

partition(+list,+nonvar,-list,-list) - one

Operators

(none)

protocol

1.64.3 setp

Set protocol.

Availability:

```
logtalk_load(sets(loader))
```

Author: Paulo Moura

Version: 1:6:0

Date: 2019-05-23

Compilation flags:

```
static
```

Dependencies:

```
(none)
```

Remarks:

```
(none)
```

Inherited public predicates:

```
(none)
```

- Public predicates
 - as_set/2
 - as_list/2
 - delete/3
 - disjoint/2
 - equal/2
 - empty/1
 - insert/3
 - insert_all/3
 - intersect/2
 - intersection/3
 - intersection/4
 - size/2
 - member/2

- memberchk/2
- powerset/2
- product/3
- select/3
- selectchk/3
- subset/2
- subtract/3
- symdiff/3
- union/3
- union/4
- Protected predicates
- Private predicates
- Operators

Public predicates

`as_set/2`

Returns a set with all unique elements from the given list.

Compilation flags:

`static`

Template:

`as_set(List,Set)`

Mode and number of proofs:

`as_set(@list,-set) - one`

`as_list/2`

Returns a list with all elements of the given set.

Compilation flags:

`static`

Template:

`as_list(Set,List)`

Mode and number of proofs:

`as_list(@set,-list) - one`

`delete/3`

Deletes an element from a set returning the set of remaining elements.

Compilation flags:

`static`

Template:

`delete(Set,Element,Remaining)`

Mode and number of proofs:

`delete(+set,@term,?set) - one`

`disjoint/2`

True if the two sets have no element in common.

Compilation flags:

`static`

Template:

`disjoint(Set1,Set2)`

Mode and number of proofs:

`disjoint(+set,+set) - zero_or_one`

equal/2

True if the two sets are equal.

Compilation flags:

static

Template:

equal(Set1,Set2)

Mode and number of proofs:

equal(+set,+set) - zero_or_one

empty/1

True if the set is empty.

Compilation flags:

static

Template:

empty(Set)

Mode and number of proofs:

empty(+set) - zero_or_one

insert/3

Inserts an element in a set, returning the resulting set.

Compilation flags:

static

Template:

insert(In,Element,Out)

Mode and number of proofs:

insert(+set,+term,?set) - one

insert_all/3

Inserts a list of elements in a set, returning the resulting set.

Compilation flags:

static

Template:

insert_all(List,In,Out)

Mode and number of proofs:

insert_all(+list,+set,?set) - one

intersect/2

True if the two sets have at least one element in common.

Compilation flags:

static

Template:

intersect(Set1,Set2)

Mode and number of proofs:

intersect(+set,+set) - zero_or_one

intersection/3

Returns the intersection of Set1 and Set2.

Compilation flags:

static

Template:

intersection(Set1,Set2,Intersection)

Mode and number of proofs:

intersection(+set,+set,?set) - zero_or_one

intersection/4

True if Intersection is the intersection of Set1 and Set2 and Difference is the difference between Set2 and Set1.

Compilation flags:

static

Template:

intersection(Set1,Set2,Intersection,Difference)

Mode and number of proofs:

intersection(+set,+set,?set,?set) - zero_or_one

size/2

Number of set elements.

Compilation flags:

static

Template:

size(Set,Size)

Mode and number of proofs:

size(+set,?integer) - zero_or_one

member/2

Element is a member of set Set.

Compilation flags:

static

Template:

member(Element,Set)

Mode and number of proofs:

member(+term,+set) - zero_or_one

member(-term,+set) - zero_or_more

memberchk/2

Checks if a term is a member of a set.

Compilation flags:

static

Template:

memberchk(Element,Set)

Mode and number of proofs:

memberchk(+term,+set) - zero_or_one

powerset/2

Returns the power set of a set, represented as a list of sets.

Compilation flags:

static

Template:

powerset(Set,PowerSet)

Mode and number of proofs:

powerset(+set,-list) - one

product/3

Returns the cartesian product of two sets.

Compilation flags:

static

Template:

product(Set1,Set2,Product)

Mode and number of proofs:

product(+set,+set,-set) - one

select/3

Selects an element from a set, returning the set of remaining elements.

Compilation flags:

static

Template:

select(Element,Set,Remaining)

Mode and number of proofs:

select(?term,+set,?set) - zero_or_more

selectchk/3

Checks that an element can be selected from a set, returning the set of remaining elements.

Compilation flags:

static

Template:

selectchk(Element,Set,Remaining)

Mode and number of proofs:

selectchk(?term,+set,?set) - zero_or_one

subset/2

True if Subset is a subset of Set.

Compilation flags:

static

Template:

subset(Subset,Set)

Mode and number of proofs:

subset(+set,+set) - zero_or_one

subtract/3

True when Difference contains all and only the elements of Set1 which are not also in Set2.

Compilation flags:

static

Template:

subtract(Set1,Set2,Difference)

Mode and number of proofs:

subtract(+set,+set,?set) - zero_or_one

symdiff/3

True if Difference is the symmetric difference of Set1 and Set2, containing all elements that are not in the sets intersection.

Compilation flags:

static

Template:

symdiff(Set1,Set2,Difference)

Mode and number of proofs:

symdiff(+set,+set,?set) - zero_or_one

union/3

True if Union is the union of Set1 and Set2.

Compilation flags:

static

Template:

union(Set1,Set2,Union)

Mode and number of proofs:

union(+set,+set,?set) - zero_or_one

union/4

True if Union is the union of Set1 and Set2 and Difference is the difference between Set2 and Set1.

Compilation flags:

static

Template:

union(Set1,Set2,Union,Difference)

Mode and number of proofs:

union(+set,+set,?set,?set) - zero_or_one

Protected predicates

(none)

Private predicates

(none)

Operators

(none)

See also:

set, set(Type)

1.65 statistics

object

1.65.1 population

Statistical population represented as a list of numbers.

Availability:

```
logtalk_load(statistics(loader))
```

Author: Paulo Moura

Version: 1:3:0

Date: 2020-02-02

Compilation flags:

```
static, context_switching_calls
```

Imports:

```
public statistics
```

Remarks:

(none)

Inherited public predicates:

```
arithmetic_mean/2 average_deviation/3 coefficient_of_variation/2 fractile/3 geometric_mean/2
harmonic_mean/2 kurtosis/2 max/2 mean_deviation/2 median/2 median_deviation/2 min/2
min_max/3 modes/2 product/2 range/2 relative_standard_deviation/2 skewness/2
standard_deviation/2 sum/2 valid/1 variance/2 weighted_mean/3 z_normalization/2
```

- Public predicates
- Protected predicates
- Private predicates

- [Operators](#)

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

See also:

[sample](#)

object

1.65.2 [sample](#)

Statistical sample represented as a list of numbers.

Availability:

```
logtalk_load(statistics(loader))
```

Author: Paulo Moura

Version: 1:4:0

Date: 2020-02-02

Compilation flags:

```
static, context_switching_calls
```

Imports:

```
public statistics
```

Remarks:

(none)

Inherited public predicates:

arithmetic_mean/2 average_deviation/3 coefficient_of_variation/2 fractile/3 geometric_mean/2
 harmonic_mean/2 kurtosis/2 max/2 mean_deviation/2 median/2 median_deviation/2 min/2
 min_max/3 modes/2 product/2 range/2 relative_standard_deviation/2 skewness/2
 standard_deviation/2 sum/2 valid/1 variance/2 weighted_mean/3 z_normalization/2

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

See also:

population

category

1.65.3 statistics

Statistical calculations over a list of numbers.

Availability:

```
logtalk_load(statistics(loader))
```

Author: Paulo Moura

Version: 1:7:1

Date: 2023-05-29

Compilation flags:

static

Implements:

public statisticsp

Uses:

list

numberlist

Remarks:

(none)

Inherited public predicates:

arithmetic_mean/2 average_deviation/3 coefficient_of_variation/2 fractile/3 geometric_mean/2
harmonic_mean/2 kurtosis/2 max/2 mean_deviation/2 median/2 median_deviation/2 min/2
min_max/3 modes/2 product/2 range/2 relative_standard_deviation/2 skewness/2
standard_deviation/2 sum/2 valid/1 variance/2 weighted_mean/3 z_normalization/2

- Public predicates
- Protected predicates
- Private predicates
 - arithmetic_mean/5
 - squares_and_cubes/6
 - squares_and_hypers/6
 - variance/6
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

arithmetic_mean/5

Auxiliary predicate for computing the arithmetic mean.

Compilation flags:

static

Template:

arithmetic_mean(List,Length0,Length,Sum,Mean)

Mode and number of proofs:

arithmetic_mean(+list(number),+integer,-integer,+number,-float) - one

squares_and_cubes/6

Auxiliary predicate for computing the skewness.

Compilation flags:

static

Template:

squares_and_cubes(List,Mean,Squares0,Squares,Cubes0,Cubes)

Mode and number of proofs:

squares_and_cubes(+list(number),+float,+float,-float,+float,-float) - one

squares_and_hypers/6

Auxiliary predicate for computing the kurtosis.

Compilation flags:

static

Template:

squares_and_hypers(List,Mean,Squares0,Squares,Hypers0,Hypers)

Mode and number of proofs:

squares_and_hypers(+list(number),+float,+float,-float,+float,-float) - one

variance/6

Auxiliary predicate for computing the variance.

Compilation flags:

static

Template:

variance(List,Length0,Length,Mean,M20,M2)

Mode and number of proofs:

variance(+list(number),+integer,-integer,+float,+float,-float) - one

Operators

(none)

protocol

1.65.4 statisticsp

Statistical calculations over a list of numbers protocol.

Availability:

logtalk_load(statistics(loader))

Author: Paulo Moura

Version: 1:3:0

Date: 2022-06-20

Compilation flags:

static

Dependencies:

(none)

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
 - product/2
 - sum/2
 - min/2
 - max/2
 - min_max/3
 - range/2
 - arithmetic_mean/2
 - geometric_mean/2
 - harmonic_mean/2
 - weighted_mean/3
 - median/2
 - modes/2
 - average_deviation/3
 - mean_deviation/2
 - median_deviation/2
 - standard_deviation/2
 - coefficient_of_variation/2
 - relative_standard_deviation/2
 - skewness/2
 - kurtosis/2
 - variance/2
 - z_normalization/2
 - fractile/3
 - valid/1
- Protected predicates
- Private predicates
- Operators

Public predicates

product/2

Calculates the product of all list numbers. Fails if the list is empty.

Compilation flags:

static

Template:

product(List,Product)

Mode and number of proofs:

product(+list(number),-number) - zero_or_one

sum/2

Calculates the sum of all list numbers. Fails if the list is empty.

Compilation flags:

static

Template:

sum(List,Sum)

Mode and number of proofs:

sum(+list(number),-number) - zero_or_one

min/2

Determines the minimum value in a list of numbers. Fails if the list is empty.

Compilation flags:

static

Template:

min(List,Minimum)

Mode and number of proofs:

min(+list,-number) - zero_or_one

max/2

Determines the list maximum value in a list of numbers. Fails if the list is empty.

Compilation flags:

static

Template:

max(List,Maximum)

Mode and number of proofs:

max(+list,-number) - zero_or_one

min_max/3

Determines the minimum and maximum values in a list of numbers. Fails if the list is empty.

Compilation flags:

static

Template:

min_max(List,Minimum,Maximum)

Mode and number of proofs:

min_max(+list(number),-number,-number) - zero_or_one

range/2

Range is the length of the smallest interval which contains all the numbers in List. Fails if the list is empty.

Compilation flags:

static

Template:

range(List,Range)

Mode and number of proofs:

`range(+list,-number) - zero_or_one`

`arithmetic_mean/2`

Calculates the arithmetic mean of a list of numbers. Fails if the list is empty.

Compilation flags:

`static`

Template:

`arithmetic_mean(List,Mean)`

Mode and number of proofs:

`arithmetic_mean(+list(number),-float) - zero_or_one`

`geometric_mean/2`

Calculates the geometric mean of a list of numbers. Fails if the list is empty.

Compilation flags:

`static`

Template:

`geometric_mean(List,Mean)`

Mode and number of proofs:

`geometric_mean(+list(number),-float) - zero_or_one`

`harmonic_mean/2`

Calculates the harmonic mean of a list of numbers. Fails if the list is empty.

Compilation flags:

`static`

Template:

harmonic_mean(List,Mean)

Mode and number of proofs:

harmonic_mean(+list(number),-float) - zero_or_one

weighted_mean/3

Calculates the weighted mean of a list of numbers. Fails if the list is empty or if the two lists have different lengths. Wights are assume to be non-negative.

Compilation flags:

static

Template:

weighted_mean(Weights,List,Mean)

Mode and number of proofs:

weighted_mean(+list(number),+list(number),-float) - zero_or_one

median/2

Calculates the median of a list of numbers. Fails if the list is empty.

Compilation flags:

static

Template:

median(List,Median)

Mode and number of proofs:

median(+list(number),-float) - zero_or_one

modes/2

Returns the list of modes of a list of numbers in ascending order. Fails if the list is empty.

Compilation flags:

static

Template:

modes(List,Modes)

Mode and number of proofs:

modes(+list(number),-list(number)) - zero_or_one

average_deviation/3

Calculates the average absolute deviation of a list of numbers given a central tendency (e.g. mean, median, or mode). Fails if the list is empty.

Compilation flags:

static

Template:

average_deviation(List,CentralTendency,Deviation)

Mode and number of proofs:

average_deviation(+list(number),+float,-float) - zero_or_one

mean_deviation/2

Calculates the mean absolute deviation of a list of numbers. Fails if the list is empty.

Compilation flags:

static

Template:

mean_deviation(List,Deviation)

Mode and number of proofs:

mean_deviation(+list(number),-float) - zero_or_one

median_deviation/2

Calculates the median absolute deviation of a list of numbers. Fails if the list is empty.

Compilation flags:

static

Template:

median_deviation(List,Deviation)

Mode and number of proofs:

median_deviation(+list(number),-float) - zero_or_one

standard_deviation/2

Calculates the standard deviation of a list of numbers. Fails if the list is empty.

Compilation flags:

static

Template:

standard_deviation(List,Deviation)

Mode and number of proofs:

standard_deviation(+list(number),-float) - zero_or_one

coefficient_of_variation/2

Calculates the coefficient of variation of a list of numbers. Fails if the list is empty.

Compilation flags:

static

Template:

coefficient_of_variation(List,Coefficient)

Mode and number of proofs:

`coefficient_of_variation(+list(number),-float) - zero_or_one`

`relative_standard_deviation/2`

Calculates the relative standard deviation of a list of numbers. Fails if the list is empty.

Compilation flags:

`static`

Template:

`relative_standard_deviation(List,Percentage)`

Mode and number of proofs:

`relative_standard_deviation(+list(number),-float) - zero_or_one`

`skewness/2`

Calculates the (moment) skewness of a list of numbers. Fails if the list is empty.

Compilation flags:

`static`

Template:

`skewness(List,Skewness)`

Mode and number of proofs:

`skewness(+list(number),-float) - zero_or_one`

`kurtosis/2`

Calculates the (excess) kurtosis of a list of numbers. Fails if the list is empty.

Compilation flags:

`static`

Template:

kurtosis(List,Kurtosis)

Mode and number of proofs:

kurtosis(+list(number),-float) - zero_or_one

variance/2

Calculates the unbiased variance of a list of numbers. Fails if the list is empty.

Compilation flags:

static

Template:

variance(List,Variance)

Mode and number of proofs:

variance(+list(number),-float) - zero_or_one

z_normalization/2

Normalizes a list of number such that for the resulting list the mean of is close to zero and the standard deviation is close to 1. Fails if the list is empty.

Compilation flags:

static

Template:

z_normalization(List,NormalizedList)

Mode and number of proofs:

z_normalization(+list(number),-list(float)) - zero_or_one

fractile/3

Calculates the smallest value in a list of numbers such that the list elements in its fraction P are less or equal to that value (with P in the open interval (0.0, 1.0)). Fails if the list is empty.

Compilation flags:

static

Template:

fractile(P,List,Fractile)

Mode and number of proofs:

fractile(+float,+list(integer),-integer) - zero_or_one

fractile(+float,+list(float),-float) - zero_or_one

valid/1

Term is a closed list of numbers.

Compilation flags:

static

Template:

valid(Term)

Mode and number of proofs:

valid(@nonvar) - zero_or_one

Protected predicates

(none)

Private predicates

(none)

Operators

(none)

See also:

statistics, sample, population

1.66 term_io

object

1.66.1 term_io

Term input/output from/to atom, chars, and codes.

Availability:

```
logtalk_load(term_io(loader))
```

Author: Paulo Moura

Version: 1:3:0

Date: 2023-11-14

Compilation flags:

```
static, context_switching_calls
```

Implements:

```
public term_io_protocol
```

Uses:

```
os
```

Remarks:

(none)

Inherited public predicates:

```
format_to_atom/3 format_to_chars/3 format_to_chars/4 format_to_codes/3  
format_to_codes/4 read_from_atom/2 read_from_chars/2 read_from_codes/2  
read_term_from_atom/3 read_term_from_chars/3 read_term_from_chars/4  
read_term_from_codes/3 read_term_from_codes/4 with_output_to/2 write_term_to_atom/3  
write_term_to_chars/3 write_term_to_chars/4 write_term_to_codes/3  
write_term_to_codes/4 write_to_atom/2 write_to_chars/2 write_to_codes/2
```

- Public predicates
- Protected predicates
- Private predicates
 - temporary_file_/1
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

temporary_file_/1

Logtalk session and term_io specific temporary file path.

Compilation flags:

dynamic

Template:

temporary_file_(Path)

Mode and number of proofs:

temporary_file_(-atom) - one

Operators

(none)

protocol

1.66.2 term_io_protocol

Predicates for term input/output from/to atom, chars, and codes. The predicates are declared as synchronized when the library is compiled using a backend supporting threads.

Availability:

```
logtalk_load(term_io(loader))
```

Author: Paulo Moura

Version: 1:3:0

Date: 2021-10-04

Compilation flags:

```
static
```

Dependencies:

```
(none)
```

Remarks:

- Portability notes: To keep calls to these library predicates portable, use only standard read/write options and specify output formats using atoms.

Inherited public predicates:

```
(none)
```

- Public predicates
 - read_term_from_atom/3
 - read_from_atom/2
 - read_term_from_chars/3
 - read_term_from_chars/4
 - read_from_chars/2
 - read_term_from_codes/3
 - read_term_from_codes/4
 - read_from_codes/2
 - write_term_to_atom/3
 - write_to_atom/2
 - write_term_to_chars/3

- write_term_to_chars/4
 - write_to_chars/2
 - write_term_to_codes/3
 - write_term_to_codes/4
 - write_to_codes/2
 - format_to_atom/3
 - format_to_chars/3
 - format_to_chars/4
 - format_to_codes/3
 - format_to_codes/4
 - with_output_to/2
- Protected predicates
 - Private predicates
 - Operators

Public predicates

read_term_from_atom/3

Reads a term from an atom using the given read options. A period at the end of the atom is optional. Valid options are those supported by the standard read_term/3 predicate.

Compilation flags:

static, synchronized

Template:

read_term_from_atom(Atom,Term,Options)

Mode and number of proofs:

read_term_from_atom(+atom,-term,+list(read_option)) - one_or_error

read_from_atom/2

Reads a term from an atom using default read options. Shorthand for read_term_from_atom(Atom,Term, []). A period at the end of the atom is optional.

Compilation flags:

static

Template:

read_from_atom(Atom,Term)

Mode and number of proofs:

read_from_atom(+atom,-term) - one_or_error

read_term_from_chars/3

Reads a term from a list of characters using the given read options. A period at the end of the list is optional. Valid options are those supported by the standard read_term/3 predicate.

Compilation flags:

static, synchronized

Template:

read_term_from_chars(Chars,Term,Options)

Mode and number of proofs:

read_term_from_chars(+list(character),-term,+list(read_option)) - one_or_error

read_term_from_chars/4

Reads a term from a list of characters using the given read options, also returning the remaining characters. A period at the end of the term is required. Valid options are those supported by the standard read_term/3 predicate.

Compilation flags:

static

Template:

read_term_from_chars(Chars,Term,Tail,Options)

Mode and number of proofs:

`read_term_from_chars(+list(character),-term,-list(character),+list(read_option)) - one_or_error`

`read_from_chars/2`

Reads a term from a list of characters using default read options. Shorthand for `read_term_from_chars(Chars,Term,[])`. A period at the end of the list is optional.

Compilation flags:

`static`

Template:

`read_from_chars(Chars,Term)`

Mode and number of proofs:

`read_from_chars(+list(character),-term) - one_or_error`

`read_term_from_codes/3`

Reads a term from a list of character codes using the given read options. A period at the end of the list is optional. Valid options are those supported by the standard `read_term/3` predicate.

Compilation flags:

`static, synchronized`

Template:

`read_term_from_codes(Codes,Term,Options)`

Mode and number of proofs:

`read_term_from_codes(+list(character_code),-term,+list(read_option)) - one_or_error`

`read_term_from_codes/4`

Reads a term from a list of character codes using the given read options, also returning the remaining character codes. A period at the end of the term is required. Valid options are those supported by the standard `read_term/3` predicate.

Compilation flags:

`static`

Template:

`read_term_from_codes(Codes,Term,Tail,Options)`

Mode and number of proofs:

`read_term_from_codes(+list(character_code),-term,-list(character_code),+list(read_option)) - one_or_error`

`read_from_codes/2`

Reads a term from a list of character codes using default read options. Shorthand for `read_term_from_codes(Codes,Term,[])`. A period at the end of the list is optional.

Compilation flags:

`static`

Template:

`read_from_codes(Codes,Term)`

Mode and number of proofs:

`read_from_codes(+list(character_code),-term) - one_or_error`

`write_term_to_atom/3`

Writes a term to an atom using the given write options. Valid options are those supported by the standard `write_term/3` predicate.

Compilation flags:

`static, synchronized`

Template:

`write_term_to_atom(Term,Atom,Options)`

Mode and number of proofs:

`write_term_to_atom(@term,-atom,+list(write_option)) - one`

`write_to_atom/2`

Writes a term to an atom using default write options. Shorthand for `write_term_to_atom(Term,Atom,[])`.

Compilation flags:

`static`

Template:

`write_to_atom(Term,Atom)`

Mode and number of proofs:

`write_to_atom(@term,-atom) - one`

`write_term_to_chars/3`

Writes a term to a list of characters using the given write options. Shorthand for `write_term_to_chars(Term,Chars,[],Options)`. Valid options are those supported by the standard `write_term/3` predicate.

Compilation flags:

`static`

Template:

`write_term_to_chars(Term,Chars,Options)`

Mode and number of proofs:

`write_term_to_chars(@term,-list(character),+list(write_option)) - one`

`write_term_to_chars/4`

Writes a term to a list of characters with the given tail using the given write options. Valid options are those supported by the standard `write_term/3` predicate.

Compilation flags:

static, synchronized

Template:

`write_term_to_chars(Term,Chars,Tail,Options)`

Mode and number of proofs:

`write_term_to_chars(@term,-list(character),@term,+list(write_option)) - one`

`write_to_chars/2`

Writes a term to a list of characters using default write options. Shorthand for `write_term_to_chars(Term,Chars,[],[])`.

Compilation flags:

static

Template:

`write_to_chars(Term,Chars)`

Mode and number of proofs:

`write_to_chars(@term,-list(character)) - one`

`write_term_to_codes/3`

Writes a term to a list of character codes using the given write options. Shorthand for `write_term_to_codes(Term,Codes,[],Options)`. Valid options are those supported by the standard `write_term/3` predicate.

Compilation flags:

static

Template:

`write_term_to_codes(Term,Codes,Options)`

Mode and number of proofs:

```
write_term_to_codes(@term,-list(character_code),+list(write_option)) - one
```

`write_term_to_codes/4`

Writes a term to a list of character codes with the given tail using the given write options. Valid options are those supported by the standard `write_term/3` predicate.

Compilation flags:

```
static, synchronized
```

Template:

```
write_term_to_codes(Term,Codes,Tail,Options)
```

Mode and number of proofs:

```
write_term_to_codes(@term,-list(character_code),@term,+list(write_option)) - one
```

`write_to_codes/2`

Writes a term to a list of character codes using default write options. Shorthand for `write_term_to_chars(Term,Codes,[],[])`.

Compilation flags:

```
static
```

Template:

```
write_to_codes(Term,Codes)
```

Mode and number of proofs:

```
write_to_codes(@term,-list(character_code)) - one
```

`format_to_atom/3`

Writes a list of arguments to an atom using the given format (specified as in the de facto standard `format/2` predicate).

Compilation flags:

static, synchronized

Template:

`format_to_atom(Format,Arguments,Atom)`

Mode and number of proofs:

`format_to_atom(@atom,+list(term),-atom) - one`

`format_to_chars/3`

Writes a list of arguments to a list of characters using the given format (specified as in the de facto standard `format/2` predicate). Shorthand for `format_to_chars(Format,Arguments,Chars,[])`.

Compilation flags:

static

Template:

`format_to_chars(Format,Arguments,Chars)`

Mode and number of proofs:

`format_to_chars(@term,+list(term),-list(character)) - one`

`format_to_chars/4`

Writes a term to a list of characters with the given tail using the given format (specified as in the de facto standard `format/2` predicate).

Compilation flags:

static, synchronized

Template:

`format_to_chars(Format,Arguments,Chars,Tail)`

Mode and number of proofs:

`format_to_chars(@term,+list(term),-list(character),@term) - one`

`format_to_codes/3`

Writes a list of arguments to a list of character codes using the given format (specified as in the de facto standard `format/2` predicate). Shorthand for `format_to_codes(Format,Arguments,Codes,[])`.

Compilation flags:

`static`

Template:

`format_to_codes(Format,Arguments,Codes)`

Mode and number of proofs:

`format_to_codes(@term,+list(term),-list(character_code)) - one`

`format_to_codes/4`

Writes a list of arguments to a list of character codes with the given tail using the given format (specified as in the de facto standard `format/2` predicate).

Compilation flags:

`static, synchronized`

Template:

`format_to_codes(Format,Arguments,Codes,Tail)`

Mode and number of proofs:

`format_to_codes(@term,+list(term),-list(character_code),@term) - one`

`with_output_to/2`

Calls a goal deterministically with output to the given format: `atom(Atom)`, `chars(Chars)`, `chars(Chars,Tail)`, `codes(Codes)`, or `codes(Codes,Tail)`.

Compilation flags:

`static`, `synchronized`

Template:

`with_output_to(Output,Goal)`

Meta-predicate template:

`with_output_to(*,0)`

Mode and number of proofs:

`with_output_to(+compound,+callable) - zero_or_one`

Protected predicates

(none)

Private predicates

(none)

Operators

(none)

1.67 timeout

object

1.67.1 timeout

Predicates for calling goal with a time limit.

Availability:

`logtalk_load(timeout(loader))`

Author: Paulo Moura

Version: 0:10:0

Date: 2022-06-15

Compilation flags:

static, context_switching_calls

Dependencies:

(none)

Remarks:

- Supported backend Prolog systems: B-Prolog, ECLiPSe, LVM, SICStus Prolog, SWI-Prolog, Trealla Prolog, XSB, and YAP.

Inherited public predicates:

(none)

- Public predicates
 - call_with_timeout/2
 - call_with_timeout/3
- Protected predicates
- Private predicates
- Operators

Public predicates

call_with_timeout/2

Calls a goal deterministically with the given time limit (expressed in seconds). Note that the goal may fail or throw an error before exhausting the time limit.

Compilation flags:

static

Template:

call_with_timeout(Goal,Timeout)

Meta-predicate template:

call_with_timeout(0,*)

Mode and number of proofs:

call_with_timeout(+callable,+positive_number) - zero_or_one

Exceptions:

Goal does not complete in the allowed time:
 timeout(Goal)

call_with_timeout/3

Calls a goal deterministically with the given time limit (expressed in seconds) returning a reified result: true, fail, timeout, or error(Error).

Compilation flags:

 static

Template:

 call_with_timeout(Goal,Timeout,Result)

Meta-predicate template:

 call_with_timeout(0,*,*)

Mode and number of proofs:

 call_with_timeout(+callable,+positive_number,--atom) - one

Protected predicates

(none)

Private predicates

(none)

Operators

(none)

1.68 toychr

object

1.68.1 toychrdb

Simple CHR interpreter/debugger based on the refined operational semantics of CHRs.

Availability:

```
logtalk_load(toychr(loader))
```

Author: Gregory J. Duck; adapted to Logtalk by Paulo Moura.

Version: 0:7:1

Date: 2024-03-15

Copyright: Copyright 2004 Gregory J. Duck; Copyright 2019-2024 Paulo Moura

License: GPL-2.0-or-later

Compilation flags:

```
static, context_switching_calls
```

Implements:

```
public expanding
```

Uses:

```
list
```

```
user
```

Remarks:

```
(none)
```

Inherited public predicates:

```
goal_expansion/2 term_expansion/2
```

- Public predicates
 - chr_is/2
 - chr_trace/0
 - chr_notrace/0
 - chr_spy/1
 - chr_nospy/0
 - chr_no_spy/1
 - chr_option/2
- Protected predicates

- current_prog/1
- chr_option_print_trace/0
- chr_option_trace_interactive/0
- chr_option_optimization_level/1
- chr_option_show_stack/0
- chr_option_show_store/0
- chr_option_show_history/0
- chr_option_show_id/0
- chr_option_allow_deep_guards/0
- chr_next_state/1
- chr_spy_point/1
- Private predicates
 - chr_rule_/1
- Operators

Public predicates

chr_is/2

Compilation flags:
static

chr_trace/0

Compilation flags:
static

chr_notrace/0

Compilation flags:
static

chr_spy/1

Compilation flags:
static

chr_nospy/0

Compilation flags:
static

chr_no_spy/1

Compilation flags:
static

chr_option/2

Compilation flags:
static

Protected predicates

current_prog/1

Compilation flags:
static

chr_option_print_trace/0

Compilation flags:

dynamic

chr_option_trace_interactive/0

Compilation flags:

dynamic

chr_option_optimization_level/1

Compilation flags:

dynamic

chr_option_show_stack/0

Compilation flags:

dynamic

chr_option_show_store/0

Compilation flags:

dynamic

chr_option_show_history/0

Compilation flags:
dynamic

chr_option_show_id/0

Compilation flags:
dynamic

chr_option_allow_deep_guards/0

Compilation flags:
dynamic

chr_next_state/1

Compilation flags:
dynamic

chr_spy_point/1

Compilation flags:
dynamic

Private predicates

chr_rule_/1

Compilation flags:
dynamic

Operators

(none)

1.69 tsv

object

1.69.1 tsv

TSV files reading and writing predicates using the option Header-keep.

Availability:
logtalk_load(tsv(loader))

Author: Paulo Moura
Version: 1:0:0
Date: 2023-11-15

Compilation flags:
static, context_switching_calls

Extends:
public tsv(keep)

Remarks:
(none)

Inherited public predicates:
read_file/2 read_file/3 read_file_by_line/2 read_file_by_line/3 read_stream/2
read_stream/3 read_stream_by_line/2 read_stream_by_line/3 write_file/3 write_stream/3

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

object

1.69.2 tsv(Header)

- Header - Header handling option with possible values skip and keep (default).

TSV file and stream reading and writing predicates.

Availability:

```
logtalk_load(tsv(loader))
```

Author: Paulo Moura

Version: 1:0:1

Date: 2024-03-11

Compilation flags:

```
static, context_switching_calls
```

Implements:

```
public tsv_protocol
```

Uses:

list
logtalk
reader
type

Remarks:

(none)

Inherited public predicates:

read_file/2 read_file/3 read_file_by_line/2 read_file_by_line/3 read_stream/2
read_stream/3 read_stream_by_line/2 read_stream_by_line/3 write_file/3 write_stream/3

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

protocol

1.69.3 tsv_protocol

TSV file and stream reading and writing protocol.

Availability:

```
logtalk_load(tsv(loader))
```

Author: Paulo Moura

Version: 1:0:0

Date: 2023-11-15

Compilation flags:

```
static
```

Dependencies:

```
(none)
```

Remarks:

- Type-checking: Some of the predicate file and stream argument type-checking exceptions depend on the Prolog backend compliance with standards.

Inherited public predicates:

```
(none)
```

- Public predicates
 - read_file/3
 - read_stream/3
 - read_file/2
 - read_stream/2
 - read_file_by_line/3
 - read_stream_by_line/3
 - read_file_by_line/2
 - read_stream_by_line/2
 - write_file/3
 - write_stream/3
- Protected predicates
- Private predicates

- Operators

Public predicates

read_file/3

Reads a TSV file saving the data as clauses for the specified object predicate. Fails if the file cannot be parsed.

Compilation flags:

static

Template:

read_file(File, Object, Predicate)

Mode and number of proofs:

read_file(+atom, +object_identifier, +predicate_indicator) - zero_or_one

Exceptions:

File is a variable:

instantiation_error

File is neither a variable nor an atom:

type_error(atom, File)

File is an atom but not an existing file:

existence_error(file, File)

File is an existing file but cannot be opened for reading:

permission_error(open, source_sink, File)

Object is a variable:

instantiation_error

Object is neither a variable nor an object identifier:

type_error(object_identifier, Object)

Object is a valid object identifier but not an existing object:

existence_error(object, Object)

Predicate is a variable:

instantiation_error

Predicate is neither a variable nor a predicate indicator:

type_error(predicate_indicator, Predicate)

Predicate is a valid predicate indicator but not an existing public predicate:

existence_error(predicate, Predicate)

read_stream/3

Reads a TSV stream saving the data as clauses for the specified object predicate. Fails if the stream cannot be parsed.

Compilation flags:

static

Template:

read_stream(Stream, Object, Predicate)

Mode and number of proofs:

read_stream(+stream_or_alias, +object_identifier, +predicate_indicator) - zero_or_one

Exceptions:

Stream is a variable:

instantiation_error

Stream is neither a variable nor a stream-term or alias:

domain_error(stream_or_alias, Stream)

Stream is not an open stream:

existence_error(stream, Stream)

Stream is an output stream:

permission_error(input, stream, Stream)

Stream is a binary stream:

permission_error(input, binary_stream, Stream)

Object is a variable:

instantiation_error

Object is neither a variable nor an object identifier:

type_error(object_identifier, Object)

Object is a valid object identifier but not an existing object:

existence_error(object, Object)

Predicate is a variable:

instantiation_error

Predicate is neither a variable nor a predicate indicator:

type_error(predicate_indicator, Predicate)

Predicate is a valid predicate indicator but not an existing public predicate:

existence_error(predicate, Predicate)

read_file/2

Reads a TSV file returning the data as a list of rows, each row a list of fields. Fails if the file cannot be parsed.

Compilation flags:

static

Template:

read_file(File,Rows)

Mode and number of proofs:

read_file(+atom,-list(list)) - zero_or_one

Exceptions:

File is a variable:

instantiation_error

File is neither a variable nor an atom:

type_error(atom,File)

File is an atom but not an existing file:

existence_error(file,File)

File is an existing file but cannot be opened for reading:

permission_error(open,source_sink,File)

read_stream/2

Reads a TSV stream returning the data as a list of rows, each row a list of fields. Fails if the stream cannot be parsed.

Compilation flags:

static

Template:

read_stream(Stream,Rows)

Mode and number of proofs:

read_stream(+stream_or_alias,-list(list)) - zero_or_one

Exceptions:

Stream is a variable:

instantiation_error

Stream is neither a variable nor a stream-term or alias:

domain_error(stream_or_alias,Stream)
Stream is not an open stream:
existence_error(stream,Stream)
Stream is an output stream:
permission_error(input,stream,Stream)
Stream is a binary stream:
permission_error(input,binary_stream,Stream)

read_file_by_line/3

Reads a TSV file saving the data as clauses for the specified object predicate. The file is read line by line. Fails if the file cannot be parsed.

Compilation flags:
static

Template:

read_file_by_line(File,Object,Predicate)

Mode and number of proofs:

read_file_by_line(+atom,+object_identifier,+predicate_indicator) - zero_or_one

Exceptions:

File is a variable:

instantiation_error

File is neither a variable nor an atom:

type_error(atom,File)

File is an atom but not an existing file:

existence_error(file,File)

File is an existing file but cannot be opened for reading:

permission_error(open,source_sink,File)

Object is a variable:

instantiation_error

Object is neither a variable nor an object identifier:

type_error(object_identifier,Object)

Object is a valid object identifier but not an existing object:

existence_error(object,Object)

Predicate is a variable:

instantiation_error

Predicate is neither a variable nor a predicate indicator:

type_error(predicate_indicator,Predicate)

Predicate is a valid predicate indicator but not an existing public predicate:

existence_error(predicate,Predicate)

`read_stream_by_line/3`

Reads a TSV stream saving the data as clauses for the specified object predicate. The stream is read line by line. Fails if the stream cannot be parsed.

Compilation flags:

`static`

Template:

`read_stream_by_line(Stream, Object, Predicate)`

Mode and number of proofs:

`read_stream_by_line(+stream_or_alias, +object_identifier, +predicate_indicator) - zero_or_one`

Exceptions:

Stream is a variable:

`instantiation_error`

Stream is neither a variable nor a stream-term or alias:

`domain_error(stream_or_alias, Stream)`

Stream is not an open stream:

`existence_error(stream, Stream)`

Stream is an output stream:

`permission_error(input, stream, Stream)`

Stream is a binary stream:

`permission_error(input, binary_stream, Stream)`

Object is a variable:

`instantiation_error`

Object is neither a variable nor an object identifier:

`type_error(object_identifier, Object)`

Object is a valid object identifier but not an existing object:

`existence_error(object, Object)`

Predicate is a variable:

`instantiation_error`

Predicate is neither a variable nor a predicate indicator:

`type_error(predicate_indicator, Predicate)`

Predicate is a valid predicate indicator but not an existing public predicate:

`existence_error(predicate, Predicate)`

`read_file_by_line/2`

Reads a TSV file returning the data as a list of rows, each row a list of fields. The file is read line by line. Fails if the file cannot be parsed.

Compilation flags:

`static`

Template:

`read_file_by_line(File,Rows)`

Mode and number of proofs:

`read_file_by_line(+atom,-list(list)) - zero_or_one`

Exceptions:

File is a variable:

`instantiation_error`

File is neither a variable nor an atom:

`type_error(atom,File)`

File is an atom but not an existing file:

`existence_error(file,File)`

File is an existing file but cannot be opened for reading:

`permission_error(open,source_sink,File)`

`read_stream_by_line/2`

Reads a TSV stream returning the data as a list of rows, each row a list of fields. The stream is read line by line. Fails if the stream cannot be parsed.

Compilation flags:

`static`

Template:

`read_stream_by_line(Stream,Rows)`

Mode and number of proofs:

`read_stream_by_line(+stream_or_alias,-list(list)) - zero_or_one`

Exceptions:

Stream is a variable:

`instantiation_error`

Stream is neither a variable nor a stream-term or alias:

```

    domain_error(stream_or_alias,Stream)
Stream is not an open stream:
    existence_error(stream,Stream)
Stream is an output stream:
    permission_error(input,stream,Stream)
Stream is a binary stream:
    permission_error(input,binary_stream,Stream)

```

write_file/3

Writes a TSV file with the data represented by the clauses of the specified object predicate.

Compilation flags:

```
static
```

Template:

```
write_file(File,Object,Predicate)
```

Mode and number of proofs:

```
write_file(+atom,+object_identifier,+predicate_indicator) - one
```

Exceptions:

File is a variable:

```
instantiation_error
```

File is neither a variable nor an atom:

```
type_error(atom,File)
```

File is an atom but cannot be opened for writing:

```
permission_error(open,source_sink,File)
```

Object is a variable:

```
instantiation_error
```

Object is neither a variable nor an object identifier:

```
type_error(object_identifier,Object)
```

Object is a valid object identifier but not an existing object:

```
existence_error(object,Object)
```

Predicate is a variable:

```
instantiation_error
```

Predicate is neither a variable nor a predicate indicator:

```
type_error(predicate_indicator,Predicate)
```

Predicate is a valid predicate indicator but not an existing public predicate:

```
existence_error(predicate,Predicate)
```

write_stream/3

Writes a TSV stream with the data represented by the clauses of the specified object predicate.

Compilation flags:

static

Template:

write_stream(Stream, Object, Predicate)

Mode and number of proofs:

write_stream(+stream_or_alias, +object_identifier, +predicate_indicator) - one

Exceptions:

Stream is a variable:

instantiation_error

Stream is neither a variable nor a stream-term or alias:

domain_error(stream_or_alias, Stream)

Stream is not an open stream:

existence_error(stream, Stream)

Stream is an input stream:

permission_error(output, stream, Stream)

Stream is a binary stream:

permission_error(output, binary_stream, Stream)

Object is a variable:

instantiation_error

Object is neither a variable nor an object identifier:

type_error(object_identifier, Object)

Object is a valid object identifier but not an existing object:

existence_error(object, Object)

Predicate is a variable:

instantiation_error

Predicate is neither a variable nor a predicate indicator:

type_error(predicate_indicator, Predicate)

Predicate is a valid predicate indicator but not an existing public predicate:

existence_error(predicate, Predicate)

Protected predicates

(none)

Private predicates

(none)

Operators

(none)

1.70 tutor

object

1.70.1 tutor

This object adds explanations and suggestions to selected compiler warning and error messages.

Availability:

```
logtalk_load(tutor(loader))
```

Author: Paulo Moura

Version: 0:63:0

Date: 2024-03-02

Compilation flags:

```
static, context_switching_calls
```

Provides:

```
logtalk::message_hook/4
```

Uses:

```
list
```

```
logtalk
```

Remarks:

- Usage: Simply load this object at startup using the goal `logtalk_load(tutor(loader))`.

Inherited public predicates:

(none)

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

1.71 types

object

1.71.1 atom

Atom data type predicates.

Availability:

`logtalk_load(types(loader))`

Author: Paulo Moura

Version: 1:9:0

Date: 2023-04-12

Compilation flags:

`static, context_switching_calls`

Extends:

public atomic

Uses:

user

Remarks:

(none)

Inherited public predicates:

(<)/2 (=:=)/2 (=<)/2 (=\\=)/2 (>)/2 (>=)/2 check/1 depth/2 ground/1 new/1
 numbervars/1 numbervars/3 occurs/2 singletons/2 subsumes/2 subterm/2 valid/1 variables/2
 variant/2 varnumbers/2 varnumbers/3

- Public predicates
 - replace_sub_atom/4
 - split/3
- Protected predicates
- Private predicates
- Operators

Public predicates

replace_sub_atom/4

Replaces all occurrences of Old by New in Input returning Output. Returns Input if Old is the empty atom. Fails when Output does not unify with the resulting atom.

Compilation flags:

static

Template:

replace_sub_atom(Old,New,Input,Output)

Mode and number of proofs:

replace_sub_atom(+atom,+atom,+atom,?atom) - zero_or_one

split/3

Splits an atom at a given delimiter into a list of sub-atoms.

Compilation flags:

static

Template:

split(Atom,Delimiter,SubAtoms)

Mode and number of proofs:

split(+atom,+atom,-list(atom)) - one

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

object

1.71.2 atomic

Atomic data type predicates.

Availability:

logtalk_load(types(loader))

Author: Paulo Moura

Version: 1:3:0

Date: 2018-07-11

Compilation flags:

static, context_switching_calls

Extends:

public term

Remarks:

(none)

Inherited public predicates:

(<)/2 (=:=)/2 (=<)/2 (=\\=)/2 (>)/2 (>=)/2 check/1 depth/2 ground/1 new/1
 numbervars/1 numbervars/3 occurs/2 singletons/2 subsumes/2 subterm/2 valid/1 variables/2
 variant/2 varnumbers/2 varnumbers/3

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

object

1.71.3 callable

Callable term type predicates.

Availability:

logtalk_load(types(loader))

Author: Paulo Moura

Version: 1:4:0

Date: 2018-07-11

Compilation flags:

static, context_switching_calls

Extends:

public term

Remarks:

(none)

Inherited public predicates:

(<)/2 (:=)/2 (=<)/2 (=\\=)/2 (>)/2 (>=)/2 check/1 depth/2 ground/1 new/1
numbervars/1 numbervars/3 occurs/2 singletons/2 subsumes/2 subterm/2 valid/1 variables/2
variant/2 varnumbers/2 varnumbers/3

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

object

1.71.4 character

Character predicates (most of them assume an ASCII representation).

Availability:

```
logtalk_load(types(loader))
```

Author: Paulo Moura

Version: 1:9:0

Date: 2019-06-29

Compilation flags:

```
static, context_switching_calls
```

Implements:

```
public characterp
```

Extends:

```
public atom
```

Remarks:

(none)

Inherited public predicates:

```
(<)/2 (=:=)/2 (=<)/2 (=\\=)/2 (>)/2 (>=)/2 check/1 depth/2 ground/1 is_alpha/1
is_alphanumeric/1 is_ascii/1 is_bin_digit/1 is_control/1 is_dec_digit/1 is_end_of_line/1
is_hex_digit/1 is_layout/1 is_letter/1 is_lower_case/1 is_newline/1 is_octal_digit/1
is_period/1 is_punctuation/1 is_quote/1 is_upper_case/1 is_vowel/1 is_white_space/1
lower_upper/2 new/1 numbervars/1 numbervars/3 occurs/2 parenthesis/2 replace_sub_atom/4
singletons/2 split/3 subsumes/2 subterm/2 valid/1 variables/2 variant/2 varnumbers/2
varnumbers/3
```

- [Public predicates](#)
- [Protected predicates](#)
- [Private predicates](#)
- [Operators](#)

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

protocol

1.71.5 characterp

Character protocol.

Availability:

logtalk_load(types(loader))

Author: Paulo Moura

Version: 1:3:0

Date: 2019-06-29

Compilation flags:

static

Dependencies:

(none)

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
 - is_ascii/1
 - is_alphanumeric/1
 - is_alpha/1
 - is_letter/1
 - is_bin_digit/1
 - is_octal_digit/1
 - is_dec_digit/1
 - is_hex_digit/1
 - is_lower_case/1
 - is_upper_case/1
 - is_vowel/1
 - is_white_space/1
 - is_layout/1
 - is_quote/1
 - is_punctuation/1
 - is_period/1
 - is_control/1
 - is_newline/1
 - is_end_of_line/1
 - parenthesis/2
 - lower_upper/2
- Protected predicates
- Private predicates
- Operators

Public predicates

is_ascii/1

True if the argument is an ASCII character.

Compilation flags:

static

Template:

is_ascii(Char)

Mode and number of proofs:

`is_ascii(+char) - zero_or_one`

`is_alphanumeric/1`

True if the argument is an alphanumeric character.

Compilation flags:

`static`

Template:

`is_alphanumeric(Char)`

Mode and number of proofs:

`is_alphanumeric(+char) - zero_or_one`

`is_alpha/1`

True if the argument is a letter or an underscore.

Compilation flags:

`static`

Template:

`is_alpha(Char)`

Mode and number of proofs:

`is_alpha(+char) - zero_or_one`

`is_letter/1`

True if the argument is a letter.

Compilation flags:

`static`

Template:

is_letter(Char)

Mode and number of proofs:

is_letter(+char) - zero_or_one

is_bin_digit/1

True if the argument is a binary digit.

Compilation flags:

static

Template:

is_bin_digit(Char)

Mode and number of proofs:

is_bin_digit(+char) - zero_or_one

is_octal_digit/1

True if the argument is an octal digit.

Compilation flags:

static

Template:

is_octal_digit(Char)

Mode and number of proofs:

is_octal_digit(+char) - zero_or_one

`is_dec_digit/1`

True if the argument is a decimal digit.

Compilation flags:

`static`

Template:

`is_dec_digit(Char)`

Mode and number of proofs:

`is_dec_digit(+char) - zero_or_one`

`is_hex_digit/1`

True if the argument is an hexadecimal digit.

Compilation flags:

`static`

Template:

`is_hex_digit(Char)`

Mode and number of proofs:

`is_hex_digit(+char) - zero_or_one`

`is_lower_case/1`

True if the argument is a lower case letter.

Compilation flags:

`static`

Template:

`is_lower_case(Char)`

Mode and number of proofs:

`is_lower_case(+char) - zero_or_one`

is_upper_case/1

True if the argument is a upper case letter.

Compilation flags:

static

Template:

is_upper_case(Char)

Mode and number of proofs:

is_upper_case(+char) - zero_or_one

is_vowel/1

True if the argument is a vowel.

Compilation flags:

static

Template:

is_vowel(Char)

Mode and number of proofs:

is_vowel(+char) - zero_or_one

is_white_space/1

True if the argument is a white space character (a space or a tab) inside a line of characters.

Compilation flags:

static

Template:

is_white_space(Char)

Mode and number of proofs:

is_white_space(+char) - zero_or_one

is_layout/1

True if the argument is a layout character.

Compilation flags:

static

Template:

is_layout(Char)

Mode and number of proofs:

is_layout(+char) - zero_or_one

is_quote/1

True if the argument is a quote character.

Compilation flags:

static

Template:

is_quote(Char)

Mode and number of proofs:

is_quote(+char) - zero_or_one

is_punctuation/1

True if the argument is a sentence punctuation character.

Compilation flags:

static

Template:

is_punctuation(Char)

Mode and number of proofs:

is_punctuation(+char) - zero_or_one

is_period/1

True if the argument is a character that ends a sentence.

Compilation flags:

static

Template:

is_period(Char)

Mode and number of proofs:

is_period(+char) - zero_or_one

is_control/1

True if the argument is an ASCII control character.

Compilation flags:

static

Template:

is_control(Char)

Mode and number of proofs:

is_control(+char) - zero_or_one

is_newline/1

True if the argument is the ASCII newline character.

Compilation flags:

static

Template:

is_newline(Char)

Mode and number of proofs:

is_newline(+char) - zero_or_one

`is_end_of_line/1`

True if the argument is the ASCII end-of-line character (either a carriage return or a line feed).

Compilation flags:

`static`

Template:

`is_end_of_line(Char)`

Mode and number of proofs:

`is_end_of_line(+char) - zero_or_one`

`parenthesis/2`

Recognizes and converts between open and close parenthesis.

Compilation flags:

`static`

Template:

`parenthesis(Char1,Char2)`

Mode and number of proofs:

`parenthesis(?char,?char) - zero_or_more`

`parenthesis(+char,?char) - zero_or_one`

`parenthesis(?char,+char) - zero_or_one`

`lower_upper/2`

Recognizes and converts between lower and upper case letters.

Compilation flags:

`static`

Template:

`lower_upper(Char1,Char2)`

Mode and number of proofs:

`lower_upper(?char,?char) - zero_or_more`

lower_upper(+char,?char) - zero_or_one
lower_upper(?char,+char) - zero_or_one

Protected predicates

(none)

Private predicates

(none)

Operators

(none)

See also:

[character](#)

[protocol](#)

1.71.6 comparingp

Comparing protocol using overloading of standard operators.

Availability:

logtalk_load(types(loader))

Author: Paulo Moura

Version: 1:0:0

Date: 2000-07-24

Compilation flags:

static

Dependencies:

(none)

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
 - ($<$)/2
 - ($=<$)/2
 - ($>$)/2
 - ($>=$)/2
 - ($=:=$)/2
 - ($=\backslash=$)/2
- Protected predicates
- Private predicates
- Operators

Public predicates

($<$)/2

True if Term1 is less than Term2.

Compilation flags:
static

Template:

Term1 $<$ Term2

Mode and number of proofs:

+term $<$ +term - zero_or_one

($=<$)/2

True if Term1 is less or equal than Term2.

Compilation flags:
static

Template:

Term1= $<$ Term2

Mode and number of proofs:

+term=< +term - zero_or_one

(>)/2

True if Term1 is greater than Term2.

Compilation flags:

static

Template:

Term1>Term2

Mode and number of proofs:

+term> +term - zero_or_one

(>=)/2

True if Term1 is equal or greater than Term2.

Compilation flags:

static

Template:

Term1>=Term2

Mode and number of proofs:

+term>= +term - zero_or_one

(=:=)/2

True if Term1 is equal to Term2.

Compilation flags:

static

Template:

Term1==Term2

Mode and number of proofs:

+term== +term - zero_or_one

(=\=)/2

True if Term1 is not equal to Term2.

Compilation flags:

static

Template:

Term1=\=Term2

Mode and number of proofs:

+term=\= +term - zero_or_one

Protected predicates

(none)

Private predicates

(none)

Operators

(none)

object

1.71.7 compound

Compound data type.

Availability:

logtalk_load(types(loader))

Author: Paulo Moura

Version: 1:3:0
Date: 2018-07-11

Compilation flags:
static, context_switching_calls

Extends:
public term

Remarks:
(none)

Inherited public predicates:
(<)/2 (=:=)/2 (=<)/2 (=\\=)/2 (>)/2 (>=)/2 check/1 depth/2 ground/1 new/1
numbervars/1 numbervars/3 occurs/2 singletons/2 subsumes/2 subterm/2 valid/1 variables/2
variant/2 varnumbers/2 varnumbers/3

- [Public predicates](#)
- [Protected predicates](#)
- [Private predicates](#)
- [Operators](#)

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

object

1.71.8 difflist

Difference list predicates.

Availability:

logtalk_load(types(loader))

Author: Paulo Moura

Version: 2:0:0

Date: 2020-05-11

Compilation flags:

static, context_switching_calls

Implements:

public listp

Extends:

public compound

Uses:

list

Remarks:

(none)

Inherited public predicates:

(<)/2 (=:=)/2 (=<)/2 (=\\=)/2 (>)/2 (>=)/2 append/2 append/3 check/1 delete/3
delete_matches/3 depth/2 drop/3 empty/1 flatten/2 ground/1 hamming_distance/3 keysort/2
last/2 length/2 max/2 member/2 memberchk/2 min/2 msort/2 msort/3 new/1 nextto/3
nth0/3 nth0/4 nth1/3 nth1/4 numbervars/1 numbervars/3 occurrences/2 occurrences/3
occurs/2 partition/5 permutation/2 prefix/2 prefix/3 proper_prefix/2 proper_prefix/3
proper_suffix/2 proper_suffix/3 remove_duplicates/2 reverse/2 same_length/2 same_length/3
select/3 select/4 selectchk/3 selectchk/4 singletons/2 sort/2 sort/3 sort/4 split/4 sublist/2
subsequence/3 subsequence/4 substitute/4 subsumes/2 subterm/2 subtract/3 suffix/2 suffix/3
take/3 valid/1 variables/2 variant/2 varnumbers/2 varnumbers/3

- Public predicates
 - add/3

– as_list/2

- Protected predicates
- Private predicates
- Operators

Public predicates

add/3

Adds a term to the end of a difference list.

Compilation flags:

static

Template:

add(Term,DiffList,NewDiffList)

Mode and number of proofs:

add(@term,+difference_list,-difference_list) - one

as_list/2

Returns a list with the elements of the difference list.

Compilation flags:

static

Template:

as_list(DiffList,List)

Mode and number of proofs:

as_list(@difference_list,-list) - one

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

See also:

list, list(Type), numberlist, varlist

object

1.71.9 float

Floating point numbers data type predicates.

Availability:

logtalk_load(types(loader))

Author: Paulo Moura

Version: 1:5:0

Date: 2018-07-15

Compilation flags:

static, context_switching_calls

Extends:

public number

Remarks:

(none)

Inherited public predicates:

(<)/2 (=:=)/2 (=<)/2 (=\\=)/2 =~= / 2 (>)/2 (>=)/2 approximately_equal/2
approximately_equal/3 check/1 depth/2 essentially_equal/3 ground/1 new/1 numbervars/1
numbervars/3 occurs/2 singletons/2 subsumes/2 subterm/2 tolerance_equal/4 valid/1
variables/2 variant/2 varnumbers/2 varnumbers/3

- [Public predicates](#)
- [Protected predicates](#)
- [Private predicates](#)
- [Operators](#)

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

object

1.71.10 integer

Integer data type predicates.

Availability:

`logtalk_load(types(loader))`

Author: Paulo Moura

Version: 1:55:0

Date: 2022-06-21

Compilation flags:

`static, context_switching_calls`

Extends:

`public number`

Remarks:

- Portability notes: This object will use the backend Prolog system between/3, plus/3, and succ/2 built-in predicates when available.

Inherited public predicates:

(<)/2 (=:=)/2 (=<)/2 (=\\=)/2 =~/2 (>)/2 (>=)/2 approximately_equal/2
approximately_equal/3 check/1 depth/2 essentially_equal/3 ground/1 new/1 numbervars/1
numbervars/3 occurs/2 singletons/2 subsumes/2 subterm/2 tolerance_equal/4 valid/1
variables/2 variant/2 varnumbers/2 varnumbers/3

- Public predicates
 - between/3
 - plus/3
 - succ/2
 - sequence/3
 - sequence/4
- Protected predicates
- Private predicates
- Operators

Public predicates

between/3

Returns integers in the interval defined by the two first arguments.

Compilation flags:

static

Template:

between(Lower,Upper,Integer)

Mode and number of proofs:

between(+integer,+integer,+integer) - zero_or_one

between(+integer,+integer,-integer) - zero_or_more

plus/3

Reversible integer sum. At least two of the arguments must be instantiated to integers.

Compilation flags:

static

Template:

plus(I,J,Sum)

Mode and number of proofs:

plus(+integer,+integer,?integer) - zero_or_one

plus(+integer,?integer,+integer) - zero_or_one

plus(?integer,+integer,+integer) - zero_or_one

succ/2

Successor of a natural number. At least one of the arguments must be instantiated to a natural number.

Compilation flags:

static

Template:

succ(I,J)

Mode and number of proofs:

succ(+integer,?integer) - zero_or_one

succ(?integer,+integer) - zero_or_one

sequence/3

Generates a list with the sequence of all integers in the interval [Lower,Upper]. Assumes Lower =< Upper and fails otherwise.

Compilation flags:

static

Template:

sequence(Lower,Upper,List)

Mode and number of proofs:

sequence(+integer,+integer,-list(integer)) - zero_or_one

sequence/4

Generates a list with the sequence of integers in the interval [Lower,Upper] by Step. Assumes Lower =< Upper, Step >= 1 and fails otherwise.

Compilation flags:

static

Template:

sequence(Lower,Upper,Step,List)

Mode and number of proofs:

sequence(+integer,+integer,+integer,-list(integer)) - zero_or_one

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

object

1.71.11 list

List predicates.

Availability:

logtalk_load(types(loader))

Author: Paulo Moura

Version: 4:2:0

Date: 2024-03-11

Compilation flags:

static, context_switching_calls

Implements:

public listp

Extends:

public compound

Remarks:

- Portability notes: This object will use the backend Prolog system `msort/2` and `sort/4` built-in predicates when available.

Inherited public predicates:

(<)/2 (=:=)/2 (=<)/2 (=\\=)/2 (>)/2 (>=)/2 append/2 append/3 check/1 delete/3
 delete_matches/3 depth/2 drop/3 empty/1 flatten/2 ground/1 hamming_distance/3 keysort/2
 last/2 length/2 max/2 member/2 memberchk/2 min/2 msort/2 msort/3 new/1 nextto/3
 nth0/3 nth0/4 nth1/3 nth1/4 numbervars/1 numbervars/3 occurrences/2 occurrences/3
 occurs/2 partition/5 permutation/2 prefix/2 prefix/3 proper_prefix/2 proper_prefix/3
 proper_suffix/2 proper_suffix/3 remove_duplicates/2 reverse/2 same_length/2 same_length/3
 select/3 select/4 selectchk/3 selectchk/4 singletons/2 sort/2 sort/3 sort/4 split/4 sublist/2
 subsequence/3 subsequence/4 substitute/4 subsumes/2 subterm/2 subtract/3 suffix/2 suffix/3
 take/3 valid/1 variables/2 variant/2 varnumbers/2 varnumbers/3

- Public predicates
 - `as_difflist/2`
- Protected predicates
- Private predicates
- Operators

Public predicates

`as_difflist/2`

Converts a list to a difference list.

Compilation flags:

static

Template:

as_difflist(List,Diffist)

Mode and number of proofs:

as_difflist(+list,-difference_list) - one

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

See also:

[list\(Type\)](#), [numberlist](#), [varlist](#), [difflist](#)

object

1.71.12 [list\(Type\)](#)

List predicates with elements constrained to a single type.

Availability:

logtalk_load(types(loader))

Author: Paulo Moura

Version: 1:22:0

Date: 2018-07-11

Compilation flags:

static, context_switching_calls

Extends:

public list

Remarks:

(none)

Inherited public predicates:

(<)/2 (=:=)/2 (=<)/2 (=\\=)/2 (>)/2 (>=)/2 append/2 append/3 as_difflist/2 check/1 delete/3 delete_matches/3 depth/2 drop/3 empty/1 flatten/2 ground/1 hamming_distance/3 keysort/2 last/2 length/2 max/2 member/2 memberchk/2 min/2 msort/2 msort/3 new/1 nextto/3 nth0/3 nth0/4 nth1/3 nth1/4 numbervars/1 numbervars/3 occurrences/2 occurrences/3 occurs/2 partition/5 permutation/2 prefix/2 prefix/3 proper_prefix/2 proper_prefix/3 proper_suffix/2 proper_suffix/3 remove_duplicates/2 reverse/2 same_length/2 same_length/3 select/3 select/4 selectchk/3 selectchk/4 singletons/2 sort/2 sort/3 sort/4 split/4 sublist/2 subsequence/3 subsequence/4 substitute/4 subsumes/2 subterm/2 subtract/3 suffix/2 suffix/3 take/3 valid/1 variables/2 variant/2 varnumbers/2 varnumbers/3

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

See also:

list, numberlist, varlist, difflist

protocol

1.71.13 listp

List protocol.

Availability:

`logtalk_load(types(loader))`

Author: Paulo Moura

Version: 1:17:0

Date: 2023-11-17

Compilation flags:

`static`

Dependencies:

`(none)`

Remarks:

`(none)`

Inherited public predicates:

`(none)`

- Public predicates
 - `append/2`
 - `append/3`
 - `delete/3`
 - `delete_matches/3`
 - `empty/1`
 - `flatten/2`
 - `hamming_distance/3`
 - `keysort/2`
 - `last/2`
 - `length/2`
 - `max/2`
 - `member/2`
 - `memberchk/2`

- min/2
- msort/2
- msort/3
- nextto/3
- nth0/3
- nth0/4
- nth1/3
- nth1/4
- occurrences/2
- occurrences/3
- partition/5
- permutation/2
- prefix/2
- prefix/3
- proper_prefix/2
- proper_prefix/3
- remove_duplicates/2
- reverse/2
- same_length/2
- same_length/3
- select/3
- selectchk/3
- select/4
- selectchk/4
- sort/2
- sort/3
- sort/4
- split/4
- sublist/2
- subsequence/3
- subsequence/4
- substitute/4
- subtract/3
- suffix/2
- suffix/3

- proper_suffix/2
- proper_suffix/3
- take/3
- drop/3
- Protected predicates
- Private predicates
- Operators

Public predicates

append/2

Appends all lists in a list of lists.

Compilation flags:

static

Template:

append(Lists,Concatenation)

Mode and number of proofs:

append(+list(list),?list) - zero_or_one

append/3

Appends two lists.

Compilation flags:

static

Template:

append(List1,List2,List)

Mode and number of proofs:

append(?list,?list,?list) - zero_or_more

`delete/3`

Deletes from a list all occurrences of an element returning the list of remaining elements. Uses `==/2` for element comparison.

Compilation flags:

`static`

Template:

`delete(List,Element,Remaining)`

Mode and number of proofs:

`delete(@list,@term,?list) - one`

`delete_matches/3`

Deletes all matching elements from a list, returning the list of remaining elements. Uses `=/2` for element comparison.

Compilation flags:

`static`

Template:

`delete_matches(List,Element,Remaining)`

Mode and number of proofs:

`delete_matches(@list,@term,?list) - one`

`empty/1`

True if the argument is an empty list.

Compilation flags:

`static`

Template:

`empty(List)`

Mode and number of proofs:

`empty(@list) - zero_or_one`

flatten/2

Flattens a list of lists into a list.

Compilation flags:

static

Template:

flatten(List,Flatted)

Mode and number of proofs:

flatten(+list,-list) - one

hamming_distance/3

Calculates the Hamming distance between two lists (using equality to compare list elements). Fails if the two lists are not of the same length.

Compilation flags:

static

Template:

hamming_distance(List1,List2,Distance)

Mode and number of proofs:

hamming_distance(+list,+list,-integer) - zero_or_one

keysort/2

Sorts a list of key-value pairs in ascending order.

Compilation flags:

static

Template:

keysort(List,Sorted)

Mode and number of proofs:

keysort(+list(pair),-list(pair)) - one

last/2

List last element (if it exists).

Compilation flags:

static

Template:

last(List,Last)

Mode and number of proofs:

last(?list,?term) - zero_or_more

length/2

List length.

Compilation flags:

static

Template:

length(List,Length)

Mode and number of proofs:

length(?list,?integer) - zero_or_more

max/2

Determines the list maximum value using standard order. Fails if the list is empty.

Compilation flags:

static

Template:

max(List,Maximum)

Mode and number of proofs:

max(+list,-term) - zero_or_one

member/2

Element is a list member.

Compilation flags:

static

Template:

member(Element,List)

Mode and number of proofs:

member(?term,?list) - zero_or_more

memberchk/2

Checks if a term is a member of a list.

Compilation flags:

static

Template:

memberchk(Element,List)

Mode and number of proofs:

memberchk(?term,?list) - zero_or_one

min/2

Determines the minimum value in a list using standard order. Fails if the list is empty.

Compilation flags:

static

Template:

min(List,Minimum)

Mode and number of proofs:

min(+list,-term) - zero_or_one

msortBy2

Sorts a list in ascending order (duplicated elements are not removed).

Compilation flags:

static

Template:

msortBy(List,Sorted)

Mode and number of proofs:

msortBy(+list,-list) - one

msortBy3

Sorts a list using a user-specified comparison predicate modeled on the standard compare/3 predicate (duplicated elements are not removed).

Compilation flags:

static

Template:

msortBy(Closure,List,Sorted)

Meta-predicate template:

msortBy(3,*,*)

Mode and number of proofs:

`msort(+callable,+list,-list)` - one

`nextto/3`

X and Y are consecutive elements in List.

Compilation flags:

`static`

Template:

`nextto(X,Y,List)`

Mode and number of proofs:

`nextto(?term,?term,?list)` - zero_or_more

`nth0/3`

Nth element of a list (counting from zero).

Compilation flags:

`static`

Template:

`nth0(Nth,List,Element)`

Mode and number of proofs:

`nth0(?integer,?list,?term)` - zero_or_more

`nth0/4`

Nth element of a list (counting from zero). Rest is a list of all the other elements. Can be used to either select the nth element of List or to insert an element before the nth element in Rest.

Compilation flags:

`static`

Template:

`nth0(Nth,List,Element,Rest)`

Mode and number of proofs:

`nth0(?integer,?list,?term,?list) - zero_or_more`

`nth1/3`

Nth element of a list (counting from one).

Compilation flags:

`static`

Template:

`nth1(Nth,List,Element)`

Mode and number of proofs:

`nth1(?integer,?list,?term) - zero_or_more`

`nth1/4`

Nth element of a list (counting from one). Rest is a list of all the other elements. Can be used to either select the nth element of List or to insert an element before the nth element in Rest.

Compilation flags:

`static`

Template:

`nth1(Nth,List,Element,Rest)`

Mode and number of proofs:

`nth1(?integer,?list,?term,?list) - zero_or_more`

occurrences/2

Counts the number of occurrences of each List element, unifying Occurrences with a sorted list of Element-Count pairs. Uses term equality for element comparison.

Compilation flags:

static

Template:

occurrences(List,Occurrences)

Mode and number of proofs:

occurrences(@list,-list(pair(term,positive_integer))) - one

occurrences/3

Counts the number of occurrences of each List element, unifying Occurrences with a sorted list of Element-Count pairs. Uses Closure for element comparison.

Compilation flags:

static

Template:

occurrences(List,Closure,Occurrences)

Meta-predicate template:

occurrences(*,2,*)

Mode and number of proofs:

occurrences(@list,@callable,-list(pair(term,positive_integer))) - one

partition/5

Partitions a list in lists with values less, equal, and greater than a given value (using standard order).

Compilation flags:

static

Template:

partition(List,Value,Less,Equal,Greater)

Mode and number of proofs:

partition(+list,+number,-list,-list,-list) - one

permutation/2

The two lists are a permutation of the same list.

Compilation flags:

static

Template:

permutation(List,Permutation)

Mode and number of proofs:

permutation(?list,?list) - zero_or_more

prefix/2

Prefix is a prefix of List.

Compilation flags:

static

Template:

prefix(Prefix,List)

Mode and number of proofs:

prefix(?list,+list) - zero_or_more

prefix/3

Prefix is a prefix of length Length of List.

Compilation flags:

static

Template:

prefix(Prefix,Length,List)

Mode and number of proofs:

prefix(?list,+integer,+list) - zero_or_one

prefix(?list,-integer,+list) - zero_or_more

proper_prefix/2

Prefix is a proper prefix of List.

Compilation flags:

static

Template:

proper_prefix(Prefix,List)

Mode and number of proofs:

proper_prefix(?list,+list) - zero_or_more

proper_prefix/3

Prefix is a proper prefix of length Length of List.

Compilation flags:

static

Template:

proper_prefix(Prefix,Length,List)

Mode and number of proofs:

proper_prefix(?list,+integer,+list) - zero_or_one

proper_prefix(?list,-integer,+list) - zero_or_more

`remove_duplicates/2`

Removes duplicated list elements using equality (`==/2`) for comparison and keeping the left-most element when repeated.

Compilation flags:

`static`

Template:

`remove_duplicates(List,Set)`

Mode and number of proofs:

`remove_duplicates(+list,-list) - one`

`reverse/2`

Reverses a list.

Compilation flags:

`static`

Template:

`reverse(List,Reversed)`

Mode and number of proofs:

`reverse(+list,?list) - zero_or_one`

`reverse(?list,+list) - zero_or_one`

`reverse(-list,-list) - one_or_more`

`same_length/2`

The two lists have the same length.

Compilation flags:

`static`

Template:

`same_length(List1,List2)`

Mode and number of proofs:

same_length(+list,?list) - zero_or_one
same_length(?list,+list) - zero_or_one
same_length(-list,-list) - one_or_more

same_length/3

The two lists have the same length.

Compilation flags:

static

Template:

same_length(List1,List2,Length)

Mode and number of proofs:

same_length(+list,?list,?integer) - zero_or_one
same_length(?list,+list,?integer) - zero_or_one
same_length(-list,-list,-integer) - one_or_more

select/3

Selects an element from a list, returning the list of remaining elements.

Compilation flags:

static

Template:

select(Element,List,Remaining)

Mode and number of proofs:

select(?term,?list,?list) - zero_or_more

selectchk/3

Checks that an element can be selected from a list, returning the list of remaining elements.

Compilation flags:

static

Template:

selectchk(Element,List,Remaining)

Mode and number of proofs:

selectchk(?term,?list,?list) - zero_or_one

select/4

Selects an element from a list, replacing it by a new element and returning the resulting list.

Compilation flags:

static

Template:

select(Old,OldList,New,NewList)

Mode and number of proofs:

select(?term,?list,?term,?list) - zero_or_more

selectchk/4

Checks that an element from a list can be replaced by a new element, returning the resulting list.

Compilation flags:

static

Template:

selectchk(Old,OldList,New,NewList)

Mode and number of proofs:

selectchk(?term,?list,?term,?list) - zero_or_one

sort/2

Sorts a list in ascending order (duplicated elements are removed).

Compilation flags:

static

Template:

sort(List,Sorted)

Mode and number of proofs:

sort(+list,-list) - one

sort/3

Sorts a list using a user-specified comparison predicate modeled on the standard compare/3 predicate (duplicated elements are removed).

Compilation flags:

static

Template:

sort(Closure,List,Sorted)

Meta-predicate template:

sort(3,*,*)

Mode and number of proofs:

sort(+callable,+list,-list) - one

sort/4

Sorts a list using the given key and order. Uses the standard term comparison operators for the order. The key selects the argument in each element in the list to use for comparisons. A key value of zero uses the whole element for comparisons.

Compilation flags:

static

Template:

sort(Key,Order,List,Sorted)

Mode and number of proofs:

sort(+non_negative_integer,+atom,+list,-list) - one

Remarks:

- Removing duplicates: Use one of the @< or @> orders.
 - Keeping duplicates: Use one of the @=< or @>= orders.
 - Sorting in ascending order: Use one of the @< or @=< orders.
 - Sorting in descending order: Use one of the @> or @>= orders.
-

split/4

Splits a list into sublists of a given length. Also returns a list with the remaining elements. Fails if the length is zero or negative.

Compilation flags:

static

Template:

split(List,Length,Sublists,Remaining)

Mode and number of proofs:

split(+list,+integer,-list(list),-list) - zero_or_one

sublist/2

The first list is a sublist of the second.

Compilation flags:

static

Template:

sublist(Sublist,List)

Mode and number of proofs:

sublist(?list,+list) - zero_or_more

subsequence/3

List is an interleaving of Subsequence and Remaining. Element order is preserved.

Compilation flags:

static

Template:

subsequence(List,Subsequence,Remaining)

Mode and number of proofs:

subsequence(?list,?list,?list) - zero_or_more

subsequence/4

Generates subsequences of a given length from a list. Also returns the remaining elements. Element order is preserved.

Compilation flags:

static

Template:

subsequence(List,Length,Subsequence,Remaining)

Mode and number of proofs:

subsequence(+list,+integer,?list,?list) - zero_or_more

substitute/4

Substitutes all occurrences of Old in List by New, returning NewList. Uses term equality for element comparison.

Compilation flags:

static

Template:

substitute(Old,List,New,NewList)

Mode and number of proofs:

substitute(@term,@list,@term,-list) - one

subtract/3

Removes all elements in the second list from the first list, returning the list of remaining elements.

Compilation flags:

static

Template:

subtract(List,Elements,Remaining)

Mode and number of proofs:

subtract(+list,+list,-list) - one

suffix/2

Suffix is a suffix of List.

Compilation flags:

static

Template:

suffix(Suffix,List)

Mode and number of proofs:

suffix(?list,+list) - zero_or_more

suffix/3

Suffix is a suffix of length Length of List.

Compilation flags:

static

Template:

suffix(Suffix,Length,List)

Mode and number of proofs:

suffix(?list,+integer,+list) - zero_or_one
suffix(?list,-integer,+list) - zero_or_more

proper_suffix/2

Suffix is a proper suffix of List.

Compilation flags:

static

Template:

proper_suffix(Suffix,List)

Mode and number of proofs:

proper_suffix(?list,+list) - zero_or_more

proper_suffix/3

Suffix is a proper suffix of length Length of List.

Compilation flags:

static

Template:

proper_suffix(Suffix,Length,List)

Mode and number of proofs:

proper_suffix(?list,+integer,+list) - zero_or_one

proper_suffix(?list,-integer,+list) - zero_or_more

take/3

Takes the first N elements of a list. Fails if the list have fewer than N elements.

Compilation flags:

static

Template:

take(N,List,Elements)

Mode and number of proofs:

take(+integer,+list,-list) - zero_or_one

drop/3

Drops the first N elements of a list. Fails if the list have fewer than N elements.

Compilation flags:

static

Template:

drop(N,List,Remaining)

Mode and number of proofs:

drop(+integer,+list,-list) - zero_or_one

Protected predicates

(none)

Private predicates

(none)

Operators

(none)

See also:

list, list(Type), numberlistp, varlistp

object

1.71.14 natural

Natural numbers data type predicates.

Availability:

logtalk_load(types(loader))

Author: Paulo Moura

Version: 1:1:0

Date: 2009-03-06

Compilation flags:

static, context_switching_calls

Extends:

public integer

Remarks:

(none)

Inherited public predicates:

(<)/2 (=:=)/2 (=<)/2 (=\\=)/2 =~= / 2 (>)/2 (>=)/2 approximately_equal/2
approximately_equal/3 between/3 check/1 depth/2 essentially_equal/3 ground/1 new/1
numbervars/1 numbervars/3 occurs/2 plus/3 sequence/3 sequence/4 singletons/2 subsumes/2
subterm/2 succ/2 tolerance_equal/4 valid/1 variables/2 variant/2 varnumbers/2 varnumbers/3

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

object

1.71.15 number

Number data type predicates.

Availability:

logtalk_load(types(loader))

Author: Paulo Moura

Version: 1:14:0

Date: 2023-12-07

Compilation flags:

static, context_switching_calls

Extends:

public atomic

Remarks:

(none)

Inherited public predicates:

(<)/2 (=:=)/2 (=<)/2 (=\\=)/2 (>)/2 (>=)/2 check/1 depth/2 ground/1 new/1
numbervars/1 numbervars/3 occurs/2 singletons/2 subsumes/2 subterm/2 valid/1 variables/2
variant/2 varnumbers/2 varnumbers/3

- Public predicates
 - `approximately_equal/2`
 - `approximately_equal/3`
 - `essentially_equal/3`
 - `tolerance_equal/4`
 - `==~/2`
- Protected predicates
- Private predicates
- Operators
 - `op(700,xfx,==~)`

Public predicates

`approximately_equal/2`

Compares two numbers for approximate equality given the epsilon arithmetic constant value using the de facto standard formula $\text{abs}(\text{Number1} - \text{Number2}) \leq \max(\text{abs}(\text{Number1}), \text{abs}(\text{Number2})) * \text{epsilon}$. No type-checking.

Compilation flags:

`static`

Template:

`approximately_equal(Number1,Number2)`

Mode and number of proofs:

`approximately_equal(+number,+number) - zero_or_one`

`approximately_equal/3`

Compares two numbers for approximate equality given a user-defined epsilon value using the de facto standard formula $\text{abs}(\text{Number1} - \text{Number2}) \leq \max(\text{abs}(\text{Number1}), \text{abs}(\text{Number2})) * \text{Epsilon}$. No type-checking.

Compilation flags:

`static`

Template:

`approximately_equal(Number1,Number2,Epsilon)`

Mode and number of proofs:

`approximately_equal(+number,+number,+number) - zero_or_one`

Remarks:

- Epsilon range: Epsilon should be the epsilon arithmetic constant value or a small multiple of it. Only use a larger value if a greater error is expected.
- Comparison with essential equality: For the same epsilon value, approximate equality is weaker requirement than essential equality.

`essentially_equal/3`

Compares two numbers for essential equality given an epsilon value using the de facto standard formula $\text{abs}(\text{Number1} - \text{Number2}) \leq \min(\text{abs}(\text{Number1}), \text{abs}(\text{Number2})) * \text{Epsilon}$. No type-checking.

Compilation flags:

`static`

Template:

`essentially_equal(Number1,Number2,Epsilon)`

Mode and number of proofs:

`essentially_equal(+number,+number,+number) - zero_or_one`

Remarks:

- Comparison with approximate equality: For the same epsilon value, essential equality is a stronger requirement than approximate equality.

`tolerance_equal/4`

Compares two numbers for close equality given relative and absolute tolerances using the de facto standard formula $\text{abs}(\text{Number1} - \text{Number2}) \leq \max(\text{RelativeTolerance} * \max(\text{abs}(\text{Number1}), \text{abs}(\text{Number2})), \text{AbsoluteTolerance})$. No type-checking.

Compilation flags:

`static`

Template:

`tolerance_equal(Number1,Number2,RelativeTolerance,AbsoluteTolerance)`

Mode and number of proofs:

tolerance_equal(+number,+number,+number,+number) - zero_or_one

=~= / 2

Compares two floats (or lists of floats) for approximate equality using 100*epsilon for the absolute error and, if that fails, 99.999% accuracy for the relative error. Note that these precision values may not be adequate for all cases. No type-checking.

Compilation flags:

static

Template:

=~=(Float1,Float2)

Mode and number of proofs:

=~=(+number,+number) - zero_or_one

=~=(+list(number),+list(number)) - zero_or_one

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

op(700,xfx,==)

Scope:

public

object

1.71.16 numberlist

List of numbers predicates.

Availability:

```
logtalk_load(types(loader))
```

Author: Paulo Moura

Version: 1:15:1

Date: 2024-01-08

Compilation flags:

```
static, context_switching_calls
```

Implements:

```
public numberlistp
```

Extends:

```
public list
```

Uses:

```
list
```

Remarks:

```
(none)
```

Inherited public predicates:

```
(<)/2 (=:=)/2 (=<)/2 (=\\=)/2 (>)/2 (>=)/2 append/2 append/3 as_difflist/2 average/2
chebyshev_distance/3 chebyshev_norm/2 check/1 delete/3 delete_matches/3 depth/2 drop/3
empty/1 euclidean_distance/3 euclidean_norm/2 flatten/2 ground/1 hamming_distance/3
keysort/2 last/2 least_common_multiple/2 length/2 manhattan_distance/3 manhattan_norm/2
max/2 median/2 member/2 memberchk/2 min/2 min_max/3 modes/2 msort/2 msort/3
new/1 nextto/3 normalize_range/2 normalize_range/4 normalize_scalar/2 normalize_unit/2
nth0/3 nth0/4 nth1/3 nth1/4 numbervars/1 numbervars/3 occurrences/2 occurrences/3
occurs/2 partition/5 permutation/2 prefix/2 prefix/3 product/2 proper_prefix/2
proper_prefix/3 proper_suffix/2 proper_suffix/3 remove_duplicates/2 rescale/3 reverse/2
same_length/2 same_length/3 scalar_product/3 select/3 select/4 selectchk/3 selectchk/4
singletons/2 sort/2 sort/3 sort/4 split/4 sublist/2 subsequence/3 subsequence/4 substitute/4
subsumes/2 subterm/2 subtract/3 suffix/2 suffix/3 sum/2 take/3 valid/1 variables/2 variant/2
varnumbers/2 varnumbers/3
```

- Public predicates
- Protected predicates
- Private predicates

- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

See also:

list, list(Type), varlist, difflist

protocol

1.71.17 numberlistp

List of numbers protocol.

Availability:

logtalk_load(types(loader))

Author: Paulo Moura

Version: 1:9:0

Date: 2023-12-10

Compilation flags:

static

Dependencies:

(none)

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
 - min/2
 - max/2
 - min_max/3
 - product/2
 - sum/2
 - average/2
 - median/2
 - modes/2
 - euclidean_norm/2
 - chebyshev_norm/2
 - manhattan_norm/2
 - euclidean_distance/3
 - chebyshev_distance/3
 - manhattan_distance/3
 - scalar_product/3
 - normalize_range/2
 - normalize_range/4
 - normalize_unit/2
 - normalize_scalar/2
 - rescale/3
 - least_common_multiple/2
- Protected predicates
- Private predicates
- Operators

Public predicates

min/2

Determines the minimum value in a list using arithmetic order. Fails if the list is empty.

Compilation flags:

static

Template:

min(List,Minimum)

Mode and number of proofs:

min(+list(number),-number) - zero_or_one

max/2

Determines the list maximum value using arithmetic order. Fails if the list is empty.

Compilation flags:

static

Template:

max(List,Maximum)

Mode and number of proofs:

max(+list(number),-number) - zero_or_one

min_max/3

Determines the minimum and maximum values in a list using arithmetic order. Fails if the list is empty.

Compilation flags:

static

Template:

min_max(List,Minimum,Maximum)

Mode and number of proofs:

min_max(+list(number),-number,-number) - zero_or_one

product/2

Calculates the product of all list numbers. Fails if the list is empty.

Compilation flags:

static

Template:

product(List,Product)

Mode and number of proofs:

product(+list(number),-number) - zero_or_one

sum/2

Calculates the sum of all list numbers. Returns the integer zero if the list is empty.

Compilation flags:

static

Template:

sum(List,Sum)

Mode and number of proofs:

sum(+list(number),-number) - one

average/2

Calculates the average (i.e. arithmetic mean) of a list of numbers. Fails if the list is empty.

Compilation flags:

static

Template:

average(List,Average)

Mode and number of proofs:

average(+list(number),-float) - zero_or_one

median/2

Calculates the median of a list of numbers. Fails if the list is empty.

Compilation flags:

static

Template:

median(List,Median)

Mode and number of proofs:

median(+list(number),-float) - zero_or_one

modes/2

Returns the list of modes of a list of numbers in ascending order. Fails if the list is empty.

Compilation flags:

static

Template:

modes(List,Modes)

Mode and number of proofs:

modes(+list(number),-list(number)) - zero_or_one

euclidean_norm/2

Calculates the Euclidean norm of a list of numbers. Fails if the list is empty.

Compilation flags:

static

Template:

euclidean_norm(List, Norm)

Mode and number of proofs:

euclidean_norm(+list(number), -float) - zero_or_one

chebyshev_norm/2

Calculates the Chebyshev norm of a list of numbers. Fails if the list is empty.

Compilation flags:

static

Template:

chebyshev_norm(List, Norm)

Mode and number of proofs:

chebyshev_norm(+list(integer), -integer) - zero_or_one

chebyshev_norm(+list(float), -float) - zero_or_one

manhattan_norm/2

Calculates the Manhattan norm of a list of numbers. Fails if the list is empty.

Compilation flags:

static

Template:

manhattan_norm(List, Norm)

Mode and number of proofs:

manhattan_norm(+list(integer), -integer) - zero_or_one

manhattan_norm(+list(float), -float) - zero_or_one

`euclidean_distance/3`

Calculates the Euclidean distance between two lists of numbers. Fails if the two lists are empty or not of the same length.

Compilation flags:

`static`

Template:

`euclidean_distance(List1,List2,Distance)`

Mode and number of proofs:

`euclidean_distance(+list(number),+list(number),-float) - zero_or_one`

`chebyshev_distance/3`

Calculates the Chebyshev distance between two lists of numbers. Fails if the two lists are empty or not of the same length.

Compilation flags:

`static`

Template:

`chebyshev_distance(List1,List2,Distance)`

Mode and number of proofs:

`chebyshev_distance(+list(integer),+list(integer),-integer) - zero_or_one`

`chebyshev_distance(+list(float),+list(float),-float) - zero_or_one`

`manhattan_distance/3`

Calculates the Manhattan distance between two lists of numbers. Fails if the two lists are empty or not of the same length.

Compilation flags:

`static`

Template:

`manhattan_distance(List1,List2,Distance)`

Mode and number of proofs:

```
manhattan_distance(+list(integer),+list(integer),-integer) - zero_or_one  
manhattan_distance(+list(float),+list(float),-float) - zero_or_one
```

scalar_product/3

Calculates the scalar product of two lists of numbers. Fails if the two lists are empty or not of the same length.

Compilation flags:

```
static
```

Template:

```
scalar_product(List1,List2,Product)
```

Mode and number of proofs:

```
scalar_product(+list(integer),+list(integer),-integer) - zero_or_one  
scalar_product(+list(float),+list(float),-float) - zero_or_one
```

normalize_range/2

Normalizes a list of numbers into the [0.0,1.0] range. Caller must handle arithmetic exceptions if the input list is not normalizable.

Compilation flags:

```
static
```

Template:

```
normalize_range(List,NormalizedList)
```

Mode and number of proofs:

```
normalize_range(+list(number),-list(float)) - one
```

normalize_range/4

Normalizes a list of numbers into the given range. Caller must handle arithmetic exceptions if the input list if not normalizable.

Compilation flags:

static

Template:

normalize_range(List,Minimum,Maximum,NormalizedList)

Mode and number of proofs:

normalize_range(+list(number),+number,+number,-list(float)) - one

normalize_unit/2

Normalizes a list of numbers returning its unit vector (i.e. a list with Euclidean norm equal to one). Caller must handle arithmetic exceptions if the input list if not normalizable.

Compilation flags:

static

Template:

normalize_unit(List,NormalizedList)

Mode and number of proofs:

normalize_unit(+list(number),-list(float)) - one

normalize_scalar/2

Normalizes a list of numbers such that the sum of all numbers is equal to one. Caller must handle arithmetic exceptions if the input list if not normalizable.

Compilation flags:

static

Template:

normalize_scalar(List,NormalizedList)

Mode and number of proofs:

`normalize_scalar(+list(number),-list(float)) - one`

`rescale/3`

Rescales all numbers in a list by the given factor.

Compilation flags:

`static`

Template:

`rescale(List,Factor,RescaledList)`

Mode and number of proofs:

`rescale(+list(integer),+integer,-list(integer)) - one`

`rescale(+list(number),+float,-list(float)) - one`

`least_common_multiple/2`

Computes the least common multiple of a list of two or more positive integers. Fails if the list is empty or contains a single element. Fails also if any of the elements is zero. May require backend support for unbound integer arithmetic.

Compilation flags:

`static`

Template:

`least_common_multiple(Integers,LeastCommonMultiple)`

Mode and number of proofs:

`least_common_multiple(+list(positive_integer),-positive_integer) - zero_or_one`

Protected predicates

(none)

Private predicates

(none)

Operators

(none)

See also:

numberlist, listp, varlistp

object

1.71.18 pairs

Useful predicates over lists of pairs (key-value terms).

Availability:

`logtalk_load(types(loader))`

Author: Paulo Moura

Version: 2:1:1

Date: 2023-11-21

Compilation flags:

`static, context_switching_calls`

Dependencies:

(none)

Remarks:

- Usage: This object can be loaded independently of other entities in the types library by using the goal `logtalk_load(types(pairs))`.

Inherited public predicates:

(none)

- Public predicates
 - keys_values/3
 - keys/2
 - key/2
 - values/2
 - value/3
 - transpose/2
 - group_sorted_by_key/2
 - group_consecutive_by_key/2
 - group_by_key/2
 - map/3
- Protected predicates
- Private predicates
- Operators

Public predicates

keys_values/3

Converts between a list of pairs and lists of keys and values. When converting to pairs, this predicate fails if the list of keys and the list of values have different lengths.

Compilation flags:

static

Template:

keys_values(Pairs,Keys,Values)

Mode and number of proofs:

keys_values(+list(pair),-list,-list) - one

keys_values(-list(pair),+list,+list) - zero_or_one

keys/2

Returns a list of keys from a list of pairs.

Compilation flags:

static

Template:

keys(Pairs,Keys)

Mode and number of proofs:

keys(+list(pair),-list) - one

key/2

Enumerates by backtracking all keys from a list of pairs.

Compilation flags:

static

Template:

key(Pairs,Key)

Mode and number of proofs:

key(+list(pair),-term) - zero_or_more

values/2

Returns a list of values from a list of pairs.

Compilation flags:

static

Template:

values(Pairs,Values)

Mode and number of proofs:

values(+list(pair),-list) - one

value/3

Returns a value addressed by the given path (a key or a list of keys in the case of nested list of pairs). Fails if path does not exist.

Compilation flags:

static

Template:

value(Pairs,Path,Value)

Mode and number of proofs:

value(+list(pair),+term,-term) - zero_or_one

value(+list(pair),+list,-term) - zero_or_one

transpose/2

Transposes a list of pairs by swapping each pair key and value. The relative order of the list elements is kept.

Compilation flags:

static

Template:

transpose(Pairs,TransposedPairs)

Mode and number of proofs:

transpose(+list(pair),-list(pair)) - one

group_sorted_by_key/2

Groups pairs by key by sorting them and then constructing new pairs by grouping all values for a given key in a list. Keys are compared using equality. Relative order of values per key is kept. Resulting list of pairs is sorted by key.

Compilation flags:

static

Template:

`group_sorted_by_key(Pairs,Groups)`

Mode and number of proofs:

`group_sorted_by_key(+list(pair),-list(pair)) - one`

`group_consecutive_by_key/2`

Groups pairs by constructing new pairs by grouping all values for consecutive key in a list. Keys are compared using equality. The relative order of the values for the same key is kept.

Compilation flags:

`static`

Template:

`group_consecutive_by_key(Pairs,Groups)`

Mode and number of proofs:

`group_consecutive_by_key(+list(pair),-list(pair)) - one`

`group_by_key/2`

Same as the `group_sorted_by_key/2` predicate. Deprecated.

Compilation flags:

`static`

Template:

`group_by_key(Pairs,Groups)`

Mode and number of proofs:

`group_by_key(+list(pair),-list(pair)) - one`

map/3

Maps a list into pairs using a closure that applies to each list element to compute its key.

Compilation flags:

static

Template:

map(Closure,List,Pairs)

Meta-predicate template:

map(2,*,*)

Mode and number of proofs:

map(@callable,+list,-list(pair)) - one

Protected predicates

(none)

Private predicates

(none)

Operators

(none)

object

1.71.19 term

Term utility predicates.

Availability:

logtalk_load(types(loader))

Author: Paulo Moura

Version: 1:11:0

Date: 2022-05-13

Compilation flags:

static, context_switching_calls

Implements:

public term

Aliases:

term variables/2 as vars/2

Remarks:

(none)

Inherited public predicates:

(<)/2 (=:=)/2 (=<)/2 (=\\=)/2 (>)/2 (>=)/2 check/1 depth/2 ground/1 new/1
numbervars/1 numbervars/3 occurs/2 singletons/2 subsumes/2 subterm/2 valid/1 variables/2
variant/2 varnumbers/2 varnumbers/3

- [Public predicates](#)
- [Protected predicates](#)
- [Private predicates](#)
- [Operators](#)

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

protocol

1.71.20 term

Term utility predicates protocol.

Availability:

```
logtalk_load(types(loader))
```

Author: Paulo Moura

Version: 1:35:0

Date: 2022-05-13

Compilation flags:

```
static
```

Extends:

```
public comparingp
```

Remarks:

```
(none)
```

Inherited public predicates:

```
(<)/2 (=:=)/2 (=<)/2 (=\\=)/2 (>)/2 (>=)/2
```

- Public predicates
 - depth/2
 - ground/1
 - new/1
 - occurs/2
 - subsumes/2
 - subterm/2
 - valid/1
 - check/1
 - variant/2
 - variables/2
 - singletons/2
 - numbervars/3
 - numbervars/1

- varnumbers/3
- varnumbers/2
- Protected predicates
- Private predicates
- Operators

Public predicates

depth/2

True if the depth of Term is Depth. The depth of atomic terms is zero; the depth of a compound term is one plus the maximum depth of its sub-terms.

Compilation flags:

static

Template:

depth(Term,Depth)

Mode and number of proofs:

depth(@term,?integer) - zero_or_one

ground/1

True if the argument is ground. Deprecated. Use the ground/1 standard predicate instead.

Compilation flags:

static

Template:

ground(Term)

Mode and number of proofs:

ground(@term) - zero_or_one

new/1

Creates a new term instance (if meaningful).

Compilation flags:

static

Template:

new(Term)

Mode and number of proofs:

new(-nonvar) - zero_or_one

occurs/2

True if the variable occurs in the term.

Compilation flags:

static

Template:

occurs(Variable,Term)

Mode and number of proofs:

occurs(@var,@term) - zero_or_one

subsumes/2

The first term subsumes the second term. Deprecated. Use the `subsumes_term/2` standard predicate instead.

Compilation flags:

static

Template:

subsumes(General,Specific)

Mode and number of proofs:

subsumes(@term,@term) - zero_or_one

subterm/2

The first term is a subterm of the second term.

Compilation flags:

static

Template:

subterm(Subterm,Term)

Mode and number of proofs:

subterm(?term,+term) - zero_or_more

valid/1

Term is valid.

Compilation flags:

static

Template:

valid(Term)

Mode and number of proofs:

valid(@nonvar) - zero_or_one

check/1

Checks if a term is valid. Throws an exception if the term is not valid.

Compilation flags:

static

Template:

check(Term)

Mode and number of proofs:

check(@nonvar) - one

variant/2

Each term is a variant of the other (i.e. they are structurally equivalent).

Compilation flags:

static

Template:

variant(Term1,Term2)

Mode and number of proofs:

variant(@term,@term) - zero_or_one

variables/2

Returns a list of all term variables (ordered as found when doing a depth-first, left-to-right traversal of Term). Deprecated. Use the standard term_variables/2 predicate instead.

Compilation flags:

static

Template:

variables(Term,List)

Mode and number of proofs:

variables(@term,-list) - one

singletons/2

Returns a list of all term singleton variables (ordered as found when doing a depth-first, left-to-right traversal of Term).

Compilation flags:

static

Template:

singletons(Term,Singletons)

Mode and number of proofs:

singletons(@term,-list) - one

numbervars/3

Grounds a term by replacing all variables with '\$VAR'(N) terms with N starting at From. The Next argument is unified with the next value for N after binding all variables.

Compilation flags:

static

Template:

numbervars(Term,From,Next)

Mode and number of proofs:

numbervars(?term,+integer,?integer) - zero_or_one

numbervars/1

Grounds a term by replacing all variables with '\$VAR'(N) terms with N starting at 0.

Compilation flags:

static

Template:

numbervars(Term)

Mode and number of proofs:

numbervars(?term) - zero_or_one

varnumbers/3

Replaces all '\$VAR'(N) sub-terms in a term with fresh variables for all values of N greater or equal to From. Variables in Term are shared with Copy.

Compilation flags:

static

Template:

varnumbers(Term,From,Copy)

Mode and number of proofs:

varnumbers(@term,+integer,?term) - zero_or_one

varnumbers/2

Replaces all '\$VAR'(N) sub-terms in a term with fresh variables for all values of N greater or equal to 0. Variables in Term are shared with Copy.

Compilation flags:

static

Template:

varnumbers(Term,Copy)

Mode and number of proofs:

varnumbers(@term,?term) - zero_or_one

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

See also:

[term](#)

[object](#)

1.71.21 type

Type checking predicates. User extensible. New types can be defined by adding clauses for the type/1 and check/2 multifile predicates.

Availability:

```
logtalk_load(types(loader))
```

Author: Paulo Moura

Version: 2:5:0

Date: 2024-03-07

Compilation flags:

```
static, context_switching_calls, complements(restrict)
```

Uses:

```
list
```

Remarks:

- Logtalk specific types: `entity`, `object`, `protocol`, `category`, `entity_identifier`, `object_identifier`, `protocol_identifier`, `category_identifier`, `event`, `predicate`.
- Prolog module related types (when the backend compiler supports modules): `module`, `module_identifier`, `qualified_callable`.
- Prolog base types: `term`, `var`, `nonvar`, `atomic`, `atom`, `number`, `integer`, `float`, `compound`, `callable`, `ground`.
- Atom derived types: `non_quoted_atom`, `non_empty_atom`, `boolean`, `character`, `in_character`, `char`, `operator_specifier`, `hex_char`.
- Atom derived parametric types: `atom(CharSet)`, `atom(CharSet,Length)`, `non_empty_atom(CharSet)`, `character(CharSet)`, `in_character(CharSet)`, `char(CharSet)`.
- Number derived types: `positive_number`, `negative_number`, `non_positive_number`, `non_negative_number`.
- Float derived types: `positive_float`, `negative_float`, `non_positive_float`, `non_negative_float`, `probability`.
- Integer derived types: `positive_integer`, `negative_integer`, `non_positive_integer`, `non_negative_integer`, `byte`, `in_byte`, `character_code`, `in_character_code`, `code`, `operator_priority`, `hex_code`.
- Integer derived parametric types: `character_code(CharSet)`, `in_character_code(CharSet)`, `code(CharSet)`.
- List types (compound derived types): `list`, `non_empty_list`, `partial_list`, `list_or_partial_list`, `list(Type)`, `list(Type,Length)`, `list(Type,Min,Max)`, `list(Type,Length,Min,Max)`, `non_empty_list(Type)`, `codes`, `chars`.
- Difference list types (compound derived types): `difference_list`, `difference_list(Type)`.

- Other compound derived types: `compound(Name,Types)`, `predicate_indicator`, `non_terminal_indicator`, `predicate_or_non_terminal_indicator`, `clause`, `grammar_rule`, `pair`, `pair(KeyType,ValueType)`, `cyclic`, `acyclic`.
- Stream types: `stream`, `stream_or_alias`, `stream(Property)`, `stream_or_alias(Property)`.
- Other types: `Object::Closure`, `between(Type,Lower,Upper)`, `property(Type,LambdaExpression)`, `one_of(Type,Set)`, `var_or(Type)`, `ground(Type)`, `types(Types)`, `constrain(Type,Closure)`, `type`.
- Type predicate notes: This type is used to check for an object public predicate specified as `Object::Functor/Arity`.
- Type boolean notes: The two value of this type are the atoms `true` and `false`.
- Stream types notes: In the case of the `stream(Property)` and `stream_or_alias(Property)` types, `Property` must be a valid stream property.
- Type order notes: The three possible values of this type are the single character atoms `<`, `=`, and `>`.
- Type `character_code` notes: This type takes into account Unicode support by the backend compiler. When Unicode is supported, it distinguishes between BMP and full support. When Unicode is not supported, it assumes a byte representation for characters.
- Type `Object::Closure` notes: Allows calling a public object predicate for type-checking. The predicate should provide valid/2 predicate semantics and assume called with a bound argument. The `Closure` closure is extended with a single argument, the value to be checked.
- Type `compound(Name,Types)` notes: This type verifies that a compound term have the given `Name` and its arguments conform to `Types`.
- Type `between(Type, Lower, Upper)` notes: The type argument allows distinguishing between numbers and other types. It also allows choosing between mixed integer/float comparisons and strict float or integer comparisons. The term is type-checked before testing for interval membership.
- Type `property(Type, Lambda)` notes: Verifies that `Term` satisfies a property described using a lambda expression of the form `[Parameter]>>Goal`. The lambda expression is applied in the context of `user`. The term is type-checked before calling the goal.
- Type `one_of(Type, Set)` notes: For checking if a given term is an element of a set. The set is represented using a list. The term is type-checked before testing for set membership.
- Type `var_or(Type)` notes: Allows checking if a term is either a variable or a valid value of the given type.
- Type `ground(Type)` notes: Allows checking if a term is ground and a valid value of the given type.
- Type `types(Types)` notes: Allows checking if a term is a valid value for one of the types in a list of types.
- Type `constrain(Type,Closure)` notes: Allows checking if a term is a valid value for the given type and satisfies the given closure.
- Type `type` notes: Allows checking if a term is a valid type.
- Type `qualified_callable` notes: Allows checking if a term is a possibly module-qualified callable term. When the term is qualified, it also checks that the qualification modules are type correct. When the term is not qualified, its semantics are the same as the callable type.
- Design choices: The main predicates are `valid/2` and `check/3`. These are defined using the predicate `check/2`. Defining clauses for `check/2` instead of `valid/2` gives the user full control of exception terms without requiring an additional predicate.
- Error context: The built-in execution-context method `context/1` can be used to provide the calling context for errors when using the predicate `check/3`.

- Registering new types: New types can be registered by defining clauses for the `type/1` and `check/2` multifile predicates. Clauses for both predicates must have a bound first argument to avoid introducing spurious choice-points when type-checking terms.
- Meta-types: Meta-types are types that have one or more sub-type arguments. E.g. `var_or(Type)`. The sub-types of a meta-type can be enumerated by defining a clause for the `meta_type/3` multifile predicate.
- Character sets: When testing character or character code based terms (e.g. `atom`), it is possible to choose a character set (`ascii_identifier`, `ascii_printable`, `ascii_full`, `byte`, `unicode_bmp`, or `unicode_full`) using the parameterizable types.
- Caveats: The type argument (and any type parameterization) to the predicates is not type-checked (or checked for consistency) for performance reasons.
- Unicode limitations: Currently, correct character/code type-checking is only ensured for LVM and SWI-Prolog as other backends do not provide support for querying a Unicode code point category.

Inherited public predicates:

`arbitrary/1` `arbitrary/2` `edge_case/2` `get_seed/1` `max_size/1` `mutation/3` `set_seed/1` `shrink/3`
`shrink_sequence/3` `shrinker/1`

- Public predicates
 - `type/1`
 - `meta_type/3`
 - `valid/2`
 - `check/3`
 - `check/2`
- Protected predicates
- Private predicates
- Operators

Public predicates

`type/1`

Table of defined types. A new type can be registered by defining a clause for this predicate and adding a clause for the `check/2` multifile predicate.

Compilation flags:

`static`, `multifile`

Template:

`type(Type)`

Mode and number of proofs:

`type(?callable) - zero_or_more`

`meta_type/3`

Table of defined meta-types. A registered type that is a meta-type can be described by defining a clause for this predicate to enumerate its sub-types and optional values in case of a single sub-type.

Compilation flags:

`static, multifile`

Template:

`meta_type(MetaType,SubTypes,Values)`

Mode and number of proofs:

`meta_type(?callable,-list,-list) - zero_or_more`

`valid/2`

True if the given term is of the specified type. Fails otherwise.

Compilation flags:

`static`

Template:

`valid(Type,Term)`

Mode and number of proofs:

`valid(@callable,@term) - zero_or_one`

`check/3`

True if the given term is of the specified type. Throws an error otherwise using the format `error(Error, Context)`. For the possible values of `Error` see the `check/2` predicate.

Compilation flags:

`static`

Template:

check(Type,Term,Context)

Mode and number of proofs:

check(@callable,@term,@term) - one_or_error

check/2

True if the given term is of the specified type. Throws an error otherwise. A new type can be added by defining a clause for this predicate and registering it by adding a clause for the type/1 multifile predicate.

Compilation flags:

static, multifile

Template:

check(Type,Term)

Meta-predicate template:

check(:,*)

Mode and number of proofs:

check(@callable,@term) - one_or_error

Exceptions:

Term is not bound as required:

instantiation_error

Term is bound but not of the specified type:

type_error(Type,Term)

Term is the of the correct type but not in the specified domain:

domain_error(Domain,Term)

Term is the of the correct type and domain but the resource it represents does not exist:

existence_error(Type,Term)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

See also:

arbitrary, os_types, either, maybe

object

1.71.22 varlist

List of variables predicates.

Availability:

logtalk_load(types(loader))

Author: Paulo Moura

Version: 2:0:0

Date: 2020-05-11

Compilation flags:

static, context_switching_calls

Implements:

public varlistp

Remarks:

(none)

Inherited public predicates:

append/3 check/1 delete/3 empty/1 flatten/2 last/2 length/2 memberchk/2 nextto/3 nth0/3
nth0/4 nth1/3 nth1/4 permutation/2 prefix/2 remove_duplicates/2 reverse/2 same_length/2
select/3 sublist/2 subtract/3 suffix/2 valid/1

- [Public predicates](#)
- [Protected predicates](#)
- [Private predicates](#)
- [Operators](#)

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

See also:

`list`, `list(Type)`, `numberlist`, `difflist`

`protocol`

1.71.23 varlistp

List of variables protocol.

Availability:

`logtalk_load(types(loader))`

Author: Paulo Moura

Version: 1:3:0

Date: 2022-09-19

Compilation flags:

`static`

Dependencies:

(none)

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
 - append/3
 - delete/3
 - empty/1
 - flatten/2
 - last/2
 - length/2
 - memberchk/2
 - nextto/3
 - nth0/3
 - nth0/4
 - nth1/3
 - nth1/4
 - permutation/2
 - prefix/2
 - remove_duplicates/2
 - reverse/2
 - same_length/2
 - select/3
 - sublist/2
 - subtract/3
 - suffix/2
 - valid/1
 - check/1
- Protected predicates
- Private predicates
- Operators

Public predicates

append/3

Appends two lists.

Compilation flags:

static

Template:

append(List1,List2,List)

Mode and number of proofs:

append(?list,?list,?list) - zero_or_more

delete/3

Deletes from a list all occurrences of an element returning the list of remaining elements.

Compilation flags:

static

Template:

delete(List,Element,Remaining)

Mode and number of proofs:

delete(@list,@term,?list) - one

empty/1

True if the argument is an empty list.

Compilation flags:

static

Template:

empty(List)

Mode and number of proofs:

empty(@list) - zero_or_one

flatten/2

Flattens a list of lists into a list.

Compilation flags:

static

Template:

flatten(List,Flatted)

Mode and number of proofs:

flatten(@list,-list) - one

last/2

List last element (if it exists).

Compilation flags:

static

Template:

last(List,Last)

Mode and number of proofs:

last(@list,@var) - zero_or_one

length/2

List length.

Compilation flags:

static

Template:

length(List,Length)

Mode and number of proofs:

length(@list,?integer) - zero_or_one

memberchk/2

Checks if a variable is a member of a list.

Compilation flags:

static

Template:

memberchk(Element,List)

Mode and number of proofs:

memberchk(@var,@list) - zero_or_one

nextto/3

X and Y are consecutive elements in List.

Compilation flags:

static

Template:

nextto(X,Y,List)

Mode and number of proofs:

nextto(@var,@var,?list) - zero_or_more

nth0/3

Nth element of a list (counting from zero).

Compilation flags:

static

Template:

nth0(Nth,List,Element)

Mode and number of proofs:

nth0(?integer,+list,@var) - zero_or_more

`nth0/4`

Nth element of a list (counting from zero). Rest is a list of all the other elements. Can be used to either select the nth element of List or to insert an element before the nth element in Rest.

Compilation flags:

`static`

Template:

`nth0(Nth,List,Element,Rest)`

Mode and number of proofs:

`nth0(?integer,+list,@var,?list) - zero_or_more`

`nth1/3`

Nth element of a list (counting from one).

Compilation flags:

`static`

Template:

`nth1(Nth,List,Element)`

Mode and number of proofs:

`nth1(?integer,+list,@var) - zero_or_more`

`nth1/4`

Nth element of a list (counting from zero). Rest is a list of all the other elements. Can be used to either select the nth element of List or to insert an element before the nth element in Rest.

Compilation flags:

`static`

Template:

`nth1(Nth,List,Element,Rest)`

Mode and number of proofs:

`nth1(?integer,+list,@var,?list) - zero_or_more`

permutation/2

The two lists are a permutation of the same list.

Compilation flags:

static

Template:

permutation(List,Permutation)

Mode and number of proofs:

permutation(@list,@list) - zero_or_one

prefix/2

Prefix is a prefix of List.

Compilation flags:

static

Template:

prefix(Prefix,List)

Mode and number of proofs:

prefix(?list,@list) - zero_or_more

remove_duplicates/2

Removes duplicated variables and keeping the left-most variable when repeated.

Compilation flags:

static

Template:

remove_duplicates(List,Set)

Mode and number of proofs:

`remove_duplicates(+list,-list)` - one

`reverse/2`

Reverses a list.

Compilation flags:

`static`

Template:

`reverse(List,Reversed)`

Mode and number of proofs:

`reverse(@list,?list)` - zero_or_one

`reverse(?list,@list)` - zero_or_one

`reverse(-list,-list)` - one_or_more

`same_length/2`

The two lists have the same length.

Compilation flags:

`static`

Template:

`same_length(List1,List2)`

Mode and number of proofs:

`same_length(@list,?list)` - zero_or_one

`same_length(?list,@list)` - zero_or_one

`same_length(-list,-list)` - one_or_more

select/3

Selects an element from a list, returning the list of remaining elements.

Compilation flags:

static

Template:

select(Element,List,Remaining)

Mode and number of proofs:

select(@var,?list,?list) - zero_or_more

sublist/2

The first list is a sublist of the second.

Compilation flags:

static

Template:

sublist(Sublist,List)

Mode and number of proofs:

sublist(?list,@list) - zero_or_more

subtract/3

Removes all elements in the second list from the first list, returning the list of remaining elements.

Compilation flags:

static

Template:

subtract(List,Elements,Remaining)

Mode and number of proofs:

subtract(@list,@list,-list) - one

suffix/2

Suffix is a suffix of List.

Compilation flags:

static

Template:

suffix(Suffix,List)

Mode and number of proofs:

suffix(?list,@list) - zero_or_more

valid/1

Term is a valid list of variables.

Compilation flags:

static

Template:

valid(Term)

Mode and number of proofs:

valid(@nonvar) - zero_or_one

check/1

Checks if a term is a valid list of variables. Throws an exception if the term is not valid.

Compilation flags:

static

Template:

check(Term)

Mode and number of proofs:

check(@nonvar) - one

Protected predicates

(none)

Private predicates

(none)

Operators

(none)

See also:

`varlist`, `listp`, `numberlistp`

1.72 ulid

object

1.72.1 ulid

Universally Unique Lexicographically Sortable Identifier (ULID) generator using an atom representation.

Availability:

```
logtalk_load(ulid(loader))
```

Author: Paulo Moura

Version: 1:0:0

Date: 2023-05-19

Compilation flags:

```
static, context_switching_calls
```

Extends:

```
public ulid(atom)
```

Remarks:

(none)

Inherited public predicates:

```
generate/1 generate/2 generate/8 timestamp/2 timestamp/8
```

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

See also:

ulid(Representation), ulid_types, uuid, uuid(Representation), ids, ids(Representation,Bytes)
object

1.72.2 ulid(Representation)

- Representation - Text representation for the ULID. Possible values are atom, chars, and codes.

Universally Unique Lexicographically Sortable Identifier (ULID) generator.

Availability:

```
logtalk_load(ulid(loader))
```

Author: Paulo Moura

Version: 1:0:0

Date: 2023-05-19

Compilation flags:

```
static, context_switching_calls
```

Implements:

public ulid_protocol

Uses:

fast_random
iso8601
list
os

Remarks:

(none)

Inherited public predicates:

generate/1 generate/2 generate/8 timestamp/2 timestamp/8

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

See also:

ulid, ulid_types, uuid(Representation), uuid, ids, ids(Representation,Bytes)

protocol

1.72.3 ulid_protocol

Universally Unique Lexicographically Sortable Identifier (ULID) generator protocol.

Availability:

```
logtalk_load(ulid(loader))
```

Author: Paulo Moura

Version: 1:0:0

Date: 2023-05-17

Compilation flags:

```
static
```

Dependencies:

```
(none)
```

Remarks:

```
(none)
```

Inherited public predicates:

```
(none)
```

- Public predicates
 - generate/1
 - generate/2
 - generate/8
 - timestamp/2
 - timestamp/8
- Protected predicates
- Private predicates
- Operators

Public predicates

generate/1

Generates a new ULID.

Compilation flags:
static

Template:

generate(ULID)

Mode and number of proofs:
generate(--ulid) - one

generate/2

Generates a new ULID from a timestamp (number of milliseconds since the Unix epoch: 00:00:00 UTC on January 1, 1970).

Compilation flags:
static

Template:

generate(Milliseconds,ULID)

Mode and number of proofs:
generate(+integer,--ulid) - one

generate/8

Generates a new ULID from a timestamp discrete components.

Compilation flags:
static

Template:

generate(Year,Month,Day,Hours,Minutes,Seconds,Milliseconds,ULID)

Mode and number of proofs:

generate(+integer,+integer,+integer,+integer,+integer,+integer,+integer,--ulid) - one

timestamp/2

Returns the given ULID timestamp (number of milliseconds since the Unix epoch: 00:00:00 UTC on January 1, 1970).

Compilation flags:

static

Template:

timestamp(ULID,Milliseconds)

Mode and number of proofs:

timestamp(++ulid,-integer) - one

timestamp/8

Decodes a ULID into its timestamp discrete components.

Compilation flags:

static

Template:

timestamp(ULID,Year,Month,Day,Hours,Minutes,Seconds,Milliseconds)

Mode and number of proofs:

timestamp(++ulid,-integer,-integer,-integer,-integer,-integer,-integer,-integer) - one

Protected predicates

(none)

Private predicates

(none)

Operators

(none)

category

1.72.4 ulid_types

ULID type definition.

Availability:

`logtalk_load(ulid(loader))`

Author: Paulo Moura

Version: 1:0:0

Date: 2023-05-19

Compilation flags:

`static`

Provides:

`type::type/1`

`type::check/2`

Uses:

`list`

`type`

Remarks:

- **Provided types:** This category adds a `ulid(Representation)` type for type-checking when using the `ulid` library object. Valid representation values are `atom`, `chars`, and `codes`.

Inherited public predicates:

(none)

- [Public predicates](#)
 - [Protected predicates](#)

- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

See also:

`ulid(Representation)`, `ulid`

1.73 union_find

object

1.73.1 union_find

Union find data structure implementation.

Availability:

`logtalk_load(union_find(loader))`

Author: José Antonio Rianza Valverde; adapted to Logtalk by Paulo Moura

Version: 1:0:0

Date: 2022-02-18

Compilation flags:

`static`, `context_switching_calls`

Implements:

`public union_find_protocol`

Extends:

public compound

Uses:

avltree

Remarks:

(none)

Inherited public predicates:

(<)/2 (=:=)/2 (=<)/2 (=\\=)/2 (>)/2 (>=)/2 check/1 depth/2 disjoint_sets/2 find/4
find/5 ground/1 make_set/3 new/1 new/2 numbervars/1 numbervars/3 occurs/2 singletons/2
subsumes/2 subterm/2 union/4 union_all/3 valid/1 variables/2 variant/2 varnumbers/2
varnumbers/3

- [Public predicates](#)
- [Protected predicates](#)
- [Private predicates](#)
- [Operators](#)

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

protocol

1.73.2 union_find_protocol

Union-find data structure protocol.

Availability:

```
logtalk_load(union_find(loader))
```

Author: José Antonio Riaza Valverde; adapted to Logtalk by Paulo Moura

Version: 1:0:0

Date: 2022-02-17

Compilation flags:

```
static
```

Dependencies:

```
(none)
```

Remarks:

```
(none)
```

Inherited public predicates:

```
(none)
```

- Public predicates
 - new/2
 - make_set/3
 - union/4
 - union_all/3
 - find/4
 - find/5
 - disjoint_sets/2
- Protected predicates
- Private predicates
- Operators

Public predicates

new/2

Creates a new union-find data structure with a list of elements as keys.

Compilation flags:

static

Template:

new(Elements,UnionFind)

Mode and number of proofs:

new(+list(element),?union_find) - zero_or_one

make_set/3

Makes a new set by creating a new element with a unique key Element, a rank of 0, and a parent pointer to itself. The parent pointer to itself indicates that the element is the representative member of its own set.

Compilation flags:

static

Template:

make_set(UnionFind,Element,NewUnionFind)

Mode and number of proofs:

make_set(+union_find,+element,?union_find) - zero_or_one

union/4

Merges the two trees, if distinct, that contain the given elements. The trees are joined by attaching the shorter tree (by rank) to the root of the taller tree. Fails if any of the elements is not found.

Compilation flags:

static

Template:

union(UnionFind,Element1,Element2,NewUnionFind)

Mode and number of proofs:

`union(+union_find,+element,+element,?union_find) - zero_or_one`

`union_all/3`

Merges the distinct trees for all the given elements returning the resulting union-find data structure. Fails if any of the elements is not found.

Compilation flags:

`static`

Template:

`union_all(UnionFind,Elements,NewUnionFind)`

Mode and number of proofs:

`union_all(+union_find,+list(element),?union_find) - zero_or_one`

`find/4`

Finds the root element of a set by following the chain of parent pointers from the given element. Root is the representative member of the set to which the element belongs, and may be element itself. Fails if the element is not found.

Compilation flags:

`static`

Template:

`find(UnionFind,Element,Root,NewUnionFind)`

Mode and number of proofs:

`find(+union_find,+element,?element,?union_find) - zero_or_one`

Remarks:

- Path compression: The structure of the tree containing the element is flattened by making every node point to the root whenever this predicate is used on it.
-

find/5

Same as the find/4 predicate, but returning also the rank of the root. Fails if the element is not found.

Compilation flags:

static

Template:

find(UnionFind,Element,Root,Rank,UnionFindOut)

Mode and number of proofs:

find(+union_find,+element,?element,?rank,?union_find) - zero_or_one

Remarks:

- Path compression: The structure of the tree containing the element is flattened by making every node point to the root whenever this predicate is used on it.
-

disjoint_sets/2

Returns the list of disjoint sets in the given union-find data structure.

Compilation flags:

static

Template:

disjoint_sets(UnionFind,Sets)

Mode and number of proofs:

disjoint_sets(+union_find,?sets) - zero_or_one

Protected predicates

(none)

Private predicates

(none)

Operators

(none)

See also:

`union_find`

1.74 uuid

object

1.74.1 uuid

Universally unique identifier (UUID) generator using an atom representation.

Availability:

`logtalk_load(uuid(loader))`

Author: Paulo Moura

Version: 0:2:0

Date: 2022-11-23

Compilation flags:

`static, context_switching_calls`

Extends:

`public uuid(atom)`

Remarks:

(none)

Inherited public predicates:

`random_node/1 uuid_null/1 uuid_v1/2 uuid_v4/1`

- Public predicates
- Protected predicates

- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

See also:

`uuid(Representation)`, `ulid`, `ulid(Representation)`, `ids`, `ids(Representation,Bytes)`
object

1.74.2 `uuid(Representation)`

- Representation - Text representation for the UUID. Possible values are atom, chars, and codes.

Universally unique identifier (UUID) generator.

Availability:

```
logtalk_load(uuid(loader))
```

Author: Paulo Moura

Version: 0:5:0

Date: 2022-11-23

Compilation flags:

```
static, context_switching_calls
```

Implements:

```
public uuid_protocol
```

Uses:

```
fast_random
```

iso8601
list
os

Remarks:
(none)

Inherited public predicates:
random_node/1 uuid_null/1 uuid_v1/2 uuid_v4/1

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

See also:

uuid, ulid, ulid(Representation), ids, ids(Representation,Bytes)

protocol

1.74.3 uuid_protocol

Universally unique identifier (UUID) generator protocol.

Availability:

```
logtalk_load(uuid(loader))
```

Author: Paulo Moura

Version: 0:3:0

Date: 2021-03-13

Compilation flags:

```
static
```

Dependencies:

```
(none)
```

Remarks:

```
(none)
```

Inherited public predicates:

```
(none)
```

- Public predicates
 - uuid_v1/2
 - uuid_v4/1
 - uuid_null/1
 - random_node/1
- Protected predicates
- Private predicates
- Operators

Public predicates`uuid_v1/2`

Returns a version 1 UUID for the given MAC address (a list of six bytes). The MAC address can be replaced by a random 6 bytes node identifier as per RFC 4122 when the MAC address is not available or should not be disclosed.

Compilation flags:

`static`

Template:

`uuid_v1(MAC,UUID)`

Mode and number of proofs:

`uuid_v1(+list(byte),--ground) - one`

`uuid_v4/1`

Returns a version 4 UUID.

Compilation flags:

`static`

Template:

`uuid_v4(UUID)`

Mode and number of proofs:

`uuid_v4(--ground) - one`

`uuid_null/1`

Returns the null UUID.

Compilation flags:

`static`

Template:

`uuid_null(UUID)`

Mode and number of proofs:

`uuid_null(--ground) - one`

`random_node/1`

Generates a list with six random bytes that can be used in alternative to a MAC address when generating version 1 UUIDs.

Compilation flags:

`static`

Template:

`random_node(Node)`

Mode and number of proofs:

`random_node(--list(byte)) - one`

Protected predicates

(none)

Private predicates

(none)

Operators

(none)

1.75 verdi_neruda

object

1.75.1 a_star_interpreter(W)

A* interpreter for general logic programs. The parameter W is used to fine tune the behavior. W = 0 gives us a breadth-first search and W = 1 gives us a greedy best-first search. The default value for W is 0.5.

Availability:

```
logtalk_load(verdi_neruda(loader))
```

Author: Victor Lagerkvist

Version: 1:0:0

Date: 2010-06-13

Compilation flags:

```
static, context_switching_calls
```

Imports:

```
public best_first
```

Remarks:

```
(none)
```

Inherited public predicates:

```
prove/2 prove/3
```

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

object

1.75.2 benchmark_generators

Generates random data structures for use in benchmarks.

Availability:

`logtalk_load(verdi_neruda(loader))`

Author: Victor Lagerkvist

Version: 1:0:0

Date: 2010-06-13

Compilation flags:

`static, context_switching_calls`

Uses:

`random`

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
 - `random_tree/1`
- Protected predicates
- Private predicates

- Operators

Public predicates

`random_tree/1`

Generates a random tree.

Compilation flags:

`static`

Template:

`random_tree(Tree)`

Mode and number of proofs:

`random_tree(-tree) - one`

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

category

1.75.3 `best_first`

Best-first framework for general logic programs.

Availability:

`logtalk_load(verdi_neruda(loader))`

Author: Victor Lagerkvist

Version: 1:1:0

Date: 2019-03-08

Compilation flags:

static

Implements:

public interpreterp

Uses:

counter

minheap

Remarks:

(none)

Inherited public predicates:

prove/2 prove/3

- Public predicates
- Protected predicates
 - f/4
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

f/4

.

Compilation flags:

static

Template:

f(Length1,Length2,Depth,Cost)

Mode and number of proofs:

f(+float,+float,+float,-float) - zero_or_more

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

object

1.75.4 bfs_interpreter

Breadth-first interpreter for general logic programs.

Availability:

```
logtalk_load(verdi_neruda(loader))
```

Author: Victor Lagerkvist

Version: 1:0:0

Date: 2010-06-13

Compilation flags:

```
static, context_switching_calls
```

Implements:

```
public interpreterp
```

Uses:

```
counter
```

```
queue
```

Remarks:

(none)

Inherited public predicates:

```
prove/2 prove/3
```

- [Public predicates](#)
- [Protected predicates](#)
- [Private predicates](#)
- [Operators](#)

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

object

1.75.5 bup_interpreter

Semi-naive bottom-up interpreter for general (stratified) logic programs. Magic transformation is realized through an expansion hook.

Availability:

```
logtalk_load(verdi_neruda(loader))
```

Author: Ulf Nilsson. Ported to Logtalk and augmented with negation by Victor Lagerkvist.

Version: 1:1:3

Date: 2023-11-30

Compilation flags:

```
static, context_switching_calls
```

Implements:

```
public interpreterp
```

Uses:

```
counter
```

```
list
```

```
magic
```

```
term
```

Remarks:

```
(none)
```

Inherited public predicates:

prove/2 prove/3

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

object

1.75.6 counter

Counter implemented with asserta/retract.

Availability:

logtalk_load(verdi_neruda(loader))

Author: Victor Lagerkvist

Version: 1:0:1

Date: 2022-10-08

Compilation flags:

static, context_switching_calls

Dependencies:

(none)

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
 - increment/0
 - increase/1
 - set/1
 - value/1
 - reset/0
- Protected predicates
- Private predicates
 - c/1
- Operators

Public predicates

increment/0

Increment the counter by 1.

Compilation flags:

static

Mode and number of proofs:

increment - one

increase/1

Increments the counter by the specified amount.

Compilation flags:

static

Template:

increase(I)

Mode and number of proofs:

increase(+number) - one

set/1

Sets the counter to the specified amount.

Compilation flags:

static

Template:

set(N)

Mode and number of proofs:

set(+number) - one

value/1

Gets the current value of the counter.

Compilation flags:

static

Template:

value(N)

Mode and number of proofs:

value(?number) - one

reset/0

Resets the counter to zero.

Compilation flags:

static

Mode and number of proofs:

reset - one

Protected predicates

(none)

Private predicates

c/1

Stores the current value of the counter.

Compilation flags:

dynamic

Template:

c(N)

Mode and number of proofs:

c(?number) - zero_or_one

Operators

(none)

protocol

1.75.7 databasep

Database protocol.

Availability:

```
logtalk_load(verdi_neruda(loader))
```

Author: Victor Lagerkvist

Version: 1:0:0

Date: 2010-06-13

Compilation flags:

```
static
```

Dependencies:

```
(none)
```

Remarks:

```
(none)
```

Inherited public predicates:

```
(none)
```

- Public predicates
 - rule/4
 - rule/3
 - rule/2
 - bench_goal/1
- Protected predicates
- Private predicates
- Operators

Public predicates

rule/4

Clauses for this predicate are automatically generated using term-expansion. The third argument contains the length of Body.

Compilation flags:

static

Template:

rule(Head,Body,Length,Tail)

Mode and number of proofs:

rule(?callable,?callable,-,-) - zero_or_more

rule/3

Clauses for this predicate are automatically generated using term-expansion. The third argument denotes the tail of the Body.

Compilation flags:

static

Template:

rule(Head,Body,Tail)

Mode and number of proofs:

rule(?callable,?callable,-) - zero_or_more

rule/2

Clauses for this predicate are automatically generated using term-expansion.

Compilation flags:

static

Template:

rule(Head,Body)

Mode and number of proofs:

rule(?callable,-list(callable)) - zero_or_more

bench_goal/1

Table of benchmark goals. They are used from shell.lgt to make benchmarking easier.

Compilation flags:

static

Template:

bench_goal(Goal)

Mode and number of proofs:

bench_goal(?callable) - zero_or_more

Protected predicates

(none)

Private predicates

(none)

Operators

(none)

object

1.75.8 debug_expansion(Mode)

Expands debug/1 calls. The parameter Mode can be either the atom “debug” or “production”.

Availability:

logtalk_load(verdi_neruda(loader))

Author: Paulo Moura

Version: 1:0:0

Date: 2010-04-15

Compilation flags:

static, context_switching_calls

Implements:

public expanding

Remarks:

(none)

Inherited public predicates:

goal_expansion/2 term_expansion/2

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

object

1.75.9 demodb

Availability:

`logtalk_load(verdi_neruda(loader))`

Compilation flags:

`static, context_switching_calls`

Implements:

public `databasep`

Remarks:

(none)

Inherited public predicates:

`bench_goal/1 rule/2 rule/3 rule/4`

- [Public predicates](#)
- [Protected predicates](#)
- [Private predicates](#)
- [Operators](#)

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

object

1.75.10 dfs_interpreter

Depth-first interpreter for general logic programs.

Availability:

`logtalk_load(verdi_neruda(loader))`

Author: Victor Lagerkvist

Version: 1:0:0

Date: 2010-06-13

Compilation flags:

`static, context_switching_calls`

Implements:

`public interpreterp`

Uses:

`counter`

Remarks:

(none)

Inherited public predicates:

`prove/2 prove/3`

- [Public predicates](#)
- [Protected predicates](#)
- [Private predicates](#)
- [Operators](#)

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

category

1.75.11 flattening

Flattens conjunction of goals with the form `f and g` into a list `[f,g]`.

Availability:

```
logtalk_load(verdi_neruda(loader))
```

Author: Victor Lagerkvist

Version: 1:0:0

Date: 2010-06-13

Compilation flags:

```
static
```

source: Based on source code from *The Craft of Prolog*, by Richard O'Keefe.

Dependencies:

```
(none)
```

Remarks:

```
(none)
```

Inherited public predicates:

```
(none)
```

- Public predicates
- Protected predicates
 - `flatten_goals//1`
- Private predicates
- Operators

Public predicates

(none)

Protected predicates

`flatten_goals//1`

Flattens a conjunction of goals.

Compilation flags:

`static`

Template:

`flatten_goals(Conjunction)`

Mode and number of proofs:

`flatten_goals(+callable) - one`

Private predicates

(none)

Operators

(none)

object

1.75.12 heuristic_expansion(Mode)

Expands rules of the form `p if f and g` to `rule(p, [f,g|Tail], Length, Tail)`.

Availability:

```
logtalk_load(verdi_neruda(loader))
```

Author: Victor Lagerkvist

Version: 1:0:2

Date: 2022-10-08

Compilation flags:

```
static, context_switching_calls
```

Implements:

```
public expanding
```

Extends:

```
public rule_expansion(Mode)
```

Uses:

```
list
```

Remarks:

```
(none)
```

Inherited public predicates:

```
goal_expansion/2 term_expansion/2
```

- [Public predicates](#)
- [Protected predicates](#)
- [Private predicates](#)
- [Operators](#)

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

object

1.75.13 iddfs_interpreter(Increment)

Iterative deepening depth-first interpreter for general logic programs. Based on source code from The Craft of Prolog, by Richard O'Keefe. The default value for the increment is 1.

Availability:

`logtalk_load(verdi_neruda(loader))`

Author: Victor Lagerkvist

Version: 1:0:0

Date: 2010-06-13

Compilation flags:

`static, context_switching_calls`

Implements:

`public interpreterp`

Uses:

`counter`

`dfs_interpreter`

Remarks:

(none)

Inherited public predicates:

`prove/2 prove/3`

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

protocol

1.75.14 interpreterp

Protocol for an interpreter.

Availability:

```
logtalk_load(verdi_neruda(loader))
```

Author: Victor Lagerkvist

Version: 1:0:0

Date: 2010-06-13

Compilation flags:

```
static
```

Dependencies:

```
(none)
```

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
 - prove/2
 - prove/3
- Protected predicates
- Private predicates
- Operators

Public predicates

prove/2

True if goal is provable in the specified database.

Compilation flags:

static

Template:

prove(Goal,DB)

Mode and number of proofs:

prove(+goal,+database) - zero_or_more

prove/3

True if goal is provable within the given depth-limit in the specified database.

Compilation flags:

static

Template:

prove(Goal,Limit,DB)

Mode and number of proofs:

prove(+goal,+limit,+database) - zero_or_more

Protected predicates

(none)

Private predicates

(none)

Operators

(none)

object

1.75.15 magic

Object encapsulating magic methods.

Availability:

`logtalk_load(verdi_neruda(loader))`

Author: Ulf Nilsson. Ported to Logtalk and augmented with stratified negation by Victor Lagerkvist.

Version: 1:0:0

Date: 2010-06-13

Compilation flags:

`static, context_switching_calls`

Uses:

`list`

Remarks:

(none)

Inherited public predicates:

(none)

- [Public predicates](#)
 - [magicise/4](#)

- magic/2
- Protected predicates
- Private predicates
- Operators

Public predicates

magicise/4

Transform (Head :- Body) into a magic clause (NewHead :- NewBody).

Compilation flags:

static

Template:

magicise(Head,Body,NewHead,NewBody)

Mode and number of proofs:

magicise(+term,+list,-term,-list) - zero_or_one

magic/2

Prefix the predicate symbol of Old with magic.

Compilation flags:

static

Template:

magic(Old,New)

Mode and number of proofs:

magic(+callable,-callable) - zero_or_one

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

object

1.75.16 magic_expansion(Mode)

Expands rules of the form p if f and g to the more manageable rule(p , [f,g]) and performs magic transformation of clauses.

Availability:

```
logtalk_load(verdi_neruda(loader))
```

Author: Victor Lagerkvist

Version: 1:0:2

Date: 2022-10-08

Compilation flags:

```
static, context_switching_calls
```

Implements:

```
public expanding
```

Imports:

```
public flatting
```

Extends:

```
public debug_expansion(Mode)
```

Uses:

```
list
```

```
magic
```

Remarks:

(none)

Inherited public predicates:

```
goal_expansion/2 term_expansion/2
```

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

object

1.75.17 rule_expansion(Mode)

Expands rules of the form p if f and g to the more manageable rule(p , [f,g]).

Availability:

```
logtalk_load(verdi_neruda(loader))
```

Author: Victor Lagerkvist

Version: 1:0:2

Date: 2022-10-08

Compilation flags:

```
static, context_switching_calls
```

Implements:

```
public expanding
```

Imports:

```
public flattening
```

Extends:


```
public debug_expansion(Mode)
```

Remarks:

(none)

Inherited public predicates:

goal_expansion/2 term_expansion/2

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

object

1.75.18 shell

User frontend to start the application.

Availability:

```
logtalk_load(verdi_neruda(loader))
```

Author: Paulo Moura

Version: 1:0:0

Date: 2019-03-20

Compilation flags:

static, context_switching_calls

Uses:

shell(Interpreters)

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
 - welcome/0
 - start/0
- Protected predicates
- Private predicates
- Operators

Public predicates

welcome/0

Compilation flags:

static

start/0

Compilation flags:

static

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

object

1.75.19 shell(Interpreters)

Prolog shell for the interpreters.

Availability:

`logtalk_load(verdi_neruda(loader))`

Author: Victor Lagerkvist and Paulo Moura

Version: 1:1:3

Date: 2024-03-15

Compilation flags:

`static, context_switching_calls`

Uses:

`counter`

`list`

`meta`

`pairs`

Remarks:

(none)

Inherited public predicates:

(none)

- [Public predicates](#)
 - [init/0](#)

- Protected predicates
- Private predicates
- Operators

Public predicates

init/0

Compilation flags:
static

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)
object

1.75.20 shell_expansion(Mode)

Expansion object for the shell.

Availability:
logtalk_load(verdi_neruda(loader))

Author: Victor Lagerkvist
Version: 1:0:1
Date: 2022-10-08

Compilation flags:
static, context_switching_calls

Implements:

public expanding

Extends:

public rule_expansion(Mode)

Remarks:

(none)

Inherited public predicates:

goal_expansion/2 term_expansion/2

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

1.76 wrapper

object

1.76.1 wrapper

Adviser tool for porting and wrapping plain Prolog applications.

Availability:

```
logtalk_load(wrapper(loader))
```

Author: Paulo Moura

Version: 0:12:1

Date: 2023-11-29

Compilation flags:

```
static, context_switching_calls
```

Implements:

```
public expanding
```

Provides:

```
logtalk::message_hook/4
```

```
logtalk::message_prefix_stream/4
```

```
logtalk::message_tokens//2
```

Uses:

```
logtalk
```

```
os
```

Remarks:

- `prolog_extensions(Extensions)` option: List of file name extensions used to recognize Prolog source files (default is `['.pl', '.pro', '.prolog']`).
- `logtalk_extension(Extension)` option: Logtalk file name extension to be used for the generated wrapper files (default is `'.lgt'`).
- `exclude_files(Files)` option: List of Prolog source files names to exclude (default is `[]`).
- `exclude_directories(Files)` option: List of sub-directory names to exclude (default is `[]`).
- `include_wrapped_files(Boolean)`: Generate `include/1` directives for the wrapped Prolog source files (default is `true`).

Inherited public predicates:

```
goal_expansion/2 term_expansion/2
```

- Public predicates
 - `rdirectory/2`

- rdirectory/1
- directory/2
- directory/1
- directories/2
- directories/1
- files/2
- files/1
- file/2
- file/1
- save/1
- save/0
- default_option/1
- default_options/1
- Protected predicates
- Private predicates
 - merge_options/2
 - predicate_called_but_not_defined_/2
 - object_predicate_called_/3
 - module_predicate_called_/3
 - unknown_predicate_called_/2
 - missing_predicate_directive_/3
 - non_standard_predicate_call_/2
 - dynamic_directive_/3
 - multifile_directive_/3
 - add_directive_before_entity_/2
 - add_directive_/2
 - add_directive_/3
 - remove_directive_/2
 - file_being_advised_/4
- Operators

Public predicates

`rdirectory/2`

Advises the user on missing directives for converting all plain Prolog files in a directory and its sub-directories to Logtalk objects using the specified options.

Compilation flags:

`static`

Template:

`rdirectory(Directory,Options)`

Mode and number of proofs:

`rdirectory(+atom,+list(compound)) - one`

`rdirectory/1`

Advises the user on missing directives for converting all plain Prolog files in a directory and its sub-directories to Logtalk objects using default options.

Compilation flags:

`static`

Template:

`rdirectory(Directory)`

Mode and number of proofs:

`rdirectory(+atom) - one`

`directory/2`

Advises the user on missing directives for converting all plain Prolog files in a directory to Logtalk objects using the specified options.

Compilation flags:

`static`

Template:

directory(Directory,Options)

Mode and number of proofs:

directory(+atom,+list(compound)) - one

directory/1

Advises the user on missing directives for converting all plain Prolog files in a directory to Logtalk objects using default options.

Compilation flags:

static

Template:

directory(Directory)

Mode and number of proofs:

directory(+atom) - one

directories/2

Advises the user on missing directives for converting all Prolog files in a set of directories to Logtalk objects using the specified options.

Compilation flags:

static

Template:

directories(Directories,Options)

Mode and number of proofs:

directories(+list(atom),+list(compound)) - one

directories/1

Advises the user on missing directives for converting all Prolog files in a set of directories to Logtalk objects using default options.

Compilation flags:

static

Template:

directories(Directories)

Mode and number of proofs:

directories(+list(atom)) - one

files/2

Advises the user on missing directives for converting a list of plain Prolog files to Logtalk objects using the specified options.

Compilation flags:

static

Template:

files(Files,Options)

Mode and number of proofs:

files(+list(atom),+list(compound)) - one

files/1

Advises the user on missing directives for converting a list of plain Prolog files to Logtalk objects using default options.

Compilation flags:

static

Template:

files(Files)

Mode and number of proofs:

files(+list(atom)) - one

file/2

Advises the user on missing directives for converting a plain Prolog file to Logtalk objects using the specified options.

Compilation flags:

static

Template:

file(File,Options)

Mode and number of proofs:

file(+atom,+list(compound)) - one

file/1

Advises the user on missing directives for converting a plain Prolog file to Logtalk objects using default options.

Compilation flags:

static

Template:

file(File)

Mode and number of proofs:

file(+atom) - one

save/1

Saves the generated wrapper objects (plus a loader file per directory) for all advised files using the specified options. The wrapper objects are saved to the same directories that contain the wrapped Prolog files.

Compilation flags:

static

Template:

save(Options)

Mode and number of proofs:

save(+list(compound)) - one

save/0

Saves the generated wrapper objects (plus a loader file per directory) for all advised files using default options. The wrapper objects are saved to the same directories that contain the wrapped Prolog files.

Compilation flags:

static

Mode and number of proofs:

save - one

default_option/1

Enumerates by backtracking the default options used when generating the wrapper objects.

Compilation flags:

static

Template:

default_option(DefaultOption)

Mode and number of proofs:

default_option(?compound) - zero_or_more

default_options/1

Returns a list of the default options used when generating the wrapper objects.

Compilation flags:

static

Template:

default_options(DefaultOptions)

Mode and number of proofs:

default_options(-list(compound)) - one

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

merge_options/2

Merges the user options with the default options, returning the list of options used when generating the wrapper objects.

Compilation flags:

static

Template:

merge_options(UserOptions,Options)

Mode and number of proofs:

merge_options(+list(compound),-list(compound)) - one

predicate_called_but_not_defined_/2

Table of called object predicates that are not locally defined.

Compilation flags:

dynamic

Template:

predicate_called_but_not_defined_(Object,Predicate)

Mode and number of proofs:

predicate_called_but_not_defined_(?atom,?predicate_indicator) - zero_or_more

object_predicate_called_/3

Table of called object predicates.

Compilation flags:

dynamic

Template:

object_predicate_called_(Object,Other,Predicate)

Mode and number of proofs:

object_predicate_called_(?atom,?atom,?predicate_indicator) - zero_or_more

module_predicate_called_/3

Table of called module predicates.

Compilation flags:

dynamic

Template:

module_predicate_called_(Object,Module,Predicate)

Mode and number of proofs:

module_predicate_called_(?atom,?atom,?predicate_indicator) - zero_or_more

unknown_predicate_called_/2

Table of predicates called but not defined.

Compilation flags:

dynamic

Template:

unknown_predicate_called_(Object,Predicate)

Mode and number of proofs:

unknown_predicate_called_(?atom,?predicate_indicator) - zero_or_more

missing_predicate_directive_/3

Table of missing predicate directives.

Compilation flags:

dynamic

Template:

missing_predicate_directive_(Object,Directive,Predicate)

Mode and number of proofs:

missing_predicate_directive_(?atom,?predicate_indicator,?predicate_indicator) - zero_or_more

non_standard_predicate_call_/2

Table of called non-standard predicates.

Compilation flags:

dynamic

Template:

non_standard_predicate_call_(Object,Predicate)

Mode and number of proofs:

non_standard_predicate_call_(?atom,?predicate_indicator) - zero_or_more

dynamic_directive_/3

Table of declared dynamic predicates.

Compilation flags:

dynamic

Template:

dynamic_directive_(Object,Line,Predicate)

Mode and number of proofs:

dynamic_directive_(?atom,?integer,?predicate_indicator) - zero_or_more

multifile_directive_/3

Table of declared multifile predicates.

Compilation flags:

dynamic

Template:

multifile_directive_(Object,Line,Predicate)

Mode and number of proofs:

multifile_directive_(?atom,?integer,?predicate_indicator) - zero_or_more

add_directive_before_entity_/2

Table of directives to be added before the entity opening directive.

Compilation flags:

dynamic

Template:

add_directive_before_entity_(Object,Directive)

Mode and number of proofs:

add_directive_before_entity_(?atom,?predicate_indicator) - zero_or_more

add_directive_/2

Table of directives to be added.

Compilation flags:

dynamic

Template:

add_directive_(Object,Directive)

Mode and number of proofs:

add_directive_(?atom,?predicate_indicator) - zero_or_more

add_directive_/3

Table of directives to be added to complement existing directives.

Compilation flags:

dynamic

Template:

add_directive_(Object,Directive,NewDirective)

Mode and number of proofs:

add_directive_(?atom,?predicate_indicator,?predicate_indicator) - zero_or_more

remove_directive_/2

Table of directives to be removed.

Compilation flags:

dynamic

Template:

remove_directive_(Object,Directive)

Mode and number of proofs:

remove_directive_(?atom,?predicate_indicator) - zero_or_more

file_being_advised_/4

Table of files being advised are respective directories and names (basename without extension).

Compilation flags:

dynamic

Template:

file_being_advised_(File,Path,Directory,Name)

Mode and number of proofs:

file_being_advised_(?atom,?atom,?atom,?atom) - zero_or_more

Operators

(none)

1.77 xml_parser

object

1.77.1 xml

Bi-directional XML parser.

Availability:

logtalk_load(xml_parser(loader))

Author: John Fletcher; adapted to Logtalk by Paulo Moura.

Version: 3:8:4

Date: 2024-03-14

Copyright: Copyright (C) 2001-2005 Binding Time Limited, Copyright (C) 2005-2013 John Fletcher

License: This program is offered free of charge, as unsupported source code. You may use it, copy it, distribute it, modify it or sell it without restriction, but entirely at your own risk.

Compilation flags:

static, context_switching_calls

Uses:

list
term

Remarks:

- On-line documentation: https://binding-time.co.uk/index.php/Parsing_XML_with_Prolog
- Compliance: This XML parser supports a subset of XML suitable for XML Data and Worldwide Web applications. It is neither as strict nor as comprehensive as the XML 1.0 Specification mandates.
- Compliance-strictness: It is not as strict, because, while the specification must eliminate ambiguities, not all errors need to be regarded as faults, and some reasonable examples of real XML usage would have to be rejected if they were.
- Compliance-comprehensive: It is not as comprehensive, because, where the XML specification makes provision for more or less complete DTDs to be provided as part of a document, xml.pl actions the local definition of ENTITIES only. Other DTD extensions are treated as commentary.
- Bi-directional conversions: Conversions are not fully symmetrical as weaker XML is accepted than can be generated. Notably, in-bound (Codes -> Document) parsing does not require strictly well-formed XML. If Codes does not represent well-formed XML, Document is instantiated to the term malformed(<attributes>,<content>).

Inherited public predicates:

(none)

- Public predicates
 - parse/2
 - parse/3
 - subterm/2
 - pp/1
- Protected predicates
- Private predicates
 - xml_to_document/3
 - empty_map/1
 - map_member/3
 - map_store/4
 - pp_string/1
 - fault/5
 - exception/4
 - document_generation//2
 - pcd_data_7bit//1
 - character_data_format/3

- cdata_generation//1
- Operators

Public predicates

parse/2

Parses a list of character codes to/from a data structure of the form `xml(<atts>,<content>)`.

Compilation flags:

static

Template:

parse(Codes,Document)

Mode and number of proofs:

parse(+list(character_code),?nonvar) - zero_or_one

parse(?list(character_code),+nonvar) - zero_or_one

parse/3

Parses a list of character codes to/from a data structure of the form `xml(<atts>,<content>)` using the given list of options.

Compilation flags:

static

Template:

parse(Options,Codes,Document)

Mode and number of proofs:

parse(++list(compound),+list(character_code),?nonvar) - zero_or_one

parse(++list(compound),?list(character_code),+nonvar) - zero_or_one

Remarks:

- `extended_characters(Boolean)` option: Use the extended character entities for XHTML (default true).
- `format(Boolean)` option: For parsing, strip layouts when no character data appears between elements (default true). For generating, indent the element content (default true).
- `remove_attribute_prefixes(Boolean)` option: Remove namespace prefixes from attributes when it's the same as the prefix of the parent element (default false).

- `allow_ampersand(Boolean)` option: Allow unescaped ampersand characters (&) to occur in PCDATA (default false).
-

subterm/2

Unifies Subterm with a sub-term of XMLTerm. Note that XMLTerm is a sub-term of itself.

Compilation flags:

static

Template:

subterm(XMLTerm,Subterm)

Mode and number of proofs:

subterm(+nonvar,?nonvar) - zero_or_one

pp/1

Pretty prints a XML document on the current output stream.

Compilation flags:

static

Template:

pp(XMLDocument)

Mode and number of proofs:

pp(+nonvar) - zero_or_one

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

xml_to_document/3

Translates the list of character codes XML into the Prolog term Document. Options is a list of terms controlling the treatment of layout characters and character entities.

Compilation flags:

static

Template:

xml_to_document(Options,XML,Document)

Mode and number of proofs:

xml_to_document(+nonvar,+nonvar,?nonvar) - zero_or_one

empty_map/1

True if Map is a null map.

Compilation flags:

static

Template:

empty_map(Map)

Mode and number of proofs:

empty_map(?nonvar) - zero_or_one

map_member/3

True if Map is a ordered map structure which records the pair Key-Data. Key must be ground.

Compilation flags:

static

Template:

map_member(Key,Map,Data)

Mode and number of proofs:

`map_member(+nonvar,+nonvar,?nonvar) - zero_or_one`

`map_store/4`

True if Map0 is an ordered map structure, Key must be ground, and Map1 is identical to Map0 except that the pair Key-Data is recorded by Map1.

Compilation flags:

`static`

Template:

`map_store(Map0,Key,Data,Map1)`

Mode and number of proofs:

`map_store(+nonvar,+nonvar,+nonvar,?nonvar) - zero_or_one`

`pp_string/1`

Prints String onto the current output stream. If String contains only 7-bit chars it is printed in shorthand quoted format, otherwise it is written as a list.

Compilation flags:

`static`

Template:

`pp_string(String)`

Mode and number of proofs:

`pp_string(+nonvar) - zero_or_one`

fault/5

Identifies SubTerm as a sub-term of Term which cannot be serialized after Indentation. Message is an atom naming the type of error; Path is a string encoding a list of SubTerm's ancestor elements in the form <tag>{(id)}* where <tag> is the element tag and <id> is the value of any attribute `_named_ id`.

Compilation flags:

static

Template:

fault(Term,Indentation,SubTerm,Path,Message)

Mode and number of proofs:

fault(+nonvar,+nonvar,?nonvar,?nonvar,?nonvar) - zero_or_one

exception/4

Hook to raise an exception to be raised in respect of a fault in the XML Term Document.

Compilation flags:

static

Template:

exception(Message,Document,Culprit,Path)

Mode and number of proofs:

exception(+atom,+nonvar,+nonvar,+nonvar) - one

document_generation//2

DCG generating Document as a list of character codes. Format is true|false defining whether layouts, to provide indentation, should be added between the element content of the resultant "string". Note that formatting is disabled for elements that are interspersed with pcdat/1 terms, such as XHTML's 'inline' elements. Also, Format is over-riden, for an individual element, by an explicit 'xml:space'="preserve" attribute.

Compilation flags:

static

Template:

document_generation(Format,Document)

Mode and number of proofs:

document_generation(+nonvar,+nonvar) - zero_or_one

pcdata_7bit//1

Represents the ASCII character set in its simplest format, using the character entities &, ", <, and > which are common to both XML and HTML. The numeric entity ' is used in place of ' because browsers don't recognize it in HTML.

Compilation flags:

static

Template:

pcdata_7bit(Code)

Mode and number of proofs:

pcdata_7bit(?nonvar) - zero_or_one

character_data_format/3

Holds when Format0 and Format1 are the statuses of XML formatting before and after Codes - which may be null.

Compilation flags:

static

Template:

character_data_format(Codes,Format0,Format1)

Mode and number of proofs:

character_data_format(+nonvar,+nonvar,?nonvar) - zero_or_one

`cdata_generation//1`

Holds when Format0 and Format1 are the statuses of XML formatting before and after Codes - which may be null.

Compilation flags:

`static`

Template:

`cdata_generation(Codes)`

Mode and number of proofs:

`cdata_generation(+list) - zero_or_one`

Operators

(none)

1.78 zippers

protocol

1.78.1 zipperp

Zipper protocol.

Availability:

`logtalk_load(zippers(loader))`

Author: Paulo Moura

Version: 1:0:0

Date: 2019-01-20

Compilation flags:

`static`

Dependencies:

(none)

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
 - zip/2
 - zip/3
 - unzip/2
 - current/2
 - next/2
 - next/3
 - previous/2
 - previous/3
 - rewind/2
 - rewind/3
 - forward/2
 - forward/3
 - apply/2
 - insert_before/3
 - insert_after/3
 - replace/3
 - delete_and_previous/2
 - delete_and_next/2
 - delete_and_unzip/2
 - delete_all_before/2
 - delete_all_before_and_unzip/2
 - delete_all_after/2
 - delete_all_after_and_unzip/2
- Protected predicates
- Private predicates
- Operators

Public predicates

zip/2

Adds a zipper to a compound term holding a sequence of elements. Fails if the sequence is empty.

Compilation flags:

static

Template:

zip(Sequence,Zipper)

Mode and number of proofs:

zip(+sequence,--zipper) - zero_or_one

zip/3

Adds a zipper to a compound term holding a sequence of elements. Also returns the first element. Fails if the sequence is empty.

Compilation flags:

static

Template:

zip(Sequence,Zipper,First)

Mode and number of proofs:

zip(+sequence,--zipper,--term) - zero_or_one

unzip/2

Removes a zipper from a sequence.

Compilation flags:

static

Template:

unzip(Zipper,Sequence)

Mode and number of proofs:

`unzip(@zipper,--sequence) - one`

`current/2`

Current element.

Compilation flags:

`static`

Template:

`current(Zipper,Current)`

Mode and number of proofs:

`current(+zipper,?term) - zero_or_one`

`next/2`

Moves to the next element. Fails if already at the last elements.

Compilation flags:

`static`

Template:

`next(Zipper,NewZipper)`

Mode and number of proofs:

`next(+zipper,--zipper) - zero_or_one`

`next/3`

Moves to and returns the next element. Fails if already at the last elements.

Compilation flags:

`static`

Template:

next(Zipper,NewZipper,Next)

Mode and number of proofs:

next(+zipper,--zipper,-term) - zero_or_one

previous/2

Moves to the previous element. Fails if already at the first elements.

Compilation flags:

static

Template:

previous(Zipper,NewZipper)

Mode and number of proofs:

previous(+zipper,--zipper) - zero_or_one

previous/3

Moves to and returns the previous element. Fails if already at the first element.

Compilation flags:

static

Template:

previous(Zipper,NewZipper,Previous)

Mode and number of proofs:

previous(+zipper,--zipper,-term) - zero_or_one

rewind/2

Rewinds the zipper so that the first element becomes the current element.

Compilation flags:

static

Template:

rewind(Zipper,NewZipper)

Mode and number of proofs:

rewind(+zipper,--zipper) - one

rewind/3

Rewinds the zipper so that the first element becomes the current element. Also returns the first element.

Compilation flags:

static

Template:

rewind(Zipper,NewZipper,First)

Mode and number of proofs:

rewind(+zipper,--zipper,?term) - zero_or_one

forward/2

Forward the zipper so that the last element becomes the current element.

Compilation flags:

static

Template:

forward(Zipper,NewZipper)

Mode and number of proofs:

forward(+zipper,--zipper) - one

forward/3

Forward the zipper so that the last element becomes the current element. Also returns the last element.

Compilation flags:

static

Template:

forward(Zipper,NewZipper,Last)

Mode and number of proofs:

forward(+zipper,--zipper,?term) - zero_or_one

apply/2

Applies a closure to the current element.

Compilation flags:

static

Template:

apply(Closure,Zipper)

Meta-predicate template:

apply(1,*)

Mode and number of proofs:

apply(+callable,+zipper) - zero_or_more

insert_before/3

Inserts an element before the current one.

Compilation flags:

static

Template:

insert_before(Zipper,Element,NewZipper)

Mode and number of proofs:

insert_before(+zipper,?term,--zipper) - zero_or_one

`insert_after/3`

Inserts an element after the current one.

Compilation flags:

`static`

Template:

`insert_after(Zipper,Element,NewZipper)`

Mode and number of proofs:

`insert_after(+zipper,?term,--zipper) - zero_or_one`

`replace/3`

Replaces the current element with a new element.

Compilation flags:

`static`

Template:

`replace(Zipper,NewCurrent,NewZipper)`

Mode and number of proofs:

`replace(+zipper,?term,--zipper) - one`

`delete_and_previous/2`

Deletes the current element and moves to the previous element. Fails if no previous element exists.

Compilation flags:

`static`

Template:

`delete_and_previous(Zipper,NewZipper)`

Mode and number of proofs:

`delete_and_previous(+zipper,--zipper) - zero_or_one`

`delete_and_next/2`

Deletes the current element and moves to the next element. Fails if no next element exists.

Compilation flags:

`static`

Template:

`delete_and_next(Zipper,NewZipper)`

Mode and number of proofs:

`delete_and_next(+zipper,--zipper) - zero_or_one`

`delete_and_unzip/2`

Deletes the current element and removes the zipper returning the resulting sequence.

Compilation flags:

`static`

Template:

`delete_and_unzip(Zipper,Sequence)`

Mode and number of proofs:

`delete_and_unzip(+zipper,--sequence) - one`

`delete_all_before/2`

Deletes all elements before the current element.

Compilation flags:

`static`

Template:

```
delete_all_before(Zipper,NewZipper)
```

Mode and number of proofs:

```
delete_all_before(+zipper,--zipper) - one
```

```
delete_all_before_and_unzip/2
```

Deletes all elements before the current element and removes the zipper returning the resulting sequence.

Compilation flags:

```
static
```

Template:

```
delete_all_before_and_unzip(Zipper,NewZipper)
```

Mode and number of proofs:

```
delete_all_before_and_unzip(+zipper,--sequence) - one
```

```
delete_all_after/2
```

Deletes all elements after the current element.

Compilation flags:

```
static
```

Template:

```
delete_all_after(Zipper,NewZipper)
```

Mode and number of proofs:

```
delete_all_after(+zipper,--zipper) - one
```

`delete_all_after_and_unzip/2`

Deletes all elements after the current element and removes the zipper returning the resulting sequence.

Compilation flags:

`static`

Template:

`delete_all_after_and_unzip(Zipper,NewZipper)`

Mode and number of proofs:

`delete_all_after_and_unzip(+zipper,--sequence) - one`

Protected predicates

(none)

Private predicates

(none)

Operators

(none)

See also:

`zlist`

object

1.78.2 `zlist`

Zipper list predicates. Zippers should be regarded as opaque terms.

Availability:

`logtalk_load(zippers(loader))`

Author: Paulo Moura

Version: 1:0:1

Date: 2019-03-12

Compilation flags:

static, context_switching_calls

Implements:

public zipperp

Remarks:

(none)

Inherited public predicates:

apply/2 current/2 delete_all_after/2 delete_all_after_and_unzip/2 delete_all_before/2
 delete_all_before_and_unzip/2 delete_and_next/2 delete_and_previous/2 delete_and_unzip/2
 forward/2 forward/3 insert_after/3 insert_before/3 next/2 next/3 previous/2 previous/3
 replace/3 rewind/2 rewind/3 unzip/2 zip/2 zip/3

- Public predicates
 - zip_at_index/4
- Protected predicates
- Private predicates
- Operators

Public predicates

zip_at_index/4

Adds a zipper to a list opened at the given index and also returns the element at the index. Fails if the list is empty or the index (starting at 1) does not exist.

Compilation flags:

static

Template:

zip_at_index(Index,List,Zipper,Element)

Mode and number of proofs:

zip_at_index(+natural,+list,--zipper,--term) - zero_or_one

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

DIRECTORIES

To load an entity, always load the library that includes it using the goal `logtalk_load(library_name(loader))` instead of using its path. The library loader file ensures that all the required dependencies are also loaded and that any required flags are used. The loading goal can be found in the entity documentation.

- 2.1** [contributions/flags/](#)
- 2.2** [contributions/iso8601/](#)
- 2.3** [contributions/pddl_parser/](#)
- 2.4** [contributions/verdi_neruda/](#)
- 2.5** [contributions/xml_parser/](#)
- 2.6** [core/](#)
- 2.7** [library/](#)
- 2.8** [library/arbitrary/](#)
- 2.9** [library/assignvars/](#)
- 2.10** [library/base64/](#)
- 2.11** [library/cbor/](#)
- 2.12** [library/coroutining/](#)
- 2.13** [library/csv/](#)
- 2.14** [library/dates/](#)
- 2.15** [library/dependents/](#)
- 2.16** [library/dictionaries/](#)
- 2.17** [library/dif/](#)
- 2.18** [library/edcg/](#)
- 2.19** [library/events/](#)
- 2.20** [library/expand_library_alias_paths/](#)
- 2.1.** [contributions/flags/](#)
- 2.21** [library/expecteds/](#)

ENTITIES

To load an entity, always load the library that includes it using the goal `logtalk_load(library_name(loader))` instead of loading just the entity. The library loader file ensures that all the required dependencies are also loaded and that any required flags are used. The loading goal can be found in the entity documentation.

3.1 Categories

3.2 Objects

3.3 Protocols

PREDICATES

This index lists all entities declaring a given predicate. To load an entity providing the predicate that you want to call, always load the library that includes it using the goal `logtalk_load(library_name(loader))` instead of loading just the entity. The library loader file ensures that all the required dependencies are also loaded and that any required flags are used. The loading goal can be found in the entity documentation.

4.1 `(/)/2`

- `help`

4.2 `(//)/2`

- `help`

4.3 `(<)/2`

- `comparingp`

4.4 `(<=)/2`

- `assignvarsp`
- `streamvars`

4.5 `(=:=)/2`

- `comparingp`

4.6 (= <)/2

- comparingp

4.7 (= >)/2

- assignvarsp
- streamvars

4.8 (= \=)/2

- comparingp

4.9 = ~ = / 2

- lgtunit
- number

4.10 (>)/2

- comparingp

4.11 (>=)/2

- comparingp

4.12 absolute_file_name/2

- osp

4.13 activate_monitor/0

- monitorp

4.14 add/1

- registries

4.15 add/2

- registries

4.16 add/3

- difflist
- registries

4.17 addDependent/1

- subject

4.18 after/2

- intervalp

4.19 after/3

- monitoring

4.20 all/0

- code_metric
- dead_code_scanner
- lgtdocp

4.21 all/1

- code_metric
- dead_code_scanner
- lgtdocp

4.22 all_files/0

- diagram(Format)
- diagrams(Format)

4.23 all_files/1

- diagram(Format)
- diagrams(Format)

4.24 all_libraries/0

- diagram(Format)
- diagrams(Format)

4.25 all_libraries/1

- diagram(Format)
- diagrams(Format)

4.26 all_score/1

- code_metric

4.27 ancestor/1

- hierarchyp

4.28 ancestors/1

- hierarchyp

4.29 apis/0

- help_info_support

4.30 apis/1

- help_info_support

4.31 append/2

- listp

4.32 append/3

- listp
- queuep
- varlistp

4.33 apply/2

- zipperp

4.34 apply/4

- dictionaryp

4.35 approximately_equal/2

- lgtunit
- number

4.36 approximately_equal/3

- lgtunit
- number

4.37 arbitrary/1

- arbitrary

4.38 arbitrary/2

- arbitrary

4.39 archive/1

- registry_protocol

4.40 arithmetic_mean/2

- statisticsp

4.41 array_list/2

- java_utils_protocol

4.42 array_to_list/2

- java_utils_protocol

4.43 array_to_terms/2

- java_utils_protocol

4.44 array_to_terms/3

- java_utils_protocol

4.45 as_curly_bracketed/2

- dictionaryp
- nested_dictionary_protocol

4.46 as_dictionary/2

- dictionaryp

4.47 as_difflist/2

- list

4.48 as_heap/2

- heapp

4.49 as_list/2

- dictionaryp
- difflist
- heapp
- queuep
- setp

4.50 as_nested_dictionary/2

- nested_dictionary_protocol

4.51 as_set/2

- setp

4.52 ask_question/5

- logtalk

4.53 assertion/1

- assertions(Mode)
- lgtunit

4.54 assertion/2

- assertions(Mode)
- lgtunit

4.55 assignable/1

- assignvarsp

4.56 assignable/2

- assignvarsp

4.57 available/0

- packs

4.58 available/1

- packs

4.59 available/2

- packs

4.60 average/2

- numberlistp

4.61 average_deviation/3

- statisticsp

4.62 before/2

- intervalp

4.63 before/3

- monitoring

4.64 bench_goal/1

- databasep

4.65 benchmark/2

- lgtunit

4.66 benchmark/3

- lgtunit

4.67 benchmark/4

- lgtunit

4.68 benchmark_reified/3

- lgtunit

4.69 between/3

- integer
- random_protocol

4.70 bit//1

- number_grammars(Format)

4.71 bits//1

- number_grammars(Format)

4.72 blank//0

- blank_grammars(Format)

4.73 blanks//0

- blank_grammars(Format)

4.74 body_pred/1

- metagol

4.75 branch/2

- git_protocol

4.76 built_in_directive/4

- help

4.77 built_in_flag/2

- flags

4.78 built_in_method/4

- help

4.79 built_in_non_terminal/4

- help

4.80 built_in_predicate/4

- help

4.81 calendar_month/3

- iso8601

4.82 call_with_timeout/2

- timeout

4.83 call_with_timeout/3

- timeout

4.84 cat/2

- maybe

4.85 change_directory/1

- osp

4.86 changed/0

- subject

4.87 changed/1

- subject

4.88 chebyshev_distance/3

- numberlistp

4.89 chebyshev_norm/2

- numberlistp

4.90 check/1

- term
- varlistp

4.91 check/2

- type

4.92 check/3

- type

4.93 check_option/1

- options_protocol

4.94 check_options/1

- options_protocol

4.95 chr_is/2

- toychrdb

4.96 chr_no_spy/1

- toychrdb

4.97 chr_nospy/0

- toychrdb

4.98 chr_notrace/0

- toychrdb

4.99 chr_option/2

- toychrdb

4.100 chr_spy/1

- toychrdb

4.101 chr_trace/0

- toychrdb

4.102 class/1

- class_hierarchy

4.103 classes/1

- class_hierarchy

4.104 clause/5

- ports_profiler

4.105 clause_location/6

- ports_profiler

4.106 clean/0

- packs
- registries

4.107 clean/1

- packs
- registries

4.108 clean/2

- packs

4.109 clone/1

- cloning
- registry_protocol

4.110 clone/3

- dictionaryp

4.111 clone/4

- dictionaryp

4.112 coefficient_of_variation/2

- statisticsp

4.113 command_line_arguments/1

- osp

4.114 commit_author/2

- git_protocol

4.115 commit_date/2

- git_protocol

4.116 commit_hash/2

- git_protocol

4.117 commit_hash_abbreviated/2

- git_protocol

4.118 commit_log/3

- git_protocol

4.119 commit_message/2

- git_protocol

4.120 compile_aux_clauses/1

- logtalk

4.121 compile_predicate_heads/4

- logtalk

4.122 compile_predicate_indicators/3

- logtalk

4.123 completion/2

- help

4.124 completions/2

- help

4.125 connect/1

- redis

4.126 connect/3

- redis

4.127 console/1

- redis

4.128 contains/2

- intervalp

4.129 control//0

- blank_grammars(Format)

4.130 control_construct/4

- help

4.131 controls//0

- blank_grammars(Format)

4.132 copy_file/2

- osp

4.133 counter/2

- counters
- mutations_store

4.134 cover/1

- lgtunit

4.135 cpu_time/1

- osp
- timep

4.136 current/2

- zipperp

4.137 data/0

- ports_profiler

4.138 data/1

- ports_profiler

4.139 data/2

- ports_profiler

4.140 date/4

- iso8601

4.141 date/5

- iso8601

4.142 date/6

- iso8601

4.143 date/7

- iso8601

4.144 date_string/3

- iso8601

4.145 date_time/7

- osp

4.146 days_in_month/3

- datep

4.147 debug/0

- debuggerp

4.148 debug_handler/2

- logtalk

4.149 debug_handler_provider/1

- logtalk

4.150 debugging/0

- debuggerp

4.151 debugging/1

- debuggerp

4.152 decide/1

- fcube

4.153 decide/2

- fcube

4.154 decode_exception/2

- java_utils_protocol

4.155 decode_exception/3

- java_utils_protocol

4.156 decompile_predicate_heads/4

- logtalk

4.157 decompile_predicate_indicators/4

- logtalk

4.158 decompose_file_name/3

- osp

4.159 decompose_file_name/4

- osp

4.160 decrement_counter/1

- counters

4.161 default_option/1

- options_protocol
- wrapper

4.162 default_options/1

- options_protocol
- wrapper

4.163 define_log_file/2

- loggingp

4.164 defined/4

- registries

4.165 defined_flag/6

- flags

4.166 del_monitors/0

- event_registry

4.167 del_monitors/4

- event_registry

4.168 del_spy_points/4

- monitorp

4.169 delete/0

- registries

4.170 delete/1

- registries

4.171 delete/2

- registries

4.172 delete/3

- listp
- setp
- varlistp

4.173 delete/4

- dictionaryp
- heapp

4.174 delete_all_after/2

- zipperp

4.175 delete_all_after_and_unzip/2

- zipperp

4.176 delete_all_before/2

- zipperp

4.177 delete_all_before_and_unzip/2

- zipperp

4.178 delete_and_next/2

- zipperp

4.179 delete_and_previous/2

- zipperp

4.180 delete_and_unzip/2

- zipperp

4.181 delete_directory/1

- osp

4.182 delete_file/1

- osp

4.183 delete_in/4

- nested_dictionary_protocol

4.184 delete_matches/3

- listp

4.185 delete_max/4

- dictionaryp

4.186 delete_min/4

- dictionaryp

4.187 dependents/1

- packs
- subject

4.188 dependents/2

- packs

4.189 dependents/3

- packs

4.190 depth/2

- temp

4.191 descendant/1

- hierarchyp

4.192 descendant_class/1

- class_hierarchyp

4.193 descendant_classes/1

- class_hierarchyp

4.194 descendant_instance/1

- class_hierarchyp

4.195 descendant_instances/1

- class_hierarchy

4.196 descendants/1

- hierarchy

4.197 describe/1

- packs
- registries

4.198 describe/2

- packs

4.199 description/1

- pack_protocol
- registry_protocol

4.200 deterministic/1

- lgtunit

4.201 deterministic/2

- lgtunit

4.202 diagram_description/1

- diagram(Format)

4.203 diagram_name_suffix/1

- diagram(Format)

4.204 dif/1

- coroutining
- dif

4.205 dif/2

- coroutining
- dif

4.206 digit//1

- number_grammars(Format)

4.207 digits//1

- number_grammars(Format)

4.208 directories/1

- lgtdocp
- wrapper

4.209 directories/2

- diagram(Format)
- diagrams(Format)
- lgtdocp
- wrapper

4.210 directories/3

- diagram(Format)
- diagrams(Format)

4.211 directory/1

- code_metric
- dead_code_scanner
- diagram(Format)
- diagrams(Format)
- lgtdocp
- packs_common
- wrapper

4.212 directory/2

- code_metric
- dead_code_scanner
- diagram(Format)
- diagrams(Format)
- lgtdocp
- packs_common
- wrapper

4.213 directory/3

- diagram(Format)
- diagrams(Format)

4.214 directory_exists/1

- osp

4.215 directory_files/2

- osp

4.216 directory_files/3

- osp

4.217 directory_score/2

- code_metric

4.218 disable/1

- debug_messages

4.219 disable/2

- debug_messages

4.220 disable_logging/1

- loggingp

4.221 disconnect/1

- redis

4.222 disjoint/2

- setp

4.223 disjoint_sets/2

- union_find_protocol

4.224 doc_goal/1

- doclet

4.225 dot//1

- number_grammars(Format)

4.226 dowhile/2

- loopp

4.227 drop/3

- listp

4.228 during/2

- intervalp

4.229 easter_day/3

- iso8601

4.230 edge/6

- graph_language_protocol

4.231 edge_case/2

- arbitrary

4.232 either/3

- expected(Expected)

4.233 empty/1

- dictionaryp
- heapp
- listp
- nested_dictionary_protocol
- optional
- queuep
- setp
- varlistp

4.234 enable/1

- debug_messages

4.235 enable/2

- debug_messages

4.236 enable_logging/1

- loggingp

4.237 enabled/1

- debug_messages

4.238 enabled/2

- debug_messages

4.239 ensure_directory/1

- osp

4.240 ensure_file/1

- osp

4.241 entity/1

- code_metric
- dead_code_scanner
- help
- xref_diagram(Format)

4.242 entity/2

- xref_diagram(Format)

4.243 entity_info_pair_score_hook/3

- doc_metric

4.244 entity_info_score_hook/2

- doc_metric

4.245 entity_predicates_weights_hook/2

- doc_metric

4.246 entity_prefix/2

- logtalk

4.247 entity_score/2

- code_metric

4.248 enumerate/2

- random_protocol

4.249 environment_variable/2

- osp

4.250 epsilon/1

- lgtunit

4.251 equal/2

- intervalp
- setp

4.252 erase/1

- recorded_database_core

4.253 essentially_equal/3

- lgtunit
- number

4.254 euclidean_distance/3

- numberlistp

4.255 euclidean_norm/2

- numberlistp

4.256 exclude/3

- metap

4.257 execution_context/7

- logtalk

4.258 expand_library_path/2

- logtalk

4.259 expected/1

- expected(Expected)

4.260 expecteds/2

- either

4.261 extension/1

- proto_hierarchy

4.262 extensions/1

- proto_hierarchy

4.263 false/1

- java_utils_protocol

4.264 fcube/0

- fcube

4.265 file/1

- code_metric
- dead_code_scanner
- entity_diagram(Format)
- lgtdocp
- wrapper

4.266 file/2

- code_metric
- dead_code_scanner
- entity_diagram(Format)
- lgtdocp
- wrapper

4.267 file_exists/1

- osp

4.268 file_footer/3

- graph_language_protocol

4.269 file_header/3

- graph_language_protocol

4.270 file_modification_time/2

- osp

4.271 file_permission/2

- osp

4.272 file_score/2

- code_metric

4.273 file_size/2

- osp

4.274 file_to_bytes/2

- reader

4.275 file_to_bytes/3

- reader

4.276 file_to_chars/2

- reader

4.277 file_to_chars/3

- reader

4.278 file_to_codes/2

- reader

4.279 file_to_codes/3

- reader

4.280 file_to_terms/2

- reader

4.281 file_to_terms/3

- reader

4.282 file_type_extension/2

- logtalk

4.283 files/1

- diagram(Format)
- diagrams(Format)
- lgtdocp
- wrapper

4.284 files/2

- diagram(Format)
- diagrams(Format)
- lgtdocp
- wrapper

4.285 files/3

- diagram(Format)
- diagrams(Format)

4.286 filter/2

- optional(Optional)

4.287 find/4

- union_find_protocol

4.288 find/5

- union_find_protocol

4.289 findall_member/4

- metap

4.290 findall_member/5

- metap

4.291 finished_by/2

- intervalp

4.292 finishes/2

- intervalp

4.293 flag_group_chk/1

- flags

4.294 flag_groups/1

- flags

4.295 flat_map/2

- expected(Expected)
- optional(Optional)

4.296 flatten/2

- listp
- varlistp

4.297 float//1

- number_grammars(Format)

4.298 fold_left/4

- metap

4.299 fold_left_1/3

- metap

4.300 fold_right/4

- metap

4.301 fold_right_1/3

- metap

4.302 fordownto/3

- loopp

4.303 fordownto/4

- loopp

4.304 fordownto/5

- loopp

4.305 foreach/3

- loopp

4.306 foreach/4

- loopp

4.307 format/2

- format

4.308 format/3

- format

4.309 format_entity_score//2

- code_metric

4.310 format_object/1

- diagram(Format)

4.311 format_to_atom/3

- term_io_protocol

4.312 format_to_chars/3

- term_io_protocol

4.313 `format_to_chars/4`

- `term_io_protocol`

4.314 `format_to_codes/3`

- `term_io_protocol`

4.315 `format_to_codes/4`

- `term_io_protocol`

4.316 `forto/3`

- `loopp`

4.317 `forto/4`

- `loopp`

4.318 `forto/5`

- `loopp`

4.319 `forward/1`

- `forwarding`

4.320 `forward/2`

- `zipperp`

4.321 forward/3

- zipperp

4.322 fractile/3

- statisticsp

4.323 freeze/2

- coroutinging

4.324 from_generator/2

- expected
- optional

4.325 from_generator/3

- expected
- optional

4.326 from_generator/4

- expected

4.327 from_goal/2

- expected
- optional

4.328 from_goal/3

- expected
- optional

4.329 from_goal/4

- expected

4.330 frozen/2

- coroutining

4.331 full_device_path/1

- osp

4.332 func_test/3

- metagol

4.333 functional/0

- metagol

4.334 generate/1

- ids(Representation,Bytes)
- ulid_protocol

4.335 generate/2

- base64
- base64url
- cbor(StringRepresentation)
- html
- json_protocol
- ulid_protocol

4.336 generate/8

- ulid_protocol

4.337 genint/2

- genint_core

4.338 gensym/2

- gensym_core

4.339 geometric_mean/2

- statisticsp

4.340 get/1

- optional(Optional)

4.341 get_field/2

- java_access_protocol

4.342 get_flag_value/2

- flags

4.343 get_seed/1

- arbitrary
- pseudo_random_protocol

4.344 gnu/0

- fcube

4.345 goal_expansion/2

- expanding

4.346 graph_footer/5

- graph_language_protocol

4.347 graph_header/5

- graph_language_protocol

4.348 ground/1

- temp

4.349 group_by_key/2

- pairs

4.350 group_consecutive_by_key/2

- pairs

4.351 group_sorted_by_key/2

- pairs

4.352 guess_arity/2

- csv_protocol

4.353 guess_separator/2

- csv_protocol

4.354 hamming_distance/3

- listp

4.355 handbook/0

- help_info_support

4.356 handbook/1

- help_info_support

4.357 harmonic_mean/2

- statisticsp

4.358 head/2

- queuep

4.359 head_pred/1

- metagol

4.360 help/0

- help
- packs_common

4.361 hex_digit//1

- number_grammars(Format)

4.362 hex_digits//1

- number_grammars(Format)

4.363 home/1

- pack_protocol
- registry_protocol

4.364 ibk/3

- metagol

4.365 if_empty/1

- optional(Optional)

4.366 if_expected/1

- expected(Expected)

4.367 if_expected_or_else/2

- expected(Expected)

4.368 if_present/1

- optional(Optional)

4.369 if_present_or_else/2

- optional(Optional)

4.370 if_unexpected/1

- expected(Expected)

4.371 include/3

- metap

4.372 increase/1

- counter

4.373 increment/0

- counter

4.374 increment_counter/1

- counters

4.375 init/0

- shell(Interpreters)

4.376 init_log_file/2

- loggingp

4.377 inorder/2

- bintree

4.378 insert/3

- setp

4.379 insert/4

- dictionaryp
- heapp

4.380 insert_after/3

- zipperp

4.381 insert_all/3

- heapp
- setp

4.382 insert_before/3

- zipperp

4.383 insert_in/4

- nested_dictionary_protocol

4.384 install/1

- packs

4.385 install/2

- packs

4.386 install/3

- packs

4.387 install/4

- packs

4.388 installed/0

- packs

4.389 installed/1

- packs

4.390 installed/3

- packs

4.391 installed/4

- packs

4.392 instance/1

- class_hierarchy

4.393 instance/2

- recorded_database_core

4.394 instances/1

- class_hierarchy

4.395 integer//1

- number_grammars(Format)

4.396 internal_os_path/2

- osp

4.397 intersect/2

- setp

4.398 intersection/2

- dictionary

4.399 intersection/3

- dictionary
- setp

4.400 intersection/4

- setp

4.401 invoke/1

- java_access_protocol

4.402 invoke/2

- java_access_protocol

4.403 ipv4//1

- ip_grammars(Format)

4.404 ipv6//1

- ip_grammars(Format)

4.405 is_absolute_file_name/1

- osp

4.406 is_alpha/1

- characterp

4.407 is_alphanumeric/1

- characterp

4.408 is_ascii/1

- characterp

4.409 is_bin_digit/1

- characterp

4.410 is_control/1

- characterp

4.411 is_dec_digit/1

- characterp

4.412 is_empty/0

- optional(Optional)

4.413 is_end_of_line/1

- characterp

4.414 is_expected/0

- expected(Expected)

4.415 is_false/1

- java_utils_protocol

4.416 is_hex_digit/1

- characterp

4.417 is_layout/1

- characterp

4.418 is_letter/1

- characterp

4.419 is_lower_case/1

- characterp

4.420 is_newline/1

- characterp

4.421 is_null/1

- java_utils_protocol

4.422 is_object/1

- java_utils_protocol

4.423 is_octal_digit/1

- characterp

4.424 is__period/1

- characterp

4.425 is__present/0

- optional(Optional)

4.426 is__punctuation/1

- characterp

4.427 is__quote/1

- characterp

4.428 is__true/1

- java_utils_protocol

4.429 is__unexpected/0

- expected(Expected)

4.430 is__upper__case/1

- characterp

4.431 is__void/1

- java_utils_protocol

4.432 is_vowel/1

- characterp

4.433 is_white_space/1

- characterp

4.434 iterator_element/2

- java_utils_protocol

4.435 join/3

- queuep

4.436 join_all/3

- queuep

4.437 jump/3

- queuep

4.438 jump_all/3

- queuep

4.439 jump_all_block/3

- queuep

4.440 key/2

- pairs

4.441 keys/2

- dictionaryp
- pairs

4.442 keys_values/3

- pairs

4.443 keysort/2

- listp

4.444 kurtosis/2

- statisticsp

4.445 language_object/2

- graph_language_registry

4.446 last/2

- listp
- varlistp

4.447 leaf/1

- hierarchyp

4.448 leaf_class/1

- class_hierarchy

4.449 leaf_classes/1

- class_hierarchy

4.450 leaf_instance/1

- class_hierarchy

4.451 leaf_instances/1

- class_hierarchy

4.452 leap_year/1

- datep
- iso8601

4.453 learn/0

- metagol_example_protocol

4.454 learn/1

- metagol_example_protocol

4.455 learn/2

- metagol

4.456 learn/3

- metagol

4.457 learn_seq/2

- metagol

4.458 learn_with_timeout/4

- metagol

4.459 leash/1

- debuggerp

4.460 leashing/1

- debuggerp

4.461 least_common_multiple/2

- numberlistp

4.462 leaves/1

- hierarchyp

4.463 length/2

- listp
- queuep
- varlistp

4.464 libraries/1

- diagram(Format)
- diagrams(Format)
- lgtdocp

4.465 libraries/2

- diagram(Format)
- diagrams(Format)
- lgtdocp

4.466 libraries/3

- diagram(Format)
- diagrams(Format)

4.467 library/0

- help

4.468 library/1

- code_metric
- dead_code_scanner
- diagram(Format)
- diagrams(Format)
- help
- lgtdocp

4.469 library/2

- code_metric
- dead_code_scanner
- diagram(Format)
- diagrams(Format)
- lgtdocp

4.470 library_score/2

- code_metric

4.471 license/1

- pack_protocol

4.472 line_to_chars/2

- reader

4.473 line_to_chars/3

- reader

4.474 line_to_codes/2

- reader

4.475 line_to_codes/3

- reader

4.476 lint/0

- packs
- registries

4.477 lint/1

- packs
- registries

4.478 lint/2

- packs

4.479 list/0

- registries

4.480 list_to_array/2

- java_utils_protocol

4.481 listing/0

- listing

4.482 listing/1

- listing

4.483 loaded_file/1

- logtalk

4.484 loaded_file_property/2

- logtalk
- modules_diagram_support

4.485 log_event/2

- loggingp

4.486 log_file/2

- loggingp

4.487 logging/1

- loggingp

4.488 logtalk_packs/0

- packs_common

4.489 logtalk_packs/1

- packs_common

4.490 lookup/2

- dictionaryp

4.491 lookup/3

- dictionaryp

4.492 lookup_in/3

- nested_dictionary_protocol

4.493 lower_upper/2

- characterp

4.494 magic/2

- magic

4.495 magicise/4

- magic

4.496 make_directory/1

- osp

4.497 make_directory_path/1

- osp

4.498 make_set/3

- union_find_protocol

4.499 man/1

- help_info_support

4.500 manhattan_distance/3

- numberlistp

4.501 manhattan_norm/2

- numberlistp

4.502 manuals/0

- help

4.503 map/2

- dictionaryp
- expected(Expected)
- metap
- optional(Optional)
- queuep

4.504 map/3

- dictionaryp
- metap
- pairs
- queuep

4.505 map/4

- metap

4.506 map/5

- metap

4.507 map/6

- metap

4.508 map/7

- metap

4.509 map/8

- metap

4.510 map_element/2

- java_utils_protocol

4.511 map_reduce/5

- metap

4.512 max/2

- listp
- numberlistp
- statisticsp

4.513 max/3

- dictionaryp

4.514 max_clauses/1

- metagol

4.515 max_inv_preds/1

- metagol

4.516 max_size/1

- arbitrary

4.517 maybe/0

- random_protocol

4.518 maybe/1

- random_protocol

4.519 maybe/2

- random_protocol

4.520 maybe_call/1

- random_protocol

4.521 maybe_call/2

- random_protocol

4.522 mean_deviation/2

- statisticsp

4.523 median/2

- numberlistp
- statisticsp

4.524 median_deviation/2

- statisticsp

4.525 meets/2

- intervalp

4.526 member/2

- listp
- random_protocol
- setp

4.527 memberchk/2

- listp
- setp
- varlistp

4.528 merge/3

- heapp

4.529 message_hook/4

- logtalk

4.530 message_prefix_stream/4

- logtalk

4.531 message_tokens//2

- logtalk

4.532 met_by/2

- intervalp

4.533 meta_type/3

- type

4.534 metarule/6

- metagol

4.535 metarule_next_id/1

- metagol

4.536 min/2

- listp
- numberlistp
- statisticsp

4.537 min/3

- dictionaryp

4.538 min_clauses/1

- metagol

4.539 min_max/3

- numberlistp
- statisticsp

4.540 modes/2

- numberlistp
- statisticsp

4.541 module_property/2

- modules_diagram_support

4.542 monitor/1

- event_registry

4.543 monitor/4

- event_registry

4.544 monitor_activated/0

- monitorp

4.545 monitored/1

- event_registry

4.546 monitors/1

- event_registry

4.547 msort/2

- listp

4.548 msort/3

- listp

4.549 mutation/3

- mutations
- mutations_store

4.550 name/1

- pack_protocol
- registry_protocol

4.551 name_of_day/3

- datep

4.552 name_of_month/3

- datep

4.553 natural//1

- number_grammars(Format)

4.554 new/1

- java_access_protocol
- nested_dictionary_protocol
- streamvars
- temp

4.555 new/2

- java_access_protocol
- streamvars
- union_find_protocol

4.556 new/3

- intervalp

4.557 new_line//0

- blank_grammars(Format)

4.558 new_lines//0

- blank_grammars(Format)

4.559 next/2

- zipperp

4.560 next/3

- zipperp

4.561 next/4

- dictionaryp

4.562 nextto/3

- listp
- varlistp

4.563 node/7

- graph_language_protocol

4.564 nodebug/0

- debuggerp

4.565 non_blank//1

- blank_grammars(Format)

4.566 non_blanks//1

- blank_grammars(Format)

4.567 normal_element/2

- html

4.568 normalize_range/2

- numberlistp

4.569 normalize_range/4

- numberlistp

4.570 normalize_scalar/2

- numberlistp

4.571 normalize_unit/2

- numberlistp

4.572 nospy/1

- debuggerp

4.573 nospy/4

- debuggerp

4.574 nospyall/0

- debuggerp

4.575 note/2

- registry_protocol

4.576 note/3

- pack_protocol

4.577 notrace/0

- debuggerp

4.578 now/3

- timep

4.579 nth0/3

- listp
- varlistp

4.580 nth0/4

- listp
- varlistp

4.581 nth1/3

- listp
- varlistp

4.582 nth1/4

- listp
- varlistp

4.583 null/1

- java_utils_protocol

4.584 null_device_path/1

- osp

4.585 number//1

- number_grammars(Format)

4.586 number_of_tests/1

- lgtunit

4.587 numbervars/1

- temp

4.588 numbervars/3

- temp

4.589 occurrences/2

- listp

4.590 occurrences/3

- listp

4.591 occurs/2

- temp

4.592 of/2

- optional

4.593 of_expected/2

- expected

4.594 of_unexpected/2

- expected

4.595 one_or_more//0

- sequence_grammars

4.596 one_or_more//1

- sequence_grammars

4.597 one_or_more//2

- sequence_grammars

4.598 operating_system_machine/1

- osp

4.599 operating_system_name/1

- osp

4.600 operating_system_release/1

- osp

4.601 operating_system_type/1

- osp

4.602 option/2

- options_protocol

4.603 option/3

- options_protocol

4.604 or/2

- optional(Optional)

4.605 or_else/2

- expected(Expected)
- optional(Optional)

4.606 or_else_call/2

- expected(Expected)
- optional(Optional)

4.607 or_else_fail/1

- expected(Expected)
- optional(Optional)

4.608 or_else_get/2

- expected(Expected)
- optional(Optional)

4.609 or_else_throw/1

- expected(Expected)

4.610 or_else_throw/2

- optional(Optional)

4.611 orphaned/0

- packs

4.612 orphaned/2

- packs

4.613 outdated/0

- packs

4.614 outdated/1

- packs

4.615 outdated/4

- packs

4.616 output_file_name/2

- graph_language_protocol

4.617 overlapped_by/2

- intervalp

4.618 overlaps/2

- intervalp

4.619 parent/1

- proto_hierarchyp

4.620 parenthesis/2

- characterp

4.621 parents/1

- proto_hierarchyp

4.622 parse/2

- base64
- base64url
- cbor(StringRepresentation)
- json_protocol
- xml

4.623 parse/3

- xml

4.624 parse_domain/2

- pddl

4.625 parse_domain/3

- pddl

4.626 parse_problem/2

- pddl

4.627 parse_problem/3

- pddl

4.628 partial_map/4

- rbtree

4.629 partition/3

- either

4.630 partition/4

- metap

4.631 partition/5

- listp

4.632 partition/6

- metap

4.633 path_concat/3

- osp

4.634 permutation/2

- listp
- random_protocol
- varlistp

4.635 pid/1

- osp

4.636 pin/0

- packs_common

4.637 pin/1

- packs_common

4.638 pinned/1

- packs_common

4.639 plus/3

- integer

4.640 port/5

- ports_profiler

4.641 portray_clause/1

- listing

4.642 postorder/2

- bintree

4.643 powerset/2

- setp

4.644 pp/1

- xml

4.645 pprint/1

- metagol

4.646 predicate/2

- dead_code_scanner

4.647 predicate_info_pair_score_hook/4

- doc_metric

4.648 predicate_info_score_hook/3

- doc_metric

4.649 predicate_mode_score_hook/3

- doc_metric

4.650 predicate_mode_score_hook/5

- doc_metric

4.651 predicates/2

- dead_code_scanner

4.652 prefix/0

- packs_common

4.653 prefix/1

- packs_common

4.654 prefix/2

- listp
- varlistp

4.655 prefix/3

- listp

4.656 preorder/2

- bintree

4.657 previous/2

- zipperp

4.658 previous/3

- zipperp

4.659 previous/4

- dictionaryp

4.660 print_flags/0

- flags
- flags_validator

4.661 print_flags/1

- flags

4.662 print_message/3

- logtalk

4.663 print_message_token/4

- logtalk

4.664 print_message_tokens/3

- logtalk

4.665 product/2

- numberlistp
- statisticsp

4.666 product/3

- setp

4.667 program_to_clauses/2

- metagol

4.668 proper_prefix/2

- listp

4.669 proper_prefix/3

- listp

4.670 proper_suffix/2

- listp

4.671 proper_suffix/3

- listp

4.672 prove/2

- interpreterp

4.673 prove/3

- interpreterp

4.674 provides/2

- registries

4.675 question_hook/6

- logtalk

4.676 question_prompt_stream/4

- logtalk

4.677 quick_check/1

- lgtunit

4.678 quick_check/2

- lgtunit

4.679 quick_check/3

- lgtunit

4.680 random/1

- random_protocol

4.681 random/3

- random_protocol

4.682 random_node/1

- uuid_protocol

4.683 random_tree/1

- benchmark_generators

4.684 randomize/1

- fast_random
- random

4.685 randseq/4

- random_protocol

4.686 randset/4

- random_protocol

4.687 range/2

- statisticsp

4.688 rdirectories/1

- lgtdocp

4.689 rdirectories/2

- lgtdocp

4.690 rdirectory/1

- code_metric
- dead_code_scanner
- diagram(Format)
- diagrams(Format)
- lgtdocp
- wrapper

4.691 rdirectory/2

- code_metric
- dead_code_scanner
- diagram(Format)
- diagrams(Format)
- lgtdocp
- wrapper

4.692 rdirectory/3

- diagram(Format)
- diagrams(Format)

4.693 rdirectory_score/2

- code_metric

4.694 read_file/2

- csv_protocol
- read_file
- tsv_protocol

4.695 read_file/3

- csv_protocol
- tsv_protocol

4.696 read_file_by_line/2

- csv_protocol
- tsv_protocol

4.697 read_file_by_line/3

- csv_protocol
- tsv_protocol

4.698 read_from_atom/2

- term_io_protocol

4.699 read_from_chars/2

- term_io_protocol

4.700 read_from_codes/2

- term_io_protocol

4.701 read_only_device_path/1

- osp

4.702 read_stream/2

- csv_protocol
- tsv_protocol

4.703 read_stream/3

- csv_protocol
- tsv_protocol

4.704 read_stream_by_line/2

- csv_protocol
- tsv_protocol

4.705 read_stream_by_line/3

- csv_protocol
- tsv_protocol

4.706 read_term_from_atom/3

- term_io_protocol

4.707 read_term_from_chars/3

- term_io_protocol

4.708 read_term_from_chars/4

- term_io_protocol

4.709 read_term_from_codes/3

- term_io_protocol

4.710 read_term_from_codes/4

- term_io_protocol

4.711 readme/1

- packs_common

4.712 readme/2

- packs_common

4.713 recorda/2

- recorded_database_core

4.714 recorda/3

- recorded_database_core

4.715 recorded/2

- recorded_database_core

4.716 recorded/3

- recorded_database_core

4.717 recordz/2

- recorded_database_core

4.718 recordz/3

- recorded_database_core

4.719 relative_standard_deviation/2

- statisticsp

4.720 removeDependent/1

- subject

4.721 remove_duplicates/2

- listp
- varlistp

4.722 rename_file/2

- osp

4.723 replace/3

- zipperp

4.724 replace_sub_atom/4

- atom

4.725 rescale/3

- numberlistp

4.726 reset/0

- counter
- debuggerp
- packs_common
- ports_profiler

4.727 reset/1

- ports_profiler

4.728 reset_counter/1

- counters

4.729 reset_counters/0

- counters

4.730 reset_flags/0

- flags

4.731 reset_flags/1

- flags

4.732 reset_genint/0

- genint_core

4.733 reset_genint/1

- genint_core

4.734 reset_gensym/0

- gensym_core

4.735 reset_gensym/1

- gensym_core

4.736 reset_monitor/0

- monitorp

4.737 reset_seed/0

- fast_random
- random

4.738 restore/1

- packs

4.739 restore/2

- packs

4.740 reverse/2

- listp
- varlistp

4.741 rewind/2

- zipperp

4.742 rewind/3

- zipperp

4.743 rlibraries/1

- lgtdocp

4.744 rlibraries/2

- lgtdocp

4.745 rlibrary/1

- code_metric
- dead_code_scanner
- diagram(Format)
- diagrams(Format)
- lgtdocp

4.746 rlibrary/2

- code_metric
- dead_code_scanner
- diagram(Format)
- diagrams(Format)
- lgtdocp

4.747 rlibrary_score/2

- code_metric

4.748 rule/2

- databasep

4.749 rule/3

- databasep

4.750 rule/4

- databasep

4.751 run/0

- lgtunit

4.752 run/1

- lgtunit

4.753 run/2

- lgtunit

4.754 run_test_sets/1

- lgtunit

4.755 same_length/2

- listp
- varlistp

4.756 same_length/3

- listp

4.757 save/0

- wrapper

4.758 save/1

- packs
- wrapper

4.759 save/2

- packs

4.760 scalar_product/3

- numberlistp

4.761 scan_left/4

- metap

4.762 scan_left_1/3

- metap

4.763 scan_right/4

- metap

4.764 scan_right_1/3

- metap

4.765 search/1

- packs

4.766 select/3

- listp
- random_protocol
- setp
- varlistp

4.767 select/4

- listp
- random_protocol

4.768 selectchk/3

- listp
- setp

4.769 selectchk/4

- listp

4.770 send/3

- redis

4.771 sequence/3

- integer

4.772 sequence/4

- integer
- random_protocol

4.773 serve/3

- queuep

4.774 set/1

- counter

4.775 set/4

- random_protocol

4.776 set_element/2

- java_utils_protocol

4.777 set_field/2

- java_access_protocol

4.778 set_flag_value/2

- flags

4.779 set_flag_value/3

- flags

4.780 set_monitor/4

- event_registryp

4.781 set_seed/1

- arbitrary
- pseudo_random_protocol

4.782 set_spy_point/4

- monitorp

4.783 setup/0

- packs_common

4.784 shell/1

- osp

4.785 shell/2

- osp

4.786 shell_command/1

- doclet

4.787 shrink/3

- arbitrary

4.788 shrink_sequence/3

- arbitrary

4.789 shrinker/1

- arbitrary

4.790 sign//1

- number_grammars(Format)

4.791 singletons/2

- temp

4.792 size/2

- dictionaryp
- heapp
- setp

4.793 skewness/2

- statisticsp

4.794 sleep/1

- osp

4.795 sort/2

- listp

4.796 sort/3

- listp

4.797 sort/4

- listp

4.798 source_file_extension/1

- modules_diagram_support

4.799 space//0

- blank_grammars(Format)

4.800 spaces//0

- blank_grammars(Format)

4.801 split/3

- atom

4.802 split/4

- listp

4.803 spy/1

- debuggerp

4.804 spy/4

- debuggerp

4.805 spy_point/4

- monitorp

4.806 spying/1

- debuggerp

4.807 spying/4

- debuggerp

4.808 standard_deviation/2

- statisticsp

4.809 start/0

- shell

4.810 start_redirect_to_file/2

- dump_trace

4.811 started_by/2

- intervalp

4.812 starts/2

- intervalp

4.813 stop_redirect_to_file/0

- dump_trace

4.814 stream_to_bytes/2

- reader

4.815 stream_to_bytes/3

- reader

4.816 stream_to_chars/2

- reader

4.817 stream_to_chars/3

- reader

4.818 stream_to_codes/2

- reader

4.819 stream_to_codes/3

- reader

4.820 stream_to_terms/2

- reader

4.821 stream_to_terms/3

- reader

4.822 subclass/1

- class_hierarchy

4.823 subclasses/1

- class_hierarchy

4.824 sublist/2

- listp
- varlistp

4.825 subsequence/3

- listp

4.826 subsequence/4

- listp

4.827 subset/2

- setp

4.828 substitute/4

- listp

4.829 subsumes/2

- temp

4.830 subterm/2

- temp
- xml

4.831 subtract/3

- listp
- setp
- varlistp

4.832 succ/2

- integer

4.833 suffix/2

- listp
- varlistp

4.834 suffix/3

- listp

4.835 sum/2

- numberlistp
- statisticsp

4.836 superclass/1

- class_hierarchy

4.837 superclasses/1

- class_hierarchy

4.838 suspend_monitor/0

- monitorp

4.839 swap/2

- random_protocol

4.840 swap_consecutive/2

- random_protocol

4.841 symdiff/3

- setp

4.842 tab//0

- blank_grammars(Format)

4.843 tabs//0

- blank_grammars(Format)

4.844 take/3

- listp

4.845 temporary_directory/1

- osp

4.846 term_expansion/2

- expanding

4.847 terms_to_array/2

- java_utils_protocol

4.848 test/1

- lgtunit

4.849 time_stamp/1

- osp

4.850 timeout/1

- metagol

4.851 timestamp/2

- ulid_protocol

4.852 timestamp/8

- ulid_protocol

4.853 today/3

- datep

4.854 tolerance_equal/4

- lgtunit
- number

4.855 top/3

- heapp

4.856 top_next/5

- heapp

4.857 trace/0

- debuggerp

4.858 trace_event/2

- logtalk

4.859 transpose/2

- pairs

4.860 true/1

- java_utils_protocol

4.861 type/1

- type

4.862 unexpected/1

- expected(Expected)

4.863 unexpecteds/2

- either

4.864 uninstall/0

- packs

4.865 uninstall/1

- packs

4.866 uninstall/2

- packs

4.867 union/3

- setp

4.868 union/4

- setp
- union_find_protocol

4.869 union_all/3

- union_find_protocol

4.870 unpin/0

- packs_common

4.871 unpin/1

- packs_common

4.872 unzip/2

- zipperp

4.873 update/0

- doclet
- packs
- registries

4.874 update/1

- observer
- packs
- registries

4.875 update/2

- packs
- registries

4.876 update/3

- dictionaryp
- packs

4.877 update/4

- dictionaryp

4.878 update/5

- dictionaryp

4.879 update_in/4

- nested_dictionary_protocol

4.880 update_in/5

- nested_dictionary_protocol

4.881 uuid_null/1

- uuid_protocol

4.882 uuid_v1/2

- uuid_protocol

4.883 uuid_v4/1

- uuid_protocol

4.884 valid/1

- intervalp
- statisticsp
- temp
- varlistp

4.885 valid/2

- type

4.886 valid/3

- datep
- timep

4.887 valid_date/3

- iso8601

4.888 valid_option/1

- options_protocol

4.889 valid_options/1

- options_protocol

4.890 validate/1

- flags_validator

4.891 value/1

- counter

4.892 value/3

- pairs

4.893 value_reference/2

- java_utils_protocol

4.894 values/2

- dictionaryp
- pairs

4.895 variables/2

- temp

4.896 variance/2

- statisticsp

4.897 variant/2

- lgtunit
- temp

4.898 varnumbers/2

- temp

4.899 varnumbers/3

- temp

4.900 verify__commands__availability/0

- packs_common

4.901 version/6

- pack_protocol

4.902 versions/3

- packs

4.903 void/1

- java_utils_protocol

4.904 void_element/1

- html

4.905 wall_time/1

- osp

4.906 weighted_mean/3

- statisticsp

4.907 welcome/0

- shell

4.908 when/2

- coroutining

4.909 whiledo/2

- loopp

4.910 white_space//0

- blank_grammars(Format)

4.911 white_spaces//0

- blank_grammars(Format)

4.912 with_output_to/2

- term_io_protocol

4.913 without//2

- sequence_grammars

4.914 working_directory/1

- osp

4.915 write_file/3

- csv_protocol
- tsv_protocol

4.916 write_stream/3

- csv_protocol
- tsv_protocol

4.917 write_term_to_atom/3

- term_io_protocol

4.918 write_term_to_chars/3

- term_io_protocol

4.919 write_term_to_chars/4

- term_io_protocol

4.920 write_term_to_codes/3

- term_io_protocol

4.921 write_term_to_codes/4

- term_io_protocol

4.922 write_to_atom/2

- term_io_protocol

4.923 write_to_chars/2

- term_io_protocol

4.924 write_to_codes/2

- term_io_protocol

4.925 z_normalization/2

- statisticsp

4.926 zero_or_more//0

- sequence_grammars

4.927 zero_or_more//1

- sequence_grammars

4.928 zero_or_more//2

- sequence_grammars

4.929 zip/2

- zipperp

4.930 zip/3

- zipperp

4.931 zip_at_index/4

- zlist

INDICES AND TABLES

- genindex
- search

Generated on Tue Apr 2 19:38:24 WEST 2024

Symbols

(/)/2, 344
 (//)/2, 345
 (<)/2, 828
 (<=)/2, 15, 530
 (:=)/2, 829
 (=<)/2, 828
 (=>)/2, 15, 530
 (=\\=)/2, 830
 (>)/2, 829
 (>=)/2, 829
 =~= / 2, 476, 868

A

a_star_interpreter(W), 928
 absolute_file_name/2, 620
 acc_info/5, 257
 acc_info/7, 257
 activate_monitor/0, 269
 add/1, 682
 add/2, 682
 add/3, 680, 833
 add_directive_/2, 970
 add_directive_/3, 971
 add_directive_before_entity_/2, 970
 add_library_documentation_url/4, 218
 add_link_options/3, 164
 add_node_zoom_option/4, 165
 addDependent/1, 143
 after/2, 401
 after/3, 80
 after_event_registry, 259
 all/0, 31, 115, 457
 all/1, 31, 115, 457
 all_files/0, 155, 177
 all_files/1, 154, 177
 all_libraries/0, 148, 171
 all_libraries/1, 148, 171
 all_score/1, 34
 ancestor/1, 362
 ancestor/4, 42
 ancestors/1, 362
 apis/0, 351
 apis/1, 351
 append/2, 844
 append/3, 709, 844, 901
 apply/2, 986
 apply/4, 248
 approximately_equal/2, 474, 866
 approximately_equal/3, 474, 866
 arbitrary, 1
 arbitrary/1, 4
 arbitrary/2, 4
 archive/1, 693
 arithmetic_mean/2, 772
 arithmetic_mean/5, 767
 array_list/2, 433
 array_to_list/2, 433
 array_to_terms/2, 432
 array_to_terms/3, 432
 as_curly_bracketed/2, 239, 588
 as_dictionary/2, 239
 as_difflist/2, 839
 as_heap/2, 339
 as_list/2, 239, 338, 710, 754, 833
 as_nested_dictionary/2, 588
 as_set/2, 754
 ask_question/5, 71
 assertion/1, 10, 468
 assertion/2, 10, 469
 assertions, 7
 assertions(Mode), 9
 assertions_messages, 11
 assignable/1, 14
 assignable/2, 14
 assignvars, 12
 assignvarsp, 13
 atom, 812
 atomic, 814
 automation_report, 458
 auxiliary_predicate_counter_/1, 507
 available/0, 641
 available/1, 640
 available/2, 640

average/2, 873
average_deviation/3, 774
avltree, 233

B

backend_adapter_hook, 371
backend_random, 712
base64, 17
base64url, 19
base_/2, 310
before/2, 400
before/3, 80
before_event_registry, 260
bench_goal/1, 941
benchmark/2, 472
benchmark/3, 473
benchmark/4, 473
benchmark_generators, 930
benchmark_reified/3, 472
best_first, 931
between/3, 722, 836
bfs_interpreter, 933
binary_file_assertion/3, 503
binary_input_assertion/2, 487
binary_input_assertion/3, 487
binary_output_assertion/2, 498
binary_output_assertion/3, 497
binary_output_contents/1, 498
binary_output_contents/2, 498
bintree, 235
bit//1, 326
bits//1, 326
blank//0, 320
blank_grammars(Format), 316
blanks//0, 320
body_pred/1, 567
body_pred_call/2, 570
branch/2, 313
built_in_directive/4, 346
built_in_flag/2, 296
built_in_method/4, 346
built_in_non_terminal/4, 347
built_in_predicate/4, 346
bup_interpreter, 934

C

c/1, 938
calendar_month/3, 415
call_with_timeout/2, 792
call_with_timeout/3, 793
callable, 815
cat/2, 593
cbor, 21
cbor(StringRepresentation), 22

cc_metric, 24
cdata_generation//1, 979
change_directory/1, 623
changed/0, 142
changed/1, 142
character, 817
character_data_format/3, 979
characterp, 818
chebyshev_distance/3, 876
chebyshev_norm/2, 875
check/1, 890, 909
check/2, 898
check/3, 897
check_binary_file/2, 502
check_binary_input/1, 486
check_binary_input/2, 486
check_binary_output/1, 497
check_binary_output/2, 496
check_option/1, 608
check_options/1, 608
check_text_file/2, 501
check_text_file/3, 500
check_text_input/1, 483
check_text_input/2, 482
check_text_output/1, 491
check_text_output/2, 490
check_text_output/3, 490
chr_is/2, 795
chr_next_state/1, 798
chr_no_spy/1, 796
chr_nospy/0, 796
chr_notrace/0, 795
chr_option/2, 796
chr_option_allow_deep_guards/0, 798
chr_option_optimization_level/1, 797
chr_option_print_trace/0, 796
chr_option_show_history/0, 797
chr_option_show_id/0, 798
chr_option_show_stack/0, 797
chr_option_show_store/0, 797
chr_option_trace_interactive/0, 797
chr_rule_/1, 799
chr_spy/1, 795
chr_spy_point/1, 798
chr_trace/0, 795
class/1, 355
class_hierarchy, 352
class_hierarchyp, 354
classes/1, 355
clause/5, 702
clause_/5, 703
clause_location/6, 701
clause_location_/6, 702
clean/0, 656, 687

clean/1, 656, 686
 clean/2, 655
 clean_binary_input/0, 488
 clean_binary_output/0, 499
 clean_directory/1, 504
 clean_file/1, 503
 clean_text_input/0, 484
 clean_text_output/0, 494
 cleanup/0, 478
 clone/1, 524, 692
 clone/3, 240
 clone/4, 240
 cloning, 523
 closed_input_stream/2, 504
 closed_output_stream/2, 505
 code_metric, 25
 code_metrics, 38
 code_metrics_messages, 40
 code_metrics_utilities, 41
 coefficient_of_variation/2, 775
 command/2, 673
 command_line_arguments/1, 633
 commit_author/2, 313
 commit_date/2, 314
 commit_hash/2, 314
 commit_hash_abbreviated/2, 315
 commit_log/3, 315
 commit_message/2, 315
 comparingp, 827
 compile_aux_clauses/1, 76
 compile_predicate_heads/4, 76
 compile_predicate_indicators/3, 77
 compiled_pred_call/2, 569
 completion/2, 345
 completions/2, 345
 compound, 830
 condition/0, 478
 connect/1, 747
 connect/3, 747
 console/1, 748
 contains/2, 403
 control//0, 321
 control_construct/4, 347
 controls//0, 322
 copy_file/2, 628
 core_messages, 62
 coroutining, 83
 counter, 935
 counter/2, 526, 581
 counter_/2, 307, 528, 582
 counters, 525
 coupling_metric, 46
 cover/1, 465
 coverage_report, 459

covered_/4, 509
 cpu_time/1, 108, 630
 create_binary_file/2, 500
 create_text_file/2, 500
 create_text_file/3, 499
 csv, 86
 csv(Header Separator IgnoreQuotes), 87
 csv_guess_questions, 89
 csv_protocol, 90
 current/2, 983
 current_entity/1, 42
 current_prog/1, 796

D

data/0, 700
 data/1, 700
 data/2, 700
 databasep, 938
 date, 101
 date/4, 407
 date/5, 408
 date/6, 409
 date/7, 410
 date_string/3, 411
 date_time/7, 630
 datep, 102
 days_in_month/3, 104
 dead_code_scanner, 109
 dead_code_scanner_messages, 116
 debug/0, 132
 debug_expansion(Mode), 941
 debug_handler/2, 73
 debug_handler_provider/1, 73
 debug_messages, 118
 debugger, 122
 debugger_messages, 128
 debuggerp, 130
 debugging/0, 132
 debugging/1, 132
 debugging_/0, 124
 decide/1, 290
 decide/2, 290
 declares_predicate/2, 43
 decode_exception/2, 435
 decode_exception/3, 435
 decode_url_spaces/2, 674
 decompile_predicate_heads/4, 77
 decompile_predicate_indicators/4, 78
 decompose_file_name/3, 620
 decompose_file_name/4, 620
 decrement_counter/1, 526
 default_atom_mutations, 572
 default_compound_mutations, 573
 default_float_mutations, 575

- default_integer_mutations, 576
- default_list_mutations, 577
- default_option/1, 610, 966
- default_options/1, 610, 966
- default_workflow_hook, 372
- define_flag/1, 297
- define_flag/2, 297
- define_log_file/2, 539
- defined/4, 680
- defined_flag/6, 296
- defined_flag_/6, 298
- defines_predicate/2, 43
- defines_predicate/3, 44
- del_monitors/0, 265
- del_monitors/4, 265
- del_spy_points/4, 270
- delete/0, 686
- delete/1, 686
- delete/2, 685
- delete/3, 755, 844, 902
- delete/4, 241, 337
- delete_all_after/2, 989
- delete_all_after_and_unzip/2, 989
- delete_all_before/2, 988
- delete_all_before_and_unzip/2, 989
- delete_and_next/2, 988
- delete_and_previous/2, 987
- delete_and_unzip/2, 988
- delete_directory/1, 622
- delete_file/1, 629
- delete_in/4, 590
- delete_matches/3, 845
- delete_max/4, 246
- delete_min/4, 246
- demodb, 942
- dependent_/1, 144
- dependents/1, 142, 661
- dependents/2, 660
- dependents/3, 660
- depth/2, 888
- descendant/1, 363
- descendant_class/1, 360
- descendant_classes/1, 360
- descendant_instance/1, 359
- descendant_instances/1, 359
- descendants/1, 363
- describe/1, 647, 679
- describe/2, 646
- description/1, 635, 691
- deterministic/1, 468
- deterministic/2, 468
- dfs_interpreter, 944
- diagram(Format), 144
- diagram_caption/3, 156
- diagram_description/1, 155
- diagram_name_suffix/1, 156
- diagrams, 166
- diagrams(Format), 168
- dictionaryp, 237
- dif, 251
- dif/1, 84, 252
- dif/2, 84, 252
- difflist, 832
- digit//1, 326
- digits//1, 327
- directories/1, 454, 963
- directories/2, 150, 173, 453, 963
- directories/3, 150, 173
- directory/1, 29, 112, 153, 175, 455, 669, 963
- directory/2, 28, 112, 152, 175, 454, 668, 962
- directory/3, 152, 175
- directory_dependency_diagram, 178
- directory_dependency_diagram(Format), 179
- directory_diagram(Format), 181
- directory_entity_/4, 443
- directory_exists/1, 626
- directory_files/2, 625
- directory_files/3, 625
- directory_load_diagram, 185
- directory_load_diagram(Format), 186
- directory_score/2, 33
- disable/1, 119
- disable/2, 120
- disable_logging/1, 541
- disconnect/1, 747
- disjoint/2, 755
- disjoint_sets/2, 922
- dit_metric, 48
- doc_goal/1, 254
- doc_metric, 49
- doclet, 253
- doctype/1, 391
- document_generation//2, 978
- dot//1, 329
- dot_graph_language, 188
- dowhile/2, 544
- drop/3, 863
- dump_trace, 137
- during/2, 403
- dynamic_directive_/3, 969

E

- easter_day/3, 415
- edcg, 255
- edge/5, 160
- edge/6, 208
- edge_/5, 166
- edge_case/2, 5

either, 273
 either/3, 285
 empty/1, 242, 338, 587, 595, 707, 756, 845, 902
 empty_map/1, 976
 enable/1, 119
 enable/2, 120
 enable_logging/1, 541
 enabled/1, 119
 enabled/2, 120
 enabled_/1, 121
 enabled_/2, 121
 ensure_directory/1, 626
 ensure_file/1, 629
 entity/1, 27, 111, 231, 348
 entity/2, 231
 entity_calls/3, 44
 entity_defines_/2, 703
 entity_diagram, 190
 entity_diagram(Format), 191
 entity_info_pair_score_hook/3, 51
 entity_info_score_hook/2, 51
 entity_kind/2, 44
 entity_predicates_weights_hook/2, 50
 entity_prefix/2, 76
 entity_property/2, 45
 entity_score/2, 32
 entity_updates/3, 45
 enumerate/2, 724
 environment_variable/2, 629
 epsilon/1, 476
 equal/2, 404, 755
 erase/1, 744
 essentially_equal/3, 475, 867
 euclidean_distance/3, 875
 euclidean_norm/2, 874
 event_registry, 261
 event_registryp, 262
 exception/4, 978
 exclude/3, 552
 execution_context/7, 78
 expand_library_alias_paths, 271
 expand_library_path/2, 74
 expanding, 63
 expected, 275
 expected(Expected), 280
 expected/1, 283
 expecteds/2, 274
 extension/1, 367
 extensions/1, 367
 external_predicate_/1, 233

F

f/4, 932
 failed_/3, 508
 false/1, 429
 fast_random, 713
 fault/5, 977
 fcube, 288
 fcube/0, 290
 file/1, 28, 111, 192, 456, 965
 file/2, 28, 111, 192, 456, 965
 file_being_advised_/4, 971
 file_dependency_diagram, 195
 file_dependency_diagram(Format), 196
 file_diagram(Format), 198
 file_exists/1, 626
 file_footer/3, 206
 file_header/3, 206
 file_load_diagram, 201
 file_load_diagram(Format), 203
 file_modification_time/2, 627
 file_path/2, 479
 file_permission/2, 627
 file_score/2, 33
 file_size/2, 627
 file_to_bytes/2, 733
 file_to_bytes/3, 733
 file_to_chars/2, 732
 file_to_chars/3, 732
 file_to_codes/2, 731
 file_to_codes/3, 731
 file_to_terms/2, 732
 file_to_terms/3, 733
 file_type_extension/2, 75
 files/1, 154, 177, 455, 964
 files/2, 153, 176, 455, 964
 files/3, 153, 176
 filter/2, 601
 filter_external_file_extension/3, 164
 filter_file_extension/3, 163
 find/4, 921
 find/5, 921
 findall_member/4, 552
 findall_member/5, 553
 finished_by/2, 404
 finishes/2, 404
 fired_/3, 509
 fix_option/2, 612
 fix_options/2, 612
 flag_group_chk/1, 295
 flag_groups/1, 295
 flag_value_/2, 298
 flags, 292
 flags_validator, 299
 flaky_/1, 508
 flat_map/2, 284, 602
 flatten/2, 846, 902
 flatten_goals//1, 946

flattening, 945
float, 834
float//1, 328
fold_left/4, 554
fold_left_1/3, 554
fold_right/4, 555
fold_right_1/3, 556
fordownto/3, 547
fordownto/4, 547
fordownto/5, 548
foreach/3, 545
foreach/4, 545
format, 301
format/2, 302
format/3, 302
format_entity_score//2, 34
format_object/1, 155
format_to_atom/3, 788
format_to_chars/3, 789
format_to_chars/4, 789
format_to_codes/3, 790
format_to_codes/4, 790
forto/3, 546
forto/4, 546
forto/5, 546
forward/1, 66
forward/2, 985
forward/3, 985
forwarding, 65
fractile/3, 777
freeze/2, 84
from_generator/2, 279, 597
from_generator/3, 279, 596
from_generator/4, 278
from_goal/2, 278, 596
from_goal/3, 277, 596
from_goal/4, 277
frozen/2, 85
full_device_path/1, 624
func_test/3, 568
functional/0, 568

G

generate/1, 396, 914
generate/2, 18, 20, 23, 390, 441, 914
generate/8, 914
generated_predicate_/1, 562
generating_/0, 513
genint, 303
genint/2, 306
genint_core, 304
gensym, 307
gensym/2, 310
gensym_core, 308

geometric_mean/2, 772
get/1, 602
get_field/2, 423
get_flag_value/2, 293
get_seed/1, 6, 717
git, 311
git_protocol, 312
gnu/0, 289
goal_expansion/2, 64
grammar_rules_hook, 373
graph_footer/5, 207
graph_header/5, 207
graph_language_protocol, 205
graph_language_registry, 209
ground/1, 888
ground_entity_identifier/3, 163
group_by_key/2, 884
group_consecutive_by_key/2, 884
group_sorted_by_key/2, 883
guess_arity/2, 99
guess_separator/2, 99

H

halstead_metric, 53
halstead_metric(Stroud), 54
hamming_distance/3, 846
handbook/0, 350
handbook/1, 350
harmonic_mean/2, 772
head/2, 707
head_pred/1, 567
heap(Order), 334
heapp, 335
help, 343
help/0, 344, 666
help_info_support, 349
heuristic_expansion(Mode), 946
hex_digit//1, 327
hex_digits//1, 327
hierarchyp, 361
home/1, 636, 692
hook_pipeline(Pipeline), 368
hook_set(Set), 369
html, 389
html5, 392

I

ibk/3, 567
iddfs_interpreter(Increment), 948
identity_hook, 374
ids, 394
ids(Representation Bytes), 395
if_empty/1, 600
if_expected/1, 282

if_expected_or_else/2, 283
 if_present/1, 600
 if_present_or_else/2, 600
 if_unexpected/1, 282
 include/3, 552
 included_directory_/1, 184
 included_entity_/1, 193
 included_file_/1, 200
 included_library_/2, 219
 included_module_/1, 193
 included_predicate_/1, 232
 increase/1, 936
 increment/0, 936
 increment_counter/1, 526
 inheritance_diagram, 210
 inheritance_diagram(Format), 211
 init/0, 958
 init_log_file/2, 540
 inorder/2, 236
 insert/3, 756
 insert/4, 241, 336
 insert_after/3, 987
 insert_all/3, 337, 756
 insert_before/3, 986
 insert_in/4, 590
 install/1, 650
 install/2, 649
 install/3, 649
 install/4, 648
 installed/0, 643
 installed/1, 642
 installed/3, 642
 installed/4, 641
 instance/1, 356
 instance/2, 744
 instances/1, 356
 integer, 835
 integer//1, 328
 internal_os_path/2, 621
 interpreterp, 949
 intersect/2, 757
 intersection/2, 244
 intersection/3, 244, 757
 intersection/4, 757
 interval, 397
 intervalp, 398
 invocation_number_/1, 127
 invoke/1, 424
 invoke/2, 425
 ip_grammars(Format), 322
 ipv4//1, 323
 ipv6//1, 324
 is_absolute_file_name/1, 619
 is_alpha/1, 820

is_alphanumeric/1, 820
 is_ascii/1, 819
 is_bin_digit/1, 821
 is_control/1, 825
 is_dec_digit/1, 821
 is_empty/0, 599
 is_end_of_line/1, 825
 is_expected/0, 281
 is_false/1, 430
 is_hex_digit/1, 822
 is_layout/1, 823
 is_letter/1, 820
 is_lower_case/1, 822
 is_newline/1, 825
 is_null/1, 431
 is_object/1, 431
 is_octal_digit/1, 821
 is_period/1, 824
 is_present/0, 599
 is_punctuation/1, 824
 is_quote/1, 824
 is_true/1, 430
 is_unexpected/0, 281
 is_upper_case/1, 822
 is_validator/1, 299
 is_void/1, 430
 is_vowel/1, 823
 is_white_space/1, 823
 iso8601, 405
 issue_creator, 417
 iterator_element/2, 434

J

java, 418
 java(Reference), 419
 java(Reference ReturnValue), 420
 java_access_protocol, 422
 java_hook, 425
 java_utils_protocol, 427
 join/3, 707
 join_all/3, 708
 json, 436
 json(ObjectRepresentation PairRepresentation StringRepresentation)
 438
 json(StringRepresentation), 437
 json_protocol, 440
 jump/3, 708
 jump_all/3, 708
 jump_all_block/3, 709
 jump_to_invocation_number_/1, 127

K

key/2, 882
 keys/2, 247, 881

keys_values/3, 881
keysort/2, 846
kurtosis/2, 776

L

language_object/2, 210
last/2, 847, 903
leaf/1, 362
leaf_class/1, 358
leaf_classes/1, 359
leaf_instance/1, 358
leaf_instances/1, 358
leap_year/1, 103, 414
leaping_/1, 125
learn/0, 571
learn/1, 571
learn/2, 565
learn/3, 564
learn_seq/2, 565
learn_with_timeout/4, 565
leash/1, 136
leashing/1, 136
leashing_/1, 127
least_common_multiple/2, 879
leaves/1, 363
length/2, 709, 847, 903
lgtdoc, 442
lgtdoc_messages, 445
lgtdocp, 446
lgtunit, 461
lgtunit_messages, 510
libraries/1, 148, 170, 450
libraries/2, 147, 170, 450
libraries/3, 147, 170
library/0, 347
library/1, 30, 113, 150, 172, 348, 451
library/2, 30, 113, 149, 172, 451
library_dependency_diagram, 213
library_dependency_diagram(Format), 214
library_diagram(Format), 216
library_entity_/4, 443
library_load_diagram, 220
library_load_diagram(Format), 222
library_score/2, 32
license/1, 635
line_to_chars/2, 737
line_to_chars/3, 737
line_to_codes/2, 737
line_to_codes/3, 738
lint/0, 663, 688
lint/1, 662, 688
lint/2, 662
list, 838
list(Type), 840

list/0, 679
list_to_array/2, 433
listing, 531
listing/0, 532
listing/1, 532
listp, 841
load_registry/1, 673
loaded_file/1, 74
loaded_file_property/2, 74, 225
locate_directory/2, 162
locate_file/5, 163
locate_library/2, 162
log_event/2, 540
log_file/2, 539
log_file_/2, 535, 537
logger, 534
logging, 536
logging/1, 540
logging_to_file_/2, 536, 537
loggingp, 538
logtalk, 67
logtalk_packs/0, 671
logtalk_packs/1, 670
lookup/2, 243
lookup/3, 243
lookup_in/3, 588
loop, 542
loopp, 543
lower_upper/2, 826

M

magic, 951
magic/2, 952
magic_expansion(Mode), 953
magicise/4, 952
make/1, 479
make_directory/1, 621
make_directory_path/1, 622
make_set/3, 920
man/1, 352
manhattan_distance/3, 876
manhattan_norm/2, 875
manuals/0, 348
map/2, 247, 284, 557, 601, 710
map/3, 248, 557, 711, 884
map/4, 558
map/5, 558
map/6, 559
map/7, 559
map/8, 559
map_element/2, 434
map_member/3, 976
map_reduce/5, 560
map_store/4, 977

max/2, 771, 847, 872
 max/3, 245
 max_clauses/1, 568
 max_inv_preds/1, 568
 max_size/1, 7
 maxheap, 340
 maybe, 592
 maybe/0, 727
 maybe/1, 727
 maybe/2, 728
 maybe_call/1, 728
 maybe_call/2, 728
 mean_deviation/2, 774
 median/2, 773, 874
 median_deviation/2, 775
 meets/2, 401
 member/2, 722, 758, 848
 memberchk/2, 759, 848, 903
 merge/3, 337
 merge_options/2, 611, 967
 message_cache_/1, 518, 519, 521, 523
 message_diagram_description/1, 165
 message_hook/4, 71
 message_prefix_stream/4, 70
 message_tokens//2, 70
 met_by/2, 401
 meta, 549
 meta_compiler, 561
 meta_type/3, 897
 metagol, 563
 metagol_example_protocol, 570
 metap, 550
 metarule/6, 567
 metarule_next_id/1, 569
 min/2, 770, 848, 872
 min/3, 245
 min_clauses/1, 568
 min_max/3, 771, 872
 minheap, 341
 minimal_output, 511
 missing_predicate_directive_/3, 969
 modes/2, 773, 874
 module_predicate_called_/3, 968
 module_property/2, 225
 modules_diagram_support, 224
 monitor, 266
 monitor/1, 264
 monitor/4, 264
 monitor_activated/0, 269
 monitored/1, 264
 monitoring, 79
 monitorp, 267
 monitors/1, 263
 msort/2, 849

msort/3, 849
 multifile_directive_/3, 970
 mutation/3, 580, 581
 mutation/4, 582
 mutations, 579
 mutations_store, 580

N

name/1, 635, 691
 name_of_day/3, 104
 name_of_month/3, 104
 natural, 864
 natural//1, 328
 navltree, 583
 nbintree, 584
 nested_dictionary_protocol, 586
 new/1, 424, 529, 587, 888
 new/2, 424, 529, 920
 new/3, 400
 new_line//0, 319
 new_lines//0, 320
 next/2, 983
 next/3, 983
 next/4, 245
 nextto/3, 850, 904
 noc_metric, 56
 node/6, 159
 node/7, 207
 node_/6, 166
 nodebug/0, 132
 non_blank//1, 321
 non_blanks//1, 321
 non_standard_predicate_call_/2, 969
 nor_metric, 58
 normal_element/2, 391
 normalize_range/2, 877
 normalize_range/4, 877
 normalize_scalar/2, 878
 normalize_unit/2, 878
 nospy/1, 135
 nospy/4, 135
 nospyall/0, 136
 not_excluded_file/3, 45
 not_excluded_file/4, 161
 note/1, 479
 note/2, 693
 note/3, 637
 notrace/0, 133
 now/3, 108
 nrbtree, 591
 nth0/3, 850, 904
 nth0/4, 850, 904
 nth1/3, 851, 905
 nth1/4, 851, 905

- null/1, 429
- null_device_path/1, 624
- number, 865
- number//1, 329
- number_grammars(Format), 324
- number_of_tests/1, 467
- numberlist, 868
- numberlistp, 870
- numbervars/1, 892
- numbervars/3, 892

O

- object_file_/2, 460
- object_predicate_called_/3, 968
- object_wrapper_hook, 376
- object_wrapper_hook(Name Relations), 378
- object_wrapper_hook(Protocol), 377
- observer, 139
- occurrences/2, 851
- occurrences/3, 852
- occurs/2, 889
- of/2, 595
- of_expected/2, 277
- of_unexpected/2, 276
- omit_path_prefix/3, 164
- one_or_more//0, 333
- one_or_more//1, 332
- one_or_more//2, 331
- operating_system_machine/1, 632
- operating_system_name/1, 631
- operating_system_release/1, 632
- operating_system_type/1, 631
- option/2, 610
- option/3, 611
- optional, 594
- optional(Optional), 598
- options, 605
- options_protocol, 607
- or/2, 602
- or_else/2, 285, 603
- or_else_call/2, 286, 604
- or_else_fail/1, 287, 604
- or_else_get/2, 286, 603
- or_else_throw/1, 287
- or_else_throw/2, 605
- orphaned/0, 645
- orphaned/2, 645
- os, 613
- os_types, 614
- osp, 616
- outdated/0, 644
- outdated/1, 644
- outdated/4, 643
- output_edges/1, 160

- output_externals/1, 157
- output_file/4, 158
- output_file_name/2, 206
- output_file_path/4, 162
- output_files/2, 158
- output_library/3, 157
- output_missing_externals/1, 161
- output_node/6, 159
- output_rdirectory/3, 157
- output_rlibrary/3, 156
- output_sub_diagrams/1, 158
- overlapped_by/2, 402
- overlaps/2, 402

P

- pack_protocol, 634
- packs, 638
- packs_common, 663
- packs_messages, 675
- packs_specs_hook, 676
- pairs, 880
- parent/1, 366
- parenthesis/2, 826
- parents/1, 366
- parse/2, 18, 20, 23, 441, 974
- parse/3, 974
- parse_domain/2, 695
- parse_domain/3, 695
- parse_problem/2, 695
- parse_problem/3, 696
- partial_/1, 513, 516
- partial_map/4, 250
- partition/3, 274
- partition/4, 553, 752
- partition/5, 852
- partition/6, 553
- pass_info/1, 258
- pass_info/2, 258
- passed_/3, 508
- path_concat/3, 621
- pcdata_7bit//1, 979
- pddl, 694
- permutation/2, 724, 853, 906
- pid/1, 618
- pin/0, 667
- pin/1, 666
- pinned/1, 668
- plus/3, 836
- population, 763
- port/5, 701
- port_/5, 703
- portray_clause/1, 533
- ports_profiler, 698
- postorder/2, 236

powerset/2, 759
 pp/1, 975
 pp_string/1, 977
 pprint/1, 566
 pprint_clause/1, 569
 pprint_clauses/1, 569
 pred_info/3, 257
 predicate/2, 116
 predicate_called_but_not_defined_/2, 967
 predicate_entity_/4, 444
 predicate_info_pair_score_hook/4, 53
 predicate_info_score_hook/3, 52
 predicate_mode_score_hook/3, 51
 predicate_mode_score_hook/5, 52
 predicates/2, 115
 prefix/0, 672
 prefix/1, 671
 prefix/2, 853, 906
 prefix/3, 853
 preorder/2, 236
 previous/2, 984
 previous/3, 984
 previous/4, 244
 print_flags/0, 295, 300
 print_flags/1, 296
 print_goal_hook, 380
 print_message/3, 69
 print_message_token/4, 70
 print_message_tokens/3, 69
 print_readme_file_path/1, 672
 process_all/1, 37
 process_directory/2, 36
 process_entity/2, 35
 process_file/2, 35
 process_library/2, 36
 process_rdirectory/2, 36
 process_rlibrary/2, 37
 product/2, 770, 873
 product/3, 759
 program_to_clauses/2, 566
 prolog_module_hook(Module), 381
 proper_prefix/2, 854
 proper_prefix/3, 854
 proper_suffix/2, 862
 proper_suffix/3, 862
 proto_hierarchy, 364
 proto_hierarchyp, 365
 prove/2, 950
 prove/3, 950
 provides/2, 687
 pseudo_random_protocol, 716

Q

quasi_skipping_/0, 125

question_hook/6, 72
 question_prompt_stream/4, 72
 queue, 704
 queuep, 705
 quick_check/1, 471
 quick_check/2, 470
 quick_check/3, 470

R

random, 718
 random/1, 722
 random/3, 726
 random_node/1, 928
 random_protocol, 720
 random_tree/1, 931
 randomize/1, 715, 719
 randseq/4, 726
 randset/4, 726
 range/2, 771
 rbtree, 249
 rdirectories/1, 452
 rdirectories/2, 452
 rdirectory/1, 29, 113, 151, 174, 453, 962
 rdirectory/2, 29, 112, 151, 174, 452, 962
 rdirectory/3, 151, 174
 rdirectory_score/2, 34
 read_file, 697
 read_file/2, 93, 698, 804
 read_file/3, 91, 803
 read_file_by_line/2, 96, 807
 read_file_by_line/3, 94, 806
 read_from_atom/2, 782
 read_from_chars/2, 784
 read_from_codes/2, 785
 read_only_device_path/1, 624
 read_stream/2, 93, 805
 read_stream/3, 92, 803
 read_stream_by_line/2, 96, 808
 read_stream_by_line/3, 95, 807
 read_term_from_atom/3, 782
 read_term_from_chars/3, 783
 read_term_from_chars/4, 783
 read_term_from_codes/3, 784
 read_term_from_codes/4, 784
 reader, 729
 readme/1, 670
 readme/2, 669
 readme_file_path/2, 672
 record_/3, 745
 recorda/2, 741
 recorda/3, 741
 recorded/2, 743
 recorded/3, 743
 recorded_database, 739

recorded_database_core, 740
recordz/2, 742
recordz/3, 742
redis, 746
reference_/1, 745
referenced_entity_/2, 194
referenced_logtalk_directory_/1, 184
referenced_logtalk_file_/1, 200
referenced_logtalk_library_/2, 219
referenced_module_/2, 194
referenced_predicate_/1, 232
referenced_prolog_directory_/1, 184
referenced_prolog_file_/1, 201
referenced_prolog_library_/2, 220
registries, 677
registry_loader_hook, 689
registry_protocol, 690
relative_standard_deviation/2, 776
remember_included_directory/1, 183
remember_included_file/1, 199
remember_included_library/2, 218
remember_referenced_logtalk_directory/1, 183
remember_referenced_logtalk_file/1, 199
remember_referenced_logtalk_library/2, 218
remember_referenced_prolog_directory/1, 183
remember_referenced_prolog_file/1, 200
remember_referenced_prolog_library/2, 219
remove_directive_/2, 971
remove_duplicates/2, 854, 906
removeDependent/1, 143
rename_file/2, 628
replace/3, 987
replace_sub_atom/4, 813
rescale/3, 879
reset/0, 131, 159, 665, 701, 937
reset/1, 701
reset_counter/1, 527
reset_counters/0, 527
reset_flags/0, 294
reset_flags/1, 294
reset_genint/0, 306
reset_genint/1, 306
reset_gensym/0, 309
reset_gensym/1, 309
reset_monitor/0, 269
reset_seed/0, 714, 719
restore/1, 659
restore/2, 658
reverse/2, 855, 907
rewind/2, 984
rewind/3, 985
rlibraries/1, 448
rlibraries/2, 448
rlibrary/1, 31, 114, 149, 172, 449
rlibrary/2, 30, 114, 149, 171, 449
rlibrary_score/2, 32
rule/2, 940
rule/3, 940
rule/4, 940
rule_expansion(Mode), 954
run/0, 465
run/1, 466
run/2, 466
run_quick_check_tests/5, 477
run_test_set/0, 477
run_test_sets/1, 467
run_tests/0, 477
run_tests/1, 477
running_test_sets_/0, 506

S

same_length/2, 855, 907
same_length/3, 856
sample, 764
save/0, 966
save/1, 658, 965
save/2, 657
save_edge/5, 160
scalar_product/3, 877
scan_left/4, 555
scan_left_1/3, 555
scan_right/4, 556
scan_right_1/3, 557
search/1, 647
seed_/3, 715, 720
select/3, 723, 760, 856, 907
select/4, 723, 857
selectchk/3, 760, 856
selectchk/4, 857
send/3, 748
sequence/3, 837
sequence/4, 725, 838
sequence_grammars, 330
serve/3, 710
set, 749
set(Type), 750
set/1, 937
set/4, 725
set_binary_input/1, 485
set_binary_input/2, 485
set_binary_input/3, 484
set_binary_output/1, 496
set_binary_output/2, 495
set_binary_output/3, 495
set_element/2, 434
set_field/2, 423
set_flag_value/2, 293
set_flag_value/3, 294

set_monitor/4, 265
 set_seed/1, 6, 717
 set_spy_point/4, 270
 set_text_input/1, 482
 set_text_input/2, 481
 set_text_input/3, 481
 set_text_output/1, 489
 set_text_output/2, 489
 set_text_output/3, 488
 setp, 752
 setup/0, 478, 665
 shell, 955
 shell(Interpreters), 957
 shell/1, 619
 shell/2, 618
 shell_command/1, 254
 shell_expansion(Mode), 958
 shrink/3, 5
 shrink_sequence/3, 5
 shrinker/1, 4
 sign//1, 329
 singletons/2, 891
 size/2, 248, 338, 758
 size_metric, 59
 skewness/2, 776
 skipped_/1, 507
 skipping_/0, 124
 skipping_unleashed_/1, 124
 sleep/1, 633
 sort/2, 752, 857
 sort/3, 858
 sort/4, 858
 source_file_extension/1, 225
 space//0, 318
 spaces//0, 318
 split/3, 813
 split/4, 859
 spy/1, 133
 spy/4, 134
 spy_point/4, 270
 spy_point_/4, 267
 spying/1, 134
 spying/4, 135
 spying_context_/4, 126
 spying_line_number_/2, 125
 spying_predicate_/3, 126
 squares_and_cubes/6, 767
 squares_and_hypers/6, 767
 standard_deviation/2, 775
 start/0, 956
 start_redirect_to_file/2, 138
 started_by/2, 403
 starts/2, 402
 statistics, 765
 statisticsp, 768
 stop_redirect_to_file/0, 138
 stream_position/1, 505
 stream_to_bytes/2, 736
 stream_to_bytes/3, 736
 stream_to_chars/2, 734
 stream_to_chars/3, 735
 stream_to_codes/2, 734
 stream_to_codes/3, 734
 stream_to_terms/2, 735
 stream_to_terms/3, 736
 streamvars, 528
 sub_diagram_/1, 197, 204, 216, 223
 sub_diagram_/2, 181, 188
 sub_directory/2, 37
 sub_library/2, 38
 subclass/1, 356
 subclasses/1, 357
 subject, 141
 sublist/2, 859, 908
 subsequence/3, 859
 subsequence/4, 860
 subset/2, 760
 substitute/4, 860
 subsumes/2, 889
 subterm/2, 889, 975
 subtract/3, 761, 861, 908
 succ/2, 837
 suffix/2, 861, 908
 suffix/3, 861
 sum/2, 770, 873
 superclass/1, 357
 superclasses/1, 357
 supported_archive/1, 674
 supported_url_archive/1, 674
 suppress_binary_output/0, 480
 suppress_goal_hook, 382
 suppress_text_output/0, 480
 suspend_monitor/0, 269
 swap/2, 723
 swap_consecutive/2, 724
 symdiff/3, 761

T

tab//0, 319
 tabs//0, 319
 take/3, 862
 tap_output, 512
 tap_report, 514
 tar_command/1, 673
 temporary_directory/1, 623
 temporary_file_/1, 780
 term, 885
 term_expansion/2, 64

term_io, 779
term_io_protocol, 780
termp, 886
terms_to_array/2, 431
test/1, 467
test/2, 506
test/3, 506
test_/2, 507
test_count_/1, 514, 516
text_file_assertion/3, 502
text_file_assertion/4, 501
text_input_assertion/2, 484
text_input_assertion/3, 483
text_output_assertion/2, 492
text_output_assertion/3, 492
text_output_assertion/4, 491
text_output_contents/1, 494
text_output_contents/2, 493
text_output_contents/3, 493
time, 105
time_stamp/1, 630
timeout, 791
timeout/1, 569
timep, 107
timestamp/2, 915
timestamp/8, 915
timestamp_/6, 460
today/3, 103
tolerance_equal/4, 475, 867
top/3, 339
top_next/5, 339
toychrdb, 793
trace/0, 133
trace_event/2, 72
tracing_/0, 124
transpose/2, 883
true/1, 428
tsv, 799
tsv(Header), 800
tsv_protocol, 801
tutor, 811
type, 893
type/1, 896
type/3, 570
type_entity_/4, 444

U

ulid, 910
ulid(Representation), 911
ulid_protocol, 912
ulid_types, 916
unexpected/1, 283
unexpecteds/2, 274
uninstall/0, 655
uninstall/1, 654
uninstall/2, 654
union/3, 761
union/4, 762, 920
union_all/3, 921
union_find, 917
union_find_protocol, 918
unknown_predicate_called_/2, 968
unpin/0, 667
unpin/1, 667
unsafe_set_flag_value/2, 297
unzip/2, 982
update/0, 254, 653, 684
update/1, 140, 653, 684
update/2, 652, 683
update/3, 242, 651
update/4, 241
update/5, 242
update_in/4, 589
update_in/5, 589
upn_metric, 61
user, 81
uses_diagram, 226
uses_diagram(Format), 227
uuid, 923
uuid(Representation), 924
uuid_null/1, 927
uuid_protocol, 925
uuid_v1/2, 927
uuid_v4/1, 927

V

valid/1, 400, 778, 890, 909
valid/2, 897
valid/3, 105, 108
valid_date/3, 413
valid_option/1, 609
valid_options/1, 609
validate/1, 300
validate/3, 299
validate_type/1, 299
value/1, 937
value/3, 882
value_reference/2, 428
values/2, 247, 882
variables/2, 891
variance/2, 777
variance/6, 768
variant/2, 473, 890
varlist, 899
varlistp, 900
varnumbers/2, 893
varnumbers/3, 892
verify_commands_availability/0, 666

version/6, 636
versions/3, 645
void/1, 429
void_element/1, 390

zipperp, 980
zlist, 990

W

wall_time/1, 631
weighted_mean/3, 773
welcome/0, 956
when/2, 85
whiledo/2, 544
white_space//0, 318
white_spaces//0, 318
with_output_to/2, 790
without//2, 333
working_directory/1, 623
wrapper, 959
write_file/3, 97, 809
write_max_depth_/1, 128
write_stream/3, 98, 809
write_term_to_atom/3, 785
write_term_to_chars/3, 786
write_term_to_chars/4, 786
write_term_to_codes/3, 787
write_term_to_codes/4, 788
write_to_atom/2, 786
write_to_chars/2, 787
write_to_codes/2, 788
write_to_file_hook(File), 384
write_to_file_hook(File Options), 385
write_to_stream_hook(Stream), 386
write_to_stream_hook(Stream Options), 388

X

xhtml11, 393
xml, 972
xml_to_document/3, 976
xref_diagram, 229
xref_diagram(Format), 230
xunit_net_v2_output, 516
xunit_net_v2_report, 518
xunit_output, 520
xunit_report, 521

Z

z_normalization/2, 777
zap_to_port_/1, 128
zero_or_more//0, 333
zero_or_more//1, 332
zero_or_more//2, 331
zip/2, 982
zip/3, 982
zip_at_index/4, 991